









P72.20-2311-09

- | | | | | | |
|---|----------------------|---|----------------------|---|------|
| 1 | Rear spoiler | 4 | Electrical connector | 6 | Nut |
| 2 | Rear-end door | 5 | Washer fluid hose | 7 | Bolt |
| 3 | Electrical connector | | | | |

 	Remove/install		
1	Remove liner from tailgate (2)	 Remove only top paneling.	AR72.20-P-3520T
2	Disconnect electrical connectors (3, 4)		
3	Remove washing water hose (5) from windshield washer nozzle	 Plug washing water hose (5) with suitable plug.	
4	Unscrew nuts (6).		*BA72.20-P-1009-02A
5	Unscrew screws (7) until a clacking noise can be heard	 The bolts (7) remain in the retaining clips on the rear spoiler (1).  Installation: Replace damaged retaining clips on rear spoiler (1). Tighten screws (7) uniformly. 	*BA72.20-P-1010-02A
6	Remove rear spoiler (1) from tailgate (2) with aid of second mechanic		
7	Install in the reverse order		

 Tailgate

Number	Designation	Model	211.2
BA72.20-P-1009-02A	Nut, rear spoiler to rear-end door	Nm	1.5
BA72.20-P-1010-02A	Bolt in rear spoiler retaining clips to rear-end door	Nm	1.5