



Mercedes-Benz

AP00.20-U-1208DF SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model Year 2010
USA

Model 212



Customer: _____

Repair order number: _____

Tire Rotation
(non-staggered width
wheel setup only)

A 5,000-mile recommended tire rotation interval will likely necessitate tire rotation at least once in between each 10,000-mile maintenance service and at every 10,000-mile maintenance service.

Tires rotated YES NO

i Note: For any condition found while performing the checks or inspections included in this maintenance sheet, determine the cause and perform the repair using a separate repair order.

Current mileage reading: _____

Oil grade/viscosity: _____

Additional notes: _____

Service work to be performed as advised by service advisor:

Completion date:

Confirm work has been performed by signing below:

| Required Service Work <input checked="" type="checkbox"/> Performed (check if performed) | miles (thousands) years | 2 | 10 | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 | 150 | Not OK ↓ |
|--|----------------------------|---|----|----|----|----|----|----|----|----|----|-----|-----|-----|-----|-----|-----|---|
| | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | | |
| <input type="checkbox"/> Reset maintenance service indicator in instrument cluster | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | <input type="checkbox"/> AP00.20-P-0042EW |
| <input type="checkbox"/> Engine - oil and filter change Engine 272, 273 | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | <input type="checkbox"/> AP18.00-P-0101EW |
| <input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | <input type="checkbox"/> AP88.40-P-8851EW |
| <input type="checkbox"/> Check condition of poly-V-belt Engine 272, 273 | | | | • | | • | | • | | • | | • | | • | | • | | <input type="checkbox"/> AP13.22-P-1352EW |
| <input type="checkbox"/> Replace fuel filter Engine 272, 273 | | | | | | | | | | | | | | | | | • | <input type="checkbox"/> AP47.20-P-0780EW |
| <input type="checkbox"/> Replace coolant <input checked="" type="checkbox"/> Observe correct coolant composition Engine 272, 273 | | | | | | | | | | | | | | | | | • | <input type="checkbox"/> AP20.00-P-2080EW |
| <input type="checkbox"/> Replace brake fluid | | | | • | | • | | • | | • | | • | | • | | • | | <input type="checkbox"/> AP42.00-P-4280EW |
| <input type="checkbox"/> Replace combination or dust filter | | | | • | | • | | • | | • | | • | | • | | • | | <input type="checkbox"/> AP83.00-P-8384EW |
| <input type="checkbox"/> Check thickness of brake pads, front and rear | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | <input type="checkbox"/> AP42.10-P-4253A |
| <input type="checkbox"/> Correct tire inflation pressure and enter in bar or psi: LF RF LR RR bar/psi: _____ | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | <input type="checkbox"/> |
| <input type="checkbox"/> Check inflation pressure in spare tire (if applicable) and enter in bar or psi: bar/psi: _____ | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | <input type="checkbox"/> |
| <input type="checkbox"/> Leakage - Major components Check underbody and engine compartment for chafe marks, line routing, damaged components. | | | | • | | • | | • | | • | | • | | • | | • | | <input type="checkbox"/> AP00.20-P-0053EW |
| <input type="checkbox"/> Visually inspect condition of front axle ball joints, rubber boots | | | | • | | • | | • | | • | | • | | • | | • | | <input type="checkbox"/> AP33.20-P-3353EW |
| <input type="checkbox"/> Visually inspect condition of driveshaft flexible discs | | | | • | | • | | • | | • | | • | | • | | • | | <input type="checkbox"/> AP41.10-P-4152EW |
| <input type="checkbox"/> Visually inspect condition of steering mechanical components, rubber boots | | | | • | | • | | • | | • | | • | | • | | • | | <input type="checkbox"/> AP46.00-P-4653EW |
| <input type="checkbox"/> Automatic transmission - oil and filter change | | | | | | • | | | | • | | | | • | | | | <input type="checkbox"/> AP27.00-P-2702W |
| <input type="checkbox"/> Replace air filter Engine 272, 273 | | | | | | • | | | | • | | | | • | | | | <input type="checkbox"/> AP09.10-P-0980EW |
| <input type="checkbox"/> Replace spark plugs Engine 272, 273 | | | | | | | | | | • | | | | | | | | <input type="checkbox"/> AP15.10-P-1580EW |
| Check the following fluid levels, correct if necessary | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Check coolant level | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | <input type="checkbox"/> AH20.00-P-1142-01V |
| <input type="checkbox"/> Brake system | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | <input type="checkbox"/> AP42.10-P-4210EW |
| | miles (thousands) years | 2 | 10 | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 | 150 | |
| | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | | |

| <input checked="" type="checkbox"/> Performed (check if performed) | miles (thousands) years | 2 | 10 | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 | 150 | Not OK ↓ | |
|--|----------------------------|---|----|----|----|----|----|----|----|----|----|-----|-----|-----|-----|-----|-----|-------------|---|
| <input type="checkbox"/> Power steering <input checked="" type="checkbox"/> i The fluid level must always be on the maximum mark, corresponding to the oil temperature. Engine 272, 273 | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP46.00-P-4611EW |
| <input type="checkbox"/> Windshield washer system | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP82.35-P-8210EW |
| Function check | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Parking brake (function test only) | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> |
| <input checked="" type="checkbox"/> i Reminder: Reset maintenance service indicator in instrument cluster | | | | | | | | | | | | | | | | | | | AP00.20-P-0042EW |
| Recommended Service Work | | | | | | | | | | | | | | | | | | | |
| <input checked="" type="checkbox"/> Performed (check if performed) | | | | | | | | | | | | | | | | | | | Not OK ↓ |
| <input type="checkbox"/> Replace wiper blades | | | | | | | | | | | | | | | | | | | |
| Electrical system checks | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Horn, high beam flasher, hazard warning flasher, turn signals | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> |
| <input type="checkbox"/> Warning/indicator lamps, illumination and interior lighting/exterior lighting | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP54.30-P-5452C |
| <input type="checkbox"/> Check trunk/cargo area lighting | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> |
| <input type="checkbox"/> Check and correct headlamp setting | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP82.10-P-8260EW |
| <input type="checkbox"/> Battery (main/starter/auxiliary) check condition using "Midtronics MCR 717" tester. Attach Midtronics MCR 717 Test Report print out here | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP54.10-U-5453A |
| Visual and functional checks | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Check seat belts and buckles for signs of external damage and proper function | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP91.40-P-9150EW |
| <input type="checkbox"/> Check windshield washer and headlamp cleaning system | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP82.30-P-8252EW |
| <input type="checkbox"/> Check, clean, and lubricate tilt/sliding roof mechanism (where applicable) | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> |
| <input type="checkbox"/> Check, clean, and lubricate panoramic roof mechanism (where applicable) | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP77.20-P-7732EW |
| <input type="checkbox"/> Check bodywork for paintwork damage | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP98.00-P-9850EW |
| Tire checks | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Tire rotation (where applicable) | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Inspect tires for damage, measure thread depth and enter in mm: LF RF LR RR outside _____ center _____ inside _____ | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP40.10-P-4051EW |
| <input type="checkbox"/> Check TIREFIT tire sealant expiration date (where applicable) | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP40.10-P-4054EW |
| | miles (thousands) years | 2 | 10 | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 | 150 | | |
| | | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | | |

| <input checked="" type="checkbox"/> Performed (check if performed) | miles (thousands) years | 2 | 10 | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 | 150 | Not OK ↓ | |
|---|----------------------------|---|----|----|----|----|----|----|----|----|----|-----|-----|-----|-----|-----|-----|-------------|---|
| <input type="checkbox"/> Activate Tire Pressure Monitoring System; Refer to vehicle Operator's Manual | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| Chassis checks | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Visually check brake system components, lines, hoses, calipers | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | <input type="checkbox"/> |
| <input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed | | | | | | | | | | | | | | | | | | | |
| Pads | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | <input type="checkbox"/> AP42.10-P-4253A |
| Discs | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | <input type="checkbox"/> AP42.10-P-4258EW |
| <input type="checkbox"/> Check chassis and load-bearing body components for damage and corrosion | | | | • | | • | | • | | • | | | | • | | • | | | <input type="checkbox"/> AP00.20-P-0090EW |
| High Mileage Required Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years | | | | | | | | | | | | | | | | | | | |
| <input checked="" type="checkbox"/> Plus any applicable additional work listed at the end of this service sheet | | | | | | | | | | | | | | | | | | | |
| <input checked="" type="checkbox"/> Performed (check if performed) | | | | | | | | | | | | | | | | | | | Not OK ↓ |
| <input type="checkbox"/> Reset maintenance service indicator in instrument cluster | | | | | | | | | | | | | | | | | | | AP00.20-P-0042EW |
| <input type="checkbox"/> Engine - oil and filter change Engine 272, 273 | | | | | | | | | | | | | | | | | | | AP18.00-P-0101EW |
| <input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP88.40-P-8851EW |
| <input type="checkbox"/> Check condition of poly-V-belt Engine 272, 273 | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP13.22-P-1352EW |
| <input type="checkbox"/> Replace brake fluid | | | | | | | | | | | | | | | | | | | AP42.00-P-4280EW |
| <input type="checkbox"/> Replace combination or dust filter | | | | | | | | | | | | | | | | | | | AP83.00-P-8384EW |
| <input type="checkbox"/> Check thickness of brake pads, front and rear | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP42.10-P-4253A |
| <input type="checkbox"/> Correct tire inflation pressure and enter in bar or psi: LF RF LR RR bar/psi: _____ | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> |
| <input type="checkbox"/> Check inflation pressure in spare tire (if applicable) and enter in bar or psi: bar/psi: _____ | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> |
| <input type="checkbox"/> Leakage - Major components Check underbody and engine compartment for chafe marks, line routing, damaged components. | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP00.20-P-0053EW |
| <input type="checkbox"/> Visually inspect condition of front axle ball joints, rubber boots | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP33.20-P-3353EW |
| <input type="checkbox"/> Visually inspect condition of driveshaft flexible discs | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP41.10-P-4152EW |
| <input type="checkbox"/> Visually inspect condition of steering mechanical components, rubber boots | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP46.00-P-4653EW |
| Check the following fluid levels, correct if necessary | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Check coolant level | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AH20.00-P-1142-01V |
| <input type="checkbox"/> Brake system | | | | | | | | | | | | | | | | | | | <input type="checkbox"/> AP42.10-P-4210EW |

| | | | | | | | | | | | | | | | | | | | | | |
|--|---|-------|-------|-------|----|---------|-------|-------|-------|-------|--------|-------|-------|-------|-------|--------|-------|-------|-------|-------|--|
| <input type="checkbox"/> Power steering | | | | | | | | | | | | | | | | | | | | | |
| i The fluid level must always be on the maximum mark, corresponding to the oil temperature. | | | | | | | | | | | | | | | | | | | | | |
| Engine 272, 273 | <input type="checkbox"/> AP46.00-P-4611EW | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Windshield washer system | <input type="checkbox"/> AP82.35-P-8210EW | | | | | | | | | | | | | | | | | | | | |
| Function check | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Parking brake (function test only) | <input type="checkbox"/> | | | | | | | | | | | | | | | | | | | | |
| i Reminder: Reset maintenance service indicator in instrument cluster | AP00.20-P-0042EW | | | | | | | | | | | | | | | | | | | | |
| High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years | | | | | | | | | | | | | | | | | | | | | |
| <input checked="" type="checkbox"/> Performed (check if performed) | Not OK ↓ | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Replace wiper blades | | | | | | | | | | | | | | | | | | | | | |
| Electrical system checks | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Horn, high beam flasher, hazard warning flasher, turn signals | <input type="checkbox"/> | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Warning/indicator lamps, illumination and interior lighting/exterior lighting | <input type="checkbox"/> AP54.30-P-5452C | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Check trunk/cargo area lighting | <input type="checkbox"/> | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Check and correct headlamp setting | <input type="checkbox"/> AP82.10-P-8260EW | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Battery (main/starter/auxiliary) check condition using "Midtronics MCR 717" tester. Attach Midtronics MCR 717 Test Report print out here | <input type="checkbox"/> AP54.10-U-5453A | | | | | | | | | | | | | | | | | | | | |
| Visual and functional checks | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Check seat belts and buckles for signs of external damage and proper function | <input type="checkbox"/> AP91.40-P-9150EW | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Check windshield washer and headlamp cleaning system | <input type="checkbox"/> AP82.30-P-8252EW | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Check, clean, and lubricate tilt/sliding roof mechanism (where applicable) | <input type="checkbox"/> | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Check, clean, and lubricate panoramic roof mechanism (where applicable) | <input type="checkbox"/> AP77.20-P-7732EW | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Check bodywork for paintwork damage | <input type="checkbox"/> AP98.00-P-9850EW | | | | | | | | | | | | | | | | | | | | |
| Tire checks | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Tire rotation (where applicable) | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Inspect tires for damage, measure thread depth and enter in mm: | <input type="checkbox"/> AP40.10-P-4051EW | | | | | | | | | | | | | | | | | | | | |
| <table border="0"> <tr> <td></td> <td>LF</td> <td>RF</td> <td>LR</td> <td>RR</td> </tr> <tr> <td>outside</td> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> <tr> <td>center</td> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> <tr> <td>inside</td> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> </table> | | LF | RF | LR | RR | outside | _____ | _____ | _____ | _____ | center | _____ | _____ | _____ | _____ | inside | _____ | _____ | _____ | _____ | |
| | LF | RF | LR | RR | | | | | | | | | | | | | | | | | |
| outside | _____ | _____ | _____ | _____ | | | | | | | | | | | | | | | | | |
| center | _____ | _____ | _____ | _____ | | | | | | | | | | | | | | | | | |
| inside | _____ | _____ | _____ | _____ | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Check TIREFIT tire sealant expiration date (where applicable) | <input type="checkbox"/> AP40.10-P-4054EW | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Activate Tire Pressure Monitoring System; Refer to vehicle Operator's Manual | | | | | | | | | | | | | | | | | | | | | |
| Chassis checks | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Visually check brake system components, lines, hoses, calipers | <input type="checkbox"/> | | | | | | | | | | | | | | | | | | | | |

| | |
|---|---|
| <input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed | |
| Pads | <input type="checkbox"/> AP42.10-P-4253A |
| Discs | <input type="checkbox"/> AP42.10-P-4258EW |
| <input type="checkbox"/> Check chassis and load-bearing body components for damage and corrosion | <input type="checkbox"/> AP00.20-P-0090EW |
| High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years | |
| i Plus any applicable additional work listed at the end of this service sheet | |
| <input checked="" type="checkbox"/> Performed (check if performed) | Not OK ↓ |
| <input type="checkbox"/> Reset maintenance service indicator in instrument cluster | AP00.20-P-0042EW |
| <input type="checkbox"/> Engine - oil and filter change Engine 272, 273 | AP18.00-P-0101EW |
| <input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation | <input type="checkbox"/> AP88.40-P-8851EW |
| <input type="checkbox"/> Check thickness of brake pads, front and rear | <input type="checkbox"/> AP42.10-P-4253A |
| <input type="checkbox"/> Correct tire inflation pressure and enter in bar or psi: LF RF LR RR bar/psi: _____ | <input type="checkbox"/> |
| <input type="checkbox"/> Check inflation pressure in spare tire (if applicable) and enter in bar or psi: bar/psi: _____ | <input type="checkbox"/> |
| Check the following fluid levels, correct if necessary | |
| <input type="checkbox"/> Check coolant level | <input type="checkbox"/> AH20.00-P-1142-01V |
| <input type="checkbox"/> Brake system | <input type="checkbox"/> AP42.10-P-4210EW |
| <input type="checkbox"/> Power steering i The fluid level must always be on the maximum mark, corresponding to the oil temperature. Engine 272, 273 | <input type="checkbox"/> AP46.00-P-4611EW |
| <input type="checkbox"/> Windshield washer system | <input type="checkbox"/> AP82.35-P-8210EW |
| i Reminder: Reset maintenance service indicator in instrument cluster | AP00.20-P-0042EW |
| High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years | |
| <input checked="" type="checkbox"/> Performed (check if performed) | Not OK ↓ |
| <input type="checkbox"/> Replace wiper blades | |
| Electrical system checks | |
| <input type="checkbox"/> Horn, high beam flasher, hazard warning flasher, turn signals | <input type="checkbox"/> |
| <input type="checkbox"/> Warning/indicator lamps, illumination and interior lighting/exterior lighting | <input type="checkbox"/> AP54.30-P-5452C |
| <input type="checkbox"/> Check trunk/cargo area lighting | <input type="checkbox"/> |
| <input type="checkbox"/> Battery (main/starter/auxiliary) check condition using "Midtronics MCR 717" tester. Attach Midtronics MCR 717 Test Report print out here | <input type="checkbox"/> AP54.10-U-5453A |

| | | | | |
|---|-------|---|---|-------|
| Visual and functional checks | | | | |
| <input type="checkbox"/> Check windshield washer and headlamp cleaning system | | | <input type="checkbox"/> AP82.30-P-8252EW | |
| Tire checks | | | | |
| <input type="checkbox"/> Tire rotation (where applicable) | | | | |
| <input type="checkbox"/> Inspect tires for damage, measure thread depth and enter in mm: | | | <input type="checkbox"/> AP40.10-P-4051EW | |
| | LF | RF | LR | RR |
| outside | _____ | _____ | _____ | _____ |
| center | _____ | _____ | _____ | _____ |
| inside | _____ | _____ | _____ | _____ |
| <input type="checkbox"/> Check TIREFIT tire sealant expiration date (where applicable) | | | <input type="checkbox"/> AP40.10-P-4054EW | |
| <input type="checkbox"/> Activate Tire Pressure Monitoring System; Refer to vehicle Operator's Manual | | | | |
| Chassis checks | | | | |
| <input type="checkbox"/> Visually check brake system components, lines, hoses, calipers | | | <input type="checkbox"/> | |
| <input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed | | | | |
| Pads | | | <input type="checkbox"/> AP42.10-P-4253A | |
| Discs | | | <input type="checkbox"/> AP42.10-P-4258EW | |
| High Mileage Additional Work | | | | |
| <input checked="" type="checkbox"/> Performed (check if performed) | | | | |
| <input type="checkbox"/> Replace fuel filter | | | | |
| Engine 272, 273 | | If more than 150,000 mi or 15 years since last replacement | AP47.20-P-0780EW | |
| <input type="checkbox"/> Replace coolant | | | | |
| <input checked="" type="checkbox"/> i Observe correct coolant composition | | | | |
| Engine 272, 273 | | If more than 150,000 mi or 15 years since last replacement | AP20.00-P-2080EW | |
| <input type="checkbox"/> Automatic transmission - oil and filter change | | If more than 40,000 mi or 4 years since last replacement | AP27.00-P-2702W | |
| <input type="checkbox"/> Replace air filter | | | | |
| Engine 272, 273 | | If more than 40,000 mi or 4 years since last replacement | AP09.10-P-0980EW | |
| <input type="checkbox"/> Replace spark plugs | | | | |
| Engine 272, 273 | | If more than 80,000 mi or 8 years since last replacement | AP15.10-P-1580EW | |