

MODEL 204.0## (except 204.077) 1# , 204.2## (except 204.277) 1# , 204.3## (except 204.377) 1#
 with CODE 954 (Avantgarde)
 without CODE 233 (DISTRONIC PLUS)
 without CODE 239 (DISTRONIC PLUS and BAS PRO)

Illustrated on model 204.3

1 Illuminated Mercedes star



P88.40-3028-05

	Remove		
	Information on preventing damage to electronic components due to electrostatic discharge		AH54.00-P-0001-01A
1	Detach front SAM control unit with fuse and relay module and place to one side		
			AR54.21-P-1260CW
2	Remove radiator grille		AR88.40-P-4001CW
3	Remove Mercedes star in radiator grille	Mercedes star is no longer required.	
4	Move drivers seat toward rear		
5	Disconnect battery ground line		
			AR54.10-P-0003CW
6	Remove front left inner door sill		
7	Detach edge guard in area of door sill and A-pillar panel		
8	Remove A-pillar panel on left side at bottom		
9	Remove cover below left of instrument panel		
10	Remove accelerator pedal		
			AR30.12-P-1321CW
11	Remove left floor covering on front footwell		
	Install		
12	Install wiring harness and illuminated Mercedes star control unit (1)	New passenger car wiring harness repair kit Wiring harness repair kit, basic	AZ88.40-P-0010-01CW *220589049900 *000589139900
13	Install illuminated Mercedes star (1) and connect		
14	Install remaining parts		
15	Document retrofitted equipment via vehicle documentation (VeDoc)	Attach note "Illuminated Mercedes star retrofitted according to AZ88.40-P-0010CW" field organization texts for design group 88.	
16	Check illuminated Mercedes star (1) for proper function	The illuminated Mercedes star (1) is switched on by opening a door as well as by activating the ambient illumination. The illuminated star (1) switches off automatically approx. 5 minutes after a door is opened or after the ambient illumination is switched off	