

Mercedes-Benz

AP00.20-U-1208FD SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

MODEL 204 except AMG models

Passenger cars Model Year 2008





Customer:		Repair order number:		
First visit	at 1,000 - 3,000 miles	Performed	YES NO	
Tire Rotation (non-staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES NO	
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES NO	
Current mileage reading:			:	
Service work to be performed as advised by completion date: service advisor:		Confirm work has been performed by signing below:		

i

Service 4-20 apply to "Additional work" items only.

 $Vehicle\ determines\ need\ for\ Service\ 3\ (Engine\ oil\ and\ filter\ change)\ as\ well\ as\ Service\ A\ and\ Service\ B.$

Perform each service as described.

Service A		first at 13,000 mi or 1 year;	after first every 26,000 mi or 2 years	
A	Service	first at 26,000 mi or 2 years;	after first every 26,000 mi or 2 years	
\downarrow	B ↓		Not OK ↓	
		Interior - Required		
	0	Reset service indicator in instrument cluster		
		with CODE 442 (Luxury multifunction steering wheel)		AP00.20-P-0043A
		except CODE 442 (Luxury multifunction steering wheel)		AP00.20-P-0043B
	0	Replace combination filter		AP83.00-P-8384EW
	0	Check parking brake (function test only)		
601		Interior - Recommended		
		Function test		
	0	Horn		
	0	Warning/indicator lamps		AP54.30-P-5451CW
	0	Illumination and interior lighting		AP54.30-P-5453CW
	0	Windshield wipers, windshield washer system, headlamp cleaning system		AP82.30-P-8252CW
		Wheels, brakes - Required		
_	. 0	Check thickness of brake pads, front and rear		AP42.10-P-4253A
	0	Correct tire inflation pressure and enter in bar or psi. LF RF LR RR		AP40.15-P-4061A
		bar/psi:		
		Wheels, brakes - Recommended		
	0	Inspect tires for damage and splits, measu-		AP40.10-P-4051EW
		re tread depth, enter in mm: LF RF LR RR		
		outside		
		center inside		
		Underside of vehicle - Required		
Ť	Ŧ O	Leakage - Major components	П	AP00.20-P-0053CW
		Check for chafe marks, line routing, dama-		
		ged components i In the event of leakage, determine cau-		
		se and perform repair via separate work or- der		
	0	Check front axle ball joints for play, check rubber boots		AP33.20-P-3353CW
	0	Inspect condition of driveshaft flexible discs		AP41.10-P-4152CW
	0	Inspect play of tie rod and drag link joints, inspect rubber boots		AP46.00-P-4653CW

Service	Servi	ce		No	t OK	
A		B			↓	
160		<u>*</u>	Vehicle front/rear - Recommended		<u> </u>	
	(\mathcal{C}	Check and correct headlamp setting			AP82.10-P-8260CW
	(_	Check wiper blade condition		П	AP82.30-P-8253G
			Trunk - Required			7.11.02.00 7.02.00
	(Correct inflation pressure of spare tire and enter in bar or psi. bar/psi:			AP40.15-P-4061A
			Trunk - Recommended			
	(С	Check trunk lighting			
			Engine compartment - Required			
	(Leakage - Major components Check for chafe marks, line routing, damaged components in the event of leakage, determine cause and perform repair via separate work order			AP00.20-P-0053CW
	(C	Check condition of poly-V-belt			AP13.22-P-1352CW
	(C	Clean water deflector			AP82.35-P-8232A
			Check fluid level, correct as required ill f there is a loss of fluid, determine cause and perform repair via separate work order			
		C	Brake system			AP42.10-P-4210EW
	(C	Power steering	i The fluid level must always be on the maximum mark, corresponding to the oil temperature.		AP46.00-P-4612CW
	(_	Windshield washer system			AP82.35-P-8210CW
			(incl. summer/winter cleanser) Engine compartment - Recommended			
	(Check battery condition using Midtronics battery tester. Attach Midtronics test report print out here			AP54.10-U-5453A
			Additional Work			
Con	npleted	× ↓		N	ot OK ↓	
US Serv Requi			every 13,000 mi or 1 year: Engine compartment			
			Engine - oil and filter change			
			engine 272.948			AP18.00-P-0101VA
			engine 272.947/961			AP18.00-P-0101PIT
US Serv Requi			every 2 years: Engine compartment			
			Replace brake fluid			AP42.00-P-4280EW

Completed ⊠			Not OK	
↓			1	
US Service 4 Recommended	every 2 years:			
	Check bodywork for paint work damage by service advisor			AP98.00-P-9850CW
	Underside of vehicle			
	Chassis and load-bearing body components: Check for damage and corrosion by service advisor			AP00.20-P-0090SX
US Service 5 -7	not applicable			
US Service 8 Required	every 52,000 mi or 4 years: Engine compartment			
	Replace engine air-cleaner insert			AP09.10-P-0980CWZ
US Service 9	not applicable			
US Service 10 Recommended	every 39,000 mi or 3 years: Passenger compartment			
	Panoramic sliding roof - clean and lubricate quide mechanism with CODE 413 (Panoramic glass roof with top sliding roof)			AP77.20-P-7732CW
US Service 11 Required	every 143,000 mi or 15 years: Passenger compartment			
	Replace fuel filter			AP47.20-P-0780CWZ
US Service 12 Required	every 91,000 mi or 5 years: Engine compartment			
	Replace spark plugs	Engine 272		AP15.10-P-1580CWZ
US Service 13 Required	every 143,000 mi or 15 years: Engine compartment			
	Replace coolant			AP20.00-P-2080CW
US Service 14 - 19	not applicable			
US Service 20 Required	once at 39,000 mi: Underside of vehicle			
	Automatic transmission - oil and filter change			AP27.00-P-2702W