

AR68.20-P-2350LW	Remove/install cover on center console	07.04.2017
------------------	--	------------

Model	205 with transmission 722, 724, 725
Model	213 with transmission 725
Model	253 with transmission 724, 725


P68.20-4707-09



Shown on model 205 with code 581 (automatic air conditioning)

1	Center console cover	6	Electrical connector
2	Stowage box cover	7	Electrical connector
3	Bolts	8	Electrical connectors
4	Electrical connector	N58/1	Climate control operating unit
5	Electrical connector	N72/1	Upper control panel control unit

Topical notes=severity=N	Information on preventing damage to electronic components due to electrostatic discharge		Information on preventing damage to electronic components due to electrostatic discharge
☒☒	Remove/install		
1	Switch off ignition and store transmitter key outside of transmission range (min. 2 m)		
2	Remove stowage box cover (2)	Model 205 with transmission 722, 724, 725 Model 253 with transmission 724, 725	Remove/install cover on stowage box
		Model 213 with transmission 725	Remove/install cover on stowage box
3	Unscrew bolts (3) from center console cover (1)		
4	Lift center console cover (1) at rear and move out of instrument panel at top front until electrical connectors (4, 5) are accessible	⚠ Cover center console and instrument panel with a cloth. Otherwise, the center	

		console and instrument panel can be damaged.	
5	Disconnect electrical connector (4) from air conditioning operating unit (N58/1)	Model 205 with transmission 722, 724, 725 with code 581 (Automatic air conditioning) Model 213 with transmission 725 with code 581 (Automatic air conditioning) Model 253 with transmission 724, 725 with code 581 (Automatic air conditioning)	
6	Disconnect electrical connector (5) at upper control panel control unit (N72/1)		
7	Disconnect electrical connectors (6, 7, 8)	 The number can vary according to the equipment.	
8	Remove cover on center console (1)		
9	Install in the reverse order		