



Mercedes-Benz

AP00.20-U-1208FAD SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

MODEL 204
AMG models only

Passenger cars Model Year 2008
USA

Model 204 [Image of Mercedes-Benz Model 204 sedan]

Customer: _____ Repair order number: _____

First visit at 1,000 - 3,000 miles Performed YES [] NO []

Tire Rotation (non-staggered width wheel setup only) Performed in accordance with the tire manufacturer's recommended intervals Tires rotated YES [] NO []







Tire Inspection (staggered and non-staggered width wheel setup) Inspect tires for damage and correct tire inflation pressure Tires inspected YES [] NO []





Current mileage reading: _____ Oil grade/viscosity: _____

Additional notes: _____

Service work to be performed as advised by service advisor: _____ Completion date: _____ Confirm work has been performed by signing below: _____

[i] Service 4-20 apply to "Additional work" items only. Vehicle determines need for Service 3 (Engine oil and filter change) as well as Service A and Service B. Perform each service as described.

Service A ↓	Service B ↓	first at 10,000 mi or 1 year; after first every 20,000 mi or 2 years	first at 20,000 mi or 2 years; after first every 20,000 mi or 2 years	Not OK ↓
		Interior - Required		
<input type="checkbox"/>	<input type="radio"/>	Reset service indicator in instrument cluster		AP00.20-P-0042CV
	<input type="radio"/>	Replace combination filter		AP83.00-P-8384CW
	<input type="radio"/>	Check parking brake (function test only)	<input type="checkbox"/>	
		Interior - Recommended		
		Function check		
<input type="checkbox"/>	<input type="radio"/>	Indicator lamps in instrument cluster, interior illumination	<input type="checkbox"/>	AP54.30-P-5452C
<input type="checkbox"/>	<input type="radio"/>	Windshield wipers, windshield washer system, headlamp cleaning system	<input type="checkbox"/>	AP82.30-P-8252CW
		Wheels, brakes - Required		
<input type="checkbox"/>	<input type="radio"/>	Check thickness of brake pads, front and rear	<input type="checkbox"/>	AP42.10-P-4253A
<input type="checkbox"/>	<input type="radio"/>	Correct tire inflation pressure and enter in bar or psi.	<input type="checkbox"/>	
		LF RF LR RR		
		bar/psi: _____		
		Wheels, brakes - Recommended		
<input type="checkbox"/>	<input type="radio"/>	Inspect tires for damage and splits, measure tread depth, enter in mm:	<input type="checkbox"/>	AP40.10-P-4051CW
		LF RF LR RR		
		outside _____		
		center _____		
		inside _____		
		Underside of vehicle - Required		
	<input type="radio"/>	Leakage - Major components Check for chafe marks, line routing, damaged components <input type="checkbox"/> In the event of leakage, determine cause and perform repair via separate work order	<input type="checkbox"/>	AP00.20-P-0053CW
	<input type="radio"/>	Check front axle ball joints for play, check rubber boots	<input type="checkbox"/>	AP33.20-P-3353CW
	<input type="radio"/>	Inspect condition of driveshaft flexible discs	<input type="checkbox"/>	AP41.10-P-4152CW
	<input type="radio"/>	Inspect play of tie rod and drag link joints, inspect rubber boots	<input type="checkbox"/>	AP46.00-P-4653CW
		Vehicle front/rear - Recommended		
	<input type="radio"/>	Check and correct headlamp setting	<input type="checkbox"/>	AP82.10-P-8260CW
<input type="checkbox"/>	<input type="radio"/>	Check wiper blade condition	<input type="checkbox"/>	AP82.30-P-8253CW

Service A ↓	Service B ↓	Not OK ↓
	Trunk - Required	
<input type="checkbox"/>	<input type="radio"/> Correct inflation pressure of spare tire and enter in bar or psi. bar/psi: _____	<input type="checkbox"/>
	Trunk - Recommended	
<input type="checkbox"/>	<input type="radio"/> Check trunk lighting	<input type="checkbox"/>
	Engine compartment - Required	
	<input type="radio"/> Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order	<input type="checkbox"/> AP00.20-P-0053CW
	<input type="radio"/> Check condition of poly-V-belt Check fluid level, correct as required i If there is a loss of fluid, determine cause and perform repair via separate work order	<input type="checkbox"/> AP13.22-P-1352CW
<input type="checkbox"/>	<input type="radio"/> Brake system	<input type="checkbox"/> AP42.10-P-4210CW
	<input type="radio"/> Power steering	<input type="checkbox"/> AP46.00-P-4611CW
	<input type="radio"/> Windshield washer system (incl. summer/winter cleanser)	AP82.35-P-8210CW
	i The fluid level must always be on the maximum mark, corresponding to the oil temperature.	
	Engine compartment - Recommended	
<input type="checkbox"/>	<input type="radio"/> Check battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here.	<input type="checkbox"/> AP54.10-U-5453A
Additional Work		
Completed <input checked="" type="checkbox"/>		Not OK ↓
US Service 3 Required	every 10,000 mi or 1 year: Engine compartment	
	<input type="checkbox"/> Engine - oil and filter change	<input type="checkbox"/> AP18.00-P-0101CMG
US Service 4 Required	every 2 years: Engine compartment	
	<input type="checkbox"/> Replace brake fluid	AP42.00-P-4280CW
US Service 4 Recommended	every 2 years:	
	<input type="checkbox"/> Check bodywork for paint work damage by service advisor	<input type="checkbox"/> AP98.00-P-9850CW
	Underside of vehicle	
	<input type="checkbox"/> Chassis and load-bearing body components: Check for damage and corrosion by service advisor	<input type="checkbox"/> AP00.20-P-0090SX

Completed <input checked="" type="checkbox"/>	Not OK
↓	↓
US Service 5 - 7	not applicable
US Service 8 Required	every 40,000 mi or 4 years: Engine compartment
<input type="checkbox"/> Replace engine air-cleaner insert	AP09.10-P-0980CMG
US Service 9	not applicable
US Service 10 Recommended	every 40,000 mi or 3 years: Passenger compartment
<input type="checkbox"/> Panoramic sliding roof - clean and lubricate guide mechanism	AP77.20-P-7732CW
US Service 11 Required	every 150,000 mi or 15 years: Passenger compartment
<input type="checkbox"/> Replace fuel filter	AP47.20-P-0780CWZ
US Service 12 Required	every 60,000 mi or 5 years: Engine compartment
<input type="checkbox"/> Replace spark plugs	Engine 156 AP15.10-P-1580CMG
US Service 13 Required	every 150,000 mi or 15 years: Engine compartment
<input type="checkbox"/> Replace coolant	AP20.00-P-2080CW
US Service 14 - 19	not applicable
US Service 20 Required	once at 40,000 mi: Underside of vehicle
<input type="checkbox"/> Automatic transmission - oil and filter change	AP27.00-P-2702W