

Front : Left

Actual	Before	Specified Range	
-1.5°*	-1.6°*	-1.3°	-0.6°
5.5°	5.5°
0.19°	0.28°	0.12°	0.29°
.....
.....
.....	-1.25°	-0.25°

Front : Right

Actual	Before	Specified Range	
-1.5°*	-1.7°*	-1.3°	-0.6°
5.6°	5.6°
0.20°	0.28°	0.12°	0.29°
.....
.....
.....	-1.25°	-0.25°

Camber
Caster
Toe
SAI
Included Angle
Turning Angle Diff.

Front

	Actual	Before	Specified Range	
Cross Camber	0.1°	0.1°	-0.3°	0.3°
Cross Caster	-0.1°	-0.1°	-0.5°	0.5°
Total Toe	0.39°	0.55°	0.23°	0.57°

Rear : Left

Actual	Before	Specified Range	
-1.7°	-1.7°	-1.9°	-0.9°
0.28°	0.25°	0.03°	0.53°

Rear : Right

Actual	Before	Specified Range	
-1.8°	-1.8°	-1.9°	-0.9°
0.21°	0.23°	0.03°	0.53°

Rear

	Actual	Before	Specified Range	
Total Toe	0.49°	0.48°	0.30°	0.80°
Thrust Angle	0.03°	0.01°	-0.25°	0.25°

* This value is not within specification. Tire wear, handling and safety problems may result.