



Mercedes-Benz

AP00.20-U-1208TB SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model 219
except AMG models

Passenger cars Model Year 2007
USA

Model 219 [Image of Mercedes-Benz Model 219]

Customer: _____

Repair order number: _____

First visit at 1,000 - 3,000 miles Performed YES [] NO []

Tire Rotation (non staggered width wheel setup only) Performed in accordance with the tire manufacturer's recommended intervals Tires rotated YES [] NO []

Tire Inspection (staggered and non-staggered width wheel setup) Inspect tires for damage and correct tire inflation pressure Tires inspected YES [] NO []






Current mileage reading: _____





Oil grade/viscosity: _____

Additional notes: _____

Service work to be performed as advised by service advisor: _____ Completion date: _____ Confirm work has been performed by signing below: _____

[i] US Service 4 through US Service 20 apply to "Additional work" items only. Vehicle determines need for US Service 3 (Engine oil and filter change) as well as US Service 1 or US Service 2. Perform each service as described.

US Service 1 ↓	US Service 2 ↓	first at 13,000 mi or 1 year; after first every 26,000 mi or 2 years	first at 26,000 mi or 2 years; after first every 26,000 mi or 2 years	Not OK ↓
	Engine compartment - Required			
<input type="radio"/> Leakage - Major components Check for chafe marks, line routing, damaged components <i>i</i> In the event of leakage, determine cause and perform repair via separate work order		<input type="checkbox"/> AP00.20-P-0053TX		
<input type="radio"/> Check condition of poly-V-belt		<input type="checkbox"/> AP13.22-P-1352TZ		
<input type="checkbox"/>	<input type="radio"/> Check catch, safety catch and hinges on engine hood for proper operation.	<input type="checkbox"/> AP88.40-P-8851TX		
Check fluid level, correct as required <i>i</i> If there is a loss of fluid, determine cause and perform repair via separate work order				
<input type="checkbox"/>	<input type="radio"/> Brake system	<input type="checkbox"/> AP42.10-P-4210TX		
<input type="radio"/> Power steering		<input type="checkbox"/> AP46.00-P-4611TX		
<input type="checkbox"/>	<input type="radio"/> Windshield washer system (incl. summer/winter cleanser)	AP82.35-P-8210TX		
	Interior - Required			
<input type="checkbox"/>	<input type="radio"/> Reset service indicator in instrument cluster	AP00.20-P-0042TX		
Function test				
<input type="checkbox"/>	<input type="radio"/> Audible warning system	<input type="checkbox"/> AP54.30-P-5450TX		
<input type="radio"/> Check parking brake (function test only)		<input type="checkbox"/> AP42.00-P-4290TX		
	Interior - Recommended			
Function test				
<input type="checkbox"/>	<input type="radio"/> Horn	<input type="checkbox"/>		
<input type="checkbox"/>	<input type="radio"/> Warning/indicator lamps, illumination and interior lighting	<input type="checkbox"/> AP54.30-P-5452C		
<input type="checkbox"/>	<input type="radio"/> Windshield wipers, windshield washer system, headlamp cleaning system	<input type="checkbox"/> AP82.30-P-8252TX		
<input type="radio"/> Check seat belts and buckles for signs of external damage and proper function		<input type="checkbox"/> AP91.40-P-9150TX		
	Wheels, brakes - Required			
<input type="checkbox"/>	<input type="radio"/> Check thickness of brake pads, front and rear	<input type="checkbox"/> AP42.10-P-4253A		
<input type="checkbox"/>	<input type="radio"/> Correct tire inflation pressure and enter in bar or psi.	<input type="checkbox"/>		
bar/psi: <u> </u> <u> </u> <u> </u> <u> </u> LF RF LR RR				
	Wheels, brakes - Recommended			
<input type="radio"/> Remove and install wheels		<input type="checkbox"/> AP40.10-P-4050TX		

US Service 1 ↓	US Service 2 ↓	Not OK ↓
<input type="checkbox"/>	<input type="radio"/> Inspect tires for damage and splits, measure tread depth, enter in mm: LF RF LR RR outside _____ center _____ inside _____	<input type="checkbox"/> AP40.10-P-4051TX
	Underside of vehicle - Required <input type="radio"/> Leakage - Major components Check for chafe marks, line routing, damaged components <input type="checkbox"/> In the event of leakage, determine cause and perform repair via separate work order <input type="radio"/> Check front axle ball joints for play, check rubber boots <input type="radio"/> Inspect condition of driveshaft flexible discs <input type="radio"/> Inspect play of tie rod and drag link joints, inspect rubber boots	<input type="checkbox"/> AP00.20-P-0053TX <input type="checkbox"/> AP33.20-P-3353TX <input type="checkbox"/> AP41.10-P-4152TX <input type="checkbox"/> AP46.00-P-4653TX
	Vehicle front/rear - Recommended <input type="checkbox"/> <input type="radio"/> Check wiper blade condition <input type="checkbox"/> <input type="radio"/> Check and correct headlamp setting	<input type="checkbox"/> AP82.30-P-8253G <input type="checkbox"/> AP82.10-P-8260TX
	Trunk - Required <input type="checkbox"/> <input type="radio"/> Correct inflation pressure in spare tire and enter in bar or psi. bar/psi: _____	<input type="checkbox"/>
	Trunk - Recommended <input type="checkbox"/> <input type="radio"/> Check battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here. <input type="checkbox"/> <input type="radio"/> Check trunk lighting	<input type="checkbox"/> AP54.10-U-5453A <input type="checkbox"/>
Completed <input checked="" type="checkbox"/>		Not OK
	↓	↓
US Service 3 Required	every 13,000 mi or 1 year: Engine compartment <input type="checkbox"/> Engine - oil and filter change	<input type="checkbox"/> AP18.00-P-0101TX
US Service 4 Required	every 2 years: Engine compartment <input type="checkbox"/> Replace brake fluid	AP42.00-P-4280R
US Service 4 Recommended	every 2 years: <input type="checkbox"/> Check bodywork for paint work damage by service advisor Underside of vehicle <input type="checkbox"/> Chassis and load-bearing body components: Check for damage and corrosion by service advisor	<input type="checkbox"/> AP98.00-P-9850TX <input type="checkbox"/> AP00.20-P-0090SX

Completed <input checked="" type="checkbox"/>	Not OK
↓	↓
US Service 5 Required <input type="checkbox"/> every 26,000 mi or 2 years: Engine compartment <input type="checkbox"/> Replace combination filter	AP83.00-P-8384TX
US Service 6 & 7 not applicable	
US Service 8 Required <input type="checkbox"/> every 52,000 mi or 4 years: Engine compartment <input type="checkbox"/> Replace engine air-cleaner insert	AP09.10-P-0980TX
US Service 9 Recommended <input type="checkbox"/> every 5 years: Passenger compartment <input type="checkbox"/> Tilting/sliding roof: Clean slide rail and slide block	AP77.20-P-7731TX
US Service 10 not applicable	
US Service 11 Required <input type="checkbox"/> every 143,000 mi or 15 years: Passenger compartment <input type="checkbox"/> Replace fuel filter	AP47.20-P-0780TX
US Service 12 Required <input type="checkbox"/> every 91,000 mi or 5 years: Engine compartment <input type="checkbox"/> Replace spark plugs Engine 273	AP15.10-P-1580TY
US Service 13 Required <input type="checkbox"/> every 143,000 mi or 15 years: Engine compartment <input type="checkbox"/> Replace coolant	AP20.00-P-2080TX
US Service 14 - 19 not applicable	
US Service 20 Required <input type="checkbox"/> once at 39,000 mi: Underside of vehicle <input type="checkbox"/> Automatic transmission - oil and filter change	AP27.00-P-2702W