

Mercedes-Benz

AP00.20-U-1208T SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

MODEL 219

except AMG models

Passenger cars Model Year 2006

Model 219	
-----------	--

Customer:		Repair order number:	
First visit	at 1,000 - 3,000 miles	Performed	YES NO
Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES NO
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES NO
Current mileage reading:			:
Service work to be performed as advised by Completion date: Confirm work has been performed by signing below:			k has been performed by signing

i

US Service 4 through US Service 20 apply to "Additional work" items only. Vehicle determines need for US Service 3 (Engine oil and filter change) as well as US Service 1 or US Service 2.

Perform each service as described.

US Service		first at 13,000 mi or 1 year;	after first every 26,000 mi or 2 years	
1	US Service	first at 26,000 mi or 2 years;	after first every 26,000 mi or 2 years	
	2		Not OK	
Y	<u></u>	Engine compartment - Required	<u> </u>	
		Liigilie compartiilent - kequileu		
	0	Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053TX
	0	Check condition of poly-V-belt		AP13.22-P-1352TZ
	0	Check catch, safety catch and hinges on engine hood for proper operation.		AP88.40-P-8851TX
		Check fluid level, correct as required i If there is a loss of fluid, determine cause and perform repair via separate work order		
	0	Brake system		AP42.10-P-4210TX
	0	Power steering		AP46.00-P-4611TX
	0	Windshield washer system (incl. summer/winter cleanser)		AP82.35-P-8210TX
		Engine compartment - Recommended		
	0	Check auxiliary battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here.		AP54.10-U-5453A
		Interior - Required		
	0	Reset service indicator in instrument cluster Function test		AP00.20-P-0042TX
	0	Check parking brake (function test only)		AP42.00-P-4290TX
	0	Audible warning system	_	AP54.30-P-5450TX
	0	Check hydraulic unit of Sensotronic Brake Control (SBC)		AP42.50-P-4259TX
		Interior - Recommended		
		Function test		
	0	Horn, warning/indicator lamps, illumination and interior lighting		
	0	Windshield wipers, windshield washer system		AP82.30-P-8252TX
	0	Headlamp cleaning system		
	0	Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150TX
		Wheels, brakes - Required		
	0	Check thickness of brake pads, front and rear		AP42.10-P-4253A

US Service	US Service		Not OK	
1	2 ↓		1	
<u> </u>		Correct tire inflation pressure and enter in	<u>↓</u>	
	O	bar or psi.		
		LF RF LR RR		
		bar/psi:		
		Wheels, brakes - Recommended		
Ť	Ť _	Barrana and install subsets		A D 40 40 D 40 COTV
	0	Remove and install wheels		AP40.10-P-4050TX
	O	Inspect tires for damage and splits, measure tread depth, enter in mm:	Ц	AP40.10-P-4051TX
		LF RF LR RR		
		outside		
		center inside		
		Underside of vehicle - Required		
		onderside of remain mequined		
Τ '	1 0	Leakage - Major components		AP00.20-P-0053TX
		Check for chafe marks, line routing, dama-		
		ged components in the event of leakage, determine cau-		
		se and perform repair via separate work or-		
		der		
	0	Check front axle ball joints for play, check		AP33.20-P-3353TX
		rubber boots	_	
	0	'		AP41.10-P-4152TX
	O	Inspect play of tie rod and drag link joints, inspect rubber boots	Ц	AP46.00-P-4653TX
		Trunk - Required		
	0	Correct inflation pressure of spare tire and		
	O	enter in bar or psi.	ь	
		bar/psi:		
		Trunk - Recommended		
	0	Check main battery condition using "Mid-		AP54.10-U-5453A
		tronics MCR 717" Tester.		
		Attach Midtronics MCR 717 Test Report print out here.		
	0	Check trunk lighting		
<u> </u>	<u></u>	Vehicle front/rear - Recommended		
160±				
	0	Check wiper blade condition		AP82.30-P-8253G
	0	Check and correct headlamp setting		AP82.10-P-8260TX
Co	mpleted 🗵		Not OK	
	<u> </u>		↓	
US Ser Requ		every 13,000 mi or 1 year: Engine compartment		
Nequ	eu	Engine - oil and filter change	П	AP18.00-P-0101AF
US Ser		every 2 years:		10.00 1 0101A1
Requ		Engine compartment		
		Replace brake fluid		AP42.00-P-4280R
		Check preload pressure of pressure reser-		
		voir		

Completed ⊠		Not OK	
↓		↓	
US Service 4 Recommended	every 2 years:		
	Check bodywork for paint work damage by service advisor		AP98.00-P-9850TX
	Underside of vehicle		
	Chassis and load-bearing body components: Check for damage and corrosion by service advisor		AP00.20-P-0090SX
US Service 5 Required	every 26,000 mi or 2 years: Engine compartment		
	Replace combination filter		AP83.00-P-8384TX
US Service 6 & 7	not applicable		
US Service 8 Required	every 52,000 mi or 4 years: Engine compartment		
	Replace engine air-cleaner insert		AP09.10-P-0980TX
US Service 9 Recommended	every 5 years: Passenger compartment		
	Tilting/sliding roof: Clean slide rail and slide block		AP77.20-P-7731TX
US Service 10	not applicable		
US Service 11 Required	every 65,000 mi or 5 years: Underside of vehicle		
	Replace fuel filter		AP47.20-P-0780TX
US Service 12 Required	every 91,000 mi or 5 years: Engine compartment		
	Replace spark plugs		AP15.10-P-1580TY
US Service 13 Required	every 143,000 mi or 15 years: Engine compartment		
	Replace coolant		AP20.00-P-2080TX
US Service 14 - 19	not applicable		
US Service 20 Required	once at 39,000 mi: Underside of vehicle		
	Automatic transmission - oil and filter change		AP27.00-P-2702W