

Mercedes-Benz

AP00.20-U-1208TC SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

MODEL 219

except AMG models

Passenger cars Model Year 2008

USA

Model 219	0
-----------	---

Customer:		Repair order number:		
First visit	at 1,000 - 3,000 miles	Performed	YES NO	
Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES NO	
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES NO	
Current mileage reading: Additional notes:			r:	
Service work to be performed as advised by Completion date: Confirm work has been performed by signing below:			rk has been performed by signing	

i

US Service 4 through US Service 20 apply to "Additional work" items only.

Vehicle determines need for US Service 3 (Engine oil and filter change) as well as US Service 1 or US Service 2.

Perform each service as described.

US Service		first at 13,000 mi or 1 year;	after first every 26,000 mi or 2 years	
1	US Service	first at 26.000 mi or 2 years:	after first every 26,000 mi or 2 years	
	2	,	Not OK	
*	→		↓	
		Engine compartment - Required		
	0	Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053TX
	0	Check condition of poly-V-belt		AP13.22-P-1352TZ
	0	Check catch, safety catch and hinges on engine hood for proper operation.		AP88.40-P-8851TX
		Check fluid level, correct as required i If there is a loss of fluid, determine cause and perform repair via separate work order		
	0	Brake system		AP42.10-P-4210TX
	0	Power steering		AP46.00-P-4611TX
	0	Windshield washer system (incl. summer/winter cleanser)		AP82.35-P-8210TX
		Interior - Required		
	0	Reset service indicator in instrument cluster		AP00.20-P-0042TX
	0	Check parking brake (function test only)		
		Interior - Recommended		
		Function test		
	0	Horn		
	0	Warning/indicator lamps, illumination and interior lighting		AP54.30-P-5452C
	0	Windshield wipers, windshield washer system, headlamp cleaning system		AP82.30-P-8252TX
	0	Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150TX
		Wheels, brakes - Required		
	, 0	Check thickness of brake pads, front and rear		AP42.10-P-4253A
	0	Correct tire inflation pressure and enter in bar or psi.		
		LF RF LR RR bar/psi:		
		Wheels, brakes - Recommended		
	, O	Inspect tires for damage and splits, measure tread depth, enter in mm: LF RF LR RR outside		AP40.10-P-4051TX

US Service	US Serv	ice		Not OK	
1		2 ↓		↓	
50		<u>*</u>	Underside of vehicle - Required		
7 1	Ť	0	Leakage - Major components Check for chafe marks, line routing, damaged components in the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053TX
		0	Check front axle ball joints for play, check rubber boots		AP33.20-P-3353TX
		0	Inspect condition of driveshaft flexible discs		AP41.10-P-4152TX
		0	Inspect play of tie rod and drag link joints, inspect rubber boots		AP46.00-P-4653TX
ide)	Vehicle front/rear - Recommended		
		0	Check wiper blade condition		AP82.30-P-8253G
		0	Check and correct headlamp setting		AP82.10-P-8260TX
		(Trunk - Required		
		0	Correct inflation pressure in spare tire and enter in bar or psi. bar/psi:		
		Í	Trunk - Recommended		
		0	Check battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here.		
		0	Check trunk lighting		
Co	mpleted	⊠ ↓		Not OK ↓	
US Ser Requ			every 13,000 mi or 1 year: Engine compartment		
			Engine - oil and filter change		AP18.00-P-0101TX
US Ser Requ			every 2 years: Engine compartment		
			Replace brake fluid		AP42.00-P-4280T
US Ser Recomn			every 2 years:		
			Check bodywork for paint work damage by service advisor		AP98.00-P-9850TX
			Underside of vehicle Chassis and load-bearing body components: Check for damage and corrosion by service advisor		AP00.20-P-0090SX
US Ser	vice 5		not applicable		
US Ser Requ			every 26,000 mi or 2 years: Engine compartment		
			Replace combination filter		AP83.00-P-8384TX

Completed ⊠			Not OK
US Service 7	not applicable		*
US Service 8 Required	every 52,000 mi or 4 years: Engine compartment		
	Replace engine air-cleaner insert		AP09.10-P-0980TX
US Service 9 Recommended	every 5 years: Passenger compartment		
	Tilting/sliding roof: Clean slide rail and s de block	li-	AP77.20-P-7731TX
US Service 10	not applicable		
US Service 11 Required	every 143,000 mi or 15 years: Passenger compartment		
	Replace fuel filter		AP47.20-P-0780TX
US Service 12 Required	every 91,000 mi or 5 years: Engine compartment		
	Replace spark plugs	Engine 273	AP15.10-P-1580TX
US Service 13 Required	every 143,000 mi or 15 years: Engine compartment		
	Replace coolant		AP20.00-P-2080TX
US Service 14 - 19	not applicable		
US Service 20 Required	once at 39,000 mi: Underside of vehicle		
	Automatic transmission - oil and filter change		AP27.00-P-2702W