



Mercedes-Benz

AP00.20-U-1208T

SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

MODEL 219  
except AMG models

Passenger cars Model Year 2006  
USA

Model 219



Customer: \_\_\_\_\_

Repair order number: \_\_\_\_\_

First visit at 1,000 - 3,000 miles Performed YES  NO

Tire Rotation (non staggered width wheel setup only) Performed in accordance with the tire manufacturer's recommended intervals Tires rotated YES  NO

Tire Inspection (staggered and non-staggered width wheel setup) Inspect tires for damage and correct tire inflation pressure Tires inspected YES  NO

Current mileage reading: \_\_\_\_\_

Oil grade/viscosity: \_\_\_\_\_

Additional notes: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Service work to be performed as advised by service advisor:

Completion date:






Confirm work has been performed by signing below:

\_\_\_\_\_



US Service 4 through US Service 20 apply to "Additional work" items only.  
Vehicle determines need for US Service 3 (Engine oil and filter change) as well as US Service 1 or US Service 2.  
Perform each service as described.



US Service 1 ↓	US Service 2 ↓	Not OK ↓
<input type="checkbox"/>	<input type="radio"/> Correct tire inflation pressure and enter in bar or psi. LF      RF      LR      RR bar/psi:    _____	<input type="checkbox"/> AP40.15-P-4061B
	<b>Wheels, brakes - Recommended</b> <input type="checkbox"/> Remove and install wheels <input type="checkbox"/> Inspect tires for damage and splits, measure tread depth, enter in mm: LF      RF      LR      RR outside _____ center    _____ inside    _____	<input type="checkbox"/> AP40.10-P-4050TX <input type="checkbox"/> AP40.10-P-4051Z
	<b>Underside of vehicle - Required</b> <input type="radio"/> <b>Leakage - Major components</b> Check for chafe marks, line routing, damaged components <input type="checkbox"/> <b>i</b> In the event of leakage, determine cause and perform repair via separate work order <input type="radio"/> Check front axle ball joints for play, check rubber boots <input type="radio"/> Inspect condition of flexible discs <input type="radio"/> Inspect play of tie rod and drag link joints, inspect rubber boots	<input type="checkbox"/> AP00.20-P-0053TX <input type="checkbox"/> AP33.20-P-3353TX <input type="checkbox"/> AP41.10-P-4152TX <input type="checkbox"/> AP46.00-P-4653TX
	<b>Trunk - Required</b> <input type="checkbox"/> Correct inflation pressure of spare tire and enter in bar or psi. bar/psi: _____	<input type="checkbox"/> AP40.15-P-4061B
	<b>Trunk - Recommended</b> <input type="checkbox"/> Check main battery condition using Midtronics battery tester. Attach Midtronics test report print out here <input type="checkbox"/> Check trunk lighting	<input type="checkbox"/> AP54.10-U-5453A <input type="checkbox"/>
	<b>Vehicle front/rear - Recommended</b> <input type="checkbox"/> Check wiper blade condition <input type="checkbox"/> Check and correct headlamp setting	<input type="checkbox"/> AP82.30-P-8253G <input type="checkbox"/> AP82.10-P-8260TX
Completed <input checked="" type="checkbox"/>		Not OK
↓		↓
US Service 3 Required	<b>every 13,000 mi or 1 year:</b> <b>Engine compartment</b> <input type="checkbox"/> Engine - oil and filter change	<input type="checkbox"/> AP18.00-P-0101GH
US Service 4 Required	<b>every 2 years:</b> <b>Engine compartment</b> <input type="checkbox"/> Replace brake fluid Check preload pressure of pressure reservoir	AP42.00-P-4280R

Completed <input checked="" type="checkbox"/>	Not OK
↓	↓
<b>US Service 4</b> <b>Recommended</b> <b>every 2 years:</b> <input type="checkbox"/> Check bodywork for paint work damage <b>by service advisor</b> <b>Underside of vehicle</b> <input type="checkbox"/> Chassis and load-bearing body components: Check for damage and corrosion <b>by service advisor</b>	<input type="checkbox"/> AP98.00-P-9850TX  <input type="checkbox"/> AP00.20-P-0090SX
<b>US Service 5</b> <b>Required</b> <b>every 26,000 mi or 2 years:</b> <b>Engine compartment</b> <input type="checkbox"/> Replace combination filter	AP83.00-P-8384TX
<b>US Service 6 &amp; 7</b> <b>not applicable</b>	
<b>US Service 8</b> <b>Required</b> <b>every 52,000 mi or 4 years:</b> <b>Engine compartment</b> <input type="checkbox"/> Replace engine air-cleaner insert	AP09.10-P-0980TX
<b>US Service 9</b> <b>Recommended</b> <b>every 5 years:</b> <b>Passenger compartment</b> <input type="checkbox"/> Tilting/sliding roof: Clean slide rail and slide block <small>CODE 414 (Power glass tilting/sliding roof)</small>	AP77.20-P-7731TX
<b>US Service 10</b> <b>not applicable</b>	
<b>US Service 11</b> <b>Required</b> <b>every 65,000 mi or 5 years:</b> <b>Underside of vehicle</b> <input type="checkbox"/> Replace fuel filter	AP47.20-P-0780TX
<b>US Service 12</b> <b>Required</b> <b>every 91,000 mi or 5 years:</b> <b>Engine compartment</b> <input type="checkbox"/> Replace spark plugs	AP15.10-P-1580TY
<b>US Service 13</b> <b>Required</b> <b>every 143,000 mi or 15 years:</b> <b>Engine compartment</b> <input type="checkbox"/> Replace coolant	AP20.00-P-2080TX
<b>US Service 14 - 19</b> <b>not applicable</b>	
<b>US Service 20</b> <b>Required</b> <b>once at 39,000 mi:</b> <b>Underside of vehicle</b> <input type="checkbox"/> Automatic transmission - oil and filter change	AP27.00-P-2702W