

VALVOLINE™ ADVANCED FULL SYNTHETIC MOTOR OILS ILSAC GRADES (Formerly marketed in North America as Synpower™)

Valvoline Advanced Full Synthetic ILSAC Grades are premium full synthetic motor oils that are formulated with the highest quality synthetic base oils, and with premium additive chemistry, to meet the demanding requirements of turbo-charged and gasoline direct-injected engines. These oils are specifically formulated to provide high levels of fuel efficiency and deposit protection under severe service conditions.

Advantages:

- Innovative anti-wear additives to help reduce wear
- Extra detergent and dispersant to help reduce deposits, sludge, and varnish formation
- Enhanced thermal and oxidative stability
- Flows easily at low temperature for enhanced cold start protection

Approvals and Licenses:

	SAE 0W-16	SAE 0W-20	SAE 5W-20	SAE 5W-30	SAE 10W-30
API SN	X	X	X	X	X
API Resource Conserving	X	X	X	X	X
ILSAC GF-5	---	X	X	X	X
GM dexos1™ Gen2 (License #)	---	X D10193GL103	X D10194GL103	X D10195GL103	---

Additional Recommended Applications:

	SAE 0W-16	SAE 0W-20	SAE 5W-20	SAE 5W-30	SAE 10W-30
Ford WSS-M2C945-A	---	---	X	---	---
Ford WSS-M2C946-A	---	---	---	X	---
Ford WSS-M2C947-A	---	X	---	---	---
Chrysler MS-6395	---	X	X	X	X
GM 6094M & 4718M (Obsolete Specs)	---	---	X	X	X
ACEA A5/B5 (Gasoline Engines Only!)	---	---	---	X	---

Typical Properties:

	SAE 0W-16	SAE 0W-20	SAE 5W-20	SAE 5W-30	SAE 10W-30
KV100 (cSt)	6.8	8.1	8.1	10.2	10.8
KV40 (cSt)	34.4	42.2	46.5	60.1	66.8
Viscosity Index	163	167	147	158	151
Density (lbs/gal)	7.0	7.1	7.1	7.1	7.1
CCS (cP @ °C)	<6000@-35°C	<6000@-35°C	<6000@-30°C	<6000@-30°C	<6200@-25°C
Pour Point (°C)	≤ -39 °C	≤ -39 °C	≤ -36 °C	≤ -36 °C	≤ -33 °C
TBN (meq KOH/g)	9.3	9.3	9.3	9.3	9.3
Zinc (ppm)	830	830	830	830	830
Phosphorous (ppm)	760	760	760	760	760
Sulfated Ash (mass %)	0.97	0.97	0.97	0.97	0.97
Noack (% loss)	11.4	11.1	7.6	9.3	8.0

This information only applies to products manufactured in the following location(s): USA, Canada

Effective Date:
10/12/2017

Replaces:
09/22/2017

Author's Initials:
MW

Code
013

VALVOLINE™ ADVANCED FULL SYNTHETIC MOTOR OILS

NON-ILSAC GRADES (Formerly marketed in North America as Synpower™)

Valvoline Advanced Full Synthetic non-ILSAC Grades are premium full synthetic motor oils that are formulated with the highest quality synthetic base oils, and with premium additive chemistry, to meet the demanding requirements of European OEM's including Mercedes Benz, BMW, Volkswagen, and Porsche. Additionally, Advanced MST and Advanced XL-III are formulated for use in diesel passenger cars with particulate filters.

Approvals and Licenses:

	MST SAE 5W-30	MST SAE 5W-40	HST SAE 5W-40	XL-III SAE 5W-30	0W-40	20W-50
API SN	X	X	X	X	X	X
MB-Approval 229.5 ^(a)	---	---	X	---	X	---
MB-Approval 229.51 ^{(b),(d)}	X	X	---	X	---	---
MB-Approval 229.52	X	---	---	---	---	---
VW 505 01	X	X	---	---	---	---
VW 502 00 & 505 00	X	X	X	---	X	---
VW 504 00 & 507 00 ^(c)	---	---	---	X	---	---
BMW LL-01	---	---	X	---	X	---
BMW LL-04 ^(d)	X	X	---	X	---	---
Porsche A40	---	X	X	---	X	---
Porsche C30	---	---	---	X	---	---
GM dexos2™ (License #)	X GB2E0227103	X GB2E0511103	---	---	---	---
FCA MS-11106	X	---	---	---	---	---
Renault RN700 & RN710	---	---	---	---	X	---

Additional Recommended Applications:

	MST SAE 5W-30	MST SAE 5W-40	HST SAE 5W-40	XL-III SAE 5W-30	0W-40	20W-50
ACEA C3	X	X	---	X	---	---
ACEA A3/B3 & A3/B4	---	---	X	---	X	X
PSA B71 2296	---	---	X	---	---	---

Typical Properties:

	MST SAE 5W-30	MST SAE 5W-40	HST SAE 5W-40	XL-III SAE 5W-30	0W-40	20W-50 ^{(e),(f)}
KV100 (cSt)	12.2	13.1	13.5	11.7	13.5	19.0
KV40 (cSt)	70.6	79.0	82.0	68.1	77.0	139.0
Viscosity Index	171	167	168	168	180	155
Density (lbs/gal)	7.1	7.1	7.1	7.1	7.0	7.2
CCS (cP @ °C)	<6400@-30°C	<6400@-30°C	<6400@-30°C	<6200@-30°C	<6200@-35°C	<8500@-15°C
Pour Point (°C)	≤ -39 °C	≤ -39 °C	≤ -39 °C	≤ -39 °C	≤ -42 °C	≤ -30 °C

^(a) Valvoline products with MB-Approval 229.5 are also suitable for use in MB229.3 applications.

^(b) Valvoline products with MB-Approval 229.51 are also suitable for use in MB 229.31 applications

^(c) Valvoline products approved under VW Standard 504 00 / 507 00 can be used in VW 505 01 / 502 00 / 505 00 applications

^(d) In the United States

>Valvoline products with MB-Approval 229.51 can also be used in MB 229.5 and 229.3 applications

>Valvoline products with BMW LL-04 approval can also be used in BMW LL-01 applications

These recommendations are not valid in region(s) with lesser fuel quality

^(e) Advanced 20W-50 is also suitable for use in applications calling for the performance levels of MB 229.51 & 229.31, VW 502 00 & 505 00, or BMW LL-04

^(f) When in doubt, always defer to vehicle owner's manual for recommended viscosity grade and performance specification

This information only applies to products manufactured in the following location(s): USA, Canada

Effective Date:
10/12/2017

Replaces:
09/227/2017

Author's Initials:
MW

Code
012