

Mercedes-Benz

AP00.20-U-1208BH

SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model	Year	2012
USΔ		

Model 207



Customer:			Repair order nu	ımber:					
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommender likely necessitate tire rotation each 10,000-mile maintenation 10,000-mile maintenance s	on at least once in between ance service and at every	Tires rotated	YES	NO				
Note: For any co	ondition found while performi m the repair using a separate	ng the checks or inspections e repair order.	s included in this r	maintenance she	et, determine				
Current mileage read	ding:	grade/viscosity:	I grade/viscosity:						
Additional notes:									
Service work to be poservice advisor:	erformed as advised by	Completion date:	Confirm work has below:	s been performed	d by signing				

Required Service Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Reset maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
□ Engine - oil and filter change engine 276 engine 278		•	•	•	•	•	•	•	•	•	•	•	•	•	•	• •		AP18.00-P-0101CWZ AP18.00-P-0101EW
Check catch, safety catch and hinges on engine hood for proper operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP88.40-P-8851EW
☐ Check condition of poly-V-belt			•		•		•		•		•		•		•			AP13.22-P-1352EW
☐ Clean water deflector		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8232A
☐ Replace brake fluid			•		•		•		•		•		•		•			AP42.00-P-4280EW
Replace combination or dust filter			•		•		•		•		•		•		•			AP83.00-P-8384EW
☐ Check thickness of brake pads, front and rear		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4253A
☐ Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.15-P-4061A
☐ Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components			•		•		•		•		•		•		•			AP00.20-P-0053EW
☐ Visually inspect condition of front axle ball joints, rubber boots			•		•		•		•		•		•		•			AP33.20-P-3353CW
☐ Visually inspect condition of driveshaft flexible discs			•		•		•		•		•		•		•			AP41.10-P-4152EW
☐ Visually inspect condition of steering mechanical components, rubber boots			•		•		•		•		•		•		•			AP46.00-P-4653CW
Coolant - check fluid level and correct if necessary irefer to AH20.00-P-1142-01CW irefer to observe correct coolant composition		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Brake system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4210EW
☐ Power steering - check fluid level and correct if necessary except CODE 211 (Direct-Steer system) ☐ the fluid level must always be on the maximum mark, corresponding to the oil temperature		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP46.00-P-4612CC
☐ Windshield washer system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210EW
☐ Parking brake (function test only)			•		•		•		•		•		•		•			AP42.00-P-4290BA
Reset maintenance service indicator in instrument cluster I reminder - if not yet performed		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
Required Additional Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Replace air filter engine 276 engine 278					•				•				•					AP09.10-P-0980MM AP09.10-P-0980AB
Replace spark plugs							•						•					AP15.10-P-1580EW
☐ Automatic transmission - oil and filter change								•							•			AP27.00-P-2702W
☐ Replace fuel filter																•		AP47.20-P-0780EW

Required Additional Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Replace coolant Dobserve correct coolant composition																•		AP20.00-P-2080EW
Recommended Service miles (thousands) Work Performed years (check if performed)	2	10	20 2	30	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Replace combination or dust filter		•		•		•		•		•		•		•		•	•	AP83.00-P-8384EW
☐ Replace wiper blades		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Horn - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Warning/indicator lamps - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451CA
☐ Illumination and interior lighting - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5453CC
☐ Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.10-P-8252EW
☐ Check trunk/cargo area lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check and correct headlamp setting			•		•		•		•		•		•		•			AP82.10-P-8260EW
Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-U-5453A
Soft top - clean sealing and apply lubricant model 207.4		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP77.30-P-7736QA
☐ Check seat belts and buckles for signs of external damage and proper function			•		•		•		•		•		•		•			AP91.40-P-9150EC
☐ Check windshield washer and headlamp cleaning system		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.30-P-8252EW
Check, clean, and lubricate tilt/sliding roof mechanism where applicable			•		•		•		•		•		•		•			
Check, clean, and lubricate panoramic roof mechanism model 207.3 with CODE 413 (panoramic sliding sunroof)			•		•		•		•		•		•		•			AP77.20-P-7732EW
☐ Check bodywork for paintwork damage			•		•		•		•		•		•		•			AP98.00-P-9850EW
☐ Tire rotation where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Inspect tires for damage, measure thread depth and enter table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051EW
☐ Check TIREFIT tire sealant expiration date where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4054R
☐ Activate Tire Pressure Monitoring System ☐ refer to vehicle Operator's Manual		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Visually check brake system components, lines, hoses, calipers		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Check thickness of brake pads and discs, front and rear wheels removed																		104040
pads 		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4253A
discs		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	Ш	AP42.10-P-4258EW

Recommended Service Work	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Performed (check if performed)	years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK ↓	
Check chassis and load-l				•		•		•		•		•		•		•			AP00.20-P-0090EW
High Mileage Required	Service Work at 1	60,	000	mi	les	or	16 y	/ea	rs;	the	n e	every	20,	000	mile	s or	2 ye	ars	
Plus any applicable additional work listed at the end of the service sheet																			
☑ Performed Not OK (check if performed)																			
☐ Reset maintenance service indicator in instrument cluster AP00.20-P-0042EW																			
Engine - oil and filter change engine 276 engine 278 AP18.00-P-0101EW																			
												AP88.40-P-8851EW							
☐ Check condition of po																			AP13.22-P-1352EW
☐ Clean water deflector	•																		AP82.35-P-8232A
Replace brake fluid																			AP42.00-P-4280EW
Replace combination	or dust filter																		AP83.00-P-8384EW
☐ Check thickness of br		rea	ır																AP42.10-P-4253A
☐ Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet AP40.15-P-4061A																			
☐ Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components										AP00.20-P-0053EW									
											AP33.20-P-3353CW								
□ Visually inspect condition of driveshaft flexible discs												AP41.10-P-4152EW							
☐ Visually inspect condi	□ Visually inspect condition of steering mechanical components, rubber boots □ AP46.00-P-4653CW											AP46.00-P-4653CW							
Coolant - check fluid level and correct if necessary i refer to AH20.00-P-1142-01CW i observe correct coolant composition																			
☐ Brake system - check	fluid level and corre	ect	if ne	ece	ssaı	'n													AP42.10-P-4210EW
Power steering - chec except CODE 211 (Dir i the fluid level must	rect-Steer system)					•	rre	sno	ndir	na t	n tl	he oi	l tem	nera	nture				AP46.00-P-4612CC
☐ Windshield washer sy	•							•			<u> </u>	110 01	1 (011	ipoic	ituio				AP82.35-P-8210EW
☐ Parking brake (function		310	<u> </u>	<u> </u>	3110	00 11	110	-	<u>ou.</u>	<u>, </u>									AP42.00-P-4290BA
Reset maintenance s	ervice indicator in in	stru	ıme	nt o	clus	ter													AP00.20-P-0042EW
High Mileage Recomm		rk a	t 10	50.0	000	mil	es	or 1	16 v	ear	s:	then	eve	rv 2	0.00	0 m	iles (or 2 veai	'S
Plus any applicable									-					., _	-,	•		<u>-</u> ,	
Performed (check if performed)																		Not OK ↓	
Replace wiper blades	<u> </u>																		
☐ Horn - Electrical syste	em check																		
☐ Warning/indicator lam	ıps - Electrical syste	m c	chec	ck															AP54.30-P-5451CA
☐ Illumination and interi	or lighting - Electrica	al s	yste	m d	che	ck													AP54.30-P-5453CC
☐ Exterior lighting, high	beam flasher, haza	rd v	varr	ning	flas	she	r, tu	ırn s	sign	als	- E	Electr	ical	syste	em c	hecl	(AP82.10-P-8252EW
☐ Check trunk/cargo are	ea lighting																		
☐ Check and correct he	☐ Check trunk/cargo area lighting ☐ Check and correct headlamp setting												AP82.10-P-8260EW						

\square Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here		AP54.10-U-5453A
☐ Soft top - clean sealing and apply lubricant model 207.4		AP77.30-P-7736QA
☐ Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150EC
☐ Check windshield washer and headlamp cleaning system		AP82.30-P-8252EW
☐ Check, clean, and lubricate tilt/sliding roof mechanism where applicable		
☐ Check, clean, and lubricate panoramic roof mechanism model 207.3 with CODE 413 (panoramic sliding sunroof)		AP77.20-P-7732EW
☐ Check bodywork for paintwork damage		AP98.00-P-9850EW
☐ Tire rotation where applicable		
\square Inspect tires for damage, measure thread depth and enter table at the end of the service sheet		AP40.10-P-4051EW
☐ Check TIREFIT tire sealant expiration date where applicable		AP40.10-P-4054R
☐ Activate Tire Pressure Monitoring System ☐ refer to vehicle Operator's Manual		
☐ Visually check brake system components, lines, hoses, calipers		
☐ Check thickness of brake pads and discs, front and rear wheels removed		
pads		AP42.10-P-4253A
discs		AP42.10-P-4258EW
Check chassis and load-bearing body components for damage and corrosion		AP00.20-P-0090EW
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y	ears	
i Plus any applicable additional work listed at the end of the service sheet		
i Plus any applicable additional work listed at the end of the service sheet ⊠ Performed	Not OK	(
i Plus any applicable additional work listed at the end of the service sheet ⊠ Performed (check if performed)		
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster	Not OK	AP00.20-P-0042EW
i Plus any applicable additional work listed at the end of the service sheet ⊠ Performed (check if performed) □ Reset maintenance service indicator in instrument cluster □ Engine - oil and filter change	Not OK	AP00.20-P-0042EW
i Plus any applicable additional work listed at the end of the service sheet ⊠ Performed (check if performed) □ Reset maintenance service indicator in instrument cluster □ Engine - oil and filter change engine 276	Not OK	AP00.20-P-0042EW AP18.00-P-0101CWZ
 i Plus any applicable additional work listed at the end of the service sheet ☑ Performed (check if performed) ☐ Reset maintenance service indicator in instrument cluster ☐ Engine - oil and filter change engine 276 engine 278 	Not OK	AP00.20-P-0042EW
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 276 engine 278 Check catch, safety catch and hinges on engine hood for proper operation	Not OK	AP18.00-P-0101CWZ AP18.00-P-0101EW
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 276 engine 278 Check catch, safety catch and hinges on engine hood for proper operation Clean water deflector	Not OK	AP00.20-P-0042EW AP18.00-P-0101CWZ AP18.00-P-0101EW AP88.40-P-8851EW
 Plus any applicable additional work listed at the end of the service sheet ☑ Performed (check if performed) ☐ Reset maintenance service indicator in instrument cluster ☐ Engine - oil and filter change engine 276 engine 278 ☐ Check catch, safety catch and hinges on engine hood for proper operation ☐ Clean water deflector ☐ Check thickness of brake pads, front and rear ☐ Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of 	Not OK	AP00.20-P-0042EW AP18.00-P-0101CWZ AP18.00-P-0101EW AP88.40-P-8851EW AP82.35-P-8232A
 Plus any applicable additional work listed at the end of the service sheet ☑ Performed (check if performed) ☐ Reset maintenance service indicator in instrument cluster ☐ Engine - oil and filter change engine 276 engine 278 ☐ Check catch, safety catch and hinges on engine hood for proper operation ☐ Clean water deflector ☐ Check thickness of brake pads, front and rear 	Not OK	AP00.20-P-0042EW AP18.00-P-0101CWZ AP18.00-P-0101EW AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4253A
I Plus any applicable additional work listed at the end of the service sheet ☐ Performed (check if performed) ☐ Reset maintenance service indicator in instrument cluster ☐ Engine - oil and filter change engine 276 engine 278 ☐ Check catch, safety catch and hinges on engine hood for proper operation ☐ Clean water deflector ☐ Check thickness of brake pads, front and rear ☐ Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet ☐ Coolant - check fluid level and correct if necessary ☐ refer to AH20.00-P-1142-01CW	Not OK	AP00.20-P-0042EW AP18.00-P-0101CWZ AP18.00-P-0101EW AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4253A
I Plus any applicable additional work listed at the end of the service sheet ☐ Performed (check if performed) ☐ Reset maintenance service indicator in instrument cluster ☐ Engine - oil and filter change engine 276 engine 278 ☐ Check catch, safety catch and hinges on engine hood for proper operation ☐ Clean water deflector ☐ Check thickness of brake pads, front and rear ☐ Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet ☐ Coolant - check fluid level and correct if necessary I refer to AH20.00-P-1142-01CW I observe correct coolant composition	Not OK	AP00.20-P-0042EW AP18.00-P-0101CWZ AP18.00-P-0101EW AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4253A AP40.15-P-4061A

Reset maintenance service indicator in ins	trument cluster		AP00.20-P-0042EW								
	High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years										
i Plus any applicable additional work list											
☑ Performed		Not OF	(
(check if performed)											
Replace combination or dust filter			AP83.00-P-8384EW								
Replace wiper blades											
☐ Horn - Electrical system check											
☐ Warning/indicator lamps - Electrical system	n check		AP54.30-P-5451CA								
☐ Illumination and interior lighting - Electrical	system check		AP54.30-P-5453CC								
☐ Exterior lighting, high beam flasher, hazard	d warning flasher, turn signals - Electrical system check		AP82.10-P-8252EW								
☐ Check trunk/cargo area lighting											
☐ Battery (Main/starter/auxiliary) check cond report print out here	ition using Midtronics battery tester. Attach Midtronics test		AP54.10-U-5453A								
Soft top - clean sealing and apply lubricant model 207.4	t .		AP77.30-P-7736QA								
☐ Check windshield washer and headlamp c	leaning system		AP82.30-P-8252EW								
☐ Tire rotation where applicable											
☐ Inspect tires for damage, measure thread of	depth and enter table at the end of the service sheet		AP40.10-P-4051EW								
Check TIREFIT tire sealant expiration date where applicable	}		AP40.10-P-4054R								
☐ Activate Tire Pressure Monitoring System											
i refer to vehicle Operator's Manual											
☐ Visually check brake system components,	lines, hoses, calipers										
☐ Check thickness of brake pads and discs,	front and rear wheels removed										
pads			AP42.10-P-4253A								
discs			AP42.10-P-4258EW								
High Mileage Additional Work Performed (check if performed)											
Replace air filter											
engine 276	If more than 40,000 mi or 4 years since last replacement		AP09.10-P-0980MM								
engine 278	If more than 40,000 mi or 4 years since last replacement		AP09.10-P-0980AB								
Replace spark plugs	If more than 60,000 mi or 6 years since last replacement		AP15.10-P-1580EW								
Automatic transmission - oil and filter change	If more than 70,000 mi or 7 years since last replacement		AP27.00-P-2702W								
Replace fuel filter	If more than 150,000 mi or 15 years since last replacement		AP47.20-P-0780EW								
Replace coolant i observe correct coolant composition	If more than 150,000 mi or 15 years since last replacement		AP20.00-P-2080EW								

Tire inflation pressure (bar/psi)												
LF	RF	LR	RR	Spare								

Tire thread depth (mm)												
	LF	RF	LR	RR								
outside												
center												
inside												