

Mercedes-Benz

AP00.20-U-1208BG SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model	Year	2011	
ΠΟΔ			

Model 207



Customer:			Repair order nur	mber:	
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommender likely necessitate tire rotation each 10,000-mile maintenance succession of the second sec	on at least once in between ince service and at every	Tires rotated	YES	NO
Note: For any co	ondition found while performin m the repair using a separate	ng the checks or inspections e repair order.	included in this m	naintenance shee	t, determine
Current mileage read	ling:	Oi	I grade/viscosity:_		
Additional notes:					
_					
Service work to be poservice advisor:	erformed as advised by		Confirm work has below:	been performed	by signing

Required Service Work miles (thousands) Performed years (check if performed)	2	10	20	30	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Reset maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
☐ Engine - oil and filter change																		
engine 273		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101SX
engine 272		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101PIT
☐ Check catch, safety catch and hinges on engine hood for proper operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP88.40-P-8851EW
☐ Check condition of poly-V-belt			•		•		•		•		•		•		•			AP13.22-P-1352CW
☐ Clean water deflector		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8232A
Replace brake fluid			•		•		•		•		•		•		•			AP42.00-P-4280EW
Replace combination or dust filter			•		•		•		•		•		•		•			AP83.00-P-8384EW
☐ Check thickness of brake pads, front and rear		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4252CA
☐ Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.15-P-4061A
Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components			•		•		•		•		•		•		•			AP00.20-P-0053EW
☐ Visually inspect condition of front axle ball joints, rubber boots			•		•		•		•		•		•		•			AP33.20-P-3353CW
☐ Visually inspect condition of driveshaft flexible discs			•		•		•		•		•		•		•			AP41.10-P-4152EW
☐ Visually inspect condition of steering mechanical components, rubber boots			•		•		•		•		•		•		•			AP46.00-P-4653CW
☐ Coolant - check fluid level and correct if necessary ☐ refer to AH20.00-P-1142-01CW ☐ observe correct coolant composition		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Brake system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4210EW
Power steering - check fluid level and correct in necessary except CODE 211 (Direct-Steer system) If the fluid level must always be on the maximum mark, corresponding to the oil temperature	F	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP46.00-P-4612CC
☐ Windshield washer system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210EW
☐ Parking brake (function test only)			•		•		•		•		•		•		•			AP42.00-P-4290BA
Reset maintenance service indicator in instrument cluster irreminder - if not yet performed		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
Required Additional Work miles (thousands)	2	10	20	30	40	50	60	70	മറ	90	100	110	120	130	140	150		
Performed (check if performed)		1	2	3	4	5	6	7	8	9	100	110	12	13	140	150	Not OK ↓	
☐ Replace air filter					•				•				•					AP09.10-P-0980EW
☐ Automatic transmission - oil and filter change					•				•				•					AP27.00-P-2702W
☐ Replace spark plugs	İ						•						•					AP15.10-P-1580EW
Replace fuel filter	l															•		AP47.20-P-0780EW

Required Additional Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Replace coolant Dobserve correct coolant composition																•		AP20.00-P-2080EW
Recommended Service miles (thousands) Work	2	10	20 2	30	40 4	50 5			80 8	90			120		140 14		Not OK	
Performed years (check if performed)		1	2	3	4	5	6	7	°	9	10	11	12	13	14	15	WOLOK	
Replace combination or dust filter		•		•		•		•		•		•		•		•		AP83.00-P-8384EW
☐ Replace wiper blades		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Horn - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Warning/indicator lamps - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451CA
☐ Illumination and interior lighting - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5453CC
☐ Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.10-P-8252EW
☐ Check trunk/cargo area lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check and correct headlamp setting			•		•		•		•		•		•		•			AP82.10-P-8260EW
☐ Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-U-5453A
☐ Soft top - clean sealing and apply lubricant model 207.4		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP77.30-P-7736QA
☐ Check seat belts and buckles for signs of external damage and proper function			•		•		•		•		•		•		•			AP91.40-P-9150EC
☐ Check windshield washer and headlamp cleaning system		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.30-P-8252EW
☐ Check, clean, and lubricate tilt/sliding roof mechanism where applicable			•		•		•		•		•		•		•			
Check, clean, and lubricate panoramic roof mechanism model 207.3 with CODE 413 (panoramic sliding sunroof)			•		•		•		•		•		•		•			AP77.20-P-7732EW
☐ Check bodywork for paintwork damage			•		•		•		•		•		•		•			AP98.00-P-9850EW
☐ Tire rotation where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Inspect tires for damage, measure thread depth and enter table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051EW
☐ Check TIREFIT tire sealant expiration date where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4054R
☐ Activate Tire Pressure Monitoring System ☐ refer to vehicle Operator's Manual		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Visually check brake system components, lines, hoses, calipers		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check thickness of brake pads and discs, front and rear wheels removed																	_	
pads		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4252CA
discs		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4258EW

Recommended Service Work	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Performed (check if performed)	years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK ↓	
Check chassis and load-l				•		•		•		•		•		•		•			AP00.20-P-0090EW
High Mileage Required	Service Work at 1	60,	000	mi	les	or	16 y	/ea	rs;	the	n e	every	/ 20 ,	000	mile	s or	2 ye	ars	
l <u> </u>	i Plus any applicable additional work listed at the end of the service sheet																		
☑ Performed (check if performed) ✓																			
☐ Reset maintenance s	ervice indicator in in	stru	ıme	nt d	clus	ter													AP00.20-P-0042EW
□ Engine - oil and filter change engine 273 engine 272 AP18.00-P-0101SX AP18.00-P-0101PIT																			
	engine 272 AP18.00-P-0101P11 ☐ Check catch, safety catch and hinges on engine hood for proper operation AP88.40-P-8851EW											AP88.40-P-8851EW							
☐ Check condition of po									•										AP13.22-P-1352CW
☐ Clean water deflector	•																		AP82.35-P-8232A
Replace brake fluid																			AP42.00-P-4280EW
Replace combination	or dust filter																		AP83.00-P-8384EW
☐ Check thickness of br		rea	ır																AP42.10-P-4252CA
☐ Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet																			
Leakage - major compouting, damaged compo		derb	ody	/ ar	ıd e	ngi	ne d	com	par	tme	ent	for c	hafe	mar	ks, li	ine			AP00.20-P-0053EW
☐ Visually inspect condi	ition of front axle ba	II joi	ints	, ru	bbe	r bo	ots												AP33.20-P-3353CW
☐ Visually inspect condi	ition of driveshaft fle	xibl	e d	iscs	;														AP41.10-P-4152EW
☐ Visually inspect condi	ition of steering med	har	nica	l co	mp	one	nts	, rul	bbe	r bo	ot	S							AP46.00-P-4653CW
i refer to AH20.00-P	□ Visually inspect condition of steering mechanical components, rubber boots □ Coolant - check fluid level and correct if necessary ■ refer to AH20.00-P-1142-01CW ■ observe correct coolant composition																		
☐ Brake system - check	fluid level and corre	ect	if ne	ece	ssaı	'n													AP42.10-P-4210EW
Power steering - chec except CODE 211 (Dir i the fluid level must	rect-Steer system)						rre	sno	ndir	na t	n t	he oi	l tem	nera	ıture				AP46.00-P-4612CC
☐ Windshield washer sy	•							•					1 (011	iporc	itaro				AP82.35-P-8210EW
☐ Parking brake (function		310	<u> </u>	<u> </u>	3110	-	1110	-	<u>ou.</u>	<u>, </u>									AP42.00-P-4290BA
Reset maintenance s	ervice indicator in in	stru	ıme	nt o	clus	ter													AP00.20-P-0042EW
High Mileage Recomm		rk a	t 16	50.0	000	mil	es	or 1	16 v	ear	s:	ther	eve	rv 2	0.00	0 m	iles (or 2 veai	's
Plus any applicable									-					., _	-,	•		<u>-</u> ,	
Performed (check if performed)																		Not OK ↓	
Replace wiper blades	<u> </u>																		
☐ Horn - Electrical syste	em check																		
☐ Warning/indicator lam	ıps - Electrical syste	m c	chec	ck															AP54.30-P-5451CA
☐ Illumination and interi	or lighting - Electrica	al s	yste	m d	che	ck													AP54.30-P-5453CC
Exterior lighting, high	□ Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check □ AP82.10-P-8252EW										AP82.10-P-8252EW								
☐ Check trunk/cargo are	ea lighting																		
☐ Check and correct he	adlamp setting																		AP82.10-P-8260EW

☐ Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here		AP54.10-U-5453A
☐ Soft top - clean sealing and apply lubricant model 207.4		AP77.30-P-7736QA
☐ Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150EC
☐ Check windshield washer and headlamp cleaning system		AP82.30-P-8252EW
☐ Check, clean, and lubricate tilt/sliding roof mechanism where applicable		
☐ Check, clean, and lubricate panoramic roof mechanism model 207.3 with CODE 413 (panoramic sliding sunroof)		AP77.20-P-7732EW
☐ Check bodywork for paintwork damage		AP98.00-P-9850EW
☐ Tire rotation where applicable		
\square Inspect tires for damage, measure thread depth and enter table at the end of the service sheet		AP40.10-P-4051EW
☐ Check TIREFIT tire sealant expiration date where applicable		AP40.10-P-4054R
☐ Activate Tire Pressure Monitoring System ☐ refer to vehicle Operator's Manual		
☐ Visually check brake system components, lines, hoses, calipers		
☐ Check thickness of brake pads and discs, front and rear wheels removed		
pads		AP42.10-P-4252CA
discs		AP42.10-P-4258EW
Check chassis and load-bearing body components for damage and corrosion		AP00.20-P-0090EW
☐ Check chassis and load-bearing body components for damage and corrosion High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y		AP00.20-P-0090EW
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y I Plus any applicable additional work listed at the end of the service sheet	rears	
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y I Plus any applicable additional work listed at the end of the service sheet Performed	vears	
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y Plus any applicable additional work listed at the end of the service sheet Performed (check if performed)	rears	
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster	vears	ζ.
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y i Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster □ Engine - oil and filter change	vears	AP00.20-P-0042EW
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster	vears	ζ.
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y ☐ Plus any applicable additional work listed at the end of the service sheet ☐ Performed (check if performed) ☐ Reset maintenance service indicator in instrument cluster ☐ Engine - oil and filter change engine 273	vears	AP00.20-P-0042EW AP18.00-P-0101SX
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 273 engine 272 Check catch, safety catch and hinges on engine hood for proper operation	vears Not OK	AP18.00-P-0101SX AP18.00-P-0101PIT
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y i Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster □ Engine - oil and filter change engine 273 engine 272	vears Not OK	AP00.20-P-0042EW AP18.00-P-0101SX AP18.00-P-0101PIT AP88.40-P-8851EW
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y i Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 273 engine 272 Check catch, safety catch and hinges on engine hood for proper operation Clean water deflector	vears Not OK	AP00.20-P-0042EW AP18.00-P-0101SX AP18.00-P-0101PIT AP88.40-P-8851EW AP82.35-P-8232A
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y i Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 273 engine 272 Check catch, safety catch and hinges on engine hood for proper operation Clean water deflector Check thickness of brake pads, front and rear Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of	vears Not OK	AP00.20-P-0042EW AP18.00-P-0101SX AP18.00-P-0101PIT AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4252CA
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 273 engine 272 Check catch, safety catch and hinges on engine hood for proper operation Clean water deflector Check thickness of brake pads, front and rear Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet Coolant - check fluid level and correct if necessary I refer to AH20.00-P-1142-01CW	vears Not OK	AP00.20-P-0042EW AP18.00-P-0101SX AP18.00-P-0101PIT AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4252CA
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 273 engine 272 Check catch, safety catch and hinges on engine hood for proper operation Clean water deflector Check thickness of brake pads, front and rear Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet Coolant - check fluid level and correct if necessary I refer to AH20.00-P-1142-01CW I observe correct coolant composition	vears Not OK	AP00.20-P-0042EW AP18.00-P-0101SX AP18.00-P-0101PIT AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4252CA AP40.15-P-4061A

Reset maintenance service indicator in inst	trument cluster		AP00.20-P-0042EW							
i reminder - if not yet performed										
High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years										
i Plus any applicable additional work list	ed at the end of the service sheet		_							
Performed		Not OK	(
(check if performed)		<u> </u>								
Replace combination or dust filter			AP83.00-P-8384EW							
Replace wiper blades										
☐ Horn - Electrical system check										
☐ Warning/indicator lamps - Electrical system	n check		AP54.30-P-5451CA							
☐ Illumination and interior lighting - Electrical	system check		AP54.30-P-5453CC							
☐ Exterior lighting, high beam flasher, hazard	warning flasher, turn signals - Electrical system check		AP82.10-P-8252EW							
☐ Check trunk/cargo area lighting										
☐ Battery (Main/starter/auxiliary) check condi report print out here	tion using Midtronics battery tester. Attach Midtronics test		AP54.10-U-5453A							
Soft top - clean sealing and apply lubricant model 207.4			AP77.30-P-7736QA							
☐ Check windshield washer and headlamp cl	eaning system		AP82.30-P-8252EW							
☐ Tire rotation where applicable										
☐ Inspect tires for damage, measure thread of	depth and enter table at the end of the service sheet		AP40.10-P-4051EW							
Check TIREFIT tire sealant expiration date where applicable			AP40.10-P-4054R							
Activate Tire Pressure Monitoring System i refer to vehicle Operator's Manual										
☐ Visually check brake system components,	lines, hoses, calipers									
Check thickness of brake pads and discs, f	·									
pads	Total and Total Wilcold Total Code		AP42.10-P-4252CA							
discs			AP42.10-P-4258EW							
High Mileage Additional Work										
Performed (check if performed)										
Replace air filter	If more than 40,000 mi or 4 years since last replacement		AP09.10-P-0980EW							
Automatic transmission - oil and filter change	If more than 40,000 mi or 4 years since last replacement		AP27.00-P-2702W							
Replace spark plugs	If more than 60,000 mi or 6 years since last replacement		AP15.10-P-1580EW							
Replace fuel filter	If more than 150,000 mi or 15 years since last replacement		AP47.20-P-0780EW							
Replace coolant	If more than 150,000 mi or 15 years since last replacement		AP20.00-P-2080EW							
i observe correct coolant composition										