AR88.70-P-9020CW Remove/install mirror glass 18.3.09

MODEL 204

MODEL 203.7## #E with CODE (809) Model year 2009


MODEL 207 MODEL 212


Shown on model 204 with code (249) Automatically dimming inside and outside mirror including folding outside mirror

1 Mirror glass2 Catch hook

3 Electrical connectors4 Electrical connector

M21/1 Left outside mirror M21/2 Right outside mirror





P88.70-2538-04

XX	Remove/install		
⚠ Danger!	Risk of injury Skin, eye and respiratory system irritation may occur through contact or inhalation of substances contained in the mirror lens	Wear protective gloves and safety glasses.	AS60.00-Z-0008-01R
1	Tilt out mirror lens (1) upward		
2	Manually pull mirror glass (1) with a jerk toward rear and unclip from left outside mirror (M21/1) or right outside mirror (M21/2)	When unclipping ensure that the mirror glass (1) does not break. I Installation: Clip mirror glass (1) from bottom upward into left outside mirror (M21/1) or right outside mirror (M21/2). Ensure that catch hooks (2) arrest completely.	
3	Disconnect electrical connectors (3, 4)and remove mirror glass (1)	The number of electrical connectors (3, 4) depends on the vehicle equipment.	
4	Install in the reverse order		