




P82.62-3512-09

**Shown with removed rear shelf**

- 1 Screw  
2 Foam material  
3 Catch hook  
4 Bracket

- 5 Electrical connector  
6 Screw  
H4/29 Rear shelf bass speaker

- H4/29x1 Bass speaker electrical connector  
H4/54 Left rear surround speaker  
H4/57 Right rear surround speaker

 	Remove/install		
	Information on preventing damage to electronic components due to electrostatic discharge		<a href="#">AH54.00-P-0001-01A</a>
1.1	Remove rear shelf	On vehicles without code (540) Roller sun blind	<a href="#">AR68.30-P-4580EC</a>
1.2	Detach and lift rear shelf, until the rear shelf bass speaker (H4/29) with right rear surround speaker (H4/57) or left rear surround speaker (H4/54) is accessible	On vehicles with code (540) Roller sun blind	<a href="#">AR68.30-P-4580EC</a>
2	Fold foam (2) to rear, until the rear shelf bass speaker (H4/29) with right rear surround speaker (H4/57) or left rear surround speaker (H4/54) is accessible	On vehicles with code (540) Roller sun blind	
3	Open catch hooks (3) and release holder (4) for left rear surround speaker (H4/54) by turning in clockwise direction	When removing left rear surround speaker (H4/54).	
4	Lift left rear surround speaker (H4/54), detach electrical connector (5) and remove left rear surround speaker (H4/54)	When removing left rear surround speaker (H4/54).	
5	Detach electrical connector for bass speaker (H4/29x1)	When removing the rear shelf bass speaker (H4/29) with right rear surround speaker (H4/57).	
6	Remove bolt (6)	When removing the rear shelf bass speaker (H4/29) with right rear surround speaker (H4/57).	
7	Remove screws (1) and then remove rear shelf bass speaker (H4/29) with right rear surround speaker (H4/57)	When removing the rear shelf bass speaker (H4/29) with right rear surround speaker (H4/57).	
8	Install in the reverse order		