

Mercedes-Benz

AP00.20-U-1208BL

SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model Year 201 USA	6	Model 207								
Customer:			Repair order nur	nber:						
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommende likely necessitate tire rotati each 10,000-mile maintena 10,000-mile maintenance s	on at least once in between ance service and at every	Tires rotated	YES	NO					
Note: For any contract the cause and performed	ondition found while performi m the repair using a separat	ng the checks or inspection e repair order.	s included in this n	naintenance shee	t, determine					
Current mileage read	ding:		il grade/viscosity:_							
Additional notes:										
Service work to be p service advisor:	erformed as advised by	Completion date:	Confirm work has below:	been performed	by signing					

Mercedes-Benz USA, LLC Reproduction or translation in whole or in part is not permitted without written authorization from the publisher. 1-800-FOR-MERCedes

Required Service Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Reset Maintenance service indicator in in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
Replace combination filter			•		•		•		•		•		•		•			AP83.00-P-8384EW
Brake system (function test)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.00-P-4290BA
Check condition of poly-V-belt			•		•		•		•		•		•		•			AP13.22-P-1352CW
Engine – oil and filter change																		
engine 276		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101CWZ
engine 278		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101EW
Check thickness of brake pads front and rear		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4252CA
□ Check and correct all tire air pressures, including spare where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.15-P-4061A
\Box Check vehicle underside for damage and leaks			•		•		•		•		•		•		٠			AP00.20-P-0054EW
Check visible parts in engine compartment for damage and leaks			•		•		•		•		•		•		•			AP00.20-P-0055EW
□ Inspect front axle joints for play inspect rubber boots			•		•		•		•		•		•		•			AP33.20-P-3353CW
□ Inspect track rod and drag link of play, rubber boots			•		•		•		•		•		•		•			AP46.00-P-4653CW
□ Inspect driveshaft flexible discs			•		•		•		٠		٠		•		٠			AP41.10-P-4152EW
Check catch, safety catch, and hinges on engine hood for proper operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP88.40-P-8851EW
□ Clean visible area of water deflector		٠	•	٠	•	•	•	•	٠	٠	•	•	•	•	٠	•		AP82.35-P-8232A
Check coolant level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP20.30-P-2050EW
Check power steering fluid level and correct if necessary except CODE 211 (Direct-Steer system)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP46.00-P-4612CC
Check windshield washer system fluid, correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210EW
Check brake fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4210EW
□ Replace brake fluid			•		•		•		•		•		•		•			AP42.00-P-4280EW
Reset Maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
Required Additional Work miles (thousands) Performed years (check if performed) years	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ✔	
□ Replace air filter engine 276																•		AP09.10-P-0980E
engine 278																		AP09.10-P-0980AB
Replace spark plugs					-		-		-							•		AP15.10-P-1580EW
Automatic transmission-oil and filter change			-			-	•				-		•			-		AP27.00-P-2702W
							-						-			•		AP47.20-P-0780EW
Replace coolant					-		-											AP20.00-P-2080EW
Replace coolant observe correct coolant composition																		
Recommended Service miles (thousands) Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK	
		-	-	-	-		-	_	_		-	-	-	-	_	-	<u> </u>	
		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AD54 30 D 54540A
Check warning/indicator lamps		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451CA

Recommended Service miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Work		1	2	3	4	5	6	7	8	9	10	11	12	13		15	Not OK	
Performed years (check if performed)			2	3	4	Э	0	<i>'</i>	°	9	10	''	12	13	14	15		
	-	_			_		_		_						_	-		AP54.30-P-5453CC
Check illumination and interior lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Check windshield and headlamp washer system operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.30-P-8252EW
Replace wiper blades		٠	•	٠	•	•	٠	٠	•	٠	•	•	•	•	•	•		
Activate Tire Pressure Monitoring System		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Clean and lubricate soft top seal model 207.4			•		•		•		•		•		•		•			AP77.30-P-7736QA
□ Check, clean and lubricate panoramic roof mechanism model 207.3 with CODE 413 (panoramic sliding sunroof)			•		•		•		•		•		•		•			AP77.20-P-7732EW
□ Check for body paint damage			•		•		•		•		•		•		•			AP98.00-P-9850EW
Check all exterior lights		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.10-P-8252EW
Check trunk / cargo area light		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Check TIREFIT tire sealant expiration date (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4054R
Check headlamp setting, correct if necessary			•		•	1	•		•		•		•		•			AP82.10-P-8260EW
Check battery condition Attach printout to sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-U-5453A
Check condition and function of trailer hitch with CODE 550 (Trailer hitch)			•		•		•		•		•		•		•			AP31.11-P-3152EW
□ Tire rotation (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Check thickness of brake pads and discs, front and rear wheels removed																		
pads		•	•	٠	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4252CA
discs		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4258EW
□ Visually inspect brake system components, lines, hoses, calipers		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
□ Inspect tires for damage and measure remaining tread life		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051EW
Check chassis and load bearing body components for damage and corrosion		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0090EW
High Mileage Required Service Work at 1	60,	000	mi	les	or	16 y	yea	rs;	the	n ev	very	20,0	000	mile	s or	2 ye	ars	
I Plus any applicable additional work li	stee	d at	th	e er	nd d	of th	ne s	serv	vice	sh	eet							
Performed																	Not OK	
(check if performed)																	↓	
Reset Maintenance service indicator in ir	nstru	ume	ent o	clus	ter													AP00.20-P-0042EW
Replace combination filter																		AP83.00-P-8384EW
Brake system (function test)																		AP42.00-P-4290BA
Check condition of poly-V-belt																		AP13.22-P-1352CW
\Box Engine – oil and filter change																		
5										AP18.00-P-0101CWZ								
engine 278																		AP18.00-P-0101EW
Check thickness of brake pads front and	rea	r																AP42.10-P-4252CA
Check and correct all tire air pressures, i	nclu	Idin	g sl	bare	e wl	here	e ap	plic	able	е								AP40.15-P-4061A
Check vehicle underside for damage and	l lea	iks																AP00.20-P-0054EW
Check visible parts in engine compartme	nt fo	or d	am	ade	an	d le	aks											AP00.20-P-0055EW
Check visible parts in engine compartment for damage and leaks																		
Inspect front axle joints for play inspect r																		AP33.20-P-3353CW

□ Inspect driveshaft flexible discs		AP41.10-P-4152EW
Check catch, safety catch, and hinges on engine hood for proper operation		AP88.40-P-8851EW
Clean visible area of water deflector		AP82.35-P-8232A
Check coolant level and correct if necessary		AP20.30-P-2050EW
i observe correct coolant composition		
Check power steering fluid level and correct if necessary except CODE 211 (Direct-Steer system)		AP46.00-P-4612CC
Check windshield washer system fluid, correct if necessary		AP82.35-P-8210EW
Check brake fluid level and correct if necessary		AP42.10-P-4210EW
Replace brake fluid		AP42.00-P-4280EW
Reset Maintenance service indicator in instrument cluster		AP00.20-P-0042EW
i reminder - if not yet performed		
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mil	les or 2 yea	ars
I Plus any applicable additional work listed at the end of the service sheet Performed	Not OK	c
(check if performed)	₩01 01	·
Check warning/indicator lamps		AP54.30-P-5451CA
Check illumination and interior lighting		AP54.30-P-5453CC
Check windshield and headlamp washer system operation		AP82.30-P-8252EW
Replace wiper blades		
Activate Tire Pressure Monitoring System		
i refer to vehicle Operator's Manual		
Clean and lubricate soft top seal model 207.4		AP77.30-P-7736QA
Check, clean and lubricate panoramic roof mechanism model 207.3 with CODE 413 (panoramic sliding sunroof)		AP77.20-P-7732EW
Check for body paint damage		AP98.00-P-9850EW
Check all exterior lights		AP82.10-P-8252EW
Check trunk / cargo area light		
Check TIREFIT tire sealant expiration date (where applicable)		AP40.10-P-4054R
Check headlamp setting, correct if necessary		AP82.10-P-8260EW
Check battery condition Attach printout to sheet		AP54.10-U-5453A
Check condition and function of trailer hitch with CODE 550 (Trailer hitch)		AP31.11-P-3152EW
Tire rotation (where applicable)		
Check thickness of brake pads and discs, front and rear wheels removed		
pads		AP42.10-P-4252CA
	<u> </u>	AP42.10-P-4258EW
Uvisually inspect brake system components, lines, hoses, calipers		AP40.10-P-4051EW
Unspect tires for damage and measure remaining tread life		AP40.10-P-4031EW AP00.20-P-0090EW
Check chassis and load bearing body components for damage and corrosion		
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or	∠ years	
Plus any applicable additional work listed at the end of the service sheet Performed	Not OK	(
(check if performed)	\mathbf{V}	
Reset Maintenance service indicator in instrument cluster		AP00.20-P-0042EW
Brake system (function test)		AP42.00-P-4290BA

Engine – oil and filter change			
engine 276			AP18.00-P-0101CWZ
engine 278			AP18.00-P-0101EW
Check thickness of brake pads front and re	ar		AP42.10-P-4252CA
Check and correct all tire air pressures, inc	luding spare where applicable		AP40.15-P-4061A
Check catch, safety catch, and hinges on e	ngine hood for proper operation		AP88.40-P-8851EW
Clean visible area of water deflector			AP82.35-P-8232A
Check coolant level and correct if necessar	у		AP20.30-P-2050EW
i observe correct coolant composition	- -		
Check power steering fluid level and correct except CODE 211 (Direct-Steer system)	t if necessary		AP46.00-P-4612CC
Check windshield washer system fluid, corr	rect if necessary		AP82.35-P-8210EW
Check brake fluid level and correct if neces	sary		AP42.10-P-4210EW
Reset Maintenance service indicator in inst	•		AP00.20-P-0042EW
I reminder - if not yet performed			
High Mileage Recommended Service Work	at 170,000 miles or 17 years; then every 20,000 miles	s or 2 yea	ars
I Plus any applicable additional work list	ed at the end of the service sheet		
I Performed		Not Of	K
(check if performed)		4	
Check horn			
Check warning/indicator lamps			AP54.30-P-5451CA
Check illumination and interior lighting			AP54.30-P-5453CC
Check windshield and headlamp washer sy	/stem operation		AP82.30-P-8252EW
Replace wiper blades			
Activate Tire Pressure Monitoring System			
i refer to vehicle Operator's Manual			
Check all exterior lights			AP82.10-P-8252EW
Check trunk / cargo area light			
Check TIREFIT tire sealant expiration date	(where applicable)		AP40.10-P-4054R
Check battery condition Attach printout to s	heet		AP54.10-U-5453A
Tire rotation (where applicable)			
Check thickness of brake pads and discs, f	ront and rear wheels removed		
pads			AP42.10-P-4252CA
discs			AP42.10-P-4258EW
□ Visually inspect brake system components	lines, hoses, calipers		
□ Inspect tires for damage and measure remain	aining tread life		AP40.10-P-4051EW
Check chassis and load bearing body com	ponents for damage and corrosion		AP00.20-P-0090EW
High Mileage Additional Work			
Performed			
(check if performed)			
Replace air filter engine 276	If more than 50,000 miles or 5 years since last replacement		AP09.10-P-0980E
engine 278	If more than 50,000 miles or 5 years since last replacement		AP09.10-P-0980AB
Replace spark plugs	If more than 50,000 miles or 5 years since last replacement		AP15.10-P-1580EW
Automatic transmission-oil and filter change	If more than 60,000 miles or 6 years since last replacement		AP27.00-P-2702W
	If more than 150,000 miles or 15 years since last replacement		AP47.20-P-0780EW

Replace coolant

i observe correct coolant composition

Tire inflation pressure (bar/psi)											
LF	RF LR RR Spare										

Tire thread depth (mm)											
	LF	RF	LR	RR							
outside											
center											
inside											