

## Mercedes-Benz

AP00.20-U-1208BJ SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model Year 201 USA		del 207		
Customer:		Repair order num	nber:	
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommended tire rotation interval will likely necessitate tire rotation at least once in between each 10,000-mile maintenance service and at every 10,000-mile maintenance service.	Tires rotated	YES [	NO
Note: For any co	ondition found while performing the checks or inspections in the repair using a separate repair order.	s included in this m	aintenance	sheet, determine
Current mileage read	ding:O	il grade/viscosity:_		
Additional notes: _				

service advisor:

Service work to be performed as advised by

Completion date:

below:

Confirm work has been performed by signing

Required Service Work miles (thousands)  Performed years (check if performed)	2	10 1	20 2	30	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK <b>↓</b>	
Reset maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
☐ Engine - oil and filter change engine 276 engine 278		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101CWZ AP18.00-P-0101EW
☐ Check catch, safety catch and hinges on engine hood for proper operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP88.40-P-8851EW
☐ Check condition of poly-V-belt			•		•		•		•		•		•		•			AP13.22-P-1352EW
☐ Clean visible area of water deflector		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8232A
☐ Replace brake fluid			•		•		•		•		•		•		•			AP42.00-P-4280EW
Replace combination or dust filter			•		•		•		•		•		•		•			AP83.00-P-8384EW
☐ Check thickness of brake pads, front and rear		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4253A
☐ Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.15-P-4061A
☐ Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components			•		•		•		•		•		•		•			AP00.20-P-0053EW
☐ Visually inspect condition of front axle ball joints, rubber boots			•		•		•		•		•		•		•			AP33.20-P-3353CW
☐ Visually inspect condition of driveshaft flexible discs			•		•		•		•		•		•		•			AP41.10-P-4152EW
☐ Visually inspect condition of steering mechanical components, rubber boots			•		•		•		•		•		•		•			AP46.00-P-4653CW
Coolant - check fluid level and correct if necessary  irefer to AH20.00-P-1142-01CW i observe correct coolant composition		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Brake system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4210EW
□ Power steering - check fluid level and correct if necessary except CODE 211 (Direct-Steer system)  ■ the fluid level must always be on the maximum mark, corresponding to the oil temperature		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP46.00-P-4612CC
☐ Windshield washer system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210EW
☐ Parking brake (function test only)			•		•		•		•		•		•		•			
Reset maintenance service indicator in instrument cluster  I reminder - if not yet performed		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
Required Additional Work miles (thousands)  Performed years (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK <b>↓</b>	
Replace air filter engine 276 engine 278					•				•				•					AP09.10-P-0980MM AP09.10-P-0980AB
Replace spark plugs							•						•					AP15.10-P-1580EW
☐ Automatic transmission - oil and filter change								•							•			AP27.00-P-2702W
Replace fuel filter																•		AP47.20-P-0780EW

Required Additional Work miles (thousands)  Performed years (check if performed)	2	10 1	20 2	30	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK <b>↓</b>	
Replace coolant  Dobserve correct coolant composition																•		AP20.00-P-2080EW
Recommended Service miles (thousands) Work	2	10	20	30		50	60	70		90	100	110	120	130	140	150		
Performed years (check if performed)		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK <b>↓</b>	
☐ Replace combination or dust filter		•		•		•		•		•		•		•		•		AP83.00-P-8384EW
☐ Replace wiper blades		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Horn - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Warning/indicator lamps - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451CA
☐ Illumination and interior lighting - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5453CC
☐ Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.10-P-8252EW
☐ Check trunk/cargo area lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check and correct headlamp setting			•		•		•		•		•		•		•			AP82.10-P-8260EW
☐ Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-U-5453A
☐ Soft top - clean sealing and apply lubricant model 207.4		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP77.30-P-7736QA
☐ Check seat belts and buckles for signs of external damage and proper function			•		•		•		•		•		•		•			AP91.40-P-9150EC
☐ Check windshield washer and headlamp cleaning system		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.30-P-8252EW
Check, clean, and lubricate tilt/sliding roof mechanism where applicable			•		•		•		•		•		•		•			
Check, clean, and lubricate panoramic roof mechanism model 207.3 with CODE 413 (panoramic sliding sunroof)			•		•		•		•		•		•		•			AP77.20-P-7732EW
☐ Check bodywork for paintwork damage			•		•		•		•		•		•		•			AP98.00-P-9850EW
☐ Tire rotation where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Inspect tires for damage, measure thread depth and enter table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051EW
☐ Check TIREFIT tire sealant expiration date where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4054R
☐ Activate Tire Pressure Monitoring System  ☐ refer to vehicle Operator's Manual		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Visually check brake system components, lines, hoses, calipers		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check thickness of brake pads and discs, front and rear wheels removed																	_	
pads		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4253A
discs		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4258EW

Recommended Service Work	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Performed (check if performed)	years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK <b>↓</b>	
Check chassis and load-components for damage an				•		•		•		•		•		•		•			AP00.20-P-0090EW
High Mileage Required	Service Work at 1	60,	000	mi	les	or	16 y	/ea	rs;	the	n e	every	20,	000	mile	s or	2 ye	ears	
I Plus any applicable additional work listed at the end of the service sheet																			
☑ Performed Not OK check if performed)   ✓																			
Reset maintenance service indicator in instrument cluster AP00.20-P-0042EW																			
□ Engine - oil and filter change engine 276 engine 278 AP18.00-P-0101EW																			
☐ Check catch, safety c												AP88.40-P-8851EW							
☐ Check condition of po																			AP13.22-P-1352EW
☐ Clean visible area of	water deflector																		AP82.35-P-8232A
Replace brake fluid																			AP42.00-P-4280EW
Replace combination	or dust filter																		AP83.00-P-8384EW
☐ Check thickness of br	rake pads, front and	rea	ır																AP42.10-P-4253A
☐ Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet  AP40.15-P-4061A																			
											AP00.20-P-0053EW								
□ Visually inspect condition of front axle ball joints, rubber boots												AP33.20-P-3353CW							
□ Visually inspect condition of driveshaft flexible discs													AP41.10-P-4152EW						
☐ Visually inspect condi	ition of steering med	har	nica	l co	mp	one	nts	, rul	bbe	r bo	ot	s							AP46.00-P-4653CW
☐ Coolant - check fluid level and correct if necessary  ☐ refer to AH20.00-P-1142-01CW ☐ observe correct coolant composition																			
☐ Brake system - check	fluid level and corre	ect	if ne	ece	ssaı	'n													AP42.10-P-4210EW
Power steering - chec except CODE 211 (Di ii the fluid level must	rect-Steer system)						rre	spo	ndir	na t	o tl	he oi	l tem	pera	ature				AP46.00-P-4612CC
☐ Windshield washer sy														,					AP82.35-P-8210EW
☐ Parking brake (function																			
Reset maintenance s	ervice indicator in in	stru	ıme	nt o	clus	ter													AP00.20-P-0042EW
High Mileage Recomm		rk a	t 10	60,0	000	mil	es	or 1	16 y	ear	s;	then	eve	ry 2	0,00	0 m	iles	or 2 year	'S
<ul><li>I Plus any applicable</li><li>☑ Performed</li></ul>	additional work lis	ste	d at	the	e er	ıd c	of th	ne s	erv	ice	sł	heet						Not OK	
(check if performed)																		•	
Replace wiper blades	<b>3</b>																		
☐ Horn - Electrical syste	em check																		
☐ Warning/indicator lam	nps - Electrical syste	m c	chec	ck															AP54.30-P-5451CA
☐ Illumination and interi	or lighting - Electrica	al s	yste	m d	che	ck													AP54.30-P-5453CC
☐ Exterior lighting, high	beam flasher, haza	rd v	varr	ning	fla	she	r, tu	ırn s	sign	als	- E	Electr	ical	syste	em c	hecl	(		AP82.10-P-8252EW
☐ Check trunk/cargo are	ea lighting																		
□ Check and correct headlamp setting													AP82.10-P-8260EW						

$\square$ Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here		AP54.10-U-5453A
☐ Soft top - clean sealing and apply lubricant model 207.4		AP77.30-P-7736QA
☐ Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150EC
☐ Check windshield washer and headlamp cleaning system		AP82.30-P-8252EW
☐ Check, clean, and lubricate tilt/sliding roof mechanism where applicable		
☐ Check, clean, and lubricate panoramic roof mechanism model 207.3 with CODE 413 (panoramic sliding sunroof)		AP77.20-P-7732EW
☐ Check bodywork for paintwork damage		AP98.00-P-9850EW
☐ Tire rotation where applicable		
$\square$ Inspect tires for damage, measure thread depth and enter table at the end of the service sheet		AP40.10-P-4051EW
☐ Check TIREFIT tire sealant expiration date where applicable		AP40.10-P-4054R
☐ Activate Tire Pressure Monitoring System  ☐ refer to vehicle Operator's Manual		
☐ Visually check brake system components, lines, hoses, calipers		
☐ Check thickness of brake pads and discs, front and rear wheels removed		
pads		AP42.10-P-4253A
discs		AP42.10-P-4258EW
$\square$ Check chassis and load-bearing body components for damage and corrosion		AP00.20-P-0090EW
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y	ears	
i Plus any applicable additional work listed at the end of the service sheet		,
i Plus any applicable additional work listed at the end of the service sheet ⊠ Performed	Not Ok	(
i Plus any applicable additional work listed at the end of the service sheet  ⊠ Performed (check if performed)		
☐ Plus any applicable additional work listed at the end of the service sheet ☐ Performed (check if performed) ☐ Reset maintenance service indicator in instrument cluster	Not Ok	AP00.20-P-0042EW
Plus any applicable additional work listed at the end of the service sheet     Performed (check if performed)      Reset maintenance service indicator in instrument cluster      □ Engine - oil and filter change	Not Ok	AP00.20-P-0042EW
Plus any applicable additional work listed at the end of the service sheet     Performed (check if performed)      Reset maintenance service indicator in instrument cluster      Engine - oil and filter change engine 276	Not Ok	AP00.20-P-0042EW  AP18.00-P-0101CWZ
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) □ Reset maintenance service indicator in instrument cluster □ Engine - oil and filter change engine 276 engine 278	Not Ok	AP00.20-P-0042EW
Plus any applicable additional work listed at the end of the service sheet     Performed (check if performed)      Reset maintenance service indicator in instrument cluster      Engine - oil and filter change engine 276 engine 278      Check catch, safety catch and hinges on engine hood for proper operation	Not Ok	AP18.00-P-0101CWZ AP18.00-P-0101EW
<ul> <li>Plus any applicable additional work listed at the end of the service sheet</li> <li>☑ Performed (check if performed)</li> <li>☐ Reset maintenance service indicator in instrument cluster</li> <li>☐ Engine - oil and filter change engine 276 engine 278</li> <li>☐ Check catch, safety catch and hinges on engine hood for proper operation</li> <li>☐ Clean visible area of water deflector</li> </ul>	Not Ok	AP00.20-P-0042EW  AP18.00-P-0101CWZ AP18.00-P-0101EW  AP88.40-P-8851EW
Plus any applicable additional work listed at the end of the service sheet     Performed (check if performed)      Reset maintenance service indicator in instrument cluster      Engine - oil and filter change engine 276 engine 278      Check catch, safety catch and hinges on engine hood for proper operation	Not Ok	AP00.20-P-0042EW  AP18.00-P-0101CWZ AP18.00-P-0101EW AP88.40-P-8851EW AP82.35-P-8232A
<ul> <li>Plus any applicable additional work listed at the end of the service sheet</li> <li>☑ Performed (check if performed)</li> <li>☐ Reset maintenance service indicator in instrument cluster</li> <li>☐ Engine - oil and filter change engine 276 engine 278</li> <li>☐ Check catch, safety catch and hinges on engine hood for proper operation</li> <li>☐ Clean visible area of water deflector</li> <li>☐ Check thickness of brake pads, front and rear</li> <li>☐ Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet</li> <li>☐ Coolant - check fluid level and correct if necessary</li> <li>☑ refer to AH20.00-P-1142-01CW</li> </ul>	Not Ok	AP00.20-P-0042EW  AP18.00-P-0101CWZ AP18.00-P-0101EW AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4253A
I Plus any applicable additional work listed at the end of the service sheet	Not Ok	AP00.20-P-0042EW  AP18.00-P-0101CWZ AP18.00-P-0101EW AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4253A
I Plus any applicable additional work listed at the end of the service sheet	Not Ok	AP00.20-P-0042EW  AP18.00-P-0101CWZ AP18.00-P-0101EW AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4253A AP40.15-P-4061A
I Plus any applicable additional work listed at the end of the service sheet  Performed (check if performed)  Reset maintenance service indicator in instrument cluster  Engine - oil and filter change engine 276 engine 278  Check catch, safety catch and hinges on engine hood for proper operation  Clean visible area of water deflector  Check thickness of brake pads, front and rear  Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet  Coolant - check fluid level and correct if necessary  I refer to AH20.00-P-1142-01CW  I observe correct coolant composition  Brake system - check fluid level and correct if necessary  Power steering - check fluid level and correct if necessary except CODE 211 (Direct-Steer system)	Not Ok	AP00.20-P-0042EW  AP18.00-P-0101CWZ AP18.00-P-0101EW AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4253A AP40.15-P-4061A
I Plus any applicable additional work listed at the end of the service sheet	Not Ok	AP00.20-P-0042EW  AP18.00-P-0101CWZ AP18.00-P-0101EW AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4253A AP40.15-P-4061A

Reset maintenance service indicator in inst	trument cluster		AP00.20-P-0042EW
High Mileage Recommended Service Work	at 170,000 miles or 17 years; then every 20,000 miles	or 2 yea	ars
i Plus any applicable additional work list	ed at the end of the service sheet		_
☑ Performed (check if performed)		Not Of	(
			AP83.00-P-8384EW
Replace combination or dust filter			AI 03.00-I -0304EW
Replace wiper blades			
☐ Horn - Electrical system check			4.D.5.4.00 D. 5.4.5.4.0.4
☐ Warning/indicator lamps - Electrical system	n check		AP54.30-P-5451CA
☐ Illumination and interior lighting - Electrical	system check		AP54.30-P-5453CC
☐ Exterior lighting, high beam flasher, hazard	warning flasher, turn signals - Electrical system check		AP82.10-P-8252EW
☐ Check trunk/cargo area lighting			
☐ Battery (Main/starter/auxiliary) check condireport print out here	tion using Midtronics battery tester. Attach Midtronics test		AP54.10-U-5453A
Soft top - clean sealing and apply lubricant model 207.4			AP77.30-P-7736QA
☐ Check windshield washer and headlamp cl	eaning system		AP82.30-P-8252EW
☐ Tire rotation where applicable			
☐ Inspect tires for damage, measure thread of	depth and enter table at the end of the service sheet		AP40.10-P-4051EW
Check TIREFIT tire sealant expiration date where applicable			AP40.10-P-4054R
☐ Activate Tire Pressure Monitoring System			
i refer to vehicle Operator's Manual			
☐ Visually check brake system components,	lines, hoses, calipers		
☐ Check thickness of brake pads and discs, t	front and rear wheels removed		
pads			AP42.10-P-4253A
discs			AP42.10-P-4258EW
High Mileage Additional Work  ☑ Performed (check if performed)			
Replace air filter			
engine 276	If more than 40,000 mi or 4 years since last replacement		AP09.10-P-0980MM
engine 278	If more than 40,000 mi or 4 years since last replacement		AP09.10-P-0980AB
Replace spark plugs	If more than 60,000 mi or 6 years since last replacement		AP15.10-P-1580EW
Automatic transmission - oil and filter change	If more than 70,000 mi or 7 years since last replacement		AP27.00-P-2702W
Replace fuel filter	If more than 150,000 mi or 15 years since last replacement		AP47.20-P-0780EW
Replace coolant	If more than 150,000 mi or 15 years since last replacement		AP20.00-P-2080EW
i observe correct coolant composition			

Tire inflation pressure (bar/psi)												
LF	RF	LR	RR	Spare								

Tire thre	ead dept	h (mm)		
	LF	RF	LR	RR
outside				
center				
inside				