

Mercedes-Benz

AP00.20-U-1208TO

SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model Year 201	8	Мос	lel 238		
Customer:			Repair order nu	mber:	
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommende likely necessitate tire rotati each 10,000-mile maintena 10,000-mile maintenance s	on at least once in between ance service and at every	Tires rotated	YES	NO
Note: For any contract the cause and perfor	ondition found while performi m the repair using a separate	ng the checks or inspections e repair order.	s included in this r	naintenance shee	t, determine
Current mileage read	ling:	0	il grade/viscosity:		
Additional notes:					
Service work to be po service advisor:	erformed as advised by	Completion date:	Confirm work has below:	s been performed	by signing

P-2374-238-18C (10/18) Dealer Workshop Services www.MBUSA.com www.startekinfo.com

Mercedes-Benz USA, LLC Reproduction or translation in whole or in part is not permitted without written authorization from the publisher. 1-800-FOR-MERCedes

Required Service Workmiles (thousands)Performedwiles (thousands)(check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK	
Reset maintenance service indicator in in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0043J
Replace activated charcoal combination filter			•		•		•		•		•		•		•			AP83.00-P-8384B
Replace dust filter			•		•		•		•		•		•		•			AP83.00-P-8381C
Perform brake test			•		•		•		•		•		•		٠			AP42.00-P-4290BA
Engine – oil and filter change		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101CWZ
Check condition of poly-V-belt			•	1	•		•	1	•		•		•		•			AP13.22-P-1352EW
Check and correct all tire air pressures, including spare where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.15-P-4061A
□ Check visible parts in engine compartment for damage and leaks			•		•		•		•		•		•		•			AP00.20-P-0055E
Check underside of vehicle for damage and leaks			•		•		•		•		•		•		•			AP00.20-P-0054I
\Box Inspect front axle ball joints and rubber boots			•		•		•		•		•		•		•			AP33.10-P-3358A
□ Inspect driveshaft flexible discs			•		•		•		•		•		•		٠			AP41.10-P-4152EW
□ Inspect rear axle and rear axle ball joints			•		•		•		•		•		•		•			AP35.20-P-3552A
Check condition of steering and tie rods			•		•		•		•		•		•		•			AP46.00-P-4651A
Check condition of suspension struts or shock absorbers and springs			•		•		•		•		•		•		•			AP32.25-P-3255A
Check catch, safety catch, and hinges on engine hood for proper operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
\Box Clean visible area of water deflector			٠		•		•		•		٠		٠	_	•			
Check coolant level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP20.30-P-2049U
Check windshield washer system fluid, correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210C
\Box Check brake fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	٠	•		AP42.10-P-4210B
□ Replace brake fluid			•		•		•		•		•		•		•			AP42.00-P-4280C
□ Check first aid kit		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP68.00-P-6850EW
Reset maintenance service indicator in instrument cluster reminder - if not yet performed		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0043J
Required Additional Work miles (thousands) Image: Second system years (check if performed) years	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Replace air filter						•					•					•		AP09.10-P-0980E
Replace spark plugs						•					•					•		AP15.10-P-1580D
Automatic transmission - oil and filter change							•						•					AP27.00-P-2702B
Replace fuel filter													•					AP47.20-P-0780C
Replace low-temperature circuit coolant													•					AP20.00-P-2083I
Replace coolant in main circuit													•					AP20.00-P-2082I
Recommended Service miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Work years (check if performed)		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK	
		-	-	-	-	-	-	-	-	_	-	-	-	-	-	-	<u>↓</u>	
		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Check warning/indicator lamps		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451HA
Check illumination and interior lighting		٠	•	٠	•	٠	•	٠	•	•	•	•	•	•	•	•		AP54.30-P-5453E

Recommended Service miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Work		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK	
Performed years (check if performed)		•		5	1	5		ľ		9	10	11	12	15	14	13		
Activate Tire Pressure Monitoring System		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Refer to vehicle Operator's Manual		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Check windshield and headlamp washer system operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8252D
Replace wiper blades		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof)			•		•		•		•		•		•		•			AP77.20-P-7732A
Check all exterior lights		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.10-P-8252EW
□ Check operation of headlamp range adjustment		-	•		•		•		•		•		•		•			AP82.10-P-8250EW
Check headlamp setting, correct if necessary			•		•		•		•		•		•		٠			AP82.10-P-8260J
Check trunk / cargo area light		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) After consultation with customer		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Check condition and operation of trailer hitch with CODE 550 (Trailer hitch)			•		•		•		•		•		•		•			AP31.11-P-3152A
Check TIREFIT tire sealant expiration date (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4054R
Check battery. Attach printout to sheet			•		•		•		•		٠		•		٠			AP54.10-P-5449U
□ Tire rotation (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Check seatbelts and buckles for proper operation or damage			•		•		•		•		•		•		•			
Check thickness of brake pads and discs, front and rear wheels removed																		AP42.10-P-4256EW
discs		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4256EW
☐ Visually inspect brake system components, lines, hoses, calipers		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Inspect tires for damage and measure remaining tread life		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051EW
Check chassis and load bearing body components for damage and corrosion		-	•		•		•		•		•		•		•			
\Box Check ex-factory driving aids (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP86.20-P-8649U
High Mileage Required Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years I Plus any applicable additional work listed at the end of the service sheet Performed Not OK (check if performed)																		
Reset maintenance service indicator in in	stru	ıme	ent o	clus	ter													AP00.20-P-0043J
□ Replace activated charcoal combination f	Replace activated charcoal combination filter AP83.00-P-8384B																	
Replace dust filter AP83.00-P-8381C i behind plastic cowl in engine compartment									AP83.00-P-8381C									
Perform brake test										AP42.00-P-4290BA								
Engine – oil and filter change																		AP18.00-P-0101CWZ
Check condition of poly-V-belt																		AP13.22-P-1352EW
Check and correct all tire air pressures, ir	nclu	din		oare	e wł	here	e an	plic	ahl	e								AP40.15-P-4061A
Check visible parts in engine compartment							-	-										AP00.20-P-0055E
				-90														AP00.20-P-0054I
Check underside of vehicle for damage and leaks																		

□ Inspect front axle ball joints and rubber boots		AP33.10-P-3358A
□ Inspect driveshaft flexible discs		AP41.10-P-4152EW
□ Inspect rear axle and rear axle ball joints		AP35.20-P-3552A
Check condition of steering and tie rods		AP46.00-P-4651A
Check condition of suspension struts or shock absorbers and springs		AP32.25-P-3255A
Check catch, safety catch, and hinges on engine hood for proper operation		
Clean visible area of water deflector		
Check coolant level and correct if necessary		AP20.30-P-2049U
i observe correct coolant composition		
Check windshield washer system fluid, correct if necessary		AP82.35-P-8210C
Check brake fluid level and correct if necessary		AP42.10-P-4210B
Replace brake fluid		AP42.00-P-4280C
Check first aid kit		AP68.00-P-6850EW
Reset maintenance service indicator in instrument cluster		AP00.20-P-0043J
I reminder - if not yet performed		
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles	s or 2 yea	ars
I Plus any applicable additional work listed at the end of the service sheet	Not Of	
Performed (check if performed)	Not Or	N
		AP54.30-P-5451HA
Check warning/indicator lamps		AP54.30-P-5453E
Check illumination and interior lighting		
Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual		
Check windshield and headlamp washer system operation		AP82.35-P-8252D
Check windshield and headlamp washer system operation		AP82.35-P-8252D
Replace wiper blades		AP82.35-P-8252D AP77.20-P-7732A
		AP77.20-P-7732A
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism		
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof)		AP77.20-P-7732A
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof) Check all exterior lights		AP77.20-P-7732A AP82.10-P-8252EW
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof) Check all exterior lights Check operation of headlamp range adjustment		AP77.20-P-7732A AP82.10-P-8252EW AP82.10-P-8250EW
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof) Check all exterior lights Check operation of headlamp range adjustment Check headlamp setting, correct if necessary Check trunk / cargo area light Replace battery for KEYLESS-GO key		AP77.20-P-7732A AP82.10-P-8252EW AP82.10-P-8250EW
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof) Check all exterior lights Check operation of headlamp range adjustment Check headlamp setting, correct if necessary Check trunk / cargo area light Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function)		AP77.20-P-7732A AP82.10-P-8252EW AP82.10-P-8250EW
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof) Check all exterior lights Check operation of headlamp range adjustment Check headlamp setting, correct if necessary Check trunk / cargo area light Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) After consultation with customer		AP77.20-P-7732A AP82.10-P-8252EW AP82.10-P-8250EW AP82.10-P-8260J
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof) Check all exterior lights Check operation of headlamp range adjustment Check headlamp setting, correct if necessary Check trunk / cargo area light Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function)		AP77.20-P-7732A AP82.10-P-8252EW AP82.10-P-8250EW
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof) Check all exterior lights Check operation of headlamp range adjustment Check headlamp setting, correct if necessary Check trunk / cargo area light Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) I After consultation with customer Check condition and operation of trailer hitch		AP77.20-P-7732A AP82.10-P-8252EW AP82.10-P-8250EW AP82.10-P-8260J
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof) Check all exterior lights Check operation of headlamp range adjustment Check headlamp setting, correct if necessary Check trunk / cargo area light Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) After consultation with customer Check condition and operation of trailer hitch with CODE 550 (Trailer hitch)		AP77.20-P-7732A AP82.10-P-8252EW AP82.10-P-8250EW AP82.10-P-8260J AP82.10-P-8260J
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof) Check all exterior lights Check operation of headlamp range adjustment Check headlamp setting, correct if necessary Check trunk / cargo area light Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) After consultation with customer Check condition and operation of trailer hitch with CODE 550 (Trailer hitch) Check TIREFIT tire sealant expiration date (where applicable)		AP77.20-P-7732A AP82.10-P-8252EW AP82.10-P-8250EW AP82.10-P-8260J AP82.10-P-8260J AP31.11-P-3152A AP31.11-P-3152A
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof) Check all exterior lights Check operation of headlamp range adjustment Check headlamp setting, correct if necessary Check trunk / cargo area light Replace battery for KEYLESS-GO key with CODE 893 (KEYLESS-GO start function) After consultation with customer Check condition and operation of trailer hitch with CODE 550 (Trailer hitch) Check TIREFIT tire sealant expiration date (where applicable) Check battery. Attach printout to sheet		AP77.20-P-7732A AP82.10-P-8252EW AP82.10-P-8250EW AP82.10-P-8260J AP82.10-P-8260J AP31.11-P-3152A AP31.11-P-3152A
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof) Check all exterior lights Check all exterior of headlamp range adjustment Check operation of headlamp range adjustment Check trunk / cargo area light Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO or with CODE 893 (KEYLESS-GO start function) I After consultation with customer Check condition and operation of trailer hitch with CODE 550 (Trailer hitch) Check TIREFIT tire sealant expiration date (where applicable) Check battery. Attach printout to sheet Tire rotation (where applicable)		AP77.20-P-7732A AP82.10-P-8252EW AP82.10-P-8250EW AP82.10-P-8260J AP82.10-P-8260J AP31.11-P-3152A AP31.11-P-3152A
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof) Check all exterior lights Check operation of headlamp range adjustment Check headlamp setting, correct if necessary Check trunk / cargo area light Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) After consultation with customer Check condition and operation of trailer hitch with CODE 550 (Trailer hitch) Check TIREFIT tire sealant expiration date (where applicable) Check battery. Attach printout to sheet Tire rotation (where applicable) Check seatbelts and buckles for proper operation or damage		AP77.20-P-7732A AP82.10-P-8252EW AP82.10-P-8250EW AP82.10-P-8260J AP82.10-P-8260J AP31.11-P-3152A AP31.11-P-3152A
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof) Check all exterior lights Check operation of headlamp range adjustment Check headlamp setting, correct if necessary Check trunk / cargo area light Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) After consultation with customer Check condition and operation of trailer hitch with CODE 550 (Trailer hitch) Check battery. Attach printout to sheet Tire rotation (where applicable) Check seatbelts and buckles for proper operation or damage Check thickness of brake pads and discs, front and rear wheels removed		AP77.20-P-7732A AP82.10-P-8252EW AP82.10-P-8250EW AP82.10-P-8260J AP82.10-P-8260J AP31.11-P-3152A AP31.11-P-3152A AP40.10-P-4054R AP54.10-P-5449U
Replace wiper blades Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof) Check all exterior lights Check operation of headlamp range adjustment Check headlamp setting, correct if necessary Check trunk / cargo area light Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) After consultation with customer Check condition and operation of trailer hitch with CODE 550 (Trailer hitch) Check battery. Attach printout to sheet Tire rotation (where applicable) Check seatbelts and buckles for proper operation or damage Check thickness of brake pads and discs, front and rear wheels removed discs		AP77.20-P-7732A AP82.10-P-8252EW AP82.10-P-8250EW AP82.10-P-8260J AP82.10-P-8260J AP31.11-P-3152A AP31.11-P-3152A AP40.10-P-4054R AP54.10-P-5449U

Check ex-factory driving aids (where applic	able)		AP86.20-P-8649U						
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years									
I Plus any applicable additional work liste	ed at the end of the service sheet								
Performed (check if performed)		Not Oł ↓	κ.						
		v	AP00.20-P-0043J						
Reset maintenance service indicator in inst			AP18.00-P-0101CWZ						
Engine – oil and filter change	uding spare where applicable		AP40.15-P-4061A						
\Box Check catch, safety catch, and hinges on e	• • • • •								
Check coolant level and correct if necessar			AP20.30-P-2049U						
observe correct coolant composition	y								
Check windshield washer system fluid, corr	ect if necessary		AP82.35-P-8210C						
Check brake fluid level and correct if neces	· · · · · · · · · · · · · · · · · · ·		AP42.10-P-4210B						
Check first aid kit			AP68.00-P-6850EW						
Reset maintenance service indicator in inst	rument cluster		AP00.20-P-0043J						
i reminder - if not yet performed									
High Mileage Recommended Service Work	at 170,000 miles or 17 years; then every 20,000 mile	s or 2 yea	ars						
I Plus any applicable additional work listed at the end of the service sheet									
Performed (check if performed)		Not Oł	κ.						
		↓							
			AP54.30-P-5451HA						
			AP54.30-P-5453E						
Check illumination and interior lighting			A 34.30-1 - 54.00L						
Activate Tire Pressure Monitoring System									
Check windshield and headlamp washer sy	stem operation		AP82.35-P-8252D						
Replace wiper blades									
Check all exterior lights			AP82.10-P-8252EW						
Check trunk / cargo area light									
Replace battery for KEYLESS-GO key									
with CODE 889 (KEYLESS-GO) or with CO	DE 893 (KEYLESS-GO start function)								
After consultation with customer									
Check TIREFIT tire sealant expiration date	(where applicable)		AP40.10-P-4054R						
☐ Tire rotation (where applicable)									
Check thickness of brake pads and discs, f	ront and rear wheels removed								
discs			AP42.10-P-4256EW						
☐ Visually inspect brake system components,			AP40.10-P-4051EW						
☐ Inspect tires for damage and measure remain	v		AP86.20-P-8649U						
Check ex-factory driving aids (where applic	able)		AF 00.20-F-00490						
High Mileage Additional Work									
(check if performed)									
Replace air filter	If more than 50,000 miles or 5 years since last replacement		AP09.10-P-0980E						
Replace spark plugs	If more than 50,000 miles or 5 years since last replacement		AP15.10-P-1580D						
Automatic transmission - oil and filter change	If more than 60,000 miles or 6 years since last replacement		AP27.00-P-2702B						
Replace fuel filter	If more than 120,000 miles or 12 years since last replacement		AP47.20-P-0780C						
Replace low-temperature circuit coolant	If more than 120,000 miles or 12 years since last replacement		AP20.00-P-2083I						

Tire inflation pressure (bar/psi)											
LF	RF	LR	RR	Spare							

Tire tread depth (mm)										
	LF	RF	LR	RR						
outside										
center										
inside										