

AP00.20-U-1208BO

SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

| Model Year 201 USA | 19 | Мос | lel 238 | | |
|--|---|--|---------------------------|------------------|---------------|
| Customer: | | | Repair order nu | ımber: | |
| Tire Rotation (non-staggered width wheel setup only) | A 5,000-mile recommende likely necessitate tire rotati each 10,000-mile maintena 10,000-mile maintenance s | on at least once in between ance service and at every | Tires rotated | YES | NO |
| Note: For any control the cause and performed | ondition found while performi m the repair using a separate | ng the checks or inspections e repair order. | s included in this | maintenance shee | et, determine |
| Current mileage read | ding: | O | il grade/viscosity: | | |
| Additional notes: | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| Service work to be p service advisor: | erformed as advised by | Completion date: | Confirm work ha below: | s been performed | by signing |
| | | | | | |
| Product Management - Se | ervice | P-: | 2374-238-19B (09/18) | | |

P-2374-238-19B (09/18) Reproduction or translation in whole or in part is not permitted without written authorization from the publisher.

| Required Service Work miles (thousands) Performed years (check if performed) | 2 | 10 1 | 20 2 | 30 3 | 40 4 | 50 5 | 60 6 | 70 7 | 80 8 | | 100 10 | 110 11 | 120 12 | 130 13 | 140 14 | 150 15 | Not OK | |
|--|---|---------|---------|---------|---------|---------|---------|---------|---------|---------|-----------|-----------|-----------|-----------|-----------|-----------|-------------|---|
| Reset maintenance service indicator in instrument cluster | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP00.20-P-0043J |
| Replace engine oil and filter Engine 256 Engine 276 Clean visible area of water deflector | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | •••• | | AP18.00-P-0101MRT AP18.00-P-0101CWZ |
| Replace activated charcoal combination filter Behind glovebox | | | • | | • | | • | | • | | • | | • | | • | | | AP83.00-P-8384B |
| Replace dust filter Behind plastic cowl in engine compartment | | | • | | • | | • | | • | | • | | • | | • | | | AP83.00-P-8381C |
| Replace brake fluid | | | • | | • | | • | | • | | ٠ | | • | | • | | | AP42.00-P-4280C |
| Perform brake test | | | • | | • | | • | | • | | ٠ | | • | | • | | | AP42.00-P-4290BA |
| Check brake fluid level, correct if necessary | | • | • | • | • | • | • | • | • | • | ٠ | ٠ | • | • | • | • | | AP42.10-P-4210B |
| Check thickness of brake pads and discs, front and rear wheels removed | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP42.10-P-4252F |
| Check and correct all tire air pressures, including spare where applicable | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP40.15-P-4061A |
| Check coolant level and correct if necessary Low-temperature circuit (engine 256) Low-temperature circuit (engine 276) | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | ••• | | AP20.30-P-2052K AP20.30-P-2052H AP20.30-P-2050I |
| Main circuit | + | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP20.30-P-20501 AP82.35-P-8210C |
| Check windshield washer system fluid, correct if necessary Observe correct coolant composition | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP02.35-P-0210C |
| Check catch, safety catch, and hinges on engine hood for proper operation | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| □ Check first aid kit | | • | • | • | • | • | • | • | • | • | • | • | ٠ | • | • | • | | AP68.00-P-6850EW |
| \Box Check underside of vehicle for damage and leaks | | | • | | • | | • | | • | | ٠ | | • | | • | | | AP00.20-P-00541 |
| \Box Check visible parts in engine compartment for damage and leaks | | | • | | • | | • | | • | | ٠ | | • | | • | | | AP00.20-P-0055E |
| \Box Check front axle and front axle ball joints, check rubber boots | | | • | | • | | • | | • | | ٠ | | ٠ | | • | | | AP33.10-P-3358A |
| \Box Check condition of steering and tie rods | | | • | | • | | • | | • | | • | | • | | • | | | AP46.00-P-4651A |
| Check rear axle and rear axle ball joints, check rubber boots | | | • | | • | | • | | • | | ٠ | | • | | • | | | AP35.20-P-3552A |
| Check driveshaft flexible couplings | | | • | | • | | • | | • | | ٠ | | • | | • | | | AP41.10-P-4152EW |
| \Box Check condition of suspension struts or shock absorbers and springs | | | • | | • | | • | | • | | ٠ | | • | | • | | | AP32.25-P-3255A |
| Check condition of poly-V-belt Engine 276 | | | • | | • | | • | | • | | • | | • | | • | | | AP13.22-P-1352EW |
| Reset maintenance service indicator in instrument cluster Reminder - if not yet performed | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP00.20-P-0043J |
| Required Additional Work miles (thousands) Performed years (check if performed) | 2 | 10 1 | 20 2 | 30 3 | 40 4 | 50 5 | 60 6 | 70 7 | 80 8 | 90 9 | 100 10 | 110 11 | 120 12 | 130 13 | 140 14 | | Not OK ↓ | |
| □ Replace engine air filter Engine 256 Engine 276 | | | | | | • | | | | | • | | | | | • | | AP09.10-P-0980L AP09.10-P-0980E |
| Replace spark plugs Engine 256 | | | | | | • | | | | | • | | | | | • | | AP15.10-P-1580E |
| Engine 276 | | | | | | • | | | | | ٠ | | | | | ٠ | | AP15.10-P-1580D |
| Replace automatic transmission oil and filter | | | | | | | • | | | | | | • | | | | | AP27.00-P-2702B |
| □ Replace transfer case oil Transmission 725.0 with CODE M005 (4MATIC) | | | | | | | • | | | | | | • | | | | | AP28.00-P-2801A |
| Replace fuel filter | | | | | | | | | | | | | • | | | | | AP47.20-P-0780C |
| Replace main circuit coolant Diserve correct coolant composition | | | | | | | | | | | | | • | | | | | AP20.00-P-2082I |

| Required Additional Work miles (thousands) Performed years (check if performed) | 2 | 10 1 | 20 2 | 30 3 | 40 4 | 50 5 | 60 6 | 70 7 | 80 8 | 90 9 | 100 10 | 110 11 | 120 12 | 130 13 | 140 14 | 150 15 | Not OK ↓ | |
|---|---|---------|---------|---------|---------|---------|---------|---------|---------|---------|-----------|-----------|---------------------|-----------|-----------|-----------|-------------|--|
| □ Replace low-temperature circuit coolant ■ Observe correct coolant composition Engine 256 Engine 276 Recommended Service Work miles (thousands) years | 2 | 10 1 | 20 2 | 30 3 | 40 4 | 50 5 | 60 6 | 70 7 | 80 8 | 90 9 | 100 10 | 110 11 | • • 120 12 | 130 13 | 140 14 | 150 15 | Not OK | AP20.00-P-2083D AP20.00-P-2083I |
| (check if performed) | _ | | _ | | | | | | | | | | | | | | - ↓ | |
| Replace wiper blades | - | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP82.35-P-8252D |
| Check windshield wiper, washer and headlamp washer system operation | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| \Box Inspect tires for damage and measure remaining tread life | | • | ٠ | • | ٠ | • | ٠ | ٠ | ٠ | • | ٠ | • | ٠ | ٠ | ٠ | • | | AP40.10-P-4051EW |
| Tire rotation (where applicable) | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| □ Check TIREFIT tire sealant expiration date (where applicable) | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP40.10-P-4054R |
| Check thickness of brake pads and discs, front and rear wheels removed | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP42.10-P-4252F |
| Check brake system components, lines, hoses, calipers | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| Check headlamp setting, correct if necessary | | | • | | • | | • | | • | | • | | • | | • | | | AP82.10-P-8260J |
| □ Check operation of headlamp range adjustment | | | • | | • | | • | | • | | • | | • | | • | | | AP82.10-P-8250EW |
| Check all exterior lights | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP82.10-P-8252EW |
| Check warning/indicator lamps | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP54.30-P-5451HA |
| Check illumination and interior lighting | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP54.30-P-5453E |
| Check trunk / cargo area lights | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| Replace battery for KEYLESS-GO key With KEYLESS-GO function After consultation with customer | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| Clean and lubricate Panoramic sliding roof guide mechanism With CODE 413 (Automatic panoramic sliding sunroof) | | | • | | • | | • | | • | | • | | • | | • | | | AP77.20-P-7732A |
| | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| Check battery condition. Attach printout to sheet | | | • | | • | | • | | • | | • | | • | | • | | | AP54.10-P-5449U |
| Check chassis and load bearing body components for damage and corrosion | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| Check ex-factory driving aids (where applicable) | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP86.20-P-8649U |
| Check for body paint damage | | | • | | • | | • | | • | | • | | • | | • | | | AP60.00-P-0050J |
| \Box Check seatbelts and buckles for proper operation or damage | | | • | | • | | • | | • | | • | | • | | • | | | |
| Check condition and operation of trailer hitch With CODE 550 (Trailer coupling) | | | | | • | | • | | • | | • | | • | | • | | | AP31.11-P-3152A |
| High Mileage Required Service Work at 160,000 miles or 16 Plus any applicable additional work listed at the end of Performed (check if performed) | - | | | | | - | 0,00 |)0 n | nile | S O | r 2 y | /ears | 5 | | | | Not OK ↓ | |
| Reset maintenance service indicator in instrument cluster | | | | | | | | | | | | | | | | | | AP00.20-P-0043J |
| □ Replace engine oil and filter Engine 256 Engine 276 | | | | | | | | | | | | | | | | | | AP18.00-P-0101MRT AP18.00-P-0101CWZ |
| Clean visible area of water deflector Replace activated charcoal combination filter Replace develops | | | | | | | | | | | | | | | | | | AP83.00-P-8384B |
| Behind glovebox Replace dust filter Behind plastic cowl in engine compartment | | | | | | | | | | | | | | | | | | AP83.00-P-8381C |

| Replace brake fluid | | AP42.00-P-4280C |
|--|------------|---|
| Perform brake test | | AP42.00-P-4290BA |
| Check brake fluid level, correct if necessary | | AP42.10-P-4210B |
| Check thickness of brake pads and discs, front and rear wheels removed | | AP42.10-P-4252F |
| Check and correct all tire air pressures, including spare where applicable | | AP40.15-P-4061A |
| Check coolant level and correct if necessary | | |
| Low-temperature circuit (engine 256) | | AP20.30-P-2052K |
| Low-temperature circuit (engine 276) | | AP20.30-P-2052H |
| Main circuit | | AP20.30-P-2050I |
| Check windshield washer system fluid, correct if necessary | | AP82.35-P-8210C |
| Check catch, safety catch, and hinges on engine hood for proper operation | | |
| Check first aid kit | | AP68.00-P-6850EW |
| Check underside of vehicle for damage and leaks | | AP00.20-P-0054I |
| Check visible parts in engine compartment for damage and leaks | | AP00.20-P-0055E |
| Check front axle and front axle ball joints, check rubber boots | | AP33.10-P-3358A |
| Check condition of steering and tie rods | | AP46.00-P-4651A |
| Check rear axle and rear axle ball joints, check rubber boots | | AP35.20-P-3552A |
| Check driveshaft flexible couplings | | AP41.10-P-4152EW |
| Check condition of suspension struts or shock absorbers and springs | | AP32.25-P-3255A |
| Check condition of poly-V-belt Engine 276 | | AP13.22-P-1352EW |
| Reset maintenance service indicator in instrument cluster Reminder - if not yet performed | | AP00.20-P-0043J |
| High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years | | |
| | | |
| | | |
| Plus any applicable additional work listed at the end of the service sheet Performed | Not Of | ¢ |
| i Plus any applicable additional work listed at the end of the service sheet | ¥ | (|
| Plus any applicable additional work listed at the end of the service sheet Performed | • | <u>x</u> |
| Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) | ↓ □ | (AP82.35-P-8252D |
| Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades | • | |
| I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation | ↓ □ | AP82.35-P-8252D |
| Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage and measure remaining tread life | ↓ □ | AP82.35-P-8252D |
| I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage and measure remaining tread life Tire rotation (where applicable) Activate Tire Pressure Monitoring System | ↓ □ | AP82.35-P-8252D |
| I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage and measure remaining tread life Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) | | AP82.35-P-8252D AP40.10-P-4051EW |
| Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage and measure remaining tread life Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R |
| I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage and measure remaining tread life Tire rotation (where applicable) Activate Tire Pressure Monitoring System I Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Check brake system components, lines, hoses, calipers | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R |
| Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage and measure remaining tread life Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Check brake system components, lines, hoses, calipers | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4252F |
| Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage and measure remaining tread life Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Check brake system components, lines, hoses, calipers Check operation of headlamp range adjustment | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R AP40.10-P-4054R AP42.10-P-4252F |
| Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage and measure remaining tread life Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Check brake system components, lines, hoses, calipers Check headlamp setting, correct if necessary Check all exterior lights | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R AP40.10-P-4054R AP42.10-P-4252F AP82.10-P-8250EW |
| Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage and measure remaining tread life Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Check brake system components, lines, hoses, calipers Check operation of headlamp range adjustment | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4252F AP82.10-P-8250EW AP82.10-P-8250EW |
| Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check windshield wiper, washer and headlamp washer system operation Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage and measure remaining tread life Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Check brake system components, lines, hoses, calipers Check headlamp setting, correct if necessary Check all exterior lights Check all exterior lighting | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4252F AP82.10-P-8250EW AP82.10-P-8250EW AP82.10-P-8252EW AP54.30-P-5451HA |
| Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage and measure remaining tread life Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Check brake system components, lines, hoses, calipers Check headlamp setting, correct if necessary Check all exterior lights Check warning/indicator lamps | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4252F AP82.10-P-8250EW AP82.10-P-8250EW AP82.10-P-8252EW AP54.30-P-5451HA |
| Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage and measure remaining tread life Tire rotation (where applicable) Activate Tire Pressure Monitoring System I Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Check brake system components, lines, hoses, calipers Check operation of headlamp range adjustment Check all exterior lights Check varning/indicator lamps Check trunk / cargo area lights Replace battery for KEYLESS-GO key | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4252F AP82.10-P-8250EW AP82.10-P-8250EW AP82.10-P-8252EW AP54.30-P-5451HA |
| Image: Performed (check if performed) □ Replace wiper blades □ Check windshield wiper, washer and headlamp washer system operation □ Inspect tires for damage and measure remaining tread life □ Tire rotation (where applicable) □ Activate Tire Pressure Monitoring System Image: Refer to vehicle Operator's Manual □ Check trinkPFIT tire sealant expiration date (where applicable) □ Check trikeness of brake pads and discs, front and rear wheels removed □ Check brake system components, lines, hoses, calipers □ Check operation of headlamp range adjustment □ Check all exterior lights □ Check trunk / cargo area lights □ Replace battery for KEYLESS-GO key With KEYLESS-GO key With KEYLESS-GO function | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4252F AP82.10-P-8250EW AP82.10-P-8250EW AP82.10-P-8252EW AP54.30-P-5451HA |
| I Plus any applicable additional work listed at the end of the service sheet ➢ Performed (check if performed) ☐ Replace wiper blades ☐ Check windshield wiper, washer and headlamp washer system operation ☐ Inspect tires for damage and measure remaining tread life ☐ Tire rotation (where applicable) ☐ Activate Tire Pressure Monitoring System I Refer to vehicle Operator's Manual ☐ Check TIREFIT tire sealant expiration date (where applicable) ☐ Check thickness of brake pads and discs, front and rear wheels removed ☐ Check brake system components, lines, hoses, calipers ☐ Check all exterior lights ☐ Check all exterior lights ☐ Check trunk / cargo area lights ☐ Replace battery for KEYLESS-GO key With KEYLESS-GO function I After consultation with customer ☐ Clean and lubricate Panoramic sliding roof guide mechanism | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4054R AP42.10-P-4252F AP82.10-P-8250EW AP82.10-P-8250EW AP82.10-P-8252EW AP54.30-P-5451HA AP54.30-P-5453E |

| Check chassis and load bearing body components for damage and corrosion | | |
|--|----------|--|
| Check ex-factory driving aids (where applicable) | | AP86.20-P-8649U |
| Check for body paint damage | | AP60.00-P-0050J |
| Check seatbelts and buckles for proper operation or damage | | |
| Check condition and operation of trailer hitch | | |
| With CODE 550 (Trailer coupling) | | AP31.11-P-3152A |
| High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years | | |
| I Plus any applicable additional work listed at the end of the service sheet | | |
| ⊠ Performed | Not OK | |
| (check if performed) | • | |
| Reset maintenance service indicator in instrument cluster | | AP00.20-P-0043J |
| Replace engine oil and filter | | |
| Engine 256 Engine 276 | | AP18.00-P-0101MRT AP18.00-P-0101CWZ |
| Clean visible area of water deflector | | A 10.00-1 -01010WZ |
| Check brake fluid level, correct if necessary | | AP42.10-P-4210B |
| Check thickness of brake pads and discs, front and rear wheels removed | | AP42.10-P-4252F |
| · | | AP40.15-P-4061A |
| Check and correct all tire air pressures, including spare where applicable | | |
| Check coolant level and correct if necessary Low-temperature circuit (engine 256) | | AP20.30-P-2052K |
| Low-temperature circuit (engine 250) | | AP20.30-P-2052H |
| Main circuit | | AP20.30-P-2050I |
| Check windshield washer system fluid, correct if necessary | | AP82.35-P-8210C |
| Observe correct coolant composition | | |
| Check catch, safety catch, and hinges on engine hood for proper operation | | |
| Check first aid kit | | AP68.00-P-6850EW |
| Reset maintenance service indicator in instrument cluster Reminder - if not yet performed | | AP00.20-P-0043J |
| High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years | | |
| I Plus any applicable additional work listed at the end of the service sheet | | |
| Performed | Not OK | ζ. |
| (check if performed) | <u>↓</u> | |
| Replace wiper blades | | |
| Check windshield wiper, washer and headlamp washer system operation | | AP82.35-P-8252D |
| □ Inspect tires for damage and measure remaining tread life | | AP40.10-P-4051EW |
| Tire rotation (where applicable) | | |
| Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual | | |
| Check TIREFIT tire sealant expiration date (where applicable) | | AP40.10-P-4054R |
| Check thickness of brake pads and discs, front and rear wheels removed | | AP42.10-P-4252F |
| | | |
| Check brake system components, lines, hoses, calipers | | AP82.10-P-8252EW |
| Check all exterior lights | | AP54.30-P-5451HA |
| Check warning/indicator lamps | | AP54.30-P-5453E |
| Check illumination and interior lighting | | |
| Check trunk / cargo area lights | | |
| Replace battery for KEYLESS-GO key With KEYLESS-GO function | | |
| After consultation with customer | | |
| Check horn | | |
| Check chassis and load bearing body components for damage and corrosion | | |

| Check ex-factory driving aids (where applicable) | | AP86.20-P-8649U |
|---|---|-----------------|
| High Mileage Additional Work | | |
| Performed (check if performed) | | |
| Replace engine air filter | | |
| Engine 256 | If more than 50,000 miles or 5 years since last replacement | AP09.10-P-0980L |
| Engine 276 | If more than 50,000 miles or 5 years since last replacement | AP09.10-P-0980E |
| Replace spark plugs | | |
| Engine 256 | If more than 50,000 miles or 5 years since last replacement | AP15.10-P-1580E |
| Engine 276 | If more than 50,000 miles or 5 years since last replacement | AP15.10-P-1580D |
| Replace automatic transmission oil and filter | If more than 60,000 miles or 6 years since last replacement | AP27.00-P-2702B |
| Replace transfer case oil Transmission 725.0 with CODE M005 (4MATIC) | If more than 60,000 miles or 6 years since last replacement | AP28.00-P-2801A |
| Replace fuel filter | If more than 120,000 miles or 12 years since last replacement | AP47.20-P-0780C |
| Replace main circuit coolant | If more than 120,000 miles or 12 years since last replacement | AP20.00-P-2082I |
| Observe correct coolant composition | | |
| Replace low-temperature circuit coolant | | |
| Observe correct coolant composition | | |
| Engine 256 | If more than 120,000 miles or 12 years since last replacement | AP20.00-P-2083D |
| Engine 276 | If more than 120,000 miles or 12 years since last replacement | AP20.00-P-2083I |

| Tire inflation pressure (bar/psi) | | | | | | | | | | | |
|-----------------------------------|----|----|----|-------|--|--|--|--|--|--|--|
| LF | RF | LR | RR | Spare | | | | | | | |
| | | | | | | | | | | | |

| Tire tread depth (mm) | | | | | | | | |
|-----------------------|----|----|----|----|--|--|--|--|
| | LF | RF | LR | RR | | | | |
| outside | | | | | | | | |
| center | | | | | | | | |
| inside | | | | | | | | |