

Brand	Viscosity	Product Description	Recommended Consumer Applications	NA Industry Approvals	ACEA Approvals	GM Service Fill Approval	Ford Service Fill Approval	Chrysler Service Fill Approval	Mercedes-Benz Approval	BMW Approval	VW Approval	Nominal & Relative Phos Level
Mobil 1 Extended Performance	5W-20	Boosted, fully synthetic formula designed for today's longer oil change intervals in Honda, Chryslers and newer Toyotas	Vehicles that require 5W-20	GF-4, SM	A1/B1-04		X	X				0.08/L
Mobil 1 Extended Performance	5W-30	Boosted, fully synthetic formula designed for today's longer oil change intervals in many domestic, including GM, and imported vehicles.	Vehicles that require 5W-30	GF-4, SM	A1/B1-04,A5/B5-04	X	X	X				0.08/L
Mobil 1 Extended Performance	10W-30	Boosted, fully synthetic formula designed for today's longer oil change intervals in many older domestics and imports.		GF-4, SM	A1/B1-04,A5/B5-04	X		X				0.08/L
Mobil 1 Extended Performance	15W-50	Boosted, higher viscosity, fully synthetic formula for today's longer oil change intervals	HT/HS applications. Racing and Flat tappet applications	SM	None							0.12/H
Mobil 1 ESP Formula M	5W-40	Fully synthetic formulas designed specifically for PCDOs that have particulate filters.	Low SAPS. Available at most MB dealers.	None					229.31, 229.51			0.08/L
Mobil 1 ESP Formula	5W-30	Fully synthetic formulas designed specifically for PCDOs that have particulate filters.	Low SAPS. Available at many Chrysler dealers.	CF	A3/B3-04,A3/B4-04,C3/C2-04			MS-11106	229.31, 229.51	Longlife-04	504/507	0.08/L