
AR88.70-P-9040T Remove/install outside rearview mirror paneling	30.8.01
---	---------

MODEL 211.0/ 2/ 6


- 1 Outside mirror paneling
- 2 Retaining clamp



Modification notes

10.12.04 "Glue sliding tape to outside mirror" added	Step 5.1	
--	----------	--

XX	Remove/Install		
1	Remove mirror glass		AR88.70-P-9020R
2	Fold outside rearview mirror toward rear	i Installation: Outside rearview mirror should catch.	
3	Press retaining clip (2) back with suitable tool and remove outside mirror paneling (1)		
4	Install in the reverse order		
⚠ Danger!	Risk of injury. Moving parts can pinch, crush or, in extreme cases even sever extremities.	No parts of the body or limbs should be within the operating range of the mechanism when moving components.	AS00.00-Z-0009-01A
5.1	Glue sliding tape to outside mirror paneling (1)	On vehicles with code (500) folding left/right outside mirror	AR88.70-P-9040-01T *110589035900 *BR00.45-Z-1029-04A *BR00.45-Z 1002.02B
		Sliding tape	*BR00.45-Z-1002-02B



Mounting wedge

Auxiliary repair materials

Number	Designation	Order number
BR00.45-Z-1029-04A	Glass cleanser	005 989 19 71
BR00.45-Z-1002-02B	Sliding tape	A 211 811 00 96