



Mercedes-Benz

AP00.20-U-1208DC SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

MODEL 211
except AMG and diesel models

Passenger cars Model Year 2007
USA

Model 211









Customer: _____ Repair order number: _____
First visit at 1,000 - 3,000 miles Performed YES [] NO []
Tire Rotation Performed in accordance with the tire manufacturer's recommended intervals Tires rotated YES [] NO []
Tire Inspection Inspect tires for damage and correct tire inflation pressure Tires inspected YES [] NO []
Current mileage reading: _____ Oil grade/viscosity: _____
Additional notes: _____




Service work to be performed as advised by service advisor: _____ Completion date: _____ Confirm work has been performed by signing below: _____



US Service 1-11 and 15-20 apply to "Additional work" items only.
Vehicle determines need for US Service 12 (Engine oil and filter change) as well as US Service 13 or US Service 14.
Perform each service as described.

Completed <input checked="" type="checkbox"/>	Not OK
↓	↓
US Service 1	Not applicable
US Service 2 Required	every 52,000 mi or 4 years: Engine compartment
<input type="checkbox"/>	Replace engine air-cleaner insert Engines 272, 273 AP09.10-P-0980TS
US Service 3 Required	every 26,000 mi or 2 years: Engine compartment
<input type="checkbox"/>	Replace combination filter AP83.00-P-8384T
US Service 4	Not applicable
US Service 5 Required	every 143,000 mi or 15 years: Passenger compartment
<input type="checkbox"/>	Replace fuel filter Engines 272, 273 AP47.20-P-0780TC
US Service 6	Not applicable
US Service 7 Required	every 91,000 mi or 5 years: Engine compartment
<input type="checkbox"/>	Replace spark plugs Engines 272, 273 AP15.10-P-1580TS
US Service 8 Required	every 143,000 mi or 15 years: Engine compartment
<input type="checkbox"/>	Replace coolant Engines 272, 273 AP20.00-P-2080DA
US Service 9 Required	every 2 years: Engine compartment
<input type="checkbox"/>	Replace brake fluid AP42.00-P-4280T
US Service 9 Recommended	every 2 years:
<input type="checkbox"/>	Check body for paint damage by service advisor AP98.00-P-9850BA
<input type="checkbox"/>	Underside of vehicle Chassis and load-bearing body components: Check for damage and corrosion by service advisor AP00.20-P-0090BA
US Service 10 Recommended	every 5 years: Interior
<input type="checkbox"/>	Tilt/sliding roof: Clean slide rails and slide shoes AP77.20-P-7731A
US Service 11 Recommended	every 3 years: Interior
<input type="checkbox"/>	Panorama sliding roof: Clean and lubricate guide mechanism AP77.20-P-7732PB
US Service 12 Required	every 13,000 mi or 1 year: Engine compartment
<input type="checkbox"/>	Engine oil and filter change Engines 272, 273 AP18.00-P-0101TS
US Service 13	first at 13,000 mi or 1 year; after first every 26,000 mi or 2 years
US Service 14	first at 26,000 mi or 2 years; after first every 26,000 mi or 2 years
↓	Not OK ↓
	Engine compartment - Required
<input type="radio"/>	Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order AP00.20-P-0053BA

US Service 13 ↓	US Service 14 ↓		Not OK ↓
<input type="checkbox"/>	<input type="radio"/> Check condition of poly-V-belt <input type="radio"/> Check catch, safety catch and hinges on engine hood for proper operation. Check fluid level, correct as required <i>i</i> If there is a loss of fluid, determine cause and perform repair via separate work order		<input type="checkbox"/> AP13.22-P-1352TS <input type="checkbox"/> AP88.40-P-8851T
<input type="checkbox"/>	<input type="radio"/> Brake system	Engines 272, 273	<input type="checkbox"/> AP42.10-P-4210Z
<input type="checkbox"/>	<input type="radio"/> Power steering		<input type="checkbox"/> AP46.00-P-4611BB
<input type="checkbox"/>	<input type="radio"/> Windshield washer system (incl. summer/winter cleanser)		AP82.35-P-8210N
	Interior - Required		
<input type="checkbox"/>	<input type="radio"/> Reset service indicator in instrument cluster		AP00.20-P-0042TA
	Function test		
<input type="checkbox"/>	<input type="radio"/> Audible warning system		<input type="checkbox"/> AP54.30-P-5450A
	<input type="radio"/> Check parking brake (function test only)		<input type="checkbox"/> AP42.00-P-4290R
	Interior - Recommended		
	Function test		
<input type="checkbox"/>	<input type="radio"/> Warning/indicator lamps, illumination and interior lighting		<input type="checkbox"/>
<input type="checkbox"/>	<input type="radio"/> Windshield washer system, incl. rear window washer (where applicable), headlamp cleaning system		<input type="checkbox"/> AP82.30-P-8252T
	<input type="radio"/> Check seat belts and buckles for signs of external damage and proper function		<input type="checkbox"/> AP91.40-P-9150M
	Wheels, brakes - Required		
<input type="checkbox"/>	<input type="radio"/> Check thickness of brake pads, front and rear		<input type="checkbox"/> AP42.10-P-4253A
<input type="checkbox"/>	<input type="radio"/> Correct tire inflation pressure and enter in bar or psi.		<input type="checkbox"/>
	LF RF LR RR bar/psi: _____		
	Wheels, brakes - Recommended		
<input type="checkbox"/>	<input type="radio"/> Remove and install wheels		<input type="checkbox"/> AP40.10-P-4050Z
<input type="checkbox"/>	<input type="radio"/> Inspect tires for damage and splits, measure tread depth, enter in mm:		<input type="checkbox"/> AP40.10-P-4051Z
	LF RF LR RR outside _____ center _____ inside _____		
	Underside of vehicle - Required		
	<input type="radio"/> Leakage - Major components Check for chafe marks, line routing, damaged components <i>i</i> In the event of leakage, determine cause and perform repair via separate work order		<input type="checkbox"/> AP00.20-P-0053BA

US Service 13 ↓	US Service 14 ↓	Not OK ↓
	<input type="radio"/> Check front axle ball joints for play, check rubber boots <input type="radio"/> Inspect condition of flexible discs <input type="radio"/> Inspect play of tie rod and drag link joints, inspect rubber boots	<input type="checkbox"/> AP33.20-P-3353BA <input type="checkbox"/> AP41.10-P-4152Z <input type="checkbox"/> AP46.00-P-4653F
	Trunk - Required	
<input type="checkbox"/>	<input type="radio"/> Correct inflation pressure in spare tire and enter in bar or psi. bar/psi: _____	<input type="checkbox"/>
	Trunk - Recommended	
<input type="checkbox"/>	<input type="radio"/> Check trunk lighting	<input type="checkbox"/>
<input type="checkbox"/>	<input type="radio"/> Check battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here.	<input type="checkbox"/> AP54.10-U-5453A
	Vehicle front/rear - Recommended	
<input type="checkbox"/>	<input type="radio"/> Check, correct headlamp setting	<input type="checkbox"/> AP82.10-P-8260T
<input type="checkbox"/>	<input type="radio"/> Check wiper blade condition	<input type="checkbox"/> AP82.30-P-8253G
Completed <input checked="" type="checkbox"/>	↓	Not OK ↓
US Service 15 - 19	not applicable	
US Service 20 Required	once at 39,000 mi: Underside of vehicle <input type="checkbox"/> Automatic transmission - Oil and filter change Transmission 722.6 Transmission 722.9 <input type="checkbox"/> Transfer case - oil change (4MATIC models)	AP27.00-P-2702I AP27.00-P-2702W AP28.00-P-2801P