



Mercedes-Benz

AP00.20-U-1208D SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

MODEL 211
except AMG models

Passenger cars Model Year 2005
USA

Model 211



Customer: _____

Repair order number: _____

First visit at 1,000 - 3,000 miles Performed YES [] NO []

Tire Rotation (non staggered width wheel setup only) Performed in accordance with the tire manufacturer's recommended intervals Tires rotated YES [] NO []

Tire Inspection (staggered and non-staggered width wheel setup) Inspect tires for damage and correct tire inflation pressure Tires inspected YES [] NO []

Current mileage reading: _____

Oil grade/viscosity: _____

Additional notes: _____

Service work to be performed as advised by service advisor:






Completion date:

Confirm work has been performed by signing below:



US Service 1 through US Service 11 apply to "Additional work" items only.
Vehicle determines need for US Service 12 (Engine oil and filter change) as well as US Service 13 or US Service 14 (formerly A-Service and B-Service respectively).
Perform service necessary as indicated in display of instrument cluster only.
Perform each service as described.

Completed <input checked="" type="checkbox"/>	Not OK
↓	↓
US Service 1 Display in instrument cluster Wheels, brakes <input type="checkbox"/> Check brake pads for lining thickness front/rear, check condition of brake discs front/rear	<input type="checkbox"/>
US Service 2 Required every 52,000 mi or 4 years: Engine compartment <input type="checkbox"/> Replace engine air-cleaner insert	
US Service 3 Required every 26,000 mi or 2 years: Engine compartment <input type="checkbox"/> Replace combination filter	Models E320, E320 CDI, E500 AP83.00-P-8384T
US Service 4 Required every 26,000 mi or 2 years: Engine compartment <input type="checkbox"/> Replace dust filter	Models E320 CDI, E500
US Service 5 Required every 65,000 mi or 5 years: Engine compartment <input type="checkbox"/> Replace fuel filter	Gasoline engines (112, 113) AP47.20-P-0780TC
US Service 5 Required every 26,000 mi or 2 years: Engine compartment <input type="checkbox"/> Replace fuel filter	Diesel engine (648) AP47.20-P-0780T
US Service 6 Recommended every 52,000 mi or 5 years: Interior <input type="checkbox"/> Replace activated charcoal filter	Models E320 CDI, E500 AP83.00-P-8382F
US Service 7 Required every 91,000 mi or 5 years: Engine compartment <input type="checkbox"/> Replace spark plugs	Engines 112, 113 AP15.10-P-1580AB
US Service 8 Required every 143,000 mi or 15 years: Engine compartment <input type="checkbox"/> Replace coolant	Gasoline engines Diesel engine AP20.00-P-2080DA AP20.00-P-2080BA
US Service 9 Required every 2 years: Engine compartment <input type="checkbox"/> Replace brake fluid <input type="checkbox"/> Prior to replacing brake fluid perform the following checks via STAR DIAGNOSIS SYSTEM (SDS): 1 - Check pretension pressure of Sensotronic Brake Control (SBC) pressure reservoir 2 - Check operating time of Sensotronic Brake Control (SBC) unit	AP42.00-P-4280R
US Service 9 Recommended every 2 years: <input type="checkbox"/> Check body for paint damage by service advisor Underside of vehicle <input type="checkbox"/> Chassis and load-bearing body components: Check for damage and corrosion by service advisor	<input type="checkbox"/> AP98.00-P-9850BA <input type="checkbox"/> AP00.20-P-0090BA

US Service 13 ↓	US Service 14 ↓	Not OK ↓
	<p>Interior - Recommended</p> <p>Function test</p> <p><input type="checkbox"/> <input type="radio"/> Warning/indicator lamps, illumination and interior lighting</p> <p><input type="checkbox"/> <input type="radio"/> Windshield washer system, incl. rear window washer (where applicable)</p> <p><input type="checkbox"/> <input type="radio"/> Headlamp cleaning system</p> <p><input type="checkbox"/> <input type="radio"/> Check seat belts and buckles for signs of external damage and proper function</p>	<p><input type="checkbox"/></p> <p><input type="checkbox"/> AP82.30-P-8252T</p> <p><input type="checkbox"/></p> <p><input type="checkbox"/> AP91.40-P-9150M</p>
	<p>Wheels, brakes - Required</p> <p><input type="checkbox"/> <input type="radio"/> Check thickness of brake pads, front and rear</p> <p><input type="checkbox"/> <input type="radio"/> Correct tire inflation pressure (incl. spare tire) and enter in bar or psi.</p> <p style="text-align: center;">LF RF LR RR Spare</p> <p>bar/psi: ___ ___ ___ ___ ___</p>	<p><input type="checkbox"/> AP42.10-P-4253A</p> <p><input type="checkbox"/></p>
	<p>Wheels, brakes - Recommended</p> <p><input type="checkbox"/> <input type="radio"/> Inspect tires for damage and splits, measure tread depth, enter in mm:</p> <p style="text-align: center;">LF RF LR RR</p> <p>outside ___ ___ ___ ___</p> <p>center ___ ___ ___ ___</p> <p>inside ___ ___ ___ ___</p>	<p><input type="checkbox"/> AP40.10-P-4051Z</p>
	<p>Underside of vehicle - Required</p> <p><input type="radio"/> Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order</p> <p><input type="radio"/> Check front axle ball joints for play, check rubber boots</p> <p><input type="radio"/> Inspect condition of flexible discs</p> <p><input type="radio"/> Inspect play of tie rod and drag link joints, inspect rubber boots</p>	<p><input type="checkbox"/> AP00.20-P-0053BA</p> <p><input type="checkbox"/> AP33.20-P-3353BA</p> <p><input type="checkbox"/> AP41.10-P-4152Z</p> <p><input type="checkbox"/> AP46.00-P-4653F</p>
	<p>Trunk - Recommended</p> <p><input type="checkbox"/> <input type="radio"/> Check main battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here.</p>	<p><input type="checkbox"/> AP54.10-U-5453A</p>