

P72.20-2400-09

- 1 Upper paneling
- 2 Lower paneling
- 3 Center paneling
- 4 Retaining clips
- 5 Retaining clips
- 6 Expanding clip
- 7 Bolt

- 8 Handle flap frame
- 9 Rear-end door
- E18/1 Luggage compartment lamp
- S62/21 Trunk lid Keyless button (with code (889) Keyless go)


- S62/35 Close rear-end door button (with code (890) Automatic rear-end door)
- S150 Loading floor switch (with code (943) Extendable automatic main loading floor)

Modification notes

8.1.04	Disconnect/connect/remove ground line from battery		
--------	--	--	--

	Remove/Install		
1	Switch off luggage compartment lamp (E18/1) by locking the rear-end door lock with suitable screwdriver	Installation: Actuate opening handle on inside of rear-end door (9) to unlock the rear-end door lock.	
2	Unclip upper paneling (1) on retaining clips (4, 5) from rear-end door (9) with mounting wedge and remove	Do not remove upper paneling (1) when only lower paneling (2) must be removed Installation: Replace defective retaining clips (4, 5) Ensure that upper paneling (1) is seated correctly.	*110589035900
3	Remove expanding clips (6)		
4.1	Remove bottom paneling (2) until electrical connector on rear-end door closing button (S62/35) is accessible and disconnect electrical connector on rear-end door closing button (S62/35)	On vehicles with code (890) Automatic rear-end door	
5.1	Remove bottom paneling (2) until electrical connector on loading floor switch (S150) is accessible and disconnect electrical connector on loading floor switch (S150)	On vehicles with code (943) Automatically extending main loading floor	
6.1	Remove bottom paneling (2) until electrical connector on trunk lid Keyless go button (S62/21) is accessible and disconnect electrical connector on trunk lid Keyless go button (S62/21)	On vehicles with code (889) Keyless go	
7	Remove bottom paneling (2) from rear-end door (9)		
8	Remove bolt (7)		

9	Slide handle flap frame (8) in direction of arrow (arrow A) and remove		
10	Lift center paneling (3) in area of inner handle flap with mounting wedge (arrowB)		*110589035900
11	Slide center paneling (3) in direction of arrow (arrow A) and lower until electrical connector on luggage compartment lamp (E18/1) is accessible		
12	Disconnect electrical connector from luggage compartment lamp (E18/1) and remove center paneling (3)		
13	Install in the reverse order		



110 589 03 59 00

Mounting wedge