


Required Service Work	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK
☒ Performed (check if performed)	years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	↓
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP00.20-P-0042TA
<input type="checkbox"/> Engine - oil and filter change																		
engine 156			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101TMG
engine 272			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101PIT
engine 273			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101SX
engine 642			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101PI
<input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP88.40-P-8851T
<input type="checkbox"/> Check condition of poly-V-belt																		
engine 156, 272, 273				•		•		•		•		•		•		•		<input type="checkbox"/> AP13.22-P-1352TS
engine 642				•		•		•		•		•		•		•		<input type="checkbox"/> AP13.22-P-1352TI
<input type="checkbox"/> Replace brake fluid				•		•		•		•		•		•		•		AP42.00-P-4280T
<input type="checkbox"/> Replace combination filter				•		•		•		•		•		•		•		AP83.00-P-8384T
<input type="checkbox"/> Check thickness of brake pads, front and rear			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4253A
<input type="checkbox"/> Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP40.15-P-4061B
<input type="checkbox"/> Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components				•		•		•		•		•		•		•		<input type="checkbox"/> AP00.20-P-0053BA
<input type="checkbox"/> Visually inspect condition of front axle ball joints, rubber boots				•		•		•		•		•		•		•		<input type="checkbox"/> AP33.20-P-3353BA
<input type="checkbox"/> Visually inspect condition of driveshaft flexible discs				•		•		•		•		•		•		•		<input type="checkbox"/> AP41.10-P-4152Z
<input type="checkbox"/> Visually inspect condition of steering mechanical components, rubber boots				•		•		•		•		•		•		•		<input type="checkbox"/> AP46.00-P-4653F
<input type="checkbox"/> Coolant - check fluid level and correct if necessary			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
☒ refer to AH20.00-P-1142-01V (except engine 642)																		
☒ refer to AH20.00-P-1142-01TI (engine 642)																		
☒ observe correct coolant composition																		
<input type="checkbox"/> Brake system - check fluid level and correct if necessary			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4210Z
<input type="checkbox"/> Power steering - check fluid level and correct if necessary			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP46.00-P-4612T
☒ the fluid level must always be on the maximum mark, corresponding to the oil temperature																		
<input type="checkbox"/> Windshield washer system - check fluid level and correct if necessary			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP82.35-P-8210N
<input type="checkbox"/> Parking brake (function test only)				•		•		•		•		•		•		•		<input type="checkbox"/> AP42.00-P-4290BA
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP00.20-P-0042TA
☒ reminder - if not yet performed																		
Required Additional Work	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK
☒ Performed (check if performed)	years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	↓
<input type="checkbox"/> Rear axle differential fluid replacement CODE 471 (manual locking differential)			•			•				•				•				
<input type="checkbox"/> Transfer case - oil change 4MATIC models						•												AP28.00-P-2801P
<input type="checkbox"/> Replace air filter engine 156						•				•				•				AP09.10-P-0980TMG

Required Additional Work <input checked="" type="checkbox"/> Performed (check if performed)	miles (thousands) years	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK ↓
			1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
engine 272, 273 engine 642						•				•				•				AP09.10-P-0980TS AP09.10-P-0980TI
<input type="checkbox"/> Automatic transmission - oil and filter change transmission 722.6 transmission 722.9						•				•				•				AP27.00-P-2702I AP27.00-P-2702W
<input type="checkbox"/> Replace spark plugs except engine 642 engine 156 engine 272, 273						•				•				•				AP15.10-P-1580TMG AP15.10-P-1580TS
<input type="checkbox"/> Replace fuel filter																	•	AP47.20-P-0780TC
<input type="checkbox"/> Replace coolant engine 156 engine 272, 273 engine 642																	• • •	AP20.00-P-2080TMG AP20.00-P-2080DA AP20.00-P-2080BA
Recommended Service Work <input checked="" type="checkbox"/> Performed (check if performed)	miles (thousands) years	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK ↓
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15		
<input type="checkbox"/> Main/starter battery - Check fluid level and correct if necessary			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP54.10-P-5410A
<input type="checkbox"/> Horn - Electrical system check			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Warning/indicator lamps - Electrical system check			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP54.30-P-5451T
<input type="checkbox"/> Illumination and interior lighting - Electrical system check			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP54.30-P-5453T
<input type="checkbox"/> Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP82.10-P-8252EW
<input type="checkbox"/> Check trunk/cargo area lighting			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Check and correct headlamp setting				•		•		•		•		•		•		•	AP82.10-P-8260T	
<input type="checkbox"/> Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP54.10-U-5453A
<input type="checkbox"/> Check seat belts and buckles for signs of external damage and proper function				•		•		•		•		•		•		•	<input type="checkbox"/> AP91.40-P-9150M	
<input type="checkbox"/> Check windshield washer and headlamp cleaning system			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP82.30-P-8252A
<input type="checkbox"/> Check, clean, and lubricate tilt/sliding roof mechanism with CODE 414 (Electric sunroof, glass version)				•		•		•		•		•		•		•	AP77.20-P-7731A	
<input type="checkbox"/> Check, clean, and lubricate panoramic roof mechanism with CODE 413 (Panoramic glass roof with top sliding roof)				•		•		•		•		•		•		•	AP77.20-P-7732PB	
<input type="checkbox"/> Check bodywork for paintwork damage				•		•		•		•		•		•		•	<input type="checkbox"/> AP98.00-P-9850BA	
<input type="checkbox"/> Tire rotation where applicable			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
<input type="checkbox"/> Inspect tires for damage, measure thread depth and enter table at the end of the service sheet			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP40.10-P-4051Z
<input type="checkbox"/> Check TIREFIT tire sealant expiration date where applicable			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP40.10-P-4054R
<input type="checkbox"/> Activate Tire Pressure Monitoring System  refer to vehicle Operator's Manual			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	

Recommended Service Work	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK ↓	
																			years
<input checked="" type="checkbox"/> Performed (check if performed)																			
<input type="checkbox"/> Visually check brake system components, lines, hoses, calipers			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed																			
pads			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4253A
discs			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4258R
<input type="checkbox"/> Check chassis and load-bearing body components for damage and corrosion				•		•		•		•		•		•		•		<input type="checkbox"/> AP00.20-P-0090SX	
<input type="checkbox"/> Replace wiper blades			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
High Mileage Required Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years																			
<i>i</i> Plus any applicable additional work listed at the end of the service sheet																			
<input checked="" type="checkbox"/> Performed (check if performed)																			Not OK ↓
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster																			AP00.20-P-0042TA
<input type="checkbox"/> Engine - oil and filter change																			
engine 156																			AP18.00-P-0101TMG
engine 272																			AP18.00-P-0101PIT
engine 273																			AP18.00-P-0101SX
engine 642																			AP18.00-P-0101PI
<input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation																			<input type="checkbox"/> AP88.40-P-8851T
<input type="checkbox"/> Check condition of poly-V-belt																			
engine 156, 272, 273																			<input type="checkbox"/> AP13.22-P-1352TS
engine 642																			<input type="checkbox"/> AP13.22-P-1352TI
<input type="checkbox"/> Replace brake fluid																			AP42.00-P-4280T
<input type="checkbox"/> Replace combination filter																			AP83.00-P-8384T
<input type="checkbox"/> Check thickness of brake pads, front and rear																			<input type="checkbox"/> AP42.10-P-4253A
<input type="checkbox"/> Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet																			AP40.15-P-4061B
<input type="checkbox"/> Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components																			<input type="checkbox"/> AP00.20-P-0053BA
<input type="checkbox"/> Visually inspect condition of front axle ball joints, rubber boots																			<input type="checkbox"/> AP33.20-P-3353BA
<input type="checkbox"/> Visually inspect condition of driveshaft flexible discs																			<input type="checkbox"/> AP41.10-P-4152Z
<input type="checkbox"/> Visually inspect condition of steering mechanical components, rubber boots																			<input type="checkbox"/> AP46.00-P-4653F
<input type="checkbox"/> Coolant - check fluid level and correct if necessary																			<input type="checkbox"/>
<i>i</i> refer to AH20.00-P-1142-01V (except engine 642)																			
<i>i</i> refer to AH20.00-P-1142-01TI (engine 642)																			
<i>i</i> observe correct coolant composition																			
<input type="checkbox"/> Brake system - check fluid level and correct if necessary																			<input type="checkbox"/> AP42.10-P-4210Z
<input type="checkbox"/> Power steering - check fluid level and correct if necessary																			<input type="checkbox"/> AP46.00-P-4612T
<i>i</i> the fluid level must always be on the maximum mark, corresponding to the oil temperature																			
<input type="checkbox"/> Windshield washer system - check fluid level and correct if necessary																			<input type="checkbox"/> AP82.35-P-8210N
<input type="checkbox"/> Parking brake (function test only)																			<input type="checkbox"/> AP42.00-P-4290BA

<input type="checkbox"/> Reset maintenance service indicator in instrument cluster	AP00.20-P-0042TA
<input type="checkbox"/> reminder - if not yet performed	
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years	
<input type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet	
<input checked="" type="checkbox"/> Performed (check if performed)	Not OK ↓
<input type="checkbox"/> Main/starter battery - Check fluid level and correct if necessary	<input type="checkbox"/> AP54.10-P-5410A
<input type="checkbox"/> Horn - Electrical system check	<input type="checkbox"/>
<input type="checkbox"/> Warning/indicator lamps - Electrical system check	<input type="checkbox"/> AP54.30-P-5451T
<input type="checkbox"/> Illumination and interior lighting - Electrical system check	<input type="checkbox"/> AP54.30-P-5453T
<input type="checkbox"/> Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check	<input type="checkbox"/> AP82.10-P-8252EW
<input type="checkbox"/> Check trunk/cargo area lighting	<input type="checkbox"/>
<input type="checkbox"/> Check and correct headlamp setting	AP82.10-P-8260T
<input type="checkbox"/> Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here	<input type="checkbox"/> AP54.10-U-5453A
<input type="checkbox"/> Check seat belts and buckles for signs of external damage and proper function	<input type="checkbox"/> AP91.40-P-9150M
<input type="checkbox"/> Check windshield washer and headlamp cleaning system	<input type="checkbox"/> AP82.30-P-8252A
<input type="checkbox"/> Check, clean, and lubricate tilt/sliding roof mechanism with CODE 414 (Electric sunroof, glass version)	AP77.20-P-7731A
<input type="checkbox"/> Check, clean, and lubricate panoramic roof mechanism with CODE 413 (Panoramic glass roof with top sliding roof)	AP77.20-P-7732PB
<input type="checkbox"/> Check bodywork for paintwork damage	<input type="checkbox"/> AP98.00-P-9850BA
<input type="checkbox"/> Tire rotation where applicable	
<input type="checkbox"/> Inspect tires for damage, measure thread depth and enter table at the end of the service sheet	<input type="checkbox"/> AP40.10-P-4051Z
<input type="checkbox"/> Check TIREFIT tire sealant expiration date where applicable	<input type="checkbox"/> AP40.10-P-4054R
<input type="checkbox"/> Activate Tire Pressure Monitoring System <input type="checkbox"/> refer to vehicle Operator's Manual	
<input type="checkbox"/> Visually check brake system components, lines, hoses, calipers	<input type="checkbox"/>
<input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed pads	<input type="checkbox"/> AP42.10-P-4253A
discs	<input type="checkbox"/> AP42.10-P-4258R
<input type="checkbox"/> Check chassis and load-bearing body components for damage and corrosion	<input type="checkbox"/> AP00.20-P-0090SX
<input type="checkbox"/> Replace wiper blades	
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years	
<input type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet	
<input checked="" type="checkbox"/> Performed (check if performed)	Not OK ↓
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster	AP00.20-P-0042TA
<input type="checkbox"/> Engine - oil and filter change engine 156	AP18.00-P-0101TMG
engine 272	AP18.00-P-0101PIT
engine 273	AP18.00-P-0101SX
engine 642	AP18.00-P-0101PI
<input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation	<input type="checkbox"/> AP88.40-P-8851T
<input type="checkbox"/> Check thickness of brake pads, front and rear	<input type="checkbox"/> AP42.10-P-4253A
<input type="checkbox"/> Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet	AP40.15-P-4061B

<input type="checkbox"/> Coolant - check fluid level and correct if necessary <input type="checkbox"/> refer to AH20.00-P-1142-01V (except engine 642) <input type="checkbox"/> refer to AH20.00-P-1142-01TI (engine 642) <input type="checkbox"/> observe correct coolant composition	<input type="checkbox"/>	
<input type="checkbox"/> Brake system - check fluid level and correct if necessary	<input type="checkbox"/>	AP42.10-P-4210Z
<input type="checkbox"/> Power steering - check fluid level and correct if necessary <input type="checkbox"/> the fluid level must always be on the maximum mark, corresponding to the oil temperature	<input type="checkbox"/>	AP46.00-P-4612T
<input type="checkbox"/> Windshield washer system - check fluid level and correct if necessary	<input type="checkbox"/>	AP82.35-P-8210N
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster <input type="checkbox"/> reminder - if not yet performed		AP00.20-P-0042TA
High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years		
<input type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet		
<input checked="" type="checkbox"/> Performed (check if performed)	Not OK ↓	
<input type="checkbox"/> Main/starter battery - Check fluid level and correct if necessary	<input type="checkbox"/>	AP54.10-P-5410A
<input type="checkbox"/> Horn - Electrical system check	<input type="checkbox"/>	
<input type="checkbox"/> Warning/indicator lamps - Electrical system check	<input type="checkbox"/>	AP54.30-P-5451T
<input type="checkbox"/> Illumination and interior lighting - Electrical system check	<input type="checkbox"/>	AP54.30-P-5453T
<input type="checkbox"/> Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check	<input type="checkbox"/>	AP82.10-P-8252EW
<input type="checkbox"/> Check trunk/cargo area lighting	<input type="checkbox"/>	
<input type="checkbox"/> Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here	<input type="checkbox"/>	AP54.10-U-5453A
<input type="checkbox"/> Check windshield washer and headlamp cleaning system	<input type="checkbox"/>	AP82.30-P-8252A
<input type="checkbox"/> Tire rotation where applicable		
<input type="checkbox"/> Inspect tires for damage, measure thread depth and enter table at the end of the service sheet	<input type="checkbox"/>	AP40.10-P-4051Z
<input type="checkbox"/> Check TIREFIT tire sealant expiration date where applicable	<input type="checkbox"/>	AP40.10-P-4054R
<input type="checkbox"/> Activate Tire Pressure Monitoring System <input type="checkbox"/> refer to vehicle Operator's Manual		
<input type="checkbox"/> Visually check brake system components, lines, hoses, calipers	<input type="checkbox"/>	
<input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed pads discs	<input type="checkbox"/> <input type="checkbox"/>	AP42.10-P-4253A AP42.10-P-4258R
<input type="checkbox"/> Replace wiper blades		
High Mileage Additional Work		
<input checked="" type="checkbox"/> Performed (check if performed)		
<input type="checkbox"/> Rear axle differential fluid replacement CODE 471 (manual locking differential)	At 2,000 miles, then if more than 40,000 mi or 4years since last replacement	
<input type="checkbox"/> Transfer case - oil change 4MATIC models	Once at 40,000 mi or 4 years	AP28.00-P-2801P
<input type="checkbox"/> Replace air filter engine 156 engine 272, 273 engine 642	If more than 40,000 mi or 4 years since last replacement If more than 40,000 mi or 4 years since last replacement If more than 40,000 mi or 4 years since last replacement	AP09.10-P-0980TMG AP09.10-P-0980TS AP09.10-P-0980TI
<input type="checkbox"/> Automatic transmission - oil and filter change transmission 722.6 transmission 722.9	If more than 40,000 mi or 4 years since last replacement If more than 40,000 mi or 4 years since last replacement	AP27.00-P-2702I AP27.00-P-2702W
<input type="checkbox"/> Replace spark plugs except engine 642 engine 156	If more than 80,000 mi or 8 years since last replacement	AP15.10-P-1580TMG

engine 272, 273	If more than 80,000 mi or 8 years since last replacement	AP15.10-P-1580TS
<input type="checkbox"/> Replace fuel filter	If more than 150,000 mi or 15 years since last replacement	AP47.20-P-0780TC
<input type="checkbox"/> Replace coolant		
<input checked="" type="checkbox"/> observe correct coolant composition		
engine 156	If more than 150,000 mi or 15 years since last replacement	AP20.00-P-2080TMG
engine 272, 273	If more than 150,000 mi or 15 years since last replacement	AP20.00-P-2080DA
engine 642	If more than 150,000 mi or 15 years since last replacement	AP20.00-P-2080BA

Tire inflation pressure (bar/psi)				
LF	RF	LR	RR	Spare

Tire thread depth (mm)				
	LF	RF	LR	RR
outside				
center				
inside				