

Mercedes-Benz

AP00.20-U-1208BF

SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model Year 2010

USA

Model 207



Customer:			Repair order num	ber:	
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recomme interval will likely nece at least once in betwee maintenance service a mile maintenance serv	essitate tire rotation en each 10,000-mile nd at every 10,000-	Tires rotated	YES	NO
i Note: For any condition f and perform the repair using	•	he checks or inspections	included in this ma	intenance sheet, de	termine the cause
Current mileage reading:			Oil grade/viscosit	y:	
Additional notes:					
Service work to be performed service advisor:	d as advised by	Completion date:	Confirm wor below:	rk has been perform	ed by signing

Required Service Work miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
☐ Performed years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK	
(check if performed)																	↓	
☐ Reset maintenance service indicator in		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
instrument cluster																		
☐ Engine - oil and filter change																		
Engine 272, 273		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101EW
☐ Check catch, safety catch and hinges on		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP88.40-P-8851EW
engine hood for proper operation																		
☐ Check condition of poly-V-belt																		
Engine 272, 273			•		•		•		•		•		•		•			AP13.22-P-1352EW
☐ Replace fuel filter																		
Engine 272, 273																•		AP47.20-P-0780EW
Replace coolant Observe correct coolant composition																		
Engine 272. 273																•		AP20.00-P-2080EW
☐ Replace brake fluid			•		•		•		•		•		•		•			AP42.00-P-4280EW
Replace combination or dust filter			•		•		•		•		•		•		•			AP83.00-P-8384EW
☐ Check thickness of brake pads, front and		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4253A
rear																	_	
☐ Correct tire inflation pressure and enter in		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
bar or psi:																		
LF RF LR RR																		
bar/psi:																		
Check inflation pressure in spare tire (if applicable) and enter in bar or psi:		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
bar/psi:																		
Leakage - Major components			•		•		•		•		•		•		•			AP00.20-P-0053EW
Check underbody and engine compartment																	_	
for chafe marks, line routing, damaged																		
components.																		
☐ Visually inspect condition of front axle ball			•		•		•		•		•		•		•			AP33.20-P-3353CW
joints, rubber boots																		
☐ Visually inspect condition of driveshaft flexible discs			•		•		•		•		•		•		•			AP41.10-P-4152EW
☐ Visually inspect condition of steering mechanical components, rubber boots			•		•		•		•		•		•		•			AP46.00-P-4653CW
Automatic transmission - oil and filter					_													A D27 OO D 2702W/
change					•				•				•					AP27.00-P-2702W
Replace air filter																		
Engine 272, 273					•													AP09.10-P-0980EW
					_				-				-					71 03.10-F-0300EVV
Replace spark plugs																		AD4E 40 D 45005147
Engine 272, 273									•									AP15.10-P-1580EW
Check the following fluid levels, correct if necessary																		
☐ Check coolant level		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AH20.00-P-1142-01V
☐ Brake system		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4210EW
miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15		

☑ Performed (check if performed)	miles (thousands) years	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10		120 12	130 13	140 14	150 15	Not OK ↓	
Power steering i The fluid level must a maximum mark, corresp temperature.																			
Engine 272, 273			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP46.00-P-4611EW
☐ Windshield washer s	system		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210EW
Function check																			
☐ Parking brake (funct	tion test only)			•		•		•		•		•		•		•			
i Reminder: Reset maint indicator in instrument clus			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
Recommended Service Performed (check if performed)	Work																	Not OK ↓	
☐ Replace wiper blades			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Electrical system checks																			
☐ Horn, high beam fla warning flasher, turn sig			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Warning/indicator la and interior lighting/ext			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5452C
☐ Check trunk/cargo a	rea lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check and correct he	eadlamp setting			•		•		•		•		•		•		•			AP82.10-P-8260EW
☐ Battery (main/starte condition using "Midtro tester. Attach Midtronic Report print out here	nics MCR 717"		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-U-5453A
Visual and functional check	s																		
☐ Check seat belts and external damage and pr				•		•		•		•		•		•		•			AP91.40-P-9150EC
☐ Check windshield wa	asher and headlamp		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.30-P-8252EW
☐ Check, clean, and lul roof mechanism (where	-			•		•		•		•		•		•		•			
☐ Check, clean, and lul roof mechanism (where	•			•		•		•		•		•		•		•			AP77.20-P-7732EW
☐ Check bodywork for	paintwork damage			•		•		•		•		•		•		•			AP98.00-P-9850EW
Tire checks																			
☐ Tire rotation (where	applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Inspect tires for dam thread depth and enter	in mm:		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051CW
☐ Check TIREFIT tire se date (where applicable)	alant expiration		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4054EW
	miles (thousands) years	2	10 1	20 2	30	40 4	50 5	60 6	70 7	80 8		100 10	110 11	120 12					

Performed miles (thousands) (check if performed) years	2	10 1	20 2	30 3	40 4	50 5		70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
☐ Activate Tire Pressure Monitoring		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
System; Refer to vehicle Operator's Manual																		
Chassis checks	+								-									
☐ Visually check brake system components, lines, hoses, calipers		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check thickness of brake pads and discs, front and rear wheels removed																		
Pads		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4253A
Discs		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4258EW
☐ Check chassis and load-bearing body components for damage and corrosion			•		•		•		•		•		•		•			AP00.20-P-0090EW
High Mileage Required Service Work at 1	60.0	000	mil	es o	or 1	6 v	ears	s:th	nen	eve	rv 2	0.00	0 mil	es or	· 2 ve	ears		
i Plus any applicable additional work listed at											•							
☑ Performed																	Not OK	
(check if performed) Reset maintenance service indicator in																	→	4 DOO 20 D 00425\A/
instrument cluster																		AP00.20-P-0042EW
☐ Engine - oil and filter change																		
Engine 272, 273																		AP18.00-P-0101EW
Check catch, safety catch and hinges on engine hood for proper operation																		AP88.40-P-8851EW
☐ Check condition of poly-V-belt																		
Engine 272, 273																		AP13.22-P-1352EW
☐ Replace brake fluid																		AP42.00-P-4280EW
☐ Replace combination or dust filter																		AP83.00-P-8384EW
Check thickness of brake pads, front and rear																		AP42.10-P-4253A
☐ Correct tire inflation pressure and enter in																		
bar or psi:																		
LF RF LR RR bar/psi:																		
☐ Check inflation pressure in spare tire																		
(if applicable) and enter in bar or psi:																	_	
bar/psi:																		
Leakage - Major components																		AP00.20-P-0053EW
Check underbody and engine compartment for chafe marks, line routing, damaged																		
components.																		
☐ Visually inspect condition of front axle ball joints, rubber boots																		AP33.20-P-3353CW
☐ Visually inspect condition of driveshaft flexible discs																		AP41.10-P-4152EW
☐ Visually inspect condition of steering																		AP46.00-P-4653CW
mechanical components, rubber boots																		
Check the following fluid levels, correct if																	<u></u>	
necessary																		
☐ Check coolant level																		AH20.00-P-1142-01V
☐ Brake system																		AP42.10-P-4210EW

Power steering i The fluid level must always be on the maximum mark, corresponding to the oil		
temperature.		
Engine 272, 273		AP46.00-P-4611EW
☐ Windshield washer system		AP82.35-P-8210EW
Function check		
☐ Parking brake (function test only)		
i Reminder: Reset maintenance service		AP00.20-P-0042EW
indicator in instrument cluster		
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles	es or 2 years	
☑ Performed	Not OK	
(check if performed)		
Replace wiper blades		
Electrical system checks		
☐ Horn, high beam flasher, hazard warning flasher, turn signals		
☐ Warning/indicator lamps, illumination and interior lighting/exterior lighting		AP54.30-P-5452C
☐ Check trunk/cargo area lighting		
☐ Check and correct headlamp setting		AP82.10-P-8260EW
☐ Battery (main/starter/auxiliary) check		AP54.10-U-5453A
condition using "Midtronics MCR 717"		
tester. Attach Midtronics MCR 717 Test		
Report print out here		
Visual and functional checks		A DOA 40 D 045056
☐ Check seat belts and buckles for signs of external damage and proper function	Ц	AP91.40-P-9150EC
Check windshield washer and headlamp		AP82.30-P-8252EW
cleaning system	Ь	AI 02.30-1 -0232LVV
☐ Check, clean, and lubricate tilt/sliding		
roof mechanism (where applicable)		
☐ Check, clean, and lubricate panoramic roof mechanism (where applicable)		AP77.20-P-7732EW
☐ Check bodywork for paintwork damage		AP98.00-P-9850EW
Tire checks		
☐ Tire rotation (where applicable)		
☐ Inspect tires for damage, measure		AP40.10-P-4051CW
thread depth and enter in mm:		
LF RF LR RR		
outsidecenter		
inside		
☐ Check TIREFIT tire sealant expiration		AP40.10-P-4054EW
date (where applicable)		
☐ Activate Tire Pressure Monitoring		
System; Refer to vehicle Operator's Manual		
Chassis checks		
☐ Visually check brake system		
components, lines, hoses, calipers		

☐ Check thickness of brake pads and discs,		
front and rear wheels removed	_	
Pads		AP42.10-P-4253A
Discs		AP42.10-P-4258EW
☐ Check chassis and load-bearing body components for damage and corrosion		AP00.20-P-0090EW
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years.	ars	
i Plus any applicable additional work listed at the end of this service sheet		
☑ Performed	Not OK	
(check if performed)		
Reset maintenance service indicator in		AP00.20-P-0042EW
instrument cluster		
Engine - oil and filter change		A D4 0 00 D 04 04 5 1 4 4
Engine 272, 273		AP18.00-P-0101EW
Check catch, safety catch and hinges on engine hood for proper operation		AP88.40-P-8851EW
☐ Check thickness of brake pads, front and		AP42.10-P-4253A
rear		
Correct tire inflation pressure and enter in		
bar or psi: LF RF LR RR		
bar/psi:		
☐ Check inflation pressure in spare tire		
(if applicable) and enter in bar or psi:		
bar/psi:		
Check the following fluid levels, correct if		
necessary		
Check coolant level		AH20.00-P-1142-01V
☐ Brake system		AP42.10-P-4210EW
Power steering i The fluid level must always be on the		
maximum mark, corresponding to the oil		
temperature.		
Engine 272, 273		AP46.00-P-4611EW
☐ Windshield washer system		AP82.35-P-8210EW
i Reminder: Reset maintenance service		AP00.20-P-0042EW
indicator in instrument cluster		
High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles	or 2 years	
☑ Performed	Not OK	
(check if performed)		
Replace wiper blades		
Electrical system checks		
☐ Horn, high beam flasher, hazard warning flasher, turn signals		
☐ Warning/indicator lamps, illumination	П	AP54.30-P-5452C
and interior lighting/exterior lighting	J	
☐ Check trunk/cargo area lighting		
☐ Battery (main/starter/auxiliary) check		AP54.10-U-5453A
condition using "Midtronics MCR 717"		
tester. Attach Midtronics MCR 717 Test Report print out here		

Visual and functional checks		
☐ Check windshield washer and headlamp cleaning system		AP82.30-P-8252EW
Tire checks		
☐ Tire rotation (where applicable)		
☐ Inspect tires for damage, measure thread depth and enter in mm: LF RF LR RR outside center inside		AP40.10-P-4051CW
☐ Check TIREFIT tire sealant expiration date (where applicable)		AP40.10-P-4054EW
☐ Activate Tire Pressure Monitoring System; Refer to vehicle Operator's Manual		
Chassis checks		
☐ Visually check brake system components, lines, hoses, calipers		
☐ Check thickness of brake pads and discs, front and rear wheels removed		
Pads		AP42.10-P-4253A
Discs		AP42.10-P-4258EW
High Mileage Additional Work ☑ Performed (check if performed)		
☐ Replace fuel filter		
Engine 272, 273	If more than 150,000 mi or 15 years since last replacement	AP47.20-P-0780EW
Replace coolant Observe correct coolant composition		
Engine 272. 273	If more than 150,000 mi or 15 years since last replacement	AP20.00-P-2080EW
☐ Automatic transmission - oil and filter change	If more than 40,000 mi or 4 years since last replacement	AP27.00-P-2702W
☐ Replace air filter		
Engine 272, 273	If more than 40,000 mi or 4 years since last replacement	AP09.10-P-0980EW
☐ Replace spark plugs		
Engine 272, 273	If more than 80,000 mi or 8 years since last replacement	AP15.10-P-1580EW