

Mercedes-Benz

AP00.20-U-1208DH

SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model Year 2012 USA

Model 212



Customer:			Repair order nur	mber:	
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommender likely necessitate tire rotation each 10,000-mile maintenance state of the state of	on at least once in between ance service and at every	Tires rotated	YES	NO
Note: For any co	ondition found while performin m the repair using a separate	ng the checks or inspections e repair order.	s included in this m	naintenance shee	et, determine
Current mileage read	ling:	_ Oi	I grade/viscosity:_		
Additional notes:					
Service work to be poservice advisor:	erformed as advised by		Confirm work has below:	been performed	by signing

Required Service Work miles (thousands) Performed years (check if performed)	2	10	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Reset maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
□ Engine - oil and filter change engine 157 engine 276 engine 278		•	•	•	•	•	•	• • •	•	•	•	• • •	•	•	• • •	•		AP18.00-P-0101EWG AP18.00-P-0101CWZ AP18.00-P-0101EW
engine 642 Check catch, safety catch and hinges on		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101EWO AP88.40-P-8851EW
engine hood for proper operation			_		_		_		•	_	_				•			AP13.22-P-1352EW
☐ Check condition of poly-V-belt ☐ Clean visible area of water deflector		_	-	_	-	_	-	_	•	_	•	_	•	_	•	_		AP82.35-P-8232A
☐ Fill up with DEF engine 642 with CODE U42 (BlueTEC diesel exhaust treatment (SCR)) i fill, subject to a separate invoice		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP14.40-P-1410BT
Replace brake fluid			•		•		•		•		•		•		•			AP42.00-P-4280EW
☐ Replace combination or dust filter			•		•		•		•		•		•		•			AP83.00-P-8384EW
☐ Check thickness of brake pads, front and rear		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4253A
Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.15-P-4061A
Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components			•		•		•		•		•		•		•			AP00.20-P-0053EW
☐ Check DEF lines and components for leaks and damage engine 642 with CODE U42 (BlueTEC diesel exhaust treatment (SCR))			•		•		•		•		•		•		•			AP00.20-P-0053EW
□ Visually inspect condition of front axle ball joints, rubber boots			•		•		•		•		•		•		•			AP33.20-P-3353EW
Usually inspect condition of driveshaft flexible discs			•		•		•		•		•		•		•			AP41.10-P-4152EW
Visually inspect condition of steering mechanical components, rubber boots			•		•		•		•		•		•		•			AP46.00-P-4653EW
Coolant - check fluid level and correct if necessary irefer to AH20.00-P-1142-01CW i observe correct coolant composition		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	П	
☐ Brake system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4210EW
Power steering - check fluid level and correct if necessary except CODE 211 (Direct-Steer system) the fluid level must always be on the maximum mark, corresponding to the oil temperature		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP46.00-P-4612EW
☐ Windshield washer system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210EW
☐ Parking brake (function test only)			•		•		•		•		•		•		•			AP42.00-P-4290BA
Reset maintenance service indicator in instrument cluster I reminder - if not yet performed		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
Required Additional Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Rear axle differential fluid replacement CODE 471 (manual locking differential)	•				•				•				•					AP35.00-P-3501CMG

	_											1	_		ı —			
Required Additional Work miles (thousands) Performed years (check if performed)	2	10	20	30	40	50 5	60	70 7	80	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Replace fuel filter engine 642					•				•				•					AP47.20-P-0780EWO
Replace fuel filter engine 157, 276, 278																•		AP47.20-P-0780EW
□ Automatic transmission - oil and filter change engine 157 with NAG2-V Sport and wet start-up clutch, engine 642 with NAG2 (transmission 722.9)					•				•				•					AP27.00-P-2702W
Automatic transmission - oil and filter change engine 276, 278 with NAG2-FE+ (transmission 722.9)								•							•			AP27.00-P-2702W
☐ Replace air filter																		
engine 276					•				•				•					AP09.10-P-0980MM
engine 157, 278					•				•				•					AP09.10-P-0980AB
engine 642					•				•				•					AP09.10-P-0980NEU
Replace spark plugs engine 157, 276, 278							•						•					AP15.10-P-1580EW
Replace coolant i observe correct coolant composition																•		AP20.00-P-2080EW
Recommended Service miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Work	-																N. (OK	
Performed years (check if performed)		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK	
																	<u> </u>	4 DOO OO D OOO 4 EU
Replace combination or dust filter		•		•		•		•		•		•		•		•		AP83.00-P-8384EW
Replace wiper blades		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Horn - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Warning/indicator lamps - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5453EW
☐ Illumination and interior lighting - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451EW
Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.10-P-8252EW
☐ Check trunk/cargo area lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check and correct headlamp setting			•		•		•		•		•		•		•			AP82.10-P-8260EW
☐ Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-U-5453A
☐ Check seat belts and buckles for signs of external damage and proper function			•		•		•		•		•		•		•			AP91.40-P-9150EW
☐ Check windshield washer and headlamp cleaning system		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.30-P-8252EW
Check, clean, and lubricate tilt/sliding roof mechanism where applicable			•		•		•		•		•		•		•			
Check, clean, and lubricate panoramic roof mechanism with CODE 413 (panoramic sliding sunroof)			•		•		•		•		•		•		•			AP77.20-P-7732EW
☐ Check bodywork for paintwork damage			•		•		•		•		•		•		•			AP98.00-P-9850EW
☐ Tire rotation where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Inspect tires for damage, measure thread depth and enter table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051EW
☐ Check TIREFIT tire sealant expiration date where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4054R

Recommended Service	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Work Performed (check if performed)	years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK ↓	
Activate Tire Pressure M			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Visually check brake sys lines, hoses, calipers	tem components,		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check thickness of brake and rear wheels removed	e pads and discs, front																		
pads			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4253A
discs - except CODE BO high-performance ceran system)			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4258EW
discs - with CODE B07 high-performance ceran system)			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4258QQ
☐ Check chassis and load- components for damage an				•		•		•		•		•		•		•			AP00.20-P-0090EW
High Mileage Required	l Service Work at 1	60,	000	mil	les	or '	16 y	eai	's; 1	the	n ev	ery	20,0	1 000	nile	s or	2 ye	ars	
i Plus any applicable	additional work li	ste	d at	the	er	ıd c	of th	e s	erv	ice	she	eet							
☑ Performed																		Not OK	
														•					
☐Reset maintenance s	ervice indicator in in	stru	ıme	nt c	lus	ter													AP00.20-P-0042EW
_																			
☐ Engine - oil and filter change engine 157 AP18.00-P-0101EWG																			
engine 157 engine 276														AP18.00-P-0101CWZ					
engine 278														AP18.00-P-0101EW					
												AP18.00-P-0101EWO							
☐ Check catch, safety catch and hinges on engine hood for proper operation													AP88.40-P-8851EW						
☐ Check condition of poly-V-belt														AP13.22-P-1352EW					
☐ Clean visible area of water deflector												AP82.35-P-8232A							
☐ Fill up with DEF engine 642 with CODE U42 (BlueTEC diesel exhaust treatment (SCR)) ☐ fill, subject to a separate invoice																			
Replace brake fluid																			AP42.00-P-4280EW
Replace combination	or dust filter																		AP83.00-P-8384EW
Check thickness of bi		rea	ar																AP42.10-P-4253A
☐ Correct tire inflation p	•			here	e ap	oplic	cabl	e) a	and	ent	er i	n the	tab	le at	the	end	of		AP40.15-P-4061A
Leakage - major com		derb	ody	/ an	d e	ngii	ne c	om	par	tme	nt f	or ch	nafe	mar	ks, li	ne			AP00.20-P-0053EW
Check DEF lines and engine 642 with COD							mer	nt (S	SCF	R))									AP00.20-P-0053EW
☐ Visually inspect cond	ition of front axle ba	II joi	ints	, rul	be	r bo	ots												AP33.20-P-3353EW
☐ Visually inspect cond	ition of driveshaft fle	xibl	e di	scs															AP41.10-P-4152EW
☐ Visually inspect cond	ition of steering med	har	nica	I co	mp	one	nts,	rul	be	r bc	ots								AP46.00-P-4653EW
☐ Coolant - check fluid	level and correct if r	ece	essa	ary															
i refer to AH20.00-P-1142-01CW																			
i observe correct coolant composition																			
☐ Brake system - check	fluid level and corre	ect	if ne	ces	saı	у													AP42.10-P-4210EW
Power steering - checexcept CODE 211 (Di		rec	t if r	nece	ess	ary													AP46.00-P-4612EW
i the fluid level must	always be on the m	axii	mur	n m	ark	CO	rres	spoi	ndir	na to	o th	e oil	tem	nera	ture				

☐ Windshield washer system - check fluid level and correct if necessary		AP82.35-P-8210EW
☐ Parking brake (function test only)		AP42.00-P-4290BA
Reset maintenance service indicator in instrument cluster i reminder - if not yet performed		AP00.20-P-0042EW
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles	or 2 yea	rs
i Plus any applicable additional work listed at the end of the service sheet		
☑ Performed	Not OK	, 1
(check if performed)	Ψ_	
Replace wiper blades		
Horn - Electrical system check		
☐ Warning/indicator lamps - Electrical system check		AP54.30-P-5453EW
□ Illumination and interior lighting - Electrical system check		AP54.30-P-5451EW
☐ Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check		AP82.10-P-8252EW
☐ Check trunk/cargo area lighting		
☐ Check and correct headlamp setting		AP82.10-P-8260EW
☐ Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here	. 🗆	AP54.10-U-5453A
☐ Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150EW
☐ Check windshield washer and headlamp cleaning system		AP82.30-P-8252EW
Check, clean, and lubricate tilt/sliding roof mechanism where applicable		
☐ Check, clean, and lubricate panoramic roof mechanism with CODE 413 (panoramic sliding sunroof)		AP77.20-P-7732EW
☐ Check bodywork for paintwork damage		AP98.00-P-9850EW
☐ Tire rotation where applicable		
☐ Inspect tires for damage, measure thread depth and enter table at the end of the service sheet		AP40.10-P-4051EW
☐ Check TIREFIT tire sealant expiration date where applicable		AP40.10-P-4054R
☐ Activate Tire Pressure Monitoring System ☐ refer to vehicle Operator's Manual		
☐ Visually check brake system components, lines, hoses, calipers		
Check thickness of brake pads and discs, front and rear wheels removed		
pads		AP42.10-P-4253A
discs - except CODE B07 (AMG high-performance ceramic composite braking system)		AP42.10-P-4258EW
discs - with CODE B07 (AMG high-performance ceramic composite braking system)		AP42.10-P-4258QQ
Check chassis and load-bearing body components for damage and corrosion		AP00.20-P-0090EW
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y	/ears	
Plus any applicable additional work listed at the end of the service sheet		,
Performed (check if performed)	Not OK	•
	Ψ	AD00 20 D 0042FW
☐ Reset maintenance service indicator in instrument cluster		AP00.20-P-0042EW
☐ Engine - oil and filter change		
engine 157		AP18.00-P-0101EWG
engine 276		AP18.00-P-0101CWZ AP18.00-P-0101EW
engine 278 engine 642		AP18.00-P-0101EW AP18.00-P-0101EWO
		AP88.40-P-8851EW
Clear visible area of water deflector		AP82.35-P-8232A
│		/ 11 UZ.UU-1 -UZUZA

☐ Fill up with DEF			AP14.40-P-1410BT
engine 642 with CODE U42 (BlueTEC dies	el exhaust treatment (SCR))		
i fill, subject to a separate invoice			AD40 40 D 4050A
Check thickness of brake pads, front and re	ear		AP42.10-P-4253A
Correct tire inflation pressure including spathe service sheet	re (where applicable) and enter in the table at the end of		AP40.15-P-4061A
☐ Coolant - check fluid level and correct if ne	cessary		
i refer to AH20.00-P-1142-01CW			
i observe correct coolant composition			
☐ Brake system - check fluid level and correct	t if necessary		AP42.10-P-4210EW
Power steering - check fluid level and correct except CODE 211 (Direct-Steer system)			AP46.00-P-4612EW
i the fluid level must always be on the ma	ximum mark, corresponding to the oil temperature		
☐ Windshield washer system - check fluid lev	rel and correct if necessary		AP82.35-P-8210EW
Reset maintenance service indicator in install reminder - if not yet performed	trument cluster		AP00.20-P-0042EW
	at 170,000 miles or 17 years; then every 20,000 miles of	or 2 yea	ırs
Plus any applicable additional work list		•	
☑ Performed		Not OK	(
(check if performed)		$lack \Psi$	
☐ Replace combination or dust filter			AP83.00-P-8384EW
☐ Replace wiper blades			
☐ Horn - Electrical system check			
☐ Warning/indicator lamps - Electrical system	check		AP54.30-P-5453EW
\square Illumination and interior lighting - Electrical	system check		AP54.30-P-5451EW
☐ Exterior lighting, high beam flasher, hazard	warning flasher, turn signals - Electrical system check		AP82.10-P-8252EW
☐ Check trunk/cargo area lighting			
$\hfill\Box$ Battery (Main/starter/auxiliary) check condireport print out here	tion using Midtronics battery tester. Attach Midtronics test		AP54.10-U-5453A
☐ Check windshield washer and headlamp cl	eaning system		AP82.30-P-8252EW
☐ Tire rotation where applicable			
☐ Inspect tires for damage, measure thread of	lepth and enter table at the end of the service sheet		AP40.10-P-4051EW
Check TIREFIT tire sealant expiration date where applicable			AP40.10-P-4054R
Activate Tire Pressure Monitoring System i refer to vehicle Operator's Manual			
☐ Visually check brake system components,	lines, hoses, calipers		
☐ Check thickness of brake pads and discs, f	·		
pads			AP42.10-P-4253A
discs - except CODE B07 (AMG high-perfo	ormance ceramic composite braking system)		AP42.10-P-4258EW
discs - with CODE B07 (AMG high-perforn	nance ceramic composite braking system)		AP42.10-P-4258QQ
High Mileage Additional Work ☑ Performed			
(check if performed)	At 2,000 miles, then if more than 40,000 miles 4 years sizes		AD25 00 D 2504CMC
Rear axle differential fluid replacement CODE 471 (manual locking differential)	At 2,000 miles, then if more than 40,000 mi or 4 years since lastreplacement		AP35.00-P-3501CMG
Replace fuel filter engine 642	If more than 40,000 mi or 4 years since last replacement		AP47.20-P-0780EWO
Replace fuel filter engine 157, 276, 278	If more than 150,000 mi or 15 years since last replacement		AP47.20-P-0780EW

Automatic transmission - oil and filter change engine 157 with NAG2-V Sport and wet start-up clutch, engine 642 with NAG2 (transmission 722.	If more than 40,000 mi or 4 years since last replacement 9)	AP27.00-P-2702W
Automatic transmission - oil and filter change engine 276, 278 with NAG2-FE+ (transmission 722.9)	If more than 70,000 mi or 7 years since last replacement	AP27.00-P-2702W
Replace air filter		
engine 276	If more than 40,000 mi or 4 years since last replacement	AP09.10-P-0980MM
engine 157, 278	If more than 40,000 mi or 4 years since last replacement	AP09.10-P-0980AB
engine 642	If more than 40,000 mi or 4 years since last replacement	AP09.10-P-0980NEU
Replace spark plugs engine 157, 276, 278	If more than 60,000 mi or 6 years since last replacement	AP15.10-P-1580EW
Replace coolant	If more than 150,000 mi or 15 years since last replacement	AP20.00-P-2080EW
i observe correct coolant composition		

Tire infl	Tire inflation pressure (bar/psi)											
LF	RF	LR	RR	Spare								

Tire thre	Tire thread depth (mm)										
	LF	RF	LR	RR							
outside											
center											
inside											