

## Mercedes-Benz

AP00.20-U-1208DJ

SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

## Model Year 2014 USA

## Model 212



| Customer:  |   |   | Repair order nur        | mber:            |               |
|--|---|---|-------------------------|------------------|---------------|
| Tire Rotation<br>(non-staggered width<br>wheel setup only) | A 5,000-mile recommender likely necessitate tire rotation each 10,000-mile maintenance state of the state of | on at least once in between ance service and at every | Tires rotated           | YES              | NO            |
| Note: For any co   | ondition found while performin<br>m the repair using a separate   | ng the checks or inspections<br>e repair order.       | s included in this m    | naintenance shee | et, determine |
| Current mileage read                                       | ling:   | _ Oi  | I grade/viscosity:_     |                  |               |
| Additional notes:  |   |   |                         |                  |               |
|  |   |   |                         |                  |               |
|  |   |   |                         |                  |               |
|  |   |   |                         |                  |               |
|  |   |   |                         |                  |               |
|  |   |   |                         |                  |               |
|  |   |   |                         |                  |               |
|  |   |   |                         |                  |               |
|  |   |   |                         |                  |               |
|  |   |   |                         |                  |               |
|  |   |   |                         |                  |               |
|  |   |   |                         |                  |               |
|  |   |   |                         |                  |               |
| Service work to be poservice advisor:                      | erformed as advised by  |   | Confirm work has below: | been performed   | by signing    |
|  |   |   |                         |                  |               |

| Required Service Work miles (thousands)  Performed years  (check if performed)   | 2 | 10<br>1 | 20<br>2 | 30      | 40<br>4 | 50<br>5 | 60<br>6 | 70<br>7 | 80<br>8 | 90 | 100<br>10 | 110<br>11 | 120<br>12 | 130<br>13 | 140<br>14 | 150<br>15 | Not OK<br><b>↓</b> |                   |
|--|---|---------|---------|---------|---------|---------|---------|---------|---------|----|-----------|-----------|-----------|-----------|-----------|-----------|--------------------|-------------------|
| ☐ Reset maintenance service indicator in instrument  |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP00.20-P-0042EW  |
| ☐ Engine - oil and filter change   |   |         |         |         |         |         |         |         |         |    |           |           |           |           |           |           |                    |                   |
| engine 157   |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP18.00-P-0101EWG |
| engine 276   |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP18.00-P-0101CWZ |
| engine 278   |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP18.00-P-0101EW  |
| engine 651   |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP18.00-P-0101CWA |
| ☐ Check catch, safety catch and hinges on engine hood for proper operation   |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP88.40-P-8851EW  |
| $\square$ Check condition of poly-V-belt   |   |         | •       |         | •       |         | •       |         | •       |    | •         |           | •         |           | •         |           |                    | AP13.22-P-1352CW  |
| ☐ Clean visible area of water deflector  |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP82.35-P-8232A   |
| Fill up with DEF engine 651 with CODE U42 (BlueTEC diesel exhaust treatment (SCR))  i fill, subject to a separate invoice    |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP14.40-P-1410BT  |
| ☐ Check starter using STAR DIAGNOSIS tester Model 212.095 (Hybrid) only  |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP15.30-P-1550AA  |
| Replace brake fluid  |   |         | •       |         | •       |         | •       |         | •       |    | •         |           | •         |           | •         |           |                    | AP42.00-P-4280EW  |
| Replace combination or dust filter   |   |         | •       |         | •       |         | •       |         | •       |    | •         |           | •         |           | •         |           |                    | AP83.00-P-8384EW  |
| ☐ Check thickness of brake pads, front and rear  |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP42.10-P-4252EW  |
| ☐ Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet  |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP40.15-P-4061A   |
| ☐ Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components      |   |         | •       |         | •       |         | •       |         | •       |    | •         |           | •         |           | •         |           |                    | AP00.20-P-0053EW  |
| ☐ Check DEF lines and components for leaks and damage engine 651 with CODE U42 (BlueTEC diesel exhaust treatment (SCR))      |   |         | •       |         | •       |         | •       |         | •       |    | •         |           | •         |           | •         |           |                    | AP00.20-P-0053EW  |
| ☐ Visually inspect condition of front axle ball joints, rubber boots   |   |         | •       |         | •       |         | •       |         | •       |    | •         |           | •         |           | •         |           |                    | AP33.20-P-3353EW  |
| ☐ Visually inspect condition of driveshaft flexible discs  |   |         | •       |         | •       |         | •       |         | •       |    | •         |           | •         |           | •         |           |                    | AP41.10-P-4152EW  |
| ☐ Visually inspect condition of steering mechanical components, rubber boots   |   |         | •       |         | •       |         | •       |         | •       |    | •         |           | •         |           | •         |           |                    | AP46.00-P-4653EW  |
| ☐ Coolant - check fluid level and correct if necessary  i refer to AH20.00-P-1142-01CW i observe correct coolant composition |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    |                   |
| $\square$ Brake system - check fluid level and correct if necessary  |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP42.10-P-4210EW  |
| ☐ Windshield washer system - check fluid level and correct if necessary  |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP82.35-P-8210EW  |
| ☐ Parking brake (function test only)   |   |         | •       |         | •       |         | •       |         | •       |    | •         |           | •         |           | •         |           |                    | AP42.00-P-4290BA  |
| ☐ Check starter. Use MB diagnosis tool.  Model 212.095 (Hybrid) only   |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP15.30-P-1550AA  |
| Reset maintenance service indicator in instrument cluster  ireminder - if not yet performed                                  |   | •       | •       | •       | •       | •       | •       | •       | •       | •  | •         | •         | •         | •         | •         | •         |                    | AP00.20-P-0042EW  |
| Required Additional Work miles (thousands)  Performed years (check if performed)   | 2 | 10<br>1 | 20<br>2 | 30<br>3 | 40<br>4 | 50<br>5 | 60<br>6 | 70<br>7 | 80<br>8 | 90 | 100<br>10 | 110<br>11 | 120<br>12 | 130<br>13 | 140<br>14 | 150<br>15 | Not OK<br><b>↓</b> |                   |
| Rear axle differential fluid replacement CODE 471 (manual locking differential)  | • |         |         |         | •       |         |         |         | •       |    |           |           | •         |           |           |           |                    | AP35.00-P-3501CMG |

| Required Additional Work miles (thousands)  Performed years (check if performed)   | 2 | 10<br>1 | 20<br>2 | 30<br>3 | 40<br>4 | 50<br>5 | 60<br>6 | 70<br>7 | 80<br>8 | 90<br>9 | 100<br>10 | 110<br>11 | 120<br>12 | 130<br>13 | 140<br>14 | 150<br>15 | Not OK<br><b>↓</b> |                       |
|--|---|---------|---------|---------|---------|---------|---------|---------|---------|---------|-----------|-----------|-----------|-----------|-----------|-----------|--------------------|-----------------------|
| Replace fuel filter engine 651   |   |         |         |         | •       |         |         |         | •       |         |           |           | •         |           |           |           |                    | AP47.20-P-0780EWD     |
| Replace fuel filter engine 157, 276, 278   |   |         |         |         |         |         |         |         |         |         |           |           |           |           |           | •         |                    | AP47.20-P-0780EW      |
| Automatic transmission - oil and filter change engine 157 with NAG2-V Sport and wet start-up clutch                              |   |         |         |         | •       |         |         |         | •       |         |           |           | •         |           |           |           |                    | AP27.00-P-2702W       |
| Automatic transmission - oil and filter change engine 276 in model E400 HYBRID (transmission 724.2)                              |   |         |         |         |         |         | •       |         |         |         |           |           | •         |           |           |           |                    | AP27.00-P-2702A       |
| Automatic transmission - oil and filter change engine 276, 278, 651 with NAG2-FE+ (transmission 722.9) except for E400 HYBRID    |   |         |         |         |         |         |         | •       |         |         |           |           |           |           | •         |           |                    | AP27.00-P-2702W       |
| Replace air filter engine 276  |   |         |         |         | •       |         |         |         | •       |         |           |           | •         |           |           |           |                    | AP09.10-P-0980MM      |
| engine 157, 278  |   |         |         |         | •       |         |         |         | •       |         |           |           | •         |           |           |           |                    | AP09.10-P-0980AB      |
| engine 651   |   |         |         |         | •       |         |         |         | •       |         |           |           | •         |           |           |           |                    | AP09.10-P-0980EWD     |
| Replace spark plugs engine 157, 276, 278   |   |         |         |         |         |         | •       |         |         |         |           |           | •         |           |           |           |                    | AP15.10-P-1580EW      |
| Replace coolant  i observe correct coolant composition   |   |         |         |         |         |         |         |         |         |         |           |           |           |           |           | •         |                    | AP20.00-P-2080EW      |
| Recommended Service miles (thousands)  | 2 | 10      | 20      | 30      | 40      | 50      | 60      | 70      | 80      | 90      | 100       | 110       | 120       | 130       | 140       | 150       |                    |                       |
| Work Performed (check if performed)  |   | 1       | 2       | 3       | 4       | 5       | 6       | 7       | 8       | 9       | 10        | 11        | 12        | 13        | 14        | 15        | Not OK             |                       |
|  |   | _       |         | _       |         | •       |         | _       |         | _       |           | _         |           | _         |           | _         | •                  | AP83.00-P-8384EW      |
| Replace combination or dust filter Replace wiper blades  |   | -       | _       | -       | _       | -       | _       | -       | _       | _       |           | •         | _         | •         | _         | •         |                    | 7.1. 00.001. 0001.211 |
| · · ·  |   | -       | -       | -       | _       | -       | _       | _       | _       | _       | -         | -         | -         | -         | _         | -         |                    |                       |
| ☐ Horn - Electrical system check ☐ Warning/indicator lamps - Electrical system   |   | •       | •       | •       | •       | •       | •       | •       | •       | •       | •         | •         | •         | •         | •         | •         |                    | AP54.30-P-5451EW      |
| check  Illumination and interior lighting/exterior lighting  |   |         | _       | _       | _       | _       | _       |         | _       |         | _         | _         | _         | _         |           | _         |                    | AP54.30-P-5453EW      |
| - Electrical system check  |   | _       | _       | _       | _       | _       | _       | _       | _       | _       | _         | •         | _         | •         | •         | •         |                    |                       |
| Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check                             |   | •       | •       | •       | •       | •       | •       | •       | •       | •       | •         | •         | •         | •         | •         | •         |                    | AP82.10-P-8252EW      |
| ☐ Check trunk/cargo area lighting  |   | •       | •       | •       | •       | •       | •       | •       | •       | •       | •         | •         | •         | •         | •         | •         |                    |                       |
| ☐ Check and correct headlamp setting   |   |         | •       |         | •       |         | •       |         | •       |         | •         |           | •         |           | •         |           |                    | AP82.10-P-8260EW      |
| ☐ Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here |   | •       | •       | •       | •       | •       | •       | •       | •       | •       | •         | •         | •         | •         | •         | •         |                    | AP54.10-U-5453A       |
| Check seat belts and buckles for signs of external damage and proper function  |   |         | •       |         | •       |         | •       |         | •       |         | •         |           | •         |           | •         |           |                    | AP91.40-P-9150EW      |
| Check windshield washer and headlamp cleaning system   |   | •       | •       | •       | •       | •       | •       | •       | •       | •       | •         | •         | •         | •         | •         | •         |                    | AP82.30-P-8252EW      |
| Check, clean, and lubricate tilt/sliding roof mechanism where applicable   |   |         | •       |         | •       |         | •       |         | •       |         | •         |           | •         |           | •         |           |                    |                       |
| Check, clean, and lubricate panoramic roof mechanism with CODE 413 (panoramic sliding sunroof)                                   |   |         | •       |         | •       |         | •       |         | •       |         | •         |           | •         |           | •         |           |                    | AP77.20-P-7732EW      |
| Check bodywork for paintwork damage  |   |         | •       |         | •       |         | •       |         | •       |         | •         |           | •         |           | •         |           |                    | AP98.00-P-9850EW      |
| ☐ Tire rotation where applicable   |   | •       | •       | •       | •       | •       | •       | •       | •       | •       | •         | •         | •         | •         | •         | •         |                    |                       |
| ☐ Inspect tires for damage, measure tread depth and enter table at the end of the service sheet                                  |   | •       | •       | •       | •       | •       | •       | •       | •       | •       | •         | •         | •         | •         | •         | •         |                    | AP40.10-P-4051EW      |
| Check TIREFIT tire sealant expiration date where applicable  |   | •       | •       | •       | •       | •       | •       | •       | •       | •       | •         | •         | •         | •         | •         | •         |                    | AP40.10-P-4054R       |

| Recommended Service   | miles (thousands)      | 2     | 10   | 20   | 30    | 40   | 50   | 60    | 70    | 80   | 90   | 100              | 110               | 120              | 130               | 140  | 150  |                    |                  |
|---|------------------------|-------|------|------|-------|------|------|-------|-------|------|------|------------------|-------------------|------------------|-------------------|------|------|--------------------|------------------|
| Work Performed (check if performed)   | years                  |       | 1    | 2    | 3     | 4    | 5    | 6     | 7     | 8    | 9    | 10               | 11                | 12               | 13                | 14   | 15   | Not OK<br><b>↓</b> |                  |
| Activate Tire Pressure M  |                        |       | •    | •    | •     | •    | •    | •     | •     | •    | •    | •                | •                 | •                | •                 | •    | •    |                    |                  |
| □ Visually check brake system components, lines, hoses, calipers                        |                        |       |      |      |       |      |      |       |       |      | •    |                  |                   |                  |                   |      |      |                    |                  |
| ☐ Check thickness of brake and rear wheels removed                                      | pads and discs, front  |       |      |      |       |      |      |       |       |      |      |                  |                   |                  |                   |      |      |                    |                  |
| pads  |                        |       | •    | •    | •     | •    | •    | •     | •     | •    | •    | •                | •                 | •                | •                 | •    | •    |                    | AP42.10-P-4252EW |
| discs - except CODE BO<br>high-performance ceran<br>system)                             |                        |       | •    | •    | •     | •    | •    | •     | •     | •    | •    | •                | •                 | •                | •                 | •    | •    |                    | AP42.10-P-4258EW |
| discs - with CODE B07 (<br>high-performance ceran<br>system)                            |                        |       | •    | •    | •     | •    | •    | •     | •     | •    | •    | •                | •                 | •                | •                 | •    | •    |                    | AP42.10-P-4258QQ |
| ☐ Check chassis and load-components for damage an                                       |                        |       |      | •    |       | •    |      | •     |       | •    |      | •                |                   | •                |                   | •    |      |                    | AP00.20-P-0090EW |
| High Mileage Required   | Service Work at 1      | 60,   | 000  | mil  | es    | or ' | 16 y | ear   | 's; 1 | the  | n ev | ery              | 20,0              | 1 000            | nile              | s or | 2 ye | ars                |                  |
| i Plus any applicable   | additional work li     | sted  | d at | the  | en    | d c  | f th | e s   | erv   | ice  | she  | et               |                   |                  |                   |      |      |                    |                  |
| ☑ Performed   |                        |       |      |      |       |      |      |       |       |      |      |                  |                   |                  |                   |      |      | Not OK             |                  |
| (check if performed)  | = 1 enormed            |       |      |      |       |      |      |       |       |      |      |                  |                   |                  | Ψ                 |      |      |                    |                  |
| ☐ Reset maintenance s   | ervice indicator in in | stru  | ıme  | nt   |       |      |      |       |       |      |      |                  |                   |                  |                   |      |      |                    | AP00.20-P-0042EW |
| ☐ Engine - oil and filter   | change                 |       |      |      |       |      |      |       |       |      |      |                  |                   |                  |                   |      |      |                    |                  |
| engine 157  |                        |       |      |      |       |      |      |       |       |      |      |                  |                   |                  | AP18.00-P-0101EWG |      |      |                    |                  |
| engine 276  |                        |       |      |      |       |      |      |       |       |      |      |                  |                   |                  | AP18.00-P-0101CWZ |      |      |                    |                  |
| engine 278  |                        |       |      |      |       |      |      |       |       |      |      |                  |                   |                  | AP18.00-P-0101EW  |      |      |                    |                  |
|   |                        |       |      |      |       |      |      |       |       |      |      |                  | AP18.00-P-0101CWA |                  |                   |      |      |                    |                  |
| ☐ Check catch, safety catch and hinges on engine hood for proper operation              |                        |       |      |      |       |      |      |       |       |      |      |                  |                   | AP88.40-P-8851EW |                   |      |      |                    |                  |
| ☐ Check condition of poly-V-belt  |                        |       |      |      |       |      |      |       |       |      |      |                  |                   | AP13.22-P-1352CW |                   |      |      |                    |                  |
|   |                        |       |      |      |       |      |      |       |       |      |      | AP82.35-P-8232A  |                   |                  |                   |      |      |                    |                  |
| ☐ Fill up with DEF  |                        |       |      |      |       |      |      |       |       |      |      |                  |                   | AP14.40-P-1410BT |                   |      |      |                    |                  |
| engine 651 with COD   | E U42 (BlueTEC die     | sel   | exh  | naus | st tr | eat  | mer  | nt (S | SCF   | R))  |      |                  |                   |                  |                   |      |      |                    |                  |
| i fill, subject to a sep  | arate invoice          |       |      |      |       |      |      |       |       |      |      |                  |                   |                  |                   |      |      |                    |                  |
| ☐ Check starter using S<br>Model 212.095 (Hybri   |                        | este  | r    |      |       |      |      |       |       |      |      |                  |                   |                  |                   |      |      |                    | AP15.30-P-1550AA |
| ☐ Replace brake fluid   |                        |       |      |      |       |      |      |       |       |      |      |                  |                   |                  |                   |      |      |                    | AP42.00-P-4280EW |
| Replace combination   | or dust filter         |       |      |      |       |      |      |       |       |      |      |                  |                   |                  |                   |      |      |                    | AP83.00-P-8384EW |
| Check thickness of br   | ake pads, front and    | rea   | ır   |      |       |      |      |       |       |      |      |                  |                   |                  |                   |      |      |                    | AP42.10-P-4252EW |
| Correct tire inflation p  |                        |       |      | here | e ap  | plio | cabl | e) a  | and   | ent  | er i | n the            | tab               | le at            | the               | end  | of   |                    | AP40.15-P-4061A  |
| Leakage - major com   |                        | derb  | ody  | / an | d e   | ngii | ne c | om    | par   | tme  | nt f | or ch            | nafe              | mar              | ks, li            | ne   |      |                    | AP00.20-P-0053EW |
| Check DEF lines and engine 651 with COD   |                        |       |      |      |       |      | mer  | nt (S | SCF   | R))  |      |                  |                   |                  |                   |      |      |                    | AP00.20-P-0053EW |
| ☐ Visually inspect condition of front axle ball joints, rubber boots ☐ AP33.20-P-3353EW |                        |       |      |      |       |      |      |       |       |      |      | AP33.20-P-3353EW |                   |                  |                   |      |      |                    |                  |
| ☐ Visually inspect condi  | tion of driveshaft fle | xibl  | e di | scs  |       |      |      |       |       |      |      |                  |                   |                  |                   |      |      |                    | AP41.10-P-4152EW |
| ☐ Visually inspect condi  | tion of steering med   | har   | nica | l co | mp    | one  | nts, | rut   | be    | r bc | ots  |                  |                   |                  |                   |      |      |                    | AP46.00-P-4653EW |
| Coolant - check fluid I   | evel and correct if r  | ece   | essa | arv  |       |      |      |       |       |      |      |                  |                   |                  |                   |      |      |                    |                  |
| irefer to AH20.00-P-1142-01CW   |                        |       |      |      |       |      |      |       |       |      |      |                  |                   |                  |                   |      |      |                    |                  |
| i observe correct co  |                        |       |      |      |       |      | _    |       |       |      |      |                  | _                 |                  | _                 |      | _    |                    |                  |
| ☐ Brake system - check  | fluid level and corre  | ect i | f ne | ces  | sar   | у    |      |       |       |      |      |                  |                   |                  |                   |      |      |                    | AP42.10-P-4210EW |
| ☐ Windshield washer sv  |                        |       |      |      |       |      | ne   | ces   | sar   | ,    |      |                  |                   |                  |                   |      |      |                    | AP82.35-P-8210EW |

| Parking brake (function test only)   |          | AP42.00-P-4290BA  |
|--|----------|-------------------|
| Check starter. Use MB diagnosis tool.  Model 212.095 (Hybrid) only                                       |          | AP15.30-P-1550AA  |
| Reset maintenance service indicator in instrument cluster  i reminder - if not yet performed             |          | AP00.20-P-0042EW  |
| High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles              | or 2 yea | rs                |
| Plus any applicable additional work listed at the end of the service sheet                               | <b>,</b> |                   |
| Performed  | Not OK   |                   |
| (check if performed)   | •        |                   |
| Replace wiper blades   |          |                   |
| ☐ Horn - Electrical system check   |          |                   |
| ☐ Warning/indicator lamps - Electrical system check  |          | AP54.30-P-5451EW  |
| ☐ Illumination and interior lighting/exterior lighting - Electrical system check                         |          | AP54.30-P-5453EW  |
| Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check     |          | AP82.10-P-8252EW  |
| Check trunk/cargo area lighting  |          |                   |
| Check and correct headlamp setting   |          | AP82.10-P-8260EW  |
| Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test |          | AP54.10-U-5453A   |
| report print out here  |          |                   |
| Check seat belts and buckles for signs of external damage and proper function                            |          | AP91.40-P-9150EW  |
| ☐ Check windshield washer and headlamp cleaning system   |          | AP82.30-P-8252EW  |
| Check, clean, and lubricate tilt/sliding roof mechanism where applicable                                 |          |                   |
| Check, clean, and lubricate panoramic roof mechanism with CODE 413 (panoramic sliding sunroof)           |          | AP77.20-P-7732EW  |
| Check bodywork for paintwork damage  |          | AP98.00-P-9850EW  |
| ☐ Tire rotation where applicable   |          |                   |
| ☐ Inspect tires for damage, measure tread depth and enter table at the end of the service sheet          |          | AP40.10-P-4051EW  |
| ☐ Check TIREFIT tire sealant expiration date   |          | AP40.10-P-4054R   |
| where applicable   | _        |                   |
| ☐ Activate Tire Pressure Monitoring System  ☐ refer to vehicle Operator's Manual                         |          |                   |
| ☐ Visually check brake system components, lines, hoses, calipers   |          |                   |
| Check thickness of brake pads and discs, front and rear wheels removed                                   | -        |                   |
| pads   |          | AP42.10-P-4252EW  |
| discs - except CODE B07 (AMG high-performance ceramic composite braking system)                          |          | AP42.10-P-4258EW  |
| discs - with CODE B07 (AMG high-performance ceramic composite braking system)                            |          | AP42.10-P-4258QQ  |
| ☐ Check chassis and load-bearing body components for damage and corrosion                                |          | AP00.20-P-0090EW  |
| High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y          | ears     |                   |
| I Plus any applicable additional work listed at the end of the service sheet                             |          |                   |
| ☑ Performed  | Not OK   |                   |
| (check if performed)   | <u> </u> |                   |
| Reset maintenance service indicator in instrument  |          | AP00.20-P-0042EW  |
| ☐ Engine - oil and filter change   |          |                   |
| engine 157   |          | AP18.00-P-0101EWG |
| engine 276   |          | AP18.00-P-0101CWZ |
| engine 278   |          | AP18.00-P-0101EW  |
| engine 651   |          | AP18.00-P-0101CWA |
| ☐ Check catch, safety catch and hinges on engine hood for proper operation                               |          | AP88.40-P-8851EW  |
| ☐ Clean visible area of water deflector  |          | AP82.35-P-8232A   |

| ☐ Fill up with DEF  |  |          | AP14.40-P-1410BT     |
|---|--|----------|----------------------|
| engine 651 with CODE U42 (BlueTEC diese   | el exhaust treatment (SCR))  |          |                      |
| i fill, subject to a separate invoice   |  |          |                      |
| ☐ Check starter using STAR DIAGNOSIS test<br>Model 212.095 (Hybrid) only        | rer  |          | AP15.30-P-1550AA     |
| ☐ Check thickness of brake pads, front and re                                   | ear  |          | AP42.10-P-4252EW     |
| $\hfill\Box$ Correct tire inflation pressure including sparthe service sheet    | re (where applicable) and enter in the table at the end of                   |          | AP40.15-P-4061A      |
| ☐ Coolant - check fluid level and correct if ned                                | cessary  |          |                      |
| i refer to AH20.00-P-1142-01CW  |  |          |                      |
| i observe correct coolant composition   |  |          |                      |
| ☐ Brake system - check fluid level and correct                                  | t if necessary   |          | AP42.10-P-4210EW     |
| ☐ Windshield washer system - check fluid leve                                   | el and correct if necessary  | Ш        | AP82.35-P-8210EW     |
| ☐ Check starter. Use MB diagnosis tool.<br>Model 212.095 (Hybrid) only          |  |          | AP15.30-P-1550AA     |
| $\square$ Reset maintenance service indicator in instr                          | rument cluster   |          | AP00.20-P-0042EW     |
| i reminder - if not yet performed   |  |          |                      |
| High Mileage Recommended Service Work   | at 170,000 miles or 17 years; then every 20,000 miles                        | or 2 yea | rs                   |
| i Plus any applicable additional work liste                                     | ed at the end of the service sheet   |          |                      |
| Performed   |  | Not OK   |                      |
| (check if performed)  |  | Ψ        | 4 DOO OO D OOO 45\4\ |
| Replace combination or dust filter  |  |          | AP83.00-P-8384EW     |
| Replace wiper blades  |  |          |                      |
| ☐ Horn - Electrical system check  |  |          |                      |
| $\square$ Warning/indicator lamps - Electrical system                           | check  |          | AP54.30-P-5451EW     |
| $\square$ Illumination and interior lighting/exterior ligh                      | iting - Electrical system check  |          | AP54.30-P-5453EW     |
| ☐ Exterior lighting, high beam flasher, hazard                                  | warning flasher, turn signals - Electrical system check                      |          | AP82.10-P-8252EW     |
| ☐ Check trunk/cargo area lighting   |  |          |                      |
|   | ion using Midtronics battery tester. Attach Midtronics test                  |          | AP54.10-U-5453A      |
| Check windshield washer and headlamp cle  | eaning system  |          | AP82.30-P-8252EW     |
| ☐ Tire rotation where applicable  |  |          |                      |
|   | pth and enter table at the end of the service sheet                          |          | AP40.10-P-4051EW     |
| ☐ Check TIREFIT tire sealant expiration date where applicable                   |  |          | AP40.10-P-4054R      |
| Activate Tire Pressure Monitoring System  i refer to vehicle Operator's Manual  |  |          |                      |
| Usually check brake system components, ⊩  | ines hoses calipers  |          |                      |
| ☐ Check thickness of brake pads and discs, fi                                   | ·  |          |                      |
| pads  | on and roar whools romeved   |          | AP42.10-P-4252EW     |
| •   | rmance ceramic composite braking system)                                     |          | AP42.10-P-4258EW     |
| discs - with CODE B07 (AMG high-perform   | ance ceramic composite braking system)                                       |          | AP42.10-P-4258QQ     |
| High Mileage Additional Work  |  |          |                      |
| Performed (check if performed)  |  |          |                      |
| Rear axle differential fluid replacement CODE 471 (manual locking differential) | At 2,000 miles, then if more than 40,000 mi or 4 years since lastreplacement |          | AP35.00-P-3501CMG    |
| Replace fuel filter engine 651  | If more than 40,000 mi or 4 years since last replacement                     |          | AP47.20-P-0780EWD    |
| Replace fuel filter engine 157, 276, 278  | If more than 150,000 mi or 15 years since last replacement                   |          | AP47.20-P-0780EW     |

| Automatic transmission - oil and filter change engine 157 with NAG2-V Sport and wet start-up clutch                           | If more than 40,000 mi or 4 years since last replacement   | AP27.00-P-2702W   |
|---|--|-------------------|
| Automatic transmission - oil and filter change engine 276 in model E400 HYBRID (transmission 724.2)                           | If more than 60,000 mi or 6 years since last replacement   | AP27.00-P-2702A   |
| Automatic transmission - oil and filter change engine 276, 278, 651 with NAG2-FE+ (transmission 722.9) except for E400 HYBRID | If more than 70,000 mi or 7 years since last replacement   | AP27.00-P-2702W   |
| Replace air filter  |  |                   |
| engine 276  | If more than 40,000 mi or 4 years since last replacement   | AP09.10-P-0980MM  |
| engine 157, 278   | If more than 40,000 mi or 4 years since last replacement   | AP09.10-P-0980AB  |
| engine 651  | If more than 40,000 mi or 4 years since last replacement   | AP09.10-P-0980EWD |
| Replace spark plugs engine 157, 276, 278  | If more than 60,000 mi or 6 years since last replacement   | AP15.10-P-1580EW  |
| Replace coolant  i observe correct coolant composition  | If more than 150,000 mi or 15 years since last replacement | AP20.00-P-2080EW  |

| Tire inflation pressure (bar/psi) |    |    |    |       |  |  |  |  |  |  |  |
|-----------------------------------|----|----|----|-------|--|--|--|--|--|--|--|
| LF                                | RF | LR | RR | Spare |  |  |  |  |  |  |  |
|                                   |    |    |    |       |  |  |  |  |  |  |  |

| Tire trea | Tire tread depth (mm) |    |    |    |  |  |  |  |  |  |  |  |
|-----------|-----------------------|----|----|----|--|--|--|--|--|--|--|--|
|           | LF                    | RF | LR | RR |  |  |  |  |  |  |  |  |
| outside   |                       |    |    |    |  |  |  |  |  |  |  |  |
| center    |                       |    |    |    |  |  |  |  |  |  |  |  |
| inside    |                       |    |    |    |  |  |  |  |  |  |  |  |