



Shown on model 212.0

- Front glass roof 1
- 2 Front glass cover

- 3 Rear glass roof
- 4 Bolts

5 Screw

X	Remove			
⚠ Danger!	Risk of injury caused by fingers being pinched or crushed when removing, installing or aligning hoods, doors, trunk lids, liftgates or sliding roof	Keep body parts and limbs well clear of moving parts.	AS00.00-Z-0011-01A	
1	Remove rubbers from front glass roof (1)		AR77.21-P-0530EW	
2	Loosen bolts (5) on left and right outer support	Only if the transition from tilting to sliding and vice versa has to be adjusted or if the or if the front glass roof (1) has been replaced.		
3	Loosen bolts (4) on front glass roof (1) on both sides.			
	Adjust			
4	Close front glass roof (1).			
5	Adjust front glass roof (1).	i Adjust gaps and height of front glass roof (1) in relation to rear glass roof (3) and to front glass cover (2). Observe measuring position (A).	*BE77.21-P-1001-01E	
6	Fix setting by tightening bolts (4) at both sides of front glass roof (1)			
7	Move front glass roof (1) to tilt position			
8	Tighten bolts (4) on both sides of front glass roof (1)			
9	Press left and right outer support upward onto front glass roof (1) and tighten with bolts (5)	Only if the transition from tilting to sliding and vice versa has to be adjusted or if the front glass roof (1) has been replaced.		
10	Open front glass roof (1) and close again	i If the front glass roof (1) is tensioned, cracking noise can occur, repeat adjustment if necessary.		
11	Check gaps and height adjustment.	i Observe measuring position (A) for height adjustment; repeat adjustment if necessary.	*BE77.21-P-1001-01E	
х	Install			
12	Remove rubbers from front glass roof (1)		AR77.21-P-0530EW	
13	Teach in and normalize front glass roof (1) Connect STAR DIAGNOSIS and read out fault memory		AD00.00-P-2000-04A	

Test and adjustment values of panoramic roof

P77.21-2271-09

17.5.11

Number	Designation		Model 204	Model 207.3
BE77.21-P-1001-01E	Height setting	Measuring position "A" (\times) m	n 140	140
		Front: deeper than outer skin of roof m	n 0 to 1	0 to 1
		Rear: higher than outer skin of roof m	n 0 to 1	0 to 1

Test and adjustment values of panoramic roof

Number	Designation		Model 212	
BE77.21-P-1001-01E	Height setting	Measuring position "A" (\times)	mm	140
		Front: deeper than outer skin of roof	mm	0 to 1
		Rear: higher than outer skin of roof	mm	0 to 1