

Mercedes-Benz

AP00.20-U-1208DF

SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model Year 2010 USA

Model 212



Customer:			Repair order nun	nber:	
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommender likely necessitate tire rotation each 10,000-mile maintenance substitution of the	on at least once in between ance service and at every	Tires rotated	YES	NO
Note: For any co	ondition found while performing the repair using a separate	ng the checks or inspections e repair order.	s included in this m	aintenance shee	t, determine
Current mileage read	ling:	_	il grade/viscosity:_		
Additional notes:					
_					
Service work to be pe service advisor:	erformed as advised by	Completion date:	Confirm work has below:	been performed	by signing

Required Service Work miles (thousands) Performed years (check if performed)	2	10 1	20	30	40 4	50 5	60 6	70 7	80	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Reset maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
□ Engine - oil and filter change engine 272.977		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101VA
engine 272.980		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101PIT
engine 273 engine 156		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101SX AP18.00-P-0101TMG
Check catch, safety catch and hinges on		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP88.40-P-8851EW
engine hood for proper operation Check condition of poly-V-belt			•		•		•		•		•		•		•			AP13.22-P-1352CW
Clean visible area of water deflector							•		•		•		•		•			AP82.35-P-8232A
Replace brake fluid		_	•	_	•	_	•	_	•	_	•		•		•			AP42.00-P-4280EW
Replace combination or dust filter							•		•		•				•			AP83.00-P-8384EW
		•	-	_	_	_	-	_	-	_	-				-	_		AP42.10-P-4252EW
Check thickness of brake pads, front and rear		-	-	•	-	-	-	-	-	-	-	-	-	-	-	-		AP40.15-P-4061A
Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AI 40.10-1 -4001A
Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components			•		•		•		•		•		•		•			AP00.20-P-0053EW
□Visually inspect condition of front axle ball joints, rubber boots			•		•		•		•		•		•		•			AP33.20-P-3353EW
☐ Visually inspect condition of driveshaft flexible discs			•		•		•		•		•		•		•			AP41.10-P-4152EW
□Visually inspect condition of steering mechanical components, rubber boots			•		•		•		•		•		•		•			AP46.00-P-4653EW
Coolant - check fluid level and correct if necessary i refer to AH20.00-P-1142-01CW i observe correct coolant composition		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Brake system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4210EW
□ Power steering - check fluid level and correct if necessary except CODE 211 (Direct-Steer system) i the fluid level must always be on the maximum mark, corresponding to the oil temperature		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP46.00-P-4612EW
Windshield washer system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210EW
☐Parking brake (function test only)			•		•		•		•		•		•		•			AP42.00-P-4290BA
Reset maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
reminder - if not yet performed Required Additional Work miles (thousands) Performed years (check if performed)	2	10 1	20	30	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Rear axle differential fluid replacement CODE 471 (manual locking differential)	•				•				•				•					AP35.00-P-3501CMG
Automatic transmission - oil and filter change					•				•				•					AP27.00-P-2702W
Replace air filter engine 272, 273 engine 156					•				•				•					AP09.10-P-0980EW AP09.10-P-0980CMG
					•				•				•					7.1 00.10-1 -00000IVIG
Replace spark plugs																		

Required Additional Work miles (thousands) Performed years (check if performed)	2	10	20	30	40 4	50 5	60 6	70 7	80	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
engine 272, 273							•						•					AP15.10-P-1580EW
engine 156							•						•					AP15.10-P-1580CMG
☐Replace fuel filter																•		AP47.20-P-0780EW
Replace coolant i observe correct coolant composition																•		AP20.00-P-2080EW
Recommended Service miles (thousands) Work	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Performed years (check if performed)		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK ↓	
Replace combination or dust filter		•		•		•		•		•		•		•		•		AP83.00-P-8384EW
Replace wiper blades		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Horn - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐Warning/indicator lamps - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5453EW
☐ Illumination and interior lighting - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451EW
☐ Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.10-P-8252EW
☐ Check trunk/cargo area lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐Check and correct headlamp setting			•		•		•		•		•		•		•			AP82.10-P-8260EW
☐ Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-U-5453A
Check seat belts and buckles for signs of external damage and proper function			•		•		•		•		•		•		•			AP91.40-P-9150EW
Check windshield washer and headlamp cleaning system		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.30-P-8252EW
Check, clean, and lubricate tilt/sliding roof mechanism where applicable			•		•		•		•		•		•		•			
Check, clean, and lubricate panoramic roof mechanism with CODE 413 (panoramic sliding sunroof)			•		•		•		•		•		•		•			AP77.20-P-7732EW
Check bodywork for paintwork damage			•		•		•		•		•		•		•			AP98.00-P-9850EW
Tire rotation where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Inspect tires for damage, measure tread depth and enter table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051EW
Check TIREFIT tire sealant expiration date where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4054R
Activate Tire Pressure Monitoring System Trefer to vehicle Operator's Manual		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
□Visually check brake system components, lines, hoses, calipers		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Check thickness of brake pads and discs, front and rear wheels removed																	П	AD42.40 D 4050514/
pads		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4252EW
discs - except CODE B07 (AMG high-performance ceramic composite braking system)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•]	AP42.10-P-4258EW
discs - CODE B07 (AMG high-performance ceramic composite braking system)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4258QQ

Recommended Service Work	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
☑ Performed	years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK	
(check if performed)																		Ψ	
Check chassis and load-components for damage an				•		•		•		•		•		•		•			AP00.20-P-0090EW
High Mileage Required	Service Work at 1	60,	000	mi	les	or	16	yea	rs;	the	n e	very	20,	000	mile	s or	2 ye	ears	
Plus any applicable additional work listed at the end of the service sheet																			
Performed (check if performed)																		Not OK	
				_	_													Ψ.	AP00.20-P-0042EW
	☐ Reset maintenance service indicator in instrument cluster ☐ Engine - oil and filter change													AP00.20-P-0042EVV					
☐ Engine - oil and filter change engine 272.977 AP18.00-P-0101VA																			
· ·											AP18.00-P-0101VA AP18.00-P-0101PIT								
engine 272.900																			AP18.00-P-0101SX
engine 156																			AP18.00-P-0101TMG
☐ Check catch, safety c	atch and hinges on	end	aine	ho	od 1	for	pror	oer	ope	rati	on								AP88.40-P-8851EW
☐ Check condition of po																			AP13.22-P-1352CW
☐ Clean visible area of	•																		AP82.35-P-8232A
Replace brake fluid																			AP42.00-P-4280EW
Replace combination	or dust filter																		AP83.00-P-8384EW
☐ Check thickness of br	ake pads, front and	rea	ar																AP42.10-P-4252EW
☐ Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet AP40.15-P-4061A																			
Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components																			
☐ Visually inspect condi	ition of front axle ba	ll jo	ints	, ru	bbe	r b	oots	;											AP33.20-P-3353EW
☐ Visually inspect condi	ition of driveshaft fle	xib	le d	iscs	3														AP41.10-P-4152EW
☐ Visually inspect condi	ition of steering med	char	nica	l cc	mp	one	ents	, ru	bbe	r bo	ots								AP46.00-P-4653EW
☐ Coolant - check fluid		nece	essa	ary															
refer to AH20.00-P																			
i observe correct co	olant composition																		
Brake system - check																			AP42.10-P-4210EW
Power steering - chece except CODE 211 (Die		rec	t if ı	nec	ess	ary	1											П	AP46.00-P-4612EW
the fluid level must	,	axi	mur	n n	nark	, C	orre	spo	ndiı	ng t	o th	e oil	tem	pera	ature	;			
☐ Windshield washer sy																			AP82.35-P-8210EW
☐ Parking brake (function										_									AP42.00-P-4290BA
Reset maintenance s	ervice indicator in ir	stru	ıme	nt (clus	ter													AP00.20-P-0042EW
i reminder - if not ye	t performed																		
High Mileage Recomm	ended Service Wo	rk a	it 10	60,0	000	mi	les	or 1	16 y	ear	s; t	hen	eve	ry 2	0,00	00 m	iles	or 2 yeaı	rs
I Plus any applicable	additional work li	ste	d at	th	e er	nd (of th	ne s	erv	ice	sh	eet						N 4 014	
Performed (check if performed)																		Not OK	
																		Ψ.	
Replace wiper blades																			
Horn - Electrical syste			. 1.	.1															AP54.30-P-5453EW
☐ Warning/indicator lam	-					_													
☐ Ilumination and interio																			AP54.30-P-5451EW
Exterior lighting, high	beam flasher, haza	rd v	varr	ning	fla	she	er, tu	ırn s	sign	als	- El	ectr	icals	syste	em c	hecl	<		AP82.10-P-8252EW
☐ Check trunk/cargo are	ea lighting																		

☐ Check and correct headlamp setting		AP82.10-P-8260EW
☐ Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics tes report print out here	t \square	AP54.10-U-5453A
☐ Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150EW
☐ Check windshield washer and headlamp cleaning system		AP82.30-P-8252EW
☐ Check, clean, and lubricate tilt/sliding roof mechanism where applicable		
☐ Check, clean, and lubricate panoramic roof mechanism with CODE 413 (panoramic sliding sunroof)		AP77.20-P-7732EW
☐ Check bodywork for paintwork damage		AP98.00-P-9850EW
☐ Tire rotation where applicable		
☐ Inspect tires for damage, measure tread depth and enter table at the end of the service sheet		AP40.10-P-4051EW
☐ Check TIREFIT tire sealant expiration date where applicable		AP40.10-P-4054R
☐ Activate Tire Pressure Monitoring System ☐ refer to vehicle Operator's Manual		
Usually check brake system components, lines, hoses, calipers		
Check thickness of brake pads and discs, front and rear wheels removed		
pads		AP42.10-P-4252EW
discs - except CODE B07 (AMG high-performance ceramic composite braking system)		AP42.10-P-4258EW
discs - CODE B07 (AMG high-performance ceramic composite braking system)		AP42.10-P-4258QQ
		AP00.20-P-0090EW
☐ Check chassis and load-bearing body components for damage and corrosion		711 00:20 1 0000211
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2	years	711 00:201 0000211
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y		
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years any applicable additional work listed at the end of the service sheet Performed	Not OK	
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y		ζ
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years any applicable additional work listed at the end of the service sheet Performed	Not OK	
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y ■ Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change	Not OK	ζ
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y ■ Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster □ Engine - oil and filter change engine 272.977	Not OK	AP00.20-P-0042EW AP18.00-P-0101VA
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y ■ Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) □ Reset maintenance service indicator in instrument cluster □ Engine - oil and filter change engine 272.977 engine 272.980	Not OK	AP00.20-P-0042EW AP18.00-P-0101VA AP18.00-P-0101PIT
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 272.977 engine 272.980 engine 273	Not OK	AP18.00-P-0101VA AP18.00-P-0101PIT AP18.00-P-0101SX
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y ■ Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) □ Reset maintenance service indicator in instrument cluster □ Engine - oil and filter change engine 272.977 engine 272.980 engine 273 engine 156	Not OK	AP00.20-P-0042EW AP18.00-P-0101VA AP18.00-P-0101PIT AP18.00-P-0101SX AP18.00-P-0101TMG
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 272.977 engine 272.980 engine 273	Not OK	AP00.20-P-0042EW AP18.00-P-0101VA AP18.00-P-0101PIT AP18.00-P-0101SX AP18.00-P-0101TMG AP88.40-P-8851EW
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y ■ Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) □ Reset maintenance service indicator in instrument cluster □ Engine - oil and filter change engine 272.977 engine 272.980 engine 273 engine 156	Not OK ↓	AP00.20-P-0042EW AP18.00-P-0101VA AP18.00-P-0101PIT AP18.00-P-0101SX AP18.00-P-0101TMG AP88.40-P-8851EW AP82.35-P-8232A
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 272.977 engine 272.980 engine 273 engine 156 Check catch, safety catch and hinges on engine hood for proper operation	Not OK	AP00.20-P-0042EW AP18.00-P-0101VA AP18.00-P-0101PIT AP18.00-P-0101SX AP18.00-P-0101TMG AP88.40-P-8851EW
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 272.977 engine 272.980 engine 273 engine 156 Check catch, safety catch and hinges on engine hood for proper operation Clean visible area of water deflector	Not OK	AP00.20-P-0042EW AP18.00-P-0101VA AP18.00-P-0101PIT AP18.00-P-0101SX AP18.00-P-0101TMG AP88.40-P-8851EW AP82.35-P-8232A
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 272.977 engine 272.980 engine 273 engine 156 Check catch, safety catch and hinges on engine hood for proper operation Clean visible area of water deflector Check thickness of brake pads, front and rear Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of	Not OK	AP00.20-P-0042EW AP18.00-P-0101VA AP18.00-P-0101PIT AP18.00-P-0101SX AP18.00-P-0101TMG AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4252EW
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 272.977 engine 272.980 engine 273 engine 156 Check catch, safety catch and hinges on engine hood for proper operation Clean visible area of water deflector Check thickness of brake pads, front and rear Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet Coolant - check fluid level and correct if necessary ill refer to AH20.00-P-1142-01CW	Not OK	AP00.20-P-0042EW AP18.00-P-0101VA AP18.00-P-0101PIT AP18.00-P-0101SX AP18.00-P-0101TMG AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4252EW
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years; then every 20,000 miles or 2 years in Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 272.977 engine 272.980 engine 273 engine 156 Check catch, safety catch and hinges on engine hood for proper operation Clean visible area of water deflector Check thickness of brake pads, front and rear Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet Coolant - check fluid level and correct if necessary	Not OK	AP00.20-P-0042EW AP18.00-P-0101VA AP18.00-P-0101PIT AP18.00-P-0101SX AP18.00-P-0101TMG AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4252EW
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 272.977 engine 272.980 engine 273 engine 156 Check catch, safety catch and hinges on engine hood for proper operation Clean visible area of water deflector Check thickness of brake pads, front and rear Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet Coolant - check fluid level and correct if necessary ill refer to AH20.00-P-1142-01CW	Not OK	AP00.20-P-0042EW AP18.00-P-0101VA AP18.00-P-0101PIT AP18.00-P-0101SX AP18.00-P-0101TMG AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4252EW
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 272.977 engine 272.980 engine 273 engine 156 Check catch, safety catch and hinges on engine hood for proper operation Clean visible area of water deflector Check thickness of brake pads, front and rear Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet Coolant - check fluid level and correct if necessary I refer to AH20.00-P-1142-01CW observe correct coolant composition	Not OK	AP00.20-P-0042EW AP18.00-P-0101VA AP18.00-P-0101PIT AP18.00-P-0101TMG AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4252EW AP40.15-P-4061A
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years and paplicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 272.977 engine 272.980 engine 273 engine 156 Check catch, safety catch and hinges on engine hood for proper operation Clean visible area of water deflector Check thickness of brake pads, front and rear Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet Coolant - check fluid level and correct if necessary irefer to AH20.00-P-1142-01CW irefer to AH20.00-P-1142-01CW irefer to Service sheet observed in necessary Power steering - check fluid level and correct if necessary	Not OK	AP00.20-P-0042EW AP18.00-P-0101VA AP18.00-P-0101PIT AP18.00-P-0101TMG AP88.40-P-8851EW AP82.35-P-8232A AP42.10-P-4252EW AP40.15-P-4061A

Reset maintenance service indicator in ins	trument cluster		AP00.20-P-0042EW
	c at 170,000 miles or 17 years; then every 20,000 miles	or 2 yea	ars
i Plus any applicable additional work list	ted at the end of the service sheet		
☑ Performed		Not OF	(
(check if performed)		Ψ	
Replace combination or dust filter			AP83.00-P-8384EW
Replace wiper blades			
☐ Horn - Electrical system check			
☐ Warning/indicator lamps - Electrical system		AP54.30-P-5453EW	
☐ Ilumination and interior lighting - Electrical	system check		AP54.30-P-5451EW
☐ Exterior lighting, high beam flasher, hazard	d warning flasher, turn signals - Electrical system check		AP82.10-P-8252EW
☐ Check trunk/cargo area lighting			
Battery (Main/starter/auxiliary) check cond report print out here	ition using Midtronics battery tester. Attach Midtronics test		AP54.10-U-5453A
☐ Check windshield washer and headlamp c	leaning system		AP82.30-P-8252EW
☐ Tire rotation where applicable			
☐ Inspect tires for damage, measure tread d	epth and enter table at the end of the service sheet		AP40.10-P-4051EW
Check TIREFIT tire sealant expiration date where applicable		AP40.10-P-4054R	
Activate Tire Pressure Monitoring System i refer to vehicle Operator's Manual			
☐ Visually check brake system components,	lines, hoses, calipers		
☐ Check thickness of brake pads and discs,	front and rear wheels removed		
pads			AP42.10-P-4252EW
discs - except CODE B07 (AMG high-perf	ormance ceramic composite braking system)		AP42.10-P-4258EW
discs - CODE B07 (AMG high-performance	e ceramic composite braking system)		AP42.10-P-4258QQ
High Mileage Additional Work Performed (check if performed)			
Rear axle differential fluid replacement CODE 471 (manual locking differential)	At 2,000 miles, then if more than 40,000 mi or 4 years since lastreplacement		AP35.00-P-3501CMG
Automatic transmission - oil and filter change	If more than 40,000 mi or 4 years since last replacement		AP27.00-P-2702W
Replace air filter			
engine 272, 273	If more than 40,000 mi or 4 years since last replacement		AP09.10-P-0980EW
engine 156	If more than 40,000 mi or 4 years since last replacement		AP09.10-P-0980CMG
Replace spark plugs			
engine 272, 273	If more than 60,000 mi or 6 years since last replacement		AP15.10-P-1580EW
engine 156	If more than 60,000 mi or 6 years since last replacement		AP15.10-P-1580CMG
Replace fuel filter		AP47.20-P-0780EW	
Replace coolant	If more than 150,000 mi or 15 years since last replacement		AP20.00-P-2080EW
i observe correct coolant composition			

Tire inflation pressure (bar/psi)													
LF	RF	LR	RR	Spare									

Tire tread depth (mm)													
	LF	RF	LR	RR									
outside													
center													
inside													