

## Mercedes-Benz

AP00.20-U-1208BG

SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model Year 201	1	Мо	del 207		
Customer:			Repair order nur	nber:	
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommende likely necessitate tire rotati each 10,000-mile maintena 10,000-mile maintenance s	on at least once in betweer ance service and at every	Tires rotated	YES	NO
Note: For any contract the cause and performed	ondition found while performi m the repair using a separat	ng the checks or inspection e repair order.	s included in this m	naintenance sheet	, determine
Current mileage read	ling:	_ c	il grade/viscosity:		
Additional notes:					
Service work to be p service advisor:	erformed as advised by	Completion date:	Confirm work has below:	been performed l	by signing

Mercedes-Benz USA, LLC Reproduction or translation in whole or in part is not permitted without written authorization from the publisher. 1-800-FOR-MERCedes

Required Service Work     miles (thousands)       Performed     years       (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ✔	
Reset maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
Engine - oil and filter change engine 273 engine 272		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101SX AP18.00-P-0101PIT
Check catch, safety catch and hinges on engine hood for proper operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP88.40-P-8851EW
Check condition of poly-V-belt			•		•		•		•		•		•		•			AP13.22-P-1352EW
Clean water deflector		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8232A
Replace brake fluid			•		•		•		•		•		•		•			AP42.00-P-4280EW
Replace combination or dust filter			•		•		•		•		•		•		•			AP83.00-P-8384EW
Check thickness of brake pads, front and rear		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4253A
Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.15-P-4061A
□ Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components			•		•		•		•		•		•		•			AP00.20-P-0053EW
□ Visually inspect condition of front axle ball joints, rubber boots			•		•		•		•		•		•		•			AP33.20-P-3353CW
□ Visually inspect condition of driveshaft flexible discs			•		•		•		•		•		•		•			AP41.10-P-4152EW
□ Visually inspect condition of steering mechanical components, rubber boots			•		•		•		•		•		•		•			AP46.00-P-4653CW
Coolant - check fluid level and correct if necessary refer to AH20.00-P-1142-01CW observe correct coolant composition		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Brake system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4210EW
Power steering - check fluid level and correct if necessary except CODE 211 (Direct-Steer system)     Ithe fluid level must always be on the maximum mark, corresponding to the oil temperature		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP46.00-P-4612CC
□Windshield washer system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210EW
Parking brake (function test only)			•		•		•		•		•		•		•			AP42.00-P-4290BA
Reset maintenance service indicator in instrument cluster     In reminder - if not yet performed		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042EW
Required Additional Workmiles (thousands)Performedyears(check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Replace air filter					•				•				•					AP09.10-P-0980EW
Automatic transmission - oil and filter change					•				•				•					AP27.00-P-2702W
Replace spark plugs							•						•					AP15.10-P-1580EW
Replace fuel filter																•		AP47.20-P-0780EW

Required Additional Work     miles (thousands)       Performed     years       (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK	
Replace coolant  Coolant composition																•		AP20.00-P-2080EW
Recommended Service miles (thousands) Work	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Performed years     (check if performed)		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK	
Replace combination or dust filter		•		•		•		•		•		•		٠		•		AP83.00-P-8384EW
Replace wiper blades		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Horn - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	٠	•	•	•		
□ Warning/indicator lamps - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451CA
☐ Illumination and interior lighting - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5453CC
Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.10-P-8252EW
Check trunk/cargo area lighting		٠	•	٠	•	٠	•	•	٠	•	•	٠	٠	٠	٠	٠		
Check and correct headlamp setting			•		٠		•		٠		٠		٠		٠			AP82.10-P-8260EW
Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-U-5453A
□ Soft top - clean sealing and apply lubricant model 207.4		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP77.30-P-7736QA
Check seat belts and buckles for signs of external damage and proper function			•		•		•		•		•		•		•			AP91.40-P-9150EC
□ Check windshield washer and headlamp cleaning system		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.30-P-8252EW
Check, clean, and lubricate tilt/sliding roof mechanism where applicable			•		•		•		•		•		•		•			
Check, clean, and lubricate panoramic roof mechanism model 207.3 with CODE 413 (panoramic sliding sunroof)			•		•		•		•		•		•		•			AP77.20-P-7732EW
$\Box$ Check bodywork for paintwork damage			•		•		•		•		•		٠		•			AP98.00-P-9850EW
□ Tire rotation where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Inspect tires for damage, measure thread depth and enter table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051EW
Check TIREFIT tire sealant expiration date where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4054R
Activate Tire Pressure Monitoring System		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
□ Visually check brake system components, lines, hoses, calipers		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Check thickness of brake pads and discs, front and rear wheels removed																		
pads		•	•	•	•	•	•	•	•	•	•	٠	•	•	•	•		AP42.10-P-4253A
discs		٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠	٠		AP42.10-P-4258EW

Recommended Service	miles (thousands) 2	10	20	30	40	0 50	60	70	80	90	100	110	120	130	140	150		
Work Performed	years	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK	
(check if performed)																	•	
Check chassis and load- components for damage an			•		•	•	•		•		•		•		•			AP00.20-P-0090EW
High Mileage Required	Service Work at 160	,000	) m	iles	or	r 16 y	/eai	rs;	the	n ev	very	20,0	1 000	mile	es ol	<sup>.</sup> 2 ye	ears	
I Plus any applicable	additional work liste	d a	t th	ie er	۱d	of th	ne s	erv	vice	she	et							
☑ Performed     Not OK       (check if performed)     ✓																		
				-1	4												•	AP00.20-P-0042EW
└┘ Engine - oil and filter engine 273	cnange																	AP18.00-P-0101SX
engine 272																		AP18.00-P-0101PIT
Check catch, safety c	atch and hinges on er	gine	e ho	bod	for	prop	ber o	ope	ratio	on								AP88.40-P-8851EW
Check condition of po		•																AP13.22-P-1352EW
Clean water deflector																		AP82.35-P-8232A
Replace brake fluid																		AP42.00-P-4280EW
Replace combination	or dust filter																	AP83.00-P-8384EW
Check thickness of br		ar																AP42.10-P-4253A
Correct tire inflation p			/he	re a	ppl	licab	le) a	and	ent	er ir	n the	e tab	le at	the	enc	lof		AP40.15-P-4061A
Leakage - major com		bod	y a	nd e	eng	gine d	com	par	tme	nt fo	or ch	nafe	mar	ks,	line			AP00.20-P-0053EW
routing, damaged components Usually inspect condition of front axle ball joints, rubber boots AP33.20-										AP33.20-P-3353CW								
												AP41.10-P-4152EW						
_												AP46.00-P-4653CW						
	-						,			0.0								
_	□ Coolant - check fluid level and correct if necessary □ I refer to AH20.00-P-1142-01CW																	
i observe correct co	olant composition																	
Brake system - check	fluid level and correct	if n	ece	essa	ry													AP42.10-P-4210EW
Power steering - chec		ct if	neo	cess	ary	у												AP46.00-P-4612CC
	except CODE 211 (Direct-Steer system) It the fluid level must always be on the maximum mark, corresponding to the oil temperature																	
Uwindshield washer sy													-					AP82.35-P-8210EW
Parking brake (function	on test only)								-									AP42.00-P-4290BA
Reset maintenance s	ervice indicator in insti	um	ent	clus	ter	r												AP00.20-P-0042EW
i reminder - if not ye	t performed																	
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years																		
Plus any applicable additional work listed at the end of the service sheet     Reformed     Not OK																		
<ul> <li>Performed</li> <li>(check if performed)</li> </ul>																	₩ V	
□ Replace wiper blades																		
□ Horn - Electrical system check																		
Warning/indicator lam		che	ck															AP54.30-P-5451CA
Illumination and interior lighting - Electrical system check       AP54.30-P-5453CC										AP54.30-P-5453CC								
_	Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check AP82.10-P-8252EW										AP82.10-P-8252EW							
	Check trunk/cargo area lighting																	
Check and correct he																		AP82.10-P-8260EW

Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here		AP54.10-U-5453A
Soft top - clean sealing and apply lubricant model 207.4		AP77.30-P-7736QA
Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150EC
Check windshield washer and headlamp cleaning system		AP82.30-P-8252EW
Check, clean, and lubricate tilt/sliding roof mechanism where applicable		
Check, clean, and lubricate panoramic roof mechanism model 207.3 with CODE 413 (panoramic sliding sunroof)		AP77.20-P-7732EW
Check bodywork for paintwork damage		AP98.00-P-9850EW
Tire rotation where applicable		
□ Inspect tires for damage, measure thread depth and enter table at the end of the service sheet		AP40.10-P-4051EW
Check TIREFIT tire sealant expiration date where applicable		AP40.10-P-4054R
Activate Tire Pressure Monitoring System refer to vehicle Operator's Manual		
□Visually check brake system components, lines, hoses, calipers		
Check thickness of brake pads and discs, front and rear wheels removed		
pads		AP42.10-P-4253A
discs		AP42.10-P-4258EW
Check chassis and load-bearing body components for damage and corrosion		AP00.20-P-0090EW
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years	ears	
I Plus any applicable additional work listed at the end of the service sheet		
Performed (check if performed)	Not OK ↓	•
	•	AP00.20-P-0042EW
		74 00.201 0012211
□ Engine - oil and filter change engine 273		AP18.00-P-0101SX
engine 272		AP18.00-P-01013X
Check catch, safety catch and hinges on engine hood for proper operation		AP88.40-P-8851EW
Clean water deflector		AP82.35-P-8232A
Check thickness of brake pads, front and rear		AP42.10-P-4253A
Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of		
the service sheet		AP40.15-P-4061A
the service sheet		AP40.15-P-4061A
		AP40.15-P-4061A
the service sheet Coolant - check fluid level and correct if necessary		AP40.15-P-4061A
the service sheet Coolant - check fluid level and correct if necessary refer to AH20.00-P-1142-01CW		AP40.15-P-4061A AP42.10-P-4210EW
the service sheet Coolant - check fluid level and correct if necessary I refer to AH20.00-P-1142-01CW I observe correct coolant composition	_	
the service sheet  Coolant - check fluid level and correct if necessary  refer to AH20.00-P-1142-01CW  observe correct coolant composition  Brake system - check fluid level and correct if necessary  Power steering - check fluid level and correct if necessary		AP42.10-P-4210EW

Reset maintenance service indicator in instrument cluster AP00.20-P-0042EW											
i reminder - if not yet performed											
High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years											
I Plus any applicable additional work listed at the end of the service sheet											
<ul> <li>Performed</li> <li>(check if performed)</li> </ul>		Not OK	L L L L L L L L L L L L L L L L L L L								
		•									
□ Replace combination or dust filter			AP83.00-P-8384EW								
Replace wiper blades											
Horn - Electrical system check											
UWarning/indicator lamps - Electrical system	n check		AP54.30-P-5451CA								
Illumination and interior lighting - Electrical	system check		AP54.30-P-5453CC								
Exterior lighting, high beam flasher, hazard	warning flasher, turn signals - Electrical system check		AP82.10-P-8252EW								
Check trunk/cargo area lighting											
Battery (Main/starter/auxiliary) check cond report print out here		AP54.10-U-5453A									
Soft top - clean sealing and apply lubricant model 207.4		AP77.30-P-7736QA									
Check windshield washer and headlamp c	leaning system		AP82.30-P-8252EW								
Tire rotation where applicable											
□ Inspect tires for damage, measure thread of	depth and enter table at the end of the service sheet		AP40.10-P-4051EW								
Check TIREFIT tire sealant expiration date where applicable			AP40.10-P-4054R								
Activate Tire Pressure Monitoring System											
I refer to vehicle Operator's Manual											
□ Visually check brake system components,	lines, hoses, calipers										
Check thickness of brake pads and discs,	front and rear wheels removed										
pads			AP42.10-P-4253A								
discs			AP42.10-P-4258EW								
High Mileage Additional Work Performed (check if performed)											
Replace air filter	If more than 40,000 mi or 4 years since last replacement		AP09.10-P-0980EW								
Automatic transmission - oil and filter change	If more than 40,000 mi or 4 years since last replacement		AP27.00-P-2702W								
Replace spark plugs	If more than 60,000 mi or 6 years since last replacement		AP15.10-P-1580EW								
Replace fuel filter	If more than 150,000 mi or 15 years since last replacement		AP47.20-P-0780EW								
Replace coolant	If more than 150,000 mi or 15 years since last replacement		AP20.00-P-2080EW								
i observe correct coolant composition											