



Shown on model 204.0/2

- 1 Driver-side wiper arm
- 2 Passenger-side wiper arm
- 3 Frame seal center piece
- 4 Screw
- 5 Strut
- 6 Water collector



P82.30-2632-11



P82.30-2665-07


Shown on model 204.0/2

- 7 Nut
- 8 Wiper system
- 9 Screw
- 10 Electrical connector

- 11 Bracket

Model 218

R2/10x1 Wiper park position heater electrical connector



P82.30-2969-04

Modification notes

10.8.10	Value changed: Nut for strut to suspension strut tower	*BA62.30-P-1006-02G
---------	--	---------------------

Icon	Remove/install		
	Risk of injury caused by moving parts that can pinch, crush or, in extreme cases even sever extremities.	Always remove ignition key when working on windshield wiper mechanism.	AS82.30-Z-0001-01A
1	Remove driver-side wiper arm (1) and passenger-side wiper arm (2)		AR82.30-P-6100CW
2	Remove frame seal center piece (3)	In model 204, 207, 212	
3	Remove water collector (6)		
4	Remove strut (5)	i On model 204 the strut (5) is attached with the bolt (4) of the suspension strut. Nm	*BA32.25-P-1003-04M

		<p>i On model 207 the strut (5) is fastened below the windshield using the bolt (4) of the suspension strut and two nuts.</p> <p>Nm</p> <p>Nm</p> <p>i In model 212 and 218 the strut (5) is attached to the mounting console with a nut.</p> <p>Nm</p>	<p>*BA32.25-P-1003-04M</p> <p>*BA62.30-P-1007-02G</p> <p>*BA62.30-P-1006-02G</p>
5	Unscrew bolt (9)	<p>! Do not change installation position of bracket (11) at partition wall, since this would change the contact pressure of the wiper arms and therefore the wiping area.</p> <p>Nm</p>	*BA82.30-P-1002-01M
6	Unscrew nuts (7)	Nm	*BA82.30-P-1003-01M
7	Disconnect electrical connector (10) on wiper motor		
8	Unplug wiper park position heater electrical connector (R2/10x1)	<p>Model 218</p> <p>! Unplug wiper park position heater electrical connector (R2/10x1) carefully to avoid damaging the wiper park position heater connections.</p> <p>Unlock wiper park position heater electrical connector (R2/10x1) at the catch tab (arrow A), detach from holder and unplug.</p> <p>Unclip wiring harness bracket (arrows B) from wiper system .</p>	
9	Remove wiper system (8)		
10	Install in the reverse order	i Installation: Before installing a new wiper system (8), the bracket (11) of the new wiper system (8) must be removed.	

Nm Suspension struts

Number	Designation		Model 204.00/02/04/05/ 06/20/22/24/25/ 30/33/34/35 without code 483	Model 204.00/02/04/05/ 06/20/22/24/25/ 30/33/34/35 with code 483, model 204.077/277/ 377
BA32.25-P-1003-04M	Suspension strut to body	Nm	33	33

Nm Suspension struts

Number	Designation		Model 204.08/09/28/29/ 38/9
BA32.25-P-1003-04M	Suspension strut to body	Nm	33

Nm Suspension struts

Number	Designation		Model 207 without code 483	Model 207 with code 483

BA32.25-P-1003-04M	Suspension strut to body	Nm	33	33
--------------------	--------------------------	----	----	----

Nm Front end assembly with front reinforcement

Number	Designation		Model 212	Model 218
BA62.30-P-1006-02G	Nut, strut to suspension strut tower	Nm	30	30

Nm Front end assembly with front reinforcement

Number	Designation		Model 207.3	Model 207.4
BA62.30-P-1007-02G	Nut, strut to firewall	Nm	35	35

Nm Windshield wiper

Number	Designation		Model 204	Model 207	Model 212	Model 218
BA82.30-P-1002-01M	Bolt, wiper system to bracket	Nm	11	11	11	11
BA82.30-P-1003-01M	Nut, wiper system to body	Nm	20	22	22	22