

AP00.20-U-1208DQ

SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

| Model | Year | 2021 |
|-------|------|------|
| USA | | |

Model 213



| Customer: | | | Repair order num | nber: | |
|--|---|--|-------------------------|------------------|--------------|
| Tire Rotation (non-staggered width wheel setup only) | A 5,000-mile recommended likely necessitate tire rotation each 10,000-mile maintenation 10,000-mile maintenance s | on at least once in between ince service and at every | Tires rotated | YES | NO |
| Note: For any co | ondition found while performin m the repair using a separate | ng the checks or inspections e repair order. | s included in this m | aintenance sheet | i, determine |
| Current mileage read | ling: | | il grade/viscosity:_ | | |
| Additional notes: | | | | | |
| _ | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| Service work to be pe service advisor: | erformed as advised by | Completion date: | Confirm work has below: | been performed | by signing |
| | | | | | |

| Required Service Work miles (thousands) ✓ Performed years (check if performed) | 2 | 10 | 20 2 | 30 | 40 4 | 50 5 | 60 6 | 70 7 | 80 8 | 90 9 | 100 | 110 11 | 120 12 | 130 13 | 140 14 | 150 15 | Not OK ↓ | |
|---|---|----|------|----|------|---------|---------|---------|---------|------|-----|-----------|-----------|-----------|-----------|-----------|--------------------|-------------------|
| ☐ Reset maintenance service indicator in instrument cluster | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP00.20-P-0043L |
| Replace engine oil and filter Engine 177 | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP18.00-P-0101DD |
| Engine 274.920 except CODE M005 (4MATIC) | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP18.00-P-0101CWI |
| Engine 274.920 with CODE M005 (4MATIC) | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP18.00-P-0101CWE |
| Engine 256 | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP18.00-P-0101MRT |
| Engine 264 without CODE M005 (4MATIC) | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP18.00-P-0101EE |
| Engine 264 with CODE M005 (4MATIC) | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP18.00-P-0101E |
| ☐ Clean visible area of water deflector | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| Replace activated charcoal combination filter Behind glovebox | | | • | | • | | • | | • | | • | | • | | • | | | AP83.00-P-8384B |
| Replace dust filter i Behind plastic cowl in engine compartment | | | • | | • | | • | | • | | • | | • | | • | | | AP83.00-P-8381C |
| Replace brake fluid i Every 2 years | | | • | | • | | • | | • | | • | | • | | • | | | AP42.00-P-4280C |
| ☐ Perform brake test | | | • | | • | | • | | • | | • | | • | | • | | | AP42.00-P-4290BA |
| ☐ Check brake fluid level, correct if necessary | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP42.10-P-4210B |
| ☐ Check thickness of brake pads and discs, front and rear wheels removed | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP42.10-P-4252E |
| ☐ Check and correct all tire air pressures, including spare where applicable | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP40.15-P-4061A |
| ☐ Check coolant level and correct if necessary ☐ Observe correct coolant composition | | | | | | | | | | | | | | | | | | |
| Low-temperature circuit (engine 177) | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP20.30-P-2052F |
| Low-temperature circuit (engine 256.9) | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP20.30-P-2052K |
| Low-temperature circuit (engine 264) | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP20.30-P-2052C |
| Main circuit | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP20.30-P-2050F |
| Check windshield washer system fluid, correct if necessary | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP82.35-P-8210C |
| Check charging cable and vehicle socket for damage Hybrid | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP54.10-P-5458B |
| ☐ Check engine compartment air flap Engine 177 | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP20.00-P-2052D |
| ☐ Check catch, safety catch, and hinges on engine hood for proper operation | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| ☐ Check first aid kit | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP68.00-P-6850EW |
| Check coolant level of high-voltage battery Hybrid | | | • | | • | | • | | • | | • | | • | | • | | | AP08.50-P-2053C |
| ☐ Check underside of vehicle for damage and leaks | | | • | | • | | • | | • | | • | | • | | • | | | AP00.20-P-0054I |
| ☐ Check visible parts in engine compartment for damage and leaks | | | • | | • | | • | | • | | • | | • | | • | | | AP00.20-P-0055E |
| ☐ Check front axle and front axle ball joints, check rubber boots | | | • | | • | | • | | • | | • | | • | | • | | | AP33.10-P-3358A |
| ☐ Check condition of steering and tie rods | | | • | | • | | • | | • | | • | | • | | • | | | AP46.00-P-4651A |
| ☐ Check rear axle and rear axle ball joints, check rubber boots | | | • | | • | | • | | • | | • | | • | | • | | | AP35.20-P-3552A |
| ☐ Check driveshaft flexible couplings | | | • | | • | | • | | • | | • | | • | | • | | | AP41.10-P-4152EW |
| ☐ Check condition of suspension struts or shock absorbers and springs | | | • | | • | | • | | • | | • | | • | | • | | | AP32.25-P-3255A |
| ☐ Check condition of poly-V-belt Engine 177, 264 | | | | | | | | | | | | | | | | | | |
| Engine 177 | | | • | | • | | • | | • | | • | | • | | • | | | AP13.22-P-1352D |
| Engine 264 | | | • | | • | | • | | • | | • | | • | | • | | | AP13.22-P-1352EW |

| Required Service Work Performed (check if performed) | miles (thousands) years | 2 | 10 1 | 20 2 | 30 | 40 4 | 50 5 | 60 6 | 70 7 | 80 8 | 90 | 100 10 | 110 11 | 120 12 | 130 13 | 140 14 | | | |
|---|----------------------------|---|---------|---------|---------|---------|---------|---------|---------|---------|---------|-----------|-----------|-----------|-----------|-----------|---|-----|---|
| Reset maintenance service indicator in instrume Reminder - if not yet performed | nt cluster | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | , | AP00.20-P-0043L |
| Required Additional Work Performed (check if performed) | miles (thousands) years | 2 | 10 1 | 20 2 | 30 3 | 40 4 | 50 5 | 60 6 | 70 7 | 80 8 | 90 9 | 100 10 | 110 11 | 120 12 | 130 13 | 140 14 | | | |
| Replace rear axle differential oil With CODE 467 (Electronic locking differential) olocking differential) With CODE 471 (Manual locking differential) With CODE 467 (Electronic locking differential) | or CODE 471 (Manual | | | | • | | | • | | | • | | | • | | | • | | AP35.00-P-3501CMG AP35.00-P-3501D AP09.10-P-0980K |
| Replace engine air filter Engine 177 Replace engine air filter Engine 256, 264, 274 Engine 274 Engine 264 | | | | | | | • | • | | | • | • | | • | | | • | | AP09.10-P-0980CWG AP09.10-P-0980EWO |
| Engine 256.9 Replace spark plugs Engine 177 Engine 274 Engine 256.9 Engine 264 | | | | | | | • • • • | | | | | • | | | | | | | AP09.10-P-0980L AP15.10-P-1580C AP15.10-P-1580CWF AP15.10-P-1580E AP15.10-P-1580MCU |
| Replace transfer case oil Only AMG models Transmission 725.096 with CODE M005 (4MAT Model 213.061 | (IC) | | | | | | • | | | | | • | | | | | • | | AP28.00-P-2801B AP28.00-P-2801C |
| Replace transfer case oil With CODE M005 (4MATIC), except AMG mode Transmission 725.0 (except 725.09) | ls | | | | | | | • | | | | | | • | | | | | AP28.00-P-2801A |
| Replace automatic transmission oil and filter Engine 177 With transmission 725.09 | | | | | • | | | • | | | • | | | • | | | • | , | AP27.00-P-2702B |
| Replace automatic transmission oil and filter Except Engine 177, with CODE M005 (4MATIC) Transmission 725.0 (except 725.017) Transmission 725.017 | | | | | | | | • | | | | | | • | | | | | AP27.00-P-2702B AP27.00-P-2702BE |
| Replace fuel filter Replace main circuit coolant | | | | | | | | | | | | | | • | | | | | AP47.20-P-0780D AP20.00-P-2082G |
| i Observe correct coolant composition Replace low-temperature circuit coolant Except Engine 274 i Observe correct coolant composition Engine 177 Engine 256.9 Engine 264 | | | | | | | | | | | | | | • | | | | | AP20.00-P-2083C AP20.00-P-2083D AP20.00-P-2083K |
| Recommended Service Work Performed (check if performed) | miles (thousands) years | 2 | 10 1 | 20 2 | 30 | 40 4 | 50 5 | 60 6 | 70 7 | 80 8 | 90 | 100 10 | 110 11 | 120 12 | 130 13 | 140 14 | | | |
| ☐ Replace wiper blades | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | , 🗆 | |
| Check windshield wiper, washer and headlamp operation | washer system | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | , | AP82.35-P-8252D |
| ☐ Inspect tires for damage, measure tread depth a end of the service sheet | nd enter table at the | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | , 🗆 | AP40.10-P-4051EW |
| ☐ Tire rotation (where applicable) | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | |

| Recommended Service Work Performed (check if performed) | miles (thousands) years | 2 | 10 1 | 20 2 | 30 | 40 4 | 50 5 | 60 6 | 70 7 | 80 8 | 90 | 100 10 | 110 11 | 120 12 | 130 13 | 140 14 | 150 15 | Not OF | 3 |
|--|----------------------------|-------|---------|---------|----|---------|---------|---------|---------|---------|------|-----------|-----------|-----------|-----------|-----------|-----------|--------|--|
| ☐ Activate Tire Pressure Monitoring System i Refer to vehicle Operator's Manual | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| Check TIREFIT tire sealant expiration date (whe | re applicable) | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP40.10-P-4054R |
| ☐ Check thickness of brake pads and discs, front a | | | | | | | | | | | | | | | | | | | |
| removed Pads | | | | | | | | | | | | | | | | | | | AP42.10-P-4252E |
| Discs | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP42.10-P-4256EW |
| ☐ Check brake system components, lines, hoses, | calipers | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| ☐ Check headlamp setting, correct if necessary | | | | • | | • | | • | | • | | • | | • | | • | | | AP82.10-P-8260J |
| ☐ Check operation of headlamp range adjustment | | | | • | | • | | • | | • | | • | | • | | • | | | AP82.10-P-8250EW |
| ☐ Check all exterior lights | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP82.10-P-8252EW |
| ☐ Check warning/indicator lamps | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP54.30-P-5451HA |
| ☐ Check illumination and interior lighting | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP54.30-P-5453E |
| ☐ Check trunk / cargo area lights | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| Replace battery for KEYLESS-GO key With KEYLESS-GO function After consultation with customer | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| Check, clean and lubricate Panoramic sliding roo With CODE 413 (Automatic panoramic sliding su | | | | • | | • | | • | | • | | • | | • | | • | | | AP77.20-P-7732A |
| ☐ Check horn | | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| ☐ Check battery condition. Attach printout to sheet | | | | • | | • | | • | | • | | • | | • | | • | | | AP54.10-P-5449U |
| Check chassis and load bearing body componer corrosion | nts for damage and | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | |
| Check ex-factory driving aids With CODE 45P (Disability conversion - Sales co | ontrol code) | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | | AP86.20-P-8649U |
| ☐ Check seatbelts and buckles for proper operation | n or damage | | | • | | • | | • | | • | | • | | • | | • | | | |
| ☐ Check for body paint damage | | | | • | | • | | • | | • | | • | | • | | • | | | AP60.00-P-0050I |
| Check condition and operation of trailer hitch With CODE 550 (Trailer coupling) | | | | • | | • | | • | | • | | • | | • | | • | | | AP31.11-P-3152A |
| High Mileage Required Service Work at 16 | • | • | | | | | • | 0,00 | 00 r | nile | es o | r 2 y | ear | S | | | | | |
| Plus any applicable additional work lis | ted at the end of t | he | ser | vice | sh | eet | t | | | | | | | | | | | Not Ok | • |
| ☐ Performed (check if performed) | | | | | | | | | | | | | | | | | | ₩OLO! | • |
| Reset maintenance service indicator in ins | strument cluster | | | | | | | | | | | | | | | | | | AP00.20-P-0043L |
| ☐Replace engine oil and filter | | | | | | | | | | | | | | | | | | | |
| Engine 177 | | | | | | | | | | | | | | | | | | | AP18.00-P-0101DD |
| Engine 274.920 except CODE M005 (4M. | * | | | | | | | | | | | | | | | | | | AP18.00-P-0101CWI |
| Engine 274.920 with CODE M005 (4MAT Engine 256 | IC) | | | | | | | | | | | | | | | | | | AP18.00-P-0101CWE AP18.00-P-0101MRT |
| Engine 266 without CODE M005 (4MATIC | 3) | | | | | | | | | | | | | | | | | | AP18.00-P-0101WR1 |
| Engine 264 with CODE M005 (4MATIC) | -, | | | | | | | | | | | | | | | | | | AP18.00-P-0101E |
| Clean visible area of water deflector | | | | | | | | | | | | | | | | | | | |
| Replace activated charcoal combination fi | Iter | | | | | | | | | | | | | | | | | | AP83.00-P-8384B |
| Behind glovebox | | | | | | | | | | | | | | | | | | | |
| Replace dust filter Behind plastic cowl in engine compartm | ent | | | | | | | | | | | | | | | | | | AP83.00-P-8381C |
| Replace brake fluid i Every 2 years | | | | | | | | | | | | | | | | | | | AP42.00-P-4280C |
| Perform brake test | | | | | | | | | | | | | | | | | | | AP42.00-P-4290BA |
| Check brake fluid level, correct if necessa | rv | | | | | | | | | | | | | | | | | | AP42.10-P-4210B |
| Check thickness of brake pads and discs, | | ا وام | rem | iove | h | | | | | | | | | | | | | | AP42.10-P-4252E |
| Check and correct all tire air pressures, in | | | | | | | | | | | | | | | | | | | AP40.15-P-4061A |

| Check coolant level and correct if necessary | | |
|--|--------------------|---|
| Observe correct coolant composition | | |
| Low-temperature circuit (engine 177) | | AP20.30-P-2052F |
| Low-temperature circuit (engine 256.9) | | AP20.30-P-2052K AP20.30-P-2052C |
| Low-temperature circuit (engine 264) Main circuit | | AP20.30-P-2052C AP20.30-P-2050F |
| Check windshield washer system fluid, correct if necessary | | AP82.35-P-8210C |
| Check charging cable and vehicle socket for damage Hybrid | | AP54.10-P-5458B |
| Check engine compartment air flap Engine 177 | | AP20.00-P-2052D |
| Check catch, safety catch, and hinges on engine hood for proper operation | | |
| □ Check first aid kit | | AP68.00-P-6850EW |
| Check coolant level of high-voltage battery Hybrid | | AP08.50-P-2053C |
| ☐ Check underside of vehicle for damage and leaks | | AP00.20-P-0054I |
| ☐ Check visible parts in engine compartment for damage and leaks | | AP00.20-P-0055E |
| ☐ Check front axle and front axle ball joints, check rubber boots | | AP33.10-P-3358A |
| ☐ Check condition of steering and tie rods | | AP46.00-P-4651A |
| ☐ Check rear axle and rear axle ball joints, check rubber boots | | AP35.20-P-3552A |
| ☐ Check driveshaft flexible couplings | | AP41.10-P-4152EW |
| ☐ Check condition of suspension struts or shock absorbers and springs | | AP32.25-P-3255A |
| □ Check condition of poly-V-belt Engine 177, 264 | | |
| Engine 177 | | AP13.22-P-1352D |
| Engine 264 | | AP13.22-P-1352EW AP00.20-P-0043L |
| I December 1 to the control of the Stanton to the stanton and about a | | A DOO 30-D-00431 |
| Reset maintenance service indicator in instrument cluster | | AI 00.20-I -0043L |
| I Reminder - if not yet performed | | AI 00.20-I -0043E |
| Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years | | AI 00.20-I -004-3E |
| Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years Plus any applicable additional work listed at the end of the service sheet | Not Ok | |
| Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years | Not Oh ↓ | |
| I Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years I Plus any applicable additional work listed at the end of the service sheet ☑ Performed (check if performed) | Not Oh ↓ | |
| I Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years I Plus any applicable additional work listed at the end of the service sheet 区 Performed | Not Or | |
| I Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years I Plus any applicable additional work listed at the end of the service sheet ☑ Performed (check if performed) ☐ Replace wiper blades | V | ζ |
| I Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage, measure tread depth and enter table at the end of the service sheet | ↓ | AP82.35-P-8252D |
| Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage, measure tread depth and enter table at the end of the service sheet Tire rotation (where applicable) | ↓ | AP82.35-P-8252D |
| I Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage, measure tread depth and enter table at the end of the service sheet | ↓ | AP82.35-P-8252D |
| I Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years I Plus any applicable additional work listed at the end of the service sheet ☑ Performed (check if performed) ☐ Replace wiper blades ☐ Check windshield wiper, washer and headlamp washer system operation ☐ Inspect tires for damage, measure tread depth and enter table at the end of the service sheet ☐ Tire rotation (where applicable) ☐ Activate Tire Pressure Monitoring System | ↓ | AP82.35-P-8252D |
| I Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years I Plus any applicable additional work listed at the end of the service sheet ☑ Performed (check if performed) ☐ Replace wiper blades ☐ Check windshield wiper, washer and headlamp washer system operation ☐ Inspect tires for damage, measure tread depth and enter table at the end of the service sheet ☐ Tire rotation (where applicable) ☐ Activate Tire Pressure Monitoring System I Refer to vehicle Operator's Manual | | AP82.35-P-8252D AP40.10-P-4051EW |
| I Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage, measure tread depth and enter table at the end of the service sheet Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Pads | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4252E |
| I Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage, measure tread depth and enter table at the end of the service sheet Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Pads Discs | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R |
| Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4252E AP42.10-P-4256EW |
| Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage, measure tread depth and enter table at the end of the service sheet Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Pads Discs Check brake system components, lines, hoses, calipers Check headlamp setting, correct if necessary | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4252E AP42.10-P-4256EW AP82.10-P-8260J |
| Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4252E AP42.10-P-4256EW AP82.10-P-8260J AP82.10-P-8250EW |
| Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage, measure tread depth and enter table at the end of the service sheet Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Pads Discs Check brake system components, lines, hoses, calipers Check headlamp setting, correct if necessary | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4252E AP42.10-P-4256EW AP82.10-P-8260J AP82.10-P-8250EW AP82.10-P-8252EW |
| Reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage, measure tread depth and enter table at the end of the service sheet Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Pads Discs Check brake system components, lines, hoses, calipers Check headlamp setting, correct if necessary Check operation of headlamp range adjustment | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4252E AP42.10-P-4256EW AP82.10-P-8250EW AP82.10-P-8250EW AP82.10-P-8251HA |
| High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage, measure tread depth and enter table at the end of the service sheet Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Pads Discs Check brake system components, lines, hoses, calipers Check headlamp setting, correct if necessary Check all exterior lights Check warning/indicator lamps Check illumination and interior lighting | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4252E AP42.10-P-4256EW AP82.10-P-8260J AP82.10-P-8250EW AP82.10-P-8252EW |
| High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Replace wiper blades Check windshield wiper, washer and headlamp washer system operation Inspect tires for damage, measure tread depth and enter table at the end of the service sheet Tire rotation (where applicable) Activate Tire Pressure Monitoring System Refer to vehicle Operator's Manual Check TIREFIT tire sealant expiration date (where applicable) Check thickness of brake pads and discs, front and rear wheels removed Pads Discs Check brake system components, lines, hoses, calipers Check headlamp setting, correct if necessary Check operation of headlamp range adjustment Check all exterior lights Check warning/indicator lamps | | AP82.35-P-8252D AP40.10-P-4051EW AP40.10-P-4054R AP42.10-P-4252E AP42.10-P-4256EW AP82.10-P-8250EW AP82.10-P-8250EW AP82.10-P-8251HA |

| ☐ Check, clean and lubricate Panoramic sliding roof guide mechanism | | AP77.20-P-7732A |
|--|----------|-------------------|
| With CODE 413 (Automatic panoramic sliding sunroof) | | |
| □ Check horn | | |
| ☐ Check battery condition. Attach printout to sheet | | AP54.10-P-5449U |
| Check chassis and load bearing body components for damage and corrosion | | |
| □ Check ex-factory driving aids | | AP86.20-P-8649U |
| With CODE 45P (Disability conversion - Sales control code) | | |
| Check seatbelts and buckles for proper operation or damage | | |
| □ Check for body paint damage | | AP60.00-P-0050I |
| Check condition and operation of trailer hitch | | AP31.11-P-3152A |
| With CODE 550 (Trailer coupling) | | |
| High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years | | |
| i Plus any applicable additional work listed at the end of the service sheet | | |
| ☑ Performed | Not OF | (|
| (check if performed) | Ψ_ | |
| Reset maintenance service indicator in instrument cluster | | AP00.20-P-0043L |
| Replace engine oil and filter | | |
| Engine 177 | | AP18.00-P-0101DD |
| Engine 274.920 except CODE M005 (4MATIC) | | AP18.00-P-0101CWI |
| Engine 274.920 with CODE M005 (4MATIC) | | AP18.00-P-0101CWE |
| Engine 256 | | AP18.00-P-0101MRT |
| Engine 264 without CODE M005 (4MATIC) | | AP18.00-P-0101EE |
| Engine 264 with CODE M005 (4MATIC) | | AP18.00-P-0101E |
| ☐ Clean visible area of water deflector | | |
| Check brake fluid level, correct if necessary | | AP42.10-P-4210B |
| ☐ Check thickness of brake pads and discs, front and rear wheels removed | | AP42.10-P-4252E |
| ☐ Check and correct all tire air pressures, including spare where applicable | | AP40.15-P-4061A |
| ☐ Check coolant level and correct if necessary | | |
| i Observe correct coolant composition | | |
| Low-temperature circuit (engine 177) | | AP20.30-P-2052F |
| Low-temperature circuit (engine 256.9) | | AP20.30-P-2052K |
| Low-temperature circuit (engine 264) | | AP20.30-P-2052C |
| Main circuit | | AP20.30-P-2050F |
| ☐ Check windshield washer system fluid, correct if necessary | | AP82.35-P-8210C |
| ☐ Check charging cable and vehicle socket for damage Hybrid | | AP54.10-P-5458B |
| ☐ Check engine compartment air flap | | AP20.00-P-2052D |
| Engine 177 | | |
| ☐ Check catch, safety catch, and hinges on engine hood for proper operation | | |
| ☐ Check first aid kit | | AP68.00-P-6850EW |
| Reset maintenance service indicator in instrument cluster | | AP00.20-P-0043L |
| I Reminder - if not yet performed | | |
| High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years | | |
| i Plus any applicable additional work listed at the end of the service sheet | | |
| ☑ Performed | Not OF | |
| (check if performed) | <u>+</u> | |
| Replace wiper blades | | |
| ☐ Check windshield wiper, washer and headlamp washer system operation | | AP82.35-P-8252D |
| ☐ Inspect tires for damage, measure tread depth and enter table at the end of the service sheet | | AP40.10-P-4051EW |
| ☐ Tire rotation (where applicable) | | |
| ☐ Activate Tire Pressure Monitoring System | | |
| i Refer to vehicle Operator's Manual | | |
| ☐ Check TIREFIT tire sealant expiration date (where applicable) | | AP40.10-P-4054R |

| ☐ Check thickness of brake pads and discs, front and rea | r wheels removed | |
|--|--|--------------------------------------|
| Pads | | AP42.10-P-4252E |
| Discs | | AP42.10-P-4256EW |
| ☐ Check brake system components, lines, hoses, calipers | 3 | |
| ☐ Check all exterior lights | | AP82.10-P-8252EW |
| ☐ Check warning/indicator lamps | | AP54.30-P-5451HA |
| Check illumination and interior lighting | | AP54.30-P-5453E |
| ☐ Check trunk / cargo area lights | | |
| Replace battery for KEYLESS-GO key | | |
| With KEYLESS-GO function | | |
| After consultation with customer | | |
| ☐ Check horn | | |
| \square Check chassis and load bearing body components for α | damage and corrosion | |
| ☐ Check ex-factory driving aids With CODE 45P (Disability conversion - Sales control or | ode) | AP86.20-P-8649U |
| High Mileage Additional Work | | |
| ☑ Performed | | |
| (check if performed) | | |
| Replace rear axle differential oil With CODE 467 (Electronic locking differential) or CODE 471 (Manual locking differential) | | |
| With CODE 471 (Manual locking differential) | If more than 30,000 miles or 3 years since last replacement | AP35.00-P-3501CMG |
| With CODE 467 (Electronic locking differential) | If more than 30,000 miles or 3 years since last replacement | AP35.00-P-3501D |
| Replace engine air filter Engine 177 | If more than 30,000 miles or 3 years since last replacement | AP09.10-P-0980K |
| Replace engine air filter Engine 256, 264, 274 | | |
| Engine 274 | If more than 50,000 miles or 5 years since last replacement | AP09.10-P-0980CWG |
| Engine 264 | If more than 50,000 miles or 5 years since last replacement | AP09.10-P-0980EWO |
| Engine 256.9 | If more than 50,000 miles or 5 years since last replacement | AP09.10-P-0980L |
| Replace spark plugs | | |
| Engine 177 | If more than 50,000 miles or 5 years since last replacement | AP15.10-P-1580C |
| Engine 274 | If more than 50,000 miles or 5 years since last replacement | AP15.10-P-1580CWF |
| Engine 256.9 Engine 264 | If more than 50,000 miles or 5 years since last replacement If more than 50,000 miles or 5 years since last replacement | AP15.10-P-1580E AP15.10-P-1580MCU |
| Replace transfer case oil | i more train 50,000 miles of 5 years since last replacement | Al 10.10-1 - 1000MCC |
| Only AMG models Transmission 725.096 with CODE M005 (4MATIC) | If more than 50,000 miles or 5 years since last replacement | AP28.00-P-2801B |
| Model 213.061 | If more than 50,000 miles or 5 years since last replacement | AP28.00-P-2801C |
| Replace transfer case oil With CODE M005 (4MATIC), except AMG models | | |
| Transmission 725.0 (except 725.09) | If more than 60,000 miles or 6 years since last replacement | AP28.00-P-2801A |
| Replace automatic transmission oil and filter Engine 177 | | |
| With transmission 725.09 | If more than 30,000 miles or 3 years since last replacement | AP27.00-P-2702B |
| Replace automatic transmission oil and filter Except Engine 177, with CODE M005 (4MATIC) | | |
| Transmission 725.0 (except 725.017) | If more than 60,000 miles or 6 years since last replacement | AP27.00-P-2702B |
| Transmission 725.017 | If more than 60,000 miles or 6 years since last replacement | AP27.00-P-2702BE |
| ☐ Replace fuel filter | If more than 120,000 miles or 12 years since last replacement | AP47.20-P-0780D |
| Replace main circuit coolant | If more than 120,000 miles or 12 years since last replacement | AP20.00-P-2082G |
| i Observe correct coolant composition | | |
| Replace low-temperature circuit coolant Except Engine 274 Observe correct coolant composition | | |
| Engine 177 | If more than 120,000 miles or 12 years since last replacement | AP20.00-P-2083C |
| Engine 256.9 | If more than 120,000 miles or 12 years since last replacement | AP20.00-P-2083D |

| Tire inflation pressure (bar/psi) | | | | | | | | | | | |
|-----------------------------------|----|----|----|-------|--|--|--|--|--|--|--|
| LF | RF | LR | RR | Spare | | | | | | | |
| | | | | | | | | | | | |

| Tire tread depth (mm) | | | | | | | | | | |
|-----------------------|----|----|----|----|--|--|--|--|--|--|
| | LF | RF | LR | RR | | | | | | |
| outside | | | | | | | | | | |
| center | | | | | | | | | | |
| inside | | | | | | | | | | |