

Required Service Work <input checked="" type="checkbox"/> Performed (check if performed)	miles (thousands)															Not OK ↓			
	years	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13		140 14	150 15	
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP00.20-P-0043E
<input type="checkbox"/> Perform brake test				•		•		•		•		•		•		•		<input type="checkbox"/> AP42.00-P-4290BA	
<input type="checkbox"/> Replace activated charcoal combination filter <input checked="" type="checkbox"/> behind glovebox				•		•		•		•		•		•		•		AP83.00-P-8384CAA	
<input type="checkbox"/> Replace dust filter <input checked="" type="checkbox"/> behind plastic cowl in engine compartment				•		•		•		•		•		•		•		AP83.00-P-8381B	
<input type="checkbox"/> Engine – oil and filter change engine 177			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101D	
engine 274.920 except CODE M005 (4MATIC)			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101CWI	
engine 274.920 with CODE M005 (4MATIC)			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101CWE	
engine 276			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101CWZ	
<input type="checkbox"/> Check thickness of brake pads front and rear			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4252CAA	
<input type="checkbox"/> Check and correct all tire air pressures, including spare where applicable			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP40.15-P-4061A	
<input type="checkbox"/> Check underside of vehicle for damage and leaks				•		•		•		•		•		•		•		<input type="checkbox"/> AP00.20-P-0054E	
<input type="checkbox"/> Check visible parts in engine compartment for damage and leaks				•		•		•		•		•		•		•		<input type="checkbox"/> AP00.20-P-0055C	
<input type="checkbox"/> Inspect front axle and front axle ball joints, check rubber boots				•		•		•		•		•		•		•		<input type="checkbox"/> AP33.10-P-3358A	
<input type="checkbox"/> Check condition of steering and tie rods				•		•		•		•		•		•		•		<input type="checkbox"/> AP46.00-P-4651A	
<input type="checkbox"/> Inspect rear axle and rear axle ball joints, check rubber boots			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP35.20-P-3552A	
<input type="checkbox"/> Inspect driveshaft flexible couplings				•		•		•		•		•		•		•		<input type="checkbox"/> AP41.10-P-4152EW	
<input type="checkbox"/> Check condition of suspension struts or shock absorbers and springs				•		•		•		•		•		•		•		<input type="checkbox"/> AP32.25-P-3255A	
<input type="checkbox"/> Check catch, safety catch, and hinges on engine hood for proper operation			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>	
<input type="checkbox"/> Check charging cable and vehicle socket for mechanical damage model 205.047 (Hybrid)				•		•		•		•		•		•		•		<input type="checkbox"/> AP54.10-P-5458B	
<input type="checkbox"/> Check condition of poly-V-belt except model 205.047 (Hybrid) engine 177				•		•		•		•		•		•		•		<input type="checkbox"/> AP13.22-P-1352D	
engine 274, 276				•		•		•		•		•		•		•		<input type="checkbox"/> AP13.22-P-1352EW	
<input type="checkbox"/> Clean visible area of water deflector			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
<input type="checkbox"/> Check brake fluid level, correct if necessary			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4210CAA	
<input type="checkbox"/> Replace brake fluid				•		•		•		•		•		•		•		AP42.00-P-4280EW	
<input type="checkbox"/> Check high-voltage battery circuit coolant level model 205.047 (Hybrid)				•		•		•		•		•		•		•		<input type="checkbox"/> AP08.50-P-2053C	
<input type="checkbox"/> Check coolant level and correct if necessary			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP20.30-P-2049U	
<input type="checkbox"/> Check windshield washer system fluid, correct if necessary <input checked="" type="checkbox"/> Observe correct coolant composition			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP82.35-P-8210CAA	
<input type="checkbox"/> Check first aid kit			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP68.00-P-6850EW	
<input type="checkbox"/> Check starter. Use MB diagnosis tool. Model 205.047 (Hybrid)			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP15.30-P-1550AA	

Required Service Work	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK	
<input checked="" type="checkbox"/> Performed (check if performed)	years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	↓	
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster <input checked="" type="checkbox"/> reminder - if not yet performed			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP00.20-P-0043E	
Required Additional Work	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK	
<input checked="" type="checkbox"/> Performed (check if performed)	years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	↓	
<input type="checkbox"/> Rear Axle differential fluid replacement with CODE 467 (electronic locking differential) with CODE 471 (mechanical locking differential) with CODE P30 (AMG performance package)		•			•			•			•			•			•	AP35.00-P-3501CMG	
<input type="checkbox"/> Replace air filter engine 177					•			•			•			•			•	AP09.10-P-0980I	
<input type="checkbox"/> Automatic transmission - oil and filter change engine 177 with transmission 722.930 (AMG models)					•			•			•			•			•	AP27.00-P-2702W	
<input type="checkbox"/> Automatic transmission - oil and filter change engine 274, 276 Model 205.047 (Hybrid) with transmission 724.2 transmission 725.0 transmission 722.9								•						•			•	AP27.00-P-2702A AP27.00-P-2702B AP27.00-P-2702W	
<input type="checkbox"/> Replace spark plugs engine 274 engine 177 engine 276							•				•						•	AP15.10-P-1580CWF AP15.10-P-1580C AP15.10-P-1580D	
<input type="checkbox"/> Replace air filter engine 274, 276 engine 276 engine 274							•				•						•	AP09.10-P-0980E AP09.10-P-0980CWG	
<input type="checkbox"/> Replace fuel filter														•				AP47.20-P-0780M	
<input type="checkbox"/> Replace main circuit coolant <input checked="" type="checkbox"/> Observe correct coolant composition														•				AP20.00-P-2082K	
<input type="checkbox"/> Replace low-temperature circuit coolant <input checked="" type="checkbox"/> Observe correct coolant composition engine 177 engine 274 engine 276														•			•	AP20.00-P-2083C AP20.00-P-2083E AP20.00-P-2083I	
Recommended Service Work	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK	
<input checked="" type="checkbox"/> Performed (check if performed)	years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	↓	
<input type="checkbox"/> Check horn			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>	
<input type="checkbox"/> Check warning/indicator lamps			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>	AP54.30-P-5451HA
<input type="checkbox"/> Check illumination and interior lighting			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>	AP54.30-P-5453CAA
<input type="checkbox"/> Activate Tire Pressure Monitoring System <input checked="" type="checkbox"/> Refer to vehicle Operator's Manual			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
<input type="checkbox"/> Check windshield and headlamp washer system operation			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>	AP82.30-P-8252CAA
<input type="checkbox"/> Replace wiper blades			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
<input type="checkbox"/> Clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof)				•		•		•		•		•		•		•		AP77.20-P-7732CW	

Recommended Service Work <input checked="" type="checkbox"/> Performed (check if performed)	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK ↓
<input type="checkbox"/> Check condition and operation of trailer hitch with CODE 550 (Trailer hitch)				•		•		•		•		•		•		•		<input type="checkbox"/> AP31.11-P-3152CW
<input type="checkbox"/> Check all exterior lights		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP82.10-P-8252EW
<input type="checkbox"/> Check operation of headlamp range adjustment			•		•		•		•		•		•		•		•	<input type="checkbox"/> AP82.10-P-8250EW
<input type="checkbox"/> Check headlamp setting, correct if necessary			•		•		•		•		•		•		•		•	<input type="checkbox"/> AP82.10-P-8260E
<input type="checkbox"/> Check for body paint damage			•		•		•		•		•		•		•		•	<input type="checkbox"/> AP60.00-P-0050H
<input type="checkbox"/> Check trunk / cargo area lights		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Check TIREFIT tire sealant expiration date (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP40.10-P-4054R
<input type="checkbox"/> Check battery. Attach printout to sheet			•		•		•		•		•		•		•		•	AP54.10-P-5449U
<input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed Discs - with CODE B07 Discs - except CODE B07 Pads		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4258AC <input type="checkbox"/> AP42.10-P-4258EW <input type="checkbox"/> AP42.10-P-4252CAA
<input type="checkbox"/> Inspect tires for damage and measure remaining tread life		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP40.10-P-4051EW
<input type="checkbox"/> Check chassis and load bearing body components for damage and corrosion		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Check ex-factory driving aids (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP86.20-P-8649U
<input type="checkbox"/> Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) <input checked="" type="checkbox"/> After consultation with customer		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
High Mileage Required Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years																		
<input checked="" type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet																		
<input checked="" type="checkbox"/> Performed (check if performed)																		Not OK ↓
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster																		AP00.20-P-0043E
<input type="checkbox"/> Perform brake test																		<input type="checkbox"/> AP42.00-P-4290BA
<input type="checkbox"/> Replace activated charcoal combination filter <input checked="" type="checkbox"/> behind glovebox																		AP83.00-P-8384CAA
<input type="checkbox"/> Replace dust filter <input checked="" type="checkbox"/> behind plastic cowl in engine compartment																		AP83.00-P-8381B
<input type="checkbox"/> Engine – oil and filter change engine 177 engine 274.920 except CODE M005 (4MATIC) engine 274.920 with CODE M005 (4MATIC) engine 276																		AP18.00-P-0101D AP18.00-P-0101CWI AP18.00-P-0101CWE AP18.00-P-0101CWZ
<input type="checkbox"/> Check thickness of brake pads front and rear																		<input type="checkbox"/> AP42.10-P-4252CAA
<input type="checkbox"/> Check and correct all tire air pressures, including spare where applicable																		AP40.15-P-4061A
<input type="checkbox"/> Check underside of vehicle for damage and leaks																		<input type="checkbox"/> AP00.20-P-0054E
<input type="checkbox"/> Check visible parts in engine compartment for damage and leaks																		<input type="checkbox"/> AP00.20-P-0055C
<input type="checkbox"/> Inspect front axle and front axle ball joints, check rubber boots																		<input type="checkbox"/> AP33.10-P-3358A
<input type="checkbox"/> Check condition of steering and tie rods																		<input type="checkbox"/> AP46.00-P-4651A
<input type="checkbox"/> Inspect rear axle and rear axle ball joints, check rubber boots																		<input type="checkbox"/> AP35.20-P-3552A
<input type="checkbox"/> Inspect driveshaft flexible couplings																		<input type="checkbox"/> AP41.10-P-4152EW

<input type="checkbox"/> Check condition of suspension struts or shock absorbers and springs	<input type="checkbox"/> AP32.25-P-3255A
<input type="checkbox"/> Check catch, safety catch, and hinges on engine hood for proper operation	<input type="checkbox"/>
<input type="checkbox"/> Check charging cable and vehicle socket for mechanical damage model 205.047 (Hybrid)	<input type="checkbox"/> AP54.10-P-5458B
<input type="checkbox"/> Check condition of poly-V-belt except model 205.047 (Hybrid) engine 177	<input type="checkbox"/> AP13.22-P-1352D
engine 274, 276	<input type="checkbox"/> AP13.22-P-1352EW
<input type="checkbox"/> Clean visible area of water deflector	
<input type="checkbox"/> Check brake fluid level, correct if necessary	<input type="checkbox"/> AP42.10-P-4210CAA
<input type="checkbox"/> Replace brake fluid	AP42.00-P-4280EW
<input type="checkbox"/> Check high-voltage battery circuit coolant level model 205.047 (Hybrid)	<input type="checkbox"/> AP08.50-P-2053C
<input type="checkbox"/> Check coolant level and correct if necessary	<input type="checkbox"/> AP20.30-P-2049U
<input type="checkbox"/> Check windshield washer system fluid, correct if necessary <input type="checkbox"/> Observe correct coolant composition	<input type="checkbox"/> AP82.35-P-8210CAA
<input type="checkbox"/> Check first aid kit	<input type="checkbox"/> AP68.00-P-6850EW
<input type="checkbox"/> Check starter. Use MB diagnosis tool. Model 205.047 (Hybrid)	<input type="checkbox"/> AP15.30-P-1550AA
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster <input type="checkbox"/> reminder - if not yet performed	AP00.20-P-0043E
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years	
<input type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet	
<input checked="" type="checkbox"/> Performed (check if performed)	Not OK ↓
<input type="checkbox"/> Check horn	<input type="checkbox"/>
<input type="checkbox"/> Check warning/indicator lamps	<input type="checkbox"/> AP54.30-P-5451HA
<input type="checkbox"/> Check illumination and interior lighting	<input type="checkbox"/> AP54.30-P-5453CAA
<input type="checkbox"/> Activate Tire Pressure Monitoring System <input type="checkbox"/> Refer to vehicle Operator's Manual	
<input type="checkbox"/> Check windshield and headlamp washer system operation	<input type="checkbox"/> AP82.30-P-8252CAA
<input type="checkbox"/> Replace wiper blades	
<input type="checkbox"/> Clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof)	AP77.20-P-7732CW
<input type="checkbox"/> Check condition and operation of trailer hitch with CODE 550 (Trailer hitch)	<input type="checkbox"/> AP31.11-P-3152CW
<input type="checkbox"/> Check all exterior lights	<input type="checkbox"/> AP82.10-P-8252EW
<input type="checkbox"/> Check operation of headlamp range adjustment	<input type="checkbox"/> AP82.10-P-8250EW
<input type="checkbox"/> Check headlamp setting, correct if necessary	<input type="checkbox"/> AP82.10-P-8260E
<input type="checkbox"/> Check for body paint damage	<input type="checkbox"/> AP60.00-P-0050H
<input type="checkbox"/> Check trunk / cargo area lights	<input type="checkbox"/>
<input type="checkbox"/> Check TIREFIT tire sealant expiration date (where applicable)	<input type="checkbox"/> AP40.10-P-4054R
<input type="checkbox"/> Check battery. Attach printout to sheet	AP54.10-P-5449U
<input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed Discs - with CODE B07	<input type="checkbox"/> AP42.10-P-4258AC
Discs - except CODE B07	<input type="checkbox"/> AP42.10-P-4258EW
Pads	<input type="checkbox"/> AP42.10-P-4252CAA
<input type="checkbox"/> Inspect tires for damage and measure remaining tread life	<input type="checkbox"/> AP40.10-P-4051EW
<input type="checkbox"/> Check chassis and load bearing body components for damage and corrosion	<input type="checkbox"/>

<input type="checkbox"/> Check ex-factory driving aids (where applicable)	<input type="checkbox"/> AP86.20-P-8649U
<input type="checkbox"/> Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) <input type="checkbox"/> After consultation with customer	
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years	
<input type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet	
<input checked="" type="checkbox"/> Performed (check if performed)	Not OK ↓
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster	AP00.20-P-0043E
<input type="checkbox"/> Engine – oil and filter change engine 177 engine 274.920 except CODE M005 (4MATIC) engine 274.920 with CODE M005 (4MATIC) engine 276	AP18.00-P-0101D AP18.00-P-0101CWI AP18.00-P-0101CWE AP18.00-P-0101CWZ
<input type="checkbox"/> Check thickness of brake pads front and rear	<input type="checkbox"/> AP42.10-P-4252CAA
<input type="checkbox"/> Check and correct all tire air pressures, including spare where applicable	AP40.15-P-4061A
<input type="checkbox"/> Inspect rear axle and rear axle ball joints, check rubber boots	<input type="checkbox"/> AP35.20-P-3552A
<input type="checkbox"/> Check catch, safety catch, and hinges on engine hood for proper operation	<input type="checkbox"/>
<input type="checkbox"/> Clean visible area of water deflector	
<input type="checkbox"/> Check brake fluid level, correct if necessary	<input type="checkbox"/> AP42.10-P-4210CAA
<input type="checkbox"/> Check coolant level and correct if necessary	<input type="checkbox"/> AP20.30-P-2049U
<input type="checkbox"/> Check windshield washer system fluid, correct if necessary <input type="checkbox"/> Observe correct coolant composition	<input type="checkbox"/> AP82.35-P-8210CAA
<input type="checkbox"/> Check first aid kit	<input type="checkbox"/> AP68.00-P-6850EW
<input type="checkbox"/> Check starter. Use MB diagnosis tool. Model 205.047 (Hybrid)	<input type="checkbox"/> AP15.30-P-1550AA
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster <input type="checkbox"/> reminder - if not yet performed	AP00.20-P-0043E
High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years	
<input type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet	
<input checked="" type="checkbox"/> Performed (check if performed)	Not OK ↓
<input type="checkbox"/> Check horn	<input type="checkbox"/>
<input type="checkbox"/> Check warning/indicator lamps	<input type="checkbox"/> AP54.30-P-5451HA
<input type="checkbox"/> Check illumination and interior lighting	<input type="checkbox"/> AP54.30-P-5453CAA
<input type="checkbox"/> Activate Tire Pressure Monitoring System <input type="checkbox"/> Refer to vehicle Operator's Manual	
<input type="checkbox"/> Check windshield and headlamp washer system operation	<input type="checkbox"/> AP82.30-P-8252CAA
<input type="checkbox"/> Replace wiper blades	
<input type="checkbox"/> Check all exterior lights	<input type="checkbox"/> AP82.10-P-8252EW
<input type="checkbox"/> Check trunk / cargo area lights	<input type="checkbox"/>
<input type="checkbox"/> Check TIREFIT tire sealant expiration date (where applicable)	<input type="checkbox"/> AP40.10-P-4054R
<input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed Discs - with CODE B07 Discs - except CODE B07 Pads	<input type="checkbox"/> AP42.10-P-4258AC <input type="checkbox"/> AP42.10-P-4258EW <input type="checkbox"/> AP42.10-P-4252CAA
<input type="checkbox"/> Inspect tires for damage and measure remaining tread life	<input type="checkbox"/> AP40.10-P-4051EW
<input type="checkbox"/> Check chassis and load bearing body components for damage and corrosion	<input type="checkbox"/>
<input type="checkbox"/> Check ex-factory driving aids (where applicable)	<input type="checkbox"/> AP86.20-P-8649U

<input type="checkbox"/> Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) <input checked="" type="checkbox"/> After consultation with customer		
High Mileage Additional Work		
<input checked="" type="checkbox"/> Performed (check if performed)		
<input type="checkbox"/> Rear Axle differential fluid replacement with CODE 467 (electronic locking differential) with CODE 471 (mechanical locking differential) with CODE P30 (AMG performance package)	At 2,000 miles, then if more than 30,000 miles or 3 years since last replacement	AP35.00-P-3501CMG
<input type="checkbox"/> Replace air filter engine 177	If more than 30,000 miles or 3 years since last replacement	AP09.10-P-0980I
<input type="checkbox"/> Automatic transmission - oil and filter change engine 177 with transmission 722.930 (AMG models)	If more than 30,000 miles or 3 years since last replacement	AP27.00-P-2702W
<input type="checkbox"/> Automatic transmission - oil and filter change engine 274, 276 Model 205.047 (Hybrid) with transmission 724.2 transmission 725.0 transmission 722.9	If more than 60,000 miles or 6 years since last replacement If more than 60,000 miles or 6 years since last replacement If more than 60,000 miles or 6 years since last replacement	AP27.00-P-2702A AP27.00-P-2702B AP27.00-P-2702W
<input type="checkbox"/> Replace spark plugs engine 274 engine 177 engine 276	If more than 50,000 miles or 5 years since last replacement If more than 50,000 miles or 5 years since last replacement If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580CWF AP15.10-P-1580C AP15.10-P-1580D
<input type="checkbox"/> Replace air filter engine 274, 276 engine 276 engine 274	If more than 50,000 miles or 5 years since last replacement If more than 50,000 miles or 5 years since last replacement	AP09.10-P-0980E AP09.10-P-0980CWF
<input type="checkbox"/> Replace fuel filter	If more than 120,000 miles or 12 years since last replacement	AP47.20-P-0780M
<input type="checkbox"/> Replace main circuit coolant <input checked="" type="checkbox"/> Observe correct coolant composition	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2082K
<input type="checkbox"/> Replace low-temperature circuit coolant <input checked="" type="checkbox"/> Observe correct coolant composition engine 177 engine 274 engine 276	If more than 120,000 miles or 12 years since last replacement If more than 120,000 miles or 12 years since last replacement If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083C AP20.00-P-2083E AP20.00-P-2083I

Tire inflation pressure (bar/psi)				
LF	RF	LR	RR	Spare

Tire tread depth (mm)				
	LF	RF	LR	RR
outside				
center				
inside				