

Mercedes-Benz

AP00.20-U-1208DM

SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model	Year	201	/
USA			

Model 213



Customer:			Repair order nur	mber:		
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommende likely necessitate tire rotati each 10,000-mile maintena 10,000-mile maintenance s	on at least once in between ance service and at every	Tires rotated	YES _		NO
Note: For any co	ondition found while performi m the repair using a separate	ng the checks or inspections e repair order.	s included in this m	naintenance	sheet,	determine
Current mileage read	ling:	_ Oi	grade/viscosity:_			
Additional notes:						
Service work to be poservice advisor:	erformed as advised by	Completion date:	Confirm work has below:	been perfor	med b	y signing

Required Service Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Reset Maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0043J
☐ Replace combination filter			•		•		•		•		•		•		•			AP83.00-P-8384B
Replace dust filter			•		•		•		•		•		•		•			AP83.00-P-8381C
☐ Perform brake test			•		•		•		•		•		•		•			AP42.00-P-4290BA
☐ Engine – oil and filter change engine 274.920 except CODE M005 (4Matic)								•								•		AP18.00-P-0101CWI
engine 274.920 with CODE M005 (4Matic)										•	•							AP18.00-P-0101CWE
engine 276			•		•			•		•	•				•	•		AP18.00-P-0101CWZ
☐ Check condition of poly-V-belt			•		•		•		•		•		•		•			AP13.22-P-1352EW
☐ Check thickness of brake pads front and rear		•	•		•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4252E
Check and correct all tire air pressures, including spare where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.15-P-4061A
Check visible parts in engine compartment for damage and leaks			•		•		•		•		•		•		•			AP00.20-P-0055E
☐ Check underside of vehicle for damage and leaks			•		•		•		•		•		•		•			AP00.20-P-0054I
☐ Inspect front axle ball joints and rubber boots			•		•		•		•		•		•		•			AP33.10-P-3358A
☐ Inspect driveshaft flexible discs			•		•		•		•		•		•		•			AP41.10-P-4152EW
☐ Inspect rear axle and rear axle ball joints			•		•		•		•		•		•		•			AP35.20-P-3552A
☐ Check condition of steering and tie rods			•		•		•		•		•		•		•			AP46.00-P-4651A
☐ Check condition of suspension struts or shock absorbers and springs			•		•		•		•		•		•		•			AP32.25-P-3255A
☐ Check catch, safety catch, and hinges on engine hood for proper operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Clean visible area of water deflector			•		•		•		•		•		•		•			AP82.35-P-8232A
☐ Check coolant level and correct if necessary ☐ observe correct coolant composition		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP20.30-P-2049U
☐ Check windshield washer system fluid, correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210C
☐ Check brake fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4210B
☐ Replace brake fluid			•		•		•		•		•		•		•			AP42.00-P-4280C
☐ Check first aid kit		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP68.00-P-6850EW
Reset Maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0043J
reminder - if not yet performed Required Additional Work miles (thousands)	2	10	20	30	40	50	60	70	80	00	100	110	120	130	140	150		
Performed years (check if performed)	2	1	2	3	4	5	6	70	8	90	100	110	120	130	140	150	Not OK ↓	
Replace air filter											_							AP09.10-P-0980CWG
engine 276						•					•					•		AP09.10-P-0980E
Replace spark plugs						_												AP15.10-P-1580CWF
engine 276						•					•					•		AP15.10-P-1580D
☐ Automatic transmission - oil and filter change							•						•					AP27.00-P-2702B
Replace fuel filter													•					AP47.20-P-0780D

Required Additional Work miles (thousands) Performed years (check if performed)	2	10	20 2	30	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Replace coolant ii observe correct coolant composition													•					AP20.00-P-2082G
Recommended Service wiles (thousands) Work ☑ Performed years (check if performed)	2	10	20	30	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
☐ Check horn		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check warning/indicator lamps		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451HA
☐ Check illumination and interior lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5453E
☐ Activate Tire Pressure Monitoring System ☐ Refer to vehicle Operator's Manual		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check windshield and headlamp washer system operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8252D
Replace wiper blades		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof)			•		•		•		•		•		•		•			AP77.20-P-7732A
☐ Check all exterior lights		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.10-P-8252EW
☐ Check operation of headlamp range adjustment			•		•		•		•		•		•		•			AP82.10-P-8250EW
☐ Check headlamp setting, correct if necessary			•		•		•		•		•		•		•			AP82.10-P-8260J
☐ Check for body paint damage			•		•		•		•		•		•		•			AP60.00-P-0050I
☐ Check trunk / cargo area light		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) I After consultation with customer		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check condition and operation of trailer hitch with CODE 550 (Trailer hitch)			•		•		•		•		•		•		•			AP31.11-P-3152A
☐ Check TIREFIT tire sealant expiration date (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4054R
☐ Check battery. Attach printout to sheet			•		•		•		•		•		•		•			AP54.10-P-5449U
☐ Tire rotation (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check seatbelts and buckles for proper operation or damage			•		•		•		•		•		•		•			
☐ Check thickness of brake pads and discs, front and rear wheels removed Pads Discs		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4252E AP42.10-P-4256EW
□Visually inspect brake system components,		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
lines, hoses, calipers																		
☐ Inspect tires for damage and measure remaining tread life		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051EW
☐ Check chassis and load bearing body components for damage and corrosion			•		•		•		•		•		•		•			
☐ Check ex-factory driving aids (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP86.20-P-8649U
High Mileage Required Service Work at 1						_					_	20,0	000	mile	s or	2 ye	ars	
Plus any applicable additional work li	ste	d at	the	e er	nd c	of th	ne s	erv	ice	she	eet						Not OK	
☑ Performed (check if performed) Wot OK																		
Reset Maintenance service indicator in in	strı	ume	ent o	clus	ter											,,	→	AP00.20-P-0043J

Replace combination filter		AP83.00-P-8384B
☐ Replace dust filter		AP83.00-P-8381C
☐ Perform brake test		AP42.00-P-4290BA
☐ Engine – oil and filter change		
engine 274.920 except CODE M005 (4Matic)		AP18.00-P-0101CWI
engine 274.920 with CODE M005 (4Matic)		AP18.00-P-0101CWE
engine 276		AP18.00-P-0101CWZ
☐ Check condition of poly-V-belt		AP13.22-P-1352EW
☐ Check thickness of brake pads front and rear		AP42.10-P-4252E
☐ Check and correct all tire air pressures, including spare where applicable		AP40.15-P-4061A
☐ Check visible parts in engine compartment for damage and leaks		AP00.20-P-0055E
☐ Check underside of vehicle for damage and leaks		AP00.20-P-0054I
☐ Inspect front axle ball joints and rubber boots		AP33.10-P-3358A
☐ Inspect driveshaft flexible discs		AP41.10-P-4152EW
☐ Inspect rear axle and rear axle ball joints		AP35.20-P-3552A
\square Check condition of steering and tie rods		AP46.00-P-4651A
\square Check condition of suspension struts or shock absorbers and springs		AP32.25-P-3255A
\square Check catch, safety catch, and hinges on engine hood for proper operation		
☐ Clean visible area of water deflector		AP82.35-P-8232A
☐ Check coolant level and correct if necessary		AP20.30-P-2049U
i observe correct coolant composition		
☐ Check windshield washer system fluid, correct if necessary		AP82.35-P-8210C
☐ Check brake fluid level and correct if necessary		AP42.10-P-4210B
Replace brake fluid		AP42.00-P-4280C
☐ Check first aid kit		AP68.00-P-6850EW
Reset Maintenance service indicator in instrument cluster		AP00.20-P-0043J
i reminder - if not yet performed		
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles	es or 2 year	ars
Plus any applicable additional work listed at the end of the service sheet	Not OF	•
☑ Performed (check if performed)	J.	`
Check horn		AP54.30-P-5451HA
Check warning/indicator lamps		AP54.30-P-5453E
Check illumination and interior lighting		711 0 1.00 1 0 1002
☐ Activate Tire Pressure Monitoring System ☐ Refer to vehicle Operator's Manual		
☐ Check windshield and headlamp washer system operation		AP82.35-P-8252D
☐ Replace wiper blades		
☐ Check, clean and lubricate Panoramic sliding roof guide mechanism with CODE 413 (Automatic panoramic sliding sunroof)		AP77.20-P-7732A
☐ Check all exterior lights		AP82.10-P-8252EW
☐ Check operation of headlamp range adjustment		AP82.10-P-8250EW
☐ Check headlamp setting, correct if necessary		AP82.10-P-8260J
☐ Check for body paint damage		AP60.00-P-0050I
Check trunk / cargo area light		

Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function)		
After consultation with customer		
Check condition and operation of trailer hitch with CODE 550 (Trailer hitch)		AP31.11-P-3152A
Check TIREFIT tire sealant expiration date (where applicable)		AP40.10-P-4054R
Check battery. Attach printout to sheet		AP54.10-P-5449U
☐ Tire rotation (where applicable)		
Check seatbelts and buckles for proper operation or damage		
Check thickness of brake pads and discs, front and rear wheels removed	-	
Pads		AP42.10-P-4252E
Discs		AP42.10-P-4256EW
☐ Visually inspect brake system components, lines, hoses, calipers		
☐ Inspect tires for damage and measure remaining tread life		AP40.10-P-4051EW
Check chassis and load bearing body components for damage and corrosion		
☐ Check ex-factory driving aids (where applicable)		AP86.20-P-8649U
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2	years	
i Plus any applicable additional work listed at the end of the service sheet		
Performed	Not OF	(
(check if performed)	<u> </u>	4.Dan an D an an I
Reset Maintenance service indicator in instrument cluster		AP00.20-P-0043J
☐ Engine – oil and filter change		
engine 274.920 except CODE M005 (4Matic)		AP18.00-P-0101CWI
engine 274.920 with CODE M005 (4Matic) engine 276		AP18.00-P-0101CWE AP18.00-P-0101CWZ
Check thickness of brake pads front and rear		AP42.10-P-4252E
Check and correct all tire air pressures, including spare where applicable		AP40.15-P-4061A
Check catch, safety catch, and hinges on engine hood for proper operation		AP20.30-P-2049U
☐ Check coolant level and correct if necessary ☐ observe correct coolant composition		AF 20.30-F-20490
Check windshield washer system fluid, correct if necessary		AP82.35-P-8210C
Check brake fluid level and correct if necessary		AP42.10-P-4210B
Check first aid kit		AP68.00-P-6850EW
		AP00.20-P-0043J
Reset Maintenance service indicator in instrument cluster ireminder - if not yet performed		711 00.20 1 00400
High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles	es or 2 vea	ars
Plus any applicable additional work listed at the end of the service sheet	<u>_</u> ,	
Performed	Not OF	<
(check if performed)	Ψ	
□ Check horn		
☐ Check warning/indicator lamps		AP54.30-P-5451HA
☐ Check illumination and interior lighting		AP54.30-P-5453E
Activate Tire Pressure Monitoring System i Refer to vehicle Operator's Manual		
Check windshield and headlamp washer system operation		AP82.35-P-8252D
Replace wiper blades		
		AP82.10-P-8252EW
☐ Check all exterior lights ☐ Check trunk / cargo area light		

Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CO	DE 893 (KEYLESS-GO start function)						
After consultation with customer	,						
☐ Check TIREFIT tire sealant expiration date	(where applicable)		AP40.10-P-4054R				
☐ Tire rotation (where applicable)							
Check thickness of brake pads and discs, f	ront and rear wheels removed						
Pads			AP42.10-P-4252E				
Discs			AP42.10-P-4256EW				
☐ Visually inspect brake system components,	lines, hoses, calipers						
☐ Inspect tires for damage and measure remains	aining tread life		AP40.10-P-4051EW				
☐ Check ex-factory driving aids (where applicable) ☐ AP86.20							
High Mileage Additional Work							
⊠ Performed							
(check if performed)							
Replace air filter							
engine 274	If more than 50,000 miles or 5 years since last replacement		AP09.10-P-0980CWG				
engine 276	If more than 50,000 miles or 5 years since last replacement		AP09.10-P-0980E				
Replace spark plugs							
engine 274	If more than 50,000 miles or 5 years since last replacement		AP15.10-P-1580CWF				
engine 276	If more than 50,000 miles or 5 years since last replacement		AP15.10-P-1580D				
Automatic transmission - oil and filter change	If more than 60,000 miles or 6 years since last replacement		AP27.00-P-2702B				
Replace fuel filter	If more than 120,000 miles or 12 years since last replacement		AP47.20-P-0780D				
Replace coolant	If more than 120,000 miles or 12 years since last replacement		AP20.00-P-2082G				
i observe correct coolant composition							

Tire inflation pressure (bar/psi)										
LF	RF	LR	RR	Spare						

Tire thread depth (mm)									
	LF	RF	LR	RR					
outside									
center									
inside									