

MODEL 166.0## (except 166.074) 1# , 166.8## (except 166.874) 1#
without CODE 233 (DISTRONIC PLUS)
without CODE 239 (DISTRONIC PLUS and BAS PRO)

1 Illuminated Mercedes star



P88.40-3032-11

	Remove		
	Information on preventing damage to electronic components due to electrostatic discharge		AH54.00-P-0001-01A
1	Switch off ignition and remove transmitter key or KEYLESS-GO start/stop button from electronic ignition lock control unit	KEYLESS-GO start/stop button only on vehicles with CODE 889 (Keyless-Go).	
2	Disconnect battery ground line		AR54.10-P-0003GZ
3	Remove right front and right rear door sill molding		AR68.30-P-4100GQ
4	Remove rear seat cushion		AR91.12-P-1020GQA
5	Remove radiator grille	MODEL 166.0 , 166.8 MODEL 166.0	AR88.40-P-4001GQ
6	Remove Mercedes star		AR88.40-P-4050NKB
7	Remove box for dust filter on air conditioning system in engine compartment		
	Install		
8	Install wiring harness and illuminated Mercedes star control unit (1)	MODEL 166.8 MODEL 166.0 Butyl cord Terostat 81 Ø 6 mm	AZ88.40-P-0010-01GQA AZ88.40-P-0010-01GQ BR00.45-Z-1085-01A
9	Install illuminated Mercedes star (1) and connect		
10	Install remaining parts		
11	Document retrofitted equipment via vehicle documentation (VeDoc)	Attach note "Illuminated Mercedes star retrofitted according to AZ88.40-P-0001GQ" to field organization texts for design group 88.	
12	Carry out function check	The illuminated Mercedes star (1) is switched on by opening a door as well as by activating the ambient illumination. The illuminated star (1) switches off automatically approx. 5 minutes after a door is opened or after the ambient illumination is switched off automatically.	

Number	Designation	Order number
	Butyl cord Terostat 81 Ø 6 mm	A 004 989 61 20

**Parts
ordering
note**

Part no.	Designation	Quantity
KG 98 (siehe EPC)	Parts kit for illuminated Mercedes star	1