RELEASE			SHARE 🖈	SAVED #	DOWNLOAD S
O Oct 31, 2018					
Vehicle Type	Four-Door five-pa	acconone SUN/			
Chassis	Steel unibody	assenger 50 V			
Drive Configuration	4MATIC All-Whe	el Drive			
Exterior Dimensions (in)					
Wheelbase	117.9				
Length Width (w/ mirrors)	194.3				
Width (w/o mirrors)	78.7				
Height	70.7				
Track (front / rear)	66.10 / 66.77				
Ground Clearance (max load)	TBA				
Weights  Curb Weight (lbs)	4,991				
Gross Vehicle Weight Rating (lbs)	6,614				
Towing (lbs)	7,700 est.				
Max. total payload (lbs) 1,623					
Interior Dimensions (in)	40.5100.0				
Head room (front/2nd row) Leg room (front/2nd row)	40.5/39.6	with optional adjustable 2nd seat row)			
Shoulder room (front/2nd row)					
Capacities (cu-ft)					
Cabin Volume	TBA				
argo Volume (behind 1st row)  TBA  TBA /TBA with out					
rgo Volume (behind 2nd row) TBA (TBA with opt		ptional adjustable 2nd seat row)			
Suspension					
Front		uble wishbone suspension with coil spring,			
single-tube shoot		k absorber with SSD and tubular torsion ba Ilti-link suspension with coil spring, single-t			
		Iti-link suspension with coil spring, single-t with SSD and tubular torsion bar	uve		
Steering					
Type         Speed-dependen           Ratio         18.7 : 1		nt, electro-mechanical rack-and-pinion			
Turning Circle (ft)	39.4 (wall-to-wall	0)			
Brake Disc Diameter / Thickness (in)					
Front	14.8 / 1.4				
Rear	13.6 / 0.9				
Standard Wheels					
Front		8.0 x 19 (Cast)			
Rear		8.0 x 19 (Cast)			
Standard Tires					
Front		255 / 50 R19			
Rear		255 / 50 R19			
		,			
Engine		3.0L Inline-6 with EQ Boost			
Engine Type  Engine Material		Aluminum-Alloy			
Valvetrain / Arrangement		DOHC, 4-valves per cylinder			
Displacement (cc)		2,999			
Bore (in / mm)		3.27 / 83.0			
Stroke (in / mm)		3.64 / 92.4			
Compression Ratio		10.5 : 1			
Horsepower @ rpm EQ Boost Starter Generator		362 @ 5,500 – 6,100 (Internal Combustic Up to 21 hp	on Engine	,	
Torque @ rpm		389 @ 1,800 - 4,000			
Redline (rpm)		6,800			
		I			
Transmission					
Transmission Type Shift Controls		9G-TRONIC  Wheel-mounted shift paddles			
Gear Ratios:		wheel-mounted smit paddles			
1st		5.35:1			
2nd		3.24 : 1			
3rd		2.25 : 1			
4th		1.84 : 1			
5th 6th		1.21 : 1			
7th		0.86:1			
8th		0.72 : 1			
9th		0.60 : 1			
Reverse		4.80 : 1			
R2		-			
Final Drive		3.27 : 1			
Performance					
0-80 mph (seconds)		5.5 est.			
Top Speed (mph)		130 (electronically limited)			
		I.			
Fuel Economy					
City / Highway / Combined (mpg)		19 / 24 / 21			
•		19/24/21			
City / Highway / Combined (mpg)					
City / Highway / Combined (mpg) Fuel Tank (gallons)					