

Category : Cars
Make : Mercedes-Benz (EU)
Model : GLE-Class, W166 (2015 - 2019)
Type : GLE 350 4MATIC (166.057) (2015 - 2019)
Remarks :

Engine M276.955

Capacity: Capacity 7 litre

Use: Flexible (max)
Intervals: Change 25000 km
Products: TITAN Supersyn LONGLIFE SAE 5W-40 (Below 10°C)
TITAN Supersyn LONGLIFE SAE 0W-30 (year-round)
TITAN Supersyn LONGLIFE SAE 0W-40 (year-round)
TITAN GT1 PRO 229.6 SAE 5W-30 (XTL-Technology) (Below 10°C)

Differential, front

Capacity: Capacity 0,8 litre

Use: Normal
Products: TITAN SINTOPOID FE SAE 75W-85 (XTL-Technology) (year-round)

Differential, rear 187 FE, Ø 187 mm

Capacity: Capacity 0,95 litre

Use: Normal
Products: TITAN SINTOPOID FE SAE 75W-85 (XTL-Technology) (year-round)

Differential, rear 200 FE, Ø 200 mm

Capacity: Capacity 1,1 litre

Use: Normal

Products: TITAN SINTOPOID FE SAE 75W-85 (XTL-Technology) (year-round)

Differential, rear 215 FE, Ø 215 mm

Capacity: Capacity 1,2 litre

Use: Normal

Products: TITAN SINTOPOID FE SAE 75W-85 (XTL-Technology) (year-round)

Transferbox

Capacity: Capacity 0,5 litre
Capacity 1,5 litre + dual range

Use: Normal

Products: TITAN ATF 4134 (year-round)
TITAN ATF 3353 (year-round)

Transmission, automatic 722.9xx 7/1

Capacity: Capacity 9 litre Dry fill

Use: Normal

Intervals: Change 125000 km/ 60 months

Products: TITAN ATF 7134 FE (year-round)

Transmission, automatic 725.031 9/1

Use: Normal

Intervals: Change 125000 km/ 60 months

Products: TITAN ATF 9134 FE (year-round)

Active curve system

Capacity: Capacity 2 litre

Use: Normal

Products: **TITAN CHF 11S (year-round)**

Hydraulic brake system, ABS

Capacity: Capacity 0,8 litre

Use: Normal

Intervals: Change 24 months

Products: **MAINTAIN DOT 514 LV (year-round)**
MAINTAIN DOT 5.1 (year-round)

Cooling system

Capacity: Capacity 10,5 litre

Use: Normal

Intervals: Change 250000 km/ 180 months

Products: **MAINTAIN FRICOFIN DP (year-round)**
MAINTAIN FRICOFIN DP 50 (Ready-Mix) (year-round)

Airconditioning compressor

Capacity: Capacity 120 cm³
Capacity 160 cm³ + code 582

Use: Normal

Products: **Special product, please use the original OEM part ()**

Airconditioning system

Capacity:	Capacity 1400 grams + code 582 Capacity 1050 grams
Use:	Normal
Products:	Special product, please use the original OEM part ()

The information contained in the oil chooser is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. The information given in the oil chooser represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products must not be used in aircrafts/spacecrafts or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all information given in the oil chooser at any time and without warning, unless otherwise provided in customer-specific agreements. With this publication, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH. © FUCHS SCHMIERSTOFFE GMBH. All rights reserved.