

2013 MERCEDES-BENZ GLK-Class

WDCGG5HB3DG123358

Last Entered Odometer: 139,267 mi



Oxygen Sensor Monitor Bank 1 - Sensor 1

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 01	Min: 0.3200657	Val: 1.0053718
TID:83	Max: 1.9990000	



Oxygen Sensor Monitor Bank 1 - Sensor 1

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 01	Min: -0.1000311	Val: -0.0075915
TID:87	Max: 0.9990000	



Oxygen Sensor Monitor Bank 1 - Sensor 1

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 01	Min: -0.9990305	Val: -0.0075915
TID:88	Max: 0.0999701	



Oxygen Sensor Monitor Bank 1 - Sensor 2

Rich to lean sensor switch time (calculated)

Status: Complete and Pass

MID: 02	Min: 00m:00s	Val: 01m:50s
TID:05	Max: 11m:40s	



Oxygen Sensor Monitor Bank 1 - Sensor 2

Lean to rich sensor switch time (calculated)

Status: Complete and Pass

MID: 02	Min: 00m:00s	Val: 01m:50s
---------	--------------	--------------

TID:06 Max: 23m:20s

 **Oxygen Sensor Monitor Bank 1 - Sensor 2**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Test not complete

MID: 02 Min: --m:--s Val: --m:--s

TID:81 Max: --m:--s

 **Oxygen Sensor Monitor Bank 1 - Sensor 2**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Test not complete

MID: 02 Min: --m:--s Val: --m:--s

TID:82 Max: --m:--s

 **Oxygen Sensor Monitor Bank 1 - Sensor 2**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 02 Min: 0.000000 Val: 0.058521 V

TID:83 Max: 0.151180

 **Oxygen Sensor Monitor Bank 1 - Sensor 2**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 02 Min: 0.799792 Val: 0.809546 V

TID:84 Max: 7.990000

 **Oxygen Sensor Monitor Bank 2 - Sensor 1**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 05 Min: 0.3200657 Val: 1.0114723

TID:83 Max: 1.9990000

 **Oxygen Sensor Monitor Bank 2 - Sensor 1**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 05	Min: -0.1000311	Val: -0.0097866
TID:87	Max: 0.9990000	

 **Oxygen Sensor Monitor Bank 2 - Sensor 1**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 05	Min: -0.9990305	Val: -0.0097866
TID:88	Max: 0.0999701	

 **Oxygen Sensor Monitor Bank 2 - Sensor 2**

Rich to lean sensor switch time (calculated)

Status: Complete and Pass

MID: 06	Min: 00m:00s	Val: 02m:00s
TID:05	Max: 11m:40s	

 **Oxygen Sensor Monitor Bank 2 - Sensor 2**

Lean to rich sensor switch time (calculated)

Status: Complete and Pass

MID: 06	Min: 00m:00s	Val: 02m:00s
TID:06	Max: 23m:20s	

 **Oxygen Sensor Monitor Bank 2 - Sensor 2**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Test not complete

MID: 06	Min: --m:--s	Val: --m:--s
TID:81	Max: --m:--s	

 **Oxygen Sensor Monitor Bank 2 - Sensor 2**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Test not complete

MID: 06	Min: --m:--s	Val: --m:--s
TID:82	Max: --m:--s	

 **Oxygen Sensor Monitor Bank 2 - Sensor 2**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 06	Min: 0.000000	Val: 0.112166 V
TID:83	Max: 0.151180	

 **Oxygen Sensor Monitor Bank 2 - Sensor 2**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 06	Min: 0.799792	Val: 0.819300 V
TID:84	Max: 7.990000	

 **Catalyst Monitor Bank 1**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 21	Min: 80.00	Val: 162.16 %
TID:92	Max: 655.35	

 **Catalyst Monitor Bank 2**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 22	Min: 80.00	Val: 161.62 %
TID:92	Max: 655.35	

 **VVT Monitor Bank 1**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 35	Min: -25.00	Val: 7.84 °
---------	-------------	-------------

TID:B8 Max: 8.16



VVT Monitor Bank 1

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 35 Min: -25.00 Val: 7.84 °

TID:B9 Max: 8.16



VVT Monitor Bank 1

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 35 Min: 12.71 Val: 12.93 °

TID:BA Max: 36.20



VVT Monitor Bank 1

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 35 Min: 12.71 Val: 12.93 °

TID:BB Max: 36.20



VVT Monitor Bank 2

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 36 Min: -25.00 Val: -7.60 °

TID:B8 Max: 3.12



VVT Monitor Bank 2

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 36 Min: -25.00 Val: -7.60 °

TID:B9 Max: 3.12



VVT Monitor Bank 2

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 36	Min: 6.10	Val: 11.48 °
TID:BA	Max: 18.10	



VVT Monitor Bank 2

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 36	Min: 6.10	Val: 11.48 °
TID:BB	Max: 18.10	



EVAP Monitor (Cap Off)

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Test not complete

MID: 39	Min: -	Val: - Pa
TID:A7	Max: -	



EVAP Monitor (0.040")

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Test not complete

MID: 3B	Min: -	Val: - Pa
TID:A4	Max: -	



EVAP Monitor (0.020")

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Test not complete

MID: 3C	Min: -	Val: - Pa
TID:A5	Max: -	



Purge Flow Monitor

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within

the On-Board Diagnostic Monitor.

Status: Test not complete

MID: 3D

Min: -

Val: - Pa

TID:AB

Max: -



Purge Flow Monitor

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 3D

Min: -300.00

Val: 3.50 Pa

TID:AC

Max: 4000.00



Purge Flow Monitor

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 3D

Min: -3150.00

Val: -306.75 Pa

TID:B1

Max: 4000.00



Oxygen Sensor Heater Monitor Bank 1 - Sensor 1

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 41

Min: 720.0

Val: 779.7 °C

TID:C1

Max: 6513.5



Oxygen Sensor Heater Monitor Bank 1 - Sensor 2

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 42

Min: 0.000

Val: 0.158 kOhm

TID:C4

Max: 17.292



Oxygen Sensor Heater Monitor Bank 2 - Sensor 1

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 45	Min: 720.0	Val: 780.6 °C
TID:C1	Max: 6513.5	

**Oxygen Sensor Heater Monitor Bank 2 - Sensor 2**

Manufacturer Defined Test ID range — This parameter is an identifier for the test performed within the On-Board Diagnostic Monitor.

Status: Complete and Pass

MID: 46	Min: 0.000	Val: 0.160 kOhm
TID:C4	Max: 17.864	

**Mis-Fire Cylinder 1 Data**

EWMA (Exponential Weighted Moving Average) misfire counts for last ten (10) driving cycles (calculated, rounded to an integer value)

Status: Complete and Pass

MID: A2	Min: 0	Val: 0 counts
TID:0B	Max: 65535	

**Mis-Fire Cylinder 1 Data**

Misfire counts for last/current driving cycles (calculated, rounded to an integer value)

Status: Complete and Pass

MID: A2	Min: 0	Val: 0 counts
TID:0C	Max: 65535	

**Mis-Fire Cylinder 2 Data**

EWMA (Exponential Weighted Moving Average) misfire counts for last ten (10) driving cycles (calculated, rounded to an integer value)

Status: Complete and Pass

MID: A3	Min: 0	Val: 0 counts
TID:0B	Max: 65535	

**Mis-Fire Cylinder 2 Data**

Misfire counts for last/current driving cycles (calculated, rounded to an integer value)

Status: Complete and Pass

MID: A3	Min: 0	Val: 0 counts
TID:0C	Max: 65535	



Mis-Fire Cylinder 3 Data

EWMA (Exponential Weighted Moving Average) misfire counts for last ten (10) driving cycles (calculated, rounded to an integer value)

Status: Complete and Pass

MID: A4 Min: 0 Val: 0 counts

TID:0B Max: 65535



Mis-Fire Cylinder 3 Data

Misfire counts for last/current driving cycles (calculated, rounded to an integer value)

Status: Complete and Pass

MID: A4 Min: 0 Val: 0 counts

TID:0C Max: 65535



Mis-Fire Cylinder 4 Data

EWMA (Exponential Weighted Moving Average) misfire counts for last ten (10) driving cycles (calculated, rounded to an integer value)

Status: Complete and Pass

MID: A5 Min: 0 Val: 0 counts

TID:0B Max: 65535



Mis-Fire Cylinder 4 Data

Misfire counts for last/current driving cycles (calculated, rounded to an integer value)

Status: Complete and Pass

MID: A5 Min: 0 Val: 0 counts

TID:0C Max: 65535



Mis-Fire Cylinder 5 Data

EWMA (Exponential Weighted Moving Average) misfire counts for last ten (10) driving cycles (calculated, rounded to an integer value)

Status: Complete and Pass

MID: A6 Min: 0 Val: 0 counts

TID:0B Max: 65535



Mis-Fire Cylinder 5 Data

Misfire counts for last/current driving cycles (calculated, rounded to an integer value)

Status: Complete and Pass

MID: A6 Min: 0 Val: 0 counts
TID:0C Max: 65535



Mis-Fire Cylinder 6 Data

EWMA (Exponential Weighted Moving Average) misfire counts for last ten (10) driving cycles (calculated, rounded to an integer value)

Status: Complete and Pass

MID: A7 Min: 0 Val: 0 counts
TID:0B Max: 65535



Mis-Fire Cylinder 6 Data

Misfire counts for last/current driving cycles (calculated, rounded to an integer value)

Status: Complete and Pass

MID: A7 Min: 0 Val: 0 counts
TID:0C Max: 65535

Disclaimer: This information is provided without warranty and is subject to the Terms of Use posted at www.bluedriver.com/eula.html. Reproduction of this information or any portion thereof constitutes infringement of copyright.