



P82.60-4772-09

Shown on model 164.1, with USA version, code 494

- 1 Radio
- 2 Instrument panel center section
- 3 Bolts
- 4 Electrical connector
- 5 Antenna cable connectors
- 6 Latch

	Remove/install		
	Information on preventing damage to electronic components due to electrostatic discharge		AH54.00-P-0001-01A
AD	1 Read out coding of radio (1) Connect STAR DIAGNOSIS and read out fault memory	ⓘ Only when replacing radio and if it can still be read out using STAR DIAGNOSIS. STAR DIAGNOSIS diagnosis system	AD00.00-P-2000-04A
2	Switch off ignition and remove transmitter key from EIS control unit	ⓘ On vehicles with code (889) Keyless-Go: Press Keyless-Go start/stop button repeatedly until ignition is switched off. Remove transmitter key from vehicle and store it in a location beyond its transmission range (at least 2 m).	
3	Disengage dashboard center part (2) at bottom edge (arrows A) and pull forward out of dashboard use plastic pry tool	ⓘ Protect trim parts of the instrument panel and center console from scratches.	
4	Remove bolts (3) and slide latches (6) on both sides downwards (arrow B)		
5	Pull radio (1) out of installation opening and detach electrical connector (4) along with antenna cable connectors (5)	ⓘ Protect dashboard, center console trim parts and the radio from scratches.	
AD	6 Install in the reverse order Code radio (1) Connect STAR DIAGNOSIS and read out fault memory	ⓘ Only after installing a new radio. STAR DIAGNOSIS diagnosis system	AD00.00-P-2000-04A