

Model 164

- 1 Front beverage holder
 2 Rubber cover
 3 Nuts
 4 Electrical connectors
 N2/7 Restraint systems control unit



P91.60-2921-11

Warning	Risk of injury during testing and repair operations related to pyrotechnical components	Do not expose pyrotechnical component parts to temperatures above 100 °C or 212 °F. Disconnect current supply when working on such component parts.	AS91.00-Z-0008-01A
	Notes on self-locking nuts and bolts		AH00.00-N-0001-01A
	Information on preventing damage to electronic components due to electrostatic discharge		AH54.00-P-0001-01A
	Information, assessment and legal requirements when working with, handling and storing pyrotechnical components		AH91.00-Z-0000-10A
	Remove/install		
1	Switch on ignition and store transmitter key outside of transmission range (min. 2 m)		
2	Disconnect battery ground line		AR54.10-P-0003GZ
3	Remove front beverage holder (1)		AR68.20-P-2240GZ
4	Lift rubber cover (2) and swivel out of working area		
5	Unscrew nuts (3)	Model 164.1/8Nut, control unit to center console	*BA91.60-P-1002-01H
6	Lift restraint systems control unit (N2/7)	Installation: Ensure that the ground line on the restraint systems control unit (N2/7) (below corner on front right) is fastened properly. Correct operation of the restraint systems control unit (N2/7) is not guaranteed otherwise.	
7	Release and disconnect electrical connections (4)		
8	Remove restraint systems control unit (N2/7)		
9	Install in the reverse order		
	Check		
10	Perform SCN coding of restraint systems control unit (N2/7)	When replacing the restraint systems control unit (N2/7).	AR54.21-P-0015X
11	Perform initial startup of restraint systems control unit (N2/7)	When replacing the restraint systems control unit (N2/7).	
12	Check and erase vehicle fault memory using the diagnostic system	When replacing the restraint systems control unit (N2/7).	AD00.00-P-2000-04A

Airbag

Number	Designation	Model 164.1/8
--------	-------------	---------------

BA91.60-P-1002-01H	Nut, control unit to center console	Nm	10
--------------------	-------------------------------------	----	----