



Mercedes-Benz

AP00.20-U-1208FFJ	SERVICE SHEET for Mercedes-Benz Maintenance System (USA)
-------------------	--

Model Year 2018
USA



Model 253

Customer: _____

Repair order number: _____

Tire Rotation
(non-staggered width wheel setup only)

A 5,000-mile recommended tire rotation interval will likely necessitate tire rotation at least once in between each 10,000-mile maintenance service and at every 10,000-mile maintenance service.

Tires rotated YES NO

Note: For any condition found while performing the checks or inspections included in this maintenance sheet, determine the cause and perform the repair using a separate repair order.

Current mileage reading: _____

Oil grade/viscosity: _____

Additional notes: _____

Service work to be performed as advised by service advisor:

Completion date:

Confirm work has been performed by signing below:

Required Service Work <input checked="" type="checkbox"/> Performed (check if performed)	miles (thousands) years	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK ↓	
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15			
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP00.20-P-0043E
<input type="checkbox"/> Replace activated charcoal combination filter <input type="checkbox"/> behind glovebox				•		•		•		•		•		•		•		•	AP83.00-P-8384B
<input type="checkbox"/> Replace dust filter <input type="checkbox"/> behind plastic cowl in engine compartment				•		•		•		•		•		•		•		•	AP83.00-P-8381C
<input type="checkbox"/> Perform brake test				•		•		•		•		•		•		•		•	<input type="checkbox"/> AP42.00-P-4290BA
<input type="checkbox"/> Engine – oil and filter change engine 177 engine 274 with CODE M005 (4MATIC) engine 274 except CODE M005 (4MATIC) engine 276			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101D AP18.00-P-0101CWE AP18.00-P-0101CWI AP18.00-P-0101CWZ
<input type="checkbox"/> Check condition of poly-V-belt except model 253.954 (Hybrid) engine 274, 276 engine 177				•		•		•		•		•		•		•		•	<input type="checkbox"/> AP13.22-P-1352EW <input type="checkbox"/> AP13.22-P-1352D
<input type="checkbox"/> Check condition and function of trailer hitch with CODE 550 (trailer hitch)				•		•		•		•		•		•		•		•	<input type="checkbox"/> AP31.11-P-3152A
<input type="checkbox"/> Check thickness of brake pads front and rear			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4252D
<input type="checkbox"/> Check and correct all tire air pressures, including spare where applicable			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP40.15-P-4061A
<input type="checkbox"/> Check charging cable and vehicle socket for mechanical damage model 253.954 (Hybrid)			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP54.10-P-5458B
<input type="checkbox"/> Leakage- major components-check underbody and engine compartment for chafe marks, line routing, damaged components underbody engine compartment				•		•		•		•		•		•		•		•	<input type="checkbox"/> AP00.20-P-0054G <input type="checkbox"/> AP00.20-P-0055E
<input type="checkbox"/> Inspect front axle and front axle ball joints				•		•		•		•		•		•		•		•	<input type="checkbox"/> AP33.10-P-3358A
<input type="checkbox"/> Inspect rear axle and rear axle ball joints				•		•		•		•		•		•		•		•	<input type="checkbox"/> AP35.20-P-3552A
<input type="checkbox"/> Inspect suspension struts or shock absorbers and springs				•		•		•		•		•		•		•		•	<input type="checkbox"/> AP32.25-P-3255E
<input type="checkbox"/> Inspect steering and tie rods				•		•		•		•		•		•		•		•	<input type="checkbox"/> AP46.00-P-4651A
<input type="checkbox"/> Inspect driveshaft flexible discs			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP41.10-P-4152EW
<input type="checkbox"/> Check high-voltage battery circuit coolant level model 253.954 (Hybrid)				•		•		•		•		•		•		•		•	<input type="checkbox"/> AP20.30-P-2053A
<input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Clean visible area of water deflector			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Active Body Control - check fluid level, correct if necessary			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Check coolant level and correct if necessary <input type="checkbox"/> refer to AH20.00-P-1142-01CW <input type="checkbox"/> observe correct coolant composition			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Check windshield washer system fluid, correct if necessary			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP82.35-P-8210C
<input type="checkbox"/> Check brake fluid level and correct if necessary			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4210B
<input type="checkbox"/> Replace brake fluid				•		•		•		•		•		•		•		•	AP42.00-P-4280C
<input type="checkbox"/> Check first aid kit			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP68.00-P-6850EW
<input type="checkbox"/> Check starter. Use MB diagnosis tool. Model 253.954 (Hybrid) only			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP15.30-P-1550AA

Required Service Work <input checked="" type="checkbox"/> Performed (check if performed)	miles (thousands) years	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster <input checked="" type="checkbox"/> reminder - if not yet performed			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP00.20-P-0043E
Required Additional Work <input checked="" type="checkbox"/> Performed (check if performed)	miles (thousands) years	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓
<input type="checkbox"/> Rear Axle differential fluid replacement with CODE 467 (electronic locking differential) with CODE 471 (mechanical locking differential) with CODE P30 (AMG performance package)		•			•			•			•			•			•	
<input type="checkbox"/> Replace air filter engine 177					•			•			•			•			•	AP09.10-P-0980K
<input type="checkbox"/> Replace air filter engine 274, 276 engine 274 engine 276							•					•					•	AP09.10-P-0980CWG AP09.10-P-0980E
<input type="checkbox"/> Replace spark plugs engine 177 engine 274 engine 276							•					•					•	AP15.10-P-1580C AP15.10-P-1580CWF AP15.10-P-1580D
<input type="checkbox"/> Automatic transmission - oil and filter change engine 177 (AMG models)				•			•				•			•			•	AP27.00-P-2702B
<input type="checkbox"/> Automatic transmission - oil and filter change engine 274, 276 transmission 725.0 transmission 742.2 (hybrid)							•							•			•	AP27.00-P-2702B AP27.00-P-2702A
<input type="checkbox"/> Replace fuel filter														•				AP47.20-P-0780E
<input type="checkbox"/> Replace coolant <input checked="" type="checkbox"/> observe correct coolant composition main circuit low-temperature circuit - engine 177 low-temperature circuit - engine 274 low-temperature circuit - engine 276														•			•	AP20.00-P-2082E AP20.00-P-2083C AP20.00-P-2083E AP20.00-P-2083I
Recommended Service Work <input checked="" type="checkbox"/> Performed (check if performed)	miles (thousands) years	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓
<input type="checkbox"/> Check horn			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Check warning/indicator lamps			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP54.30-P-5451HA
<input type="checkbox"/> Check illumination and interior lighting			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP54.30-P-5453CAA
<input type="checkbox"/> Check all exterior lights			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP82.10-P-8252EW
<input type="checkbox"/> Check trunk / cargo area light			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Check operation of headlamp range adjustment				•		•		•		•		•		•		•		<input type="checkbox"/> AP82.10-P-8250EW
<input type="checkbox"/> Check headlight setting, correct if necessary				•		•		•		•		•		•		•		AP82.10-P-8260E
<input type="checkbox"/> Check battery condition. Attach printout to sheet			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Check seatbelts and buckles for proper operation or damage				•		•		•		•		•		•		•		<input type="checkbox"/>
<input type="checkbox"/> Check windshield wiper, washer and headlamp washer system operation			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP82.35-P-8252C
<input type="checkbox"/> Replace wiper blades			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	

Recommended Service Work <input checked="" type="checkbox"/> Performed (check if performed)	miles (thousands) years	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK ↓
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15		
<input type="checkbox"/> Clean and lubricate Panoramic guide mechanism with CODE 413 (panoramic sliding sunroof)				•		•		•		•		•		•		•		AP77.20-P-7732A
<input type="checkbox"/> Check for body paint damage				•		•		•		•		•		•		•		<input type="checkbox"/> AP60.00-P-0050F
<input type="checkbox"/> Tire rotation (where applicable)			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
<input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed pads discs			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4252D <input type="checkbox"/> AP42.10-P-4256EW
<input type="checkbox"/> Visually inspect brake system components			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Inspect tires for damage and measure remaining tread life			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP40.10-P-4051EW
<input type="checkbox"/> Check TIREFIT tire sealant expiration date (where applicable)			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP40.10-P-4054R
<input type="checkbox"/> Activate Tire Pressure Monitoring System <input checked="" type="checkbox"/> refer to vehicle Operator's Manual			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
<input type="checkbox"/> Check chassis and load bearing body components for damage and corrosion				•		•		•		•		•		•		•		<input type="checkbox"/>
<input type="checkbox"/> Check ex-factory driving aids (where applicable)			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP86.20-P-8649U
<input type="checkbox"/> Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) <input checked="" type="checkbox"/> After consultation with customer			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	

High Mileage Required Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years																		
<input checked="" type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet																		
<input checked="" type="checkbox"/> Performed (check if performed)																		Not OK ↓
	<input type="checkbox"/> Reset maintenance service indicator in instrument cluster																	
<input type="checkbox"/> Replace activated charcoal combination filter <input checked="" type="checkbox"/> behind glovebox																		AP83.00-P-8384B
<input type="checkbox"/> Replace dust filter <input checked="" type="checkbox"/> behind plastic cowl in engine compartment																		AP83.00-P-8381C
<input type="checkbox"/> Perform brake test																		<input type="checkbox"/> AP42.00-P-4290BA
<input type="checkbox"/> Engine – oil and filter change engine 177 engine 274 with CODE M005 (4MATIC) engine 274 except CODE M005 (4MATIC) engine 276																		AP18.00-P-0101D AP18.00-P-0101CWE AP18.00-P-0101CWI AP18.00-P-0101CWZ
<input type="checkbox"/> Check condition of poly-V-belt except model 253.954 (Hybrid) engine 274, 276 engine 177																		<input type="checkbox"/> AP13.22-P-1352EW <input type="checkbox"/> AP13.22-P-1352D
<input type="checkbox"/> Check condition and function of trailer hitch with CODE 550 (trailer hitch)																		<input type="checkbox"/> AP31.11-P-3152A
<input type="checkbox"/> Check thickness of brake pads front and rear																		<input type="checkbox"/> AP42.10-P-4252D
<input type="checkbox"/> Check and correct all tire air pressures, including spare where applicable																		AP40.15-P-4061A
<input type="checkbox"/> Check charging cable and vehicle socket for mechanical damage model 253.954 (Hybrid)																		<input type="checkbox"/> AP54.10-P-5458B
<input type="checkbox"/> Leakage- major components-check underbody and engine compartment for chafe marks, line routing, damaged components																		

underbody	<input type="checkbox"/>	AP00.20-P-0054G
engine compartment	<input type="checkbox"/>	AP00.20-P-0055E
<input type="checkbox"/> Inspect front axle and front axle ball joints	<input type="checkbox"/>	AP33.10-P-3358A
<input type="checkbox"/> Inspect rear axle and rear axle ball joints	<input type="checkbox"/>	AP35.20-P-3552A
<input type="checkbox"/> Inspect suspension struts or shock absorbers and springs	<input type="checkbox"/>	AP32.25-P-3255E
<input type="checkbox"/> Inspect steering and tie rods	<input type="checkbox"/>	AP46.00-P-4651A
<input type="checkbox"/> Inspect driveshaft flexible discs	<input type="checkbox"/>	AP41.10-P-4152EW
<input type="checkbox"/> Check high-voltage battery circuit coolant level model 253.954 (Hybrid)	<input type="checkbox"/>	AP20.30-P-2053A
<input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation	<input type="checkbox"/>	
<input type="checkbox"/> Clean visible area of water deflector		
<input type="checkbox"/> Active Body Control - check fluid level, correct if necessary	<input type="checkbox"/>	
<input type="checkbox"/> Check coolant level and correct if necessary <input type="checkbox"/> refer to AH20.00-P-1142-01CW <input type="checkbox"/> observe correct coolant composition	<input type="checkbox"/>	
<input type="checkbox"/> Check windshield washer system fluid, correct if necessary	<input type="checkbox"/>	AP82.35-P-8210C
<input type="checkbox"/> Check brake fluid level and correct if necessary	<input type="checkbox"/>	AP42.10-P-4210B
<input type="checkbox"/> Replace brake fluid		AP42.00-P-4280C
<input type="checkbox"/> Check first aid kit	<input type="checkbox"/>	AP68.00-P-6850EW
<input type="checkbox"/> Check starter. Use MB diagnosis tool. Model 253.954 (Hybrid) only	<input type="checkbox"/>	AP15.30-P-1550AA
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster <input type="checkbox"/> reminder - if not yet performed		AP00.20-P-0043E
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years		
<input type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet		
<input checked="" type="checkbox"/> Performed (check if performed)		Not OK
		↓
<input type="checkbox"/> Check horn	<input type="checkbox"/>	
<input type="checkbox"/> Check warning/indicator lamps	<input type="checkbox"/>	AP54.30-P-5451HA
<input type="checkbox"/> Check illumination and interior lighting	<input type="checkbox"/>	AP54.30-P-5453CAA
<input type="checkbox"/> Check all exterior lights	<input type="checkbox"/>	AP82.10-P-8252EW
<input type="checkbox"/> Check trunk / cargo area light	<input type="checkbox"/>	
<input type="checkbox"/> Check operation of headlamp range adjustment	<input type="checkbox"/>	AP82.10-P-8250EW
<input type="checkbox"/> Check headlight setting, correct if necessary		AP82.10-P-8260E
<input type="checkbox"/> Check battery condition. Attach printout to sheet	<input type="checkbox"/>	
<input type="checkbox"/> Check seatbelts and buckles for proper operation or damage	<input type="checkbox"/>	
<input type="checkbox"/> Check windshield wiper, washer and headlamp washer system operation	<input type="checkbox"/>	AP82.35-P-8252C
<input type="checkbox"/> Replace wiper blades		
<input type="checkbox"/> Clean and lubricate Panoramic guide mechanism with CODE 413 (panoramic sliding sunroof)		AP77.20-P-7732A
<input type="checkbox"/> Check for body paint damage	<input type="checkbox"/>	AP60.00-P-0050F
<input type="checkbox"/> Tire rotation (where applicable)		
<input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed pads	<input type="checkbox"/>	AP42.10-P-4252D
discs	<input type="checkbox"/>	AP42.10-P-4256EW
<input type="checkbox"/> Visually inspect brake system components	<input type="checkbox"/>	
<input type="checkbox"/> Inspect tires for damage and measure remaining tread life	<input type="checkbox"/>	AP40.10-P-4051EW
<input type="checkbox"/> Check TIREFIT tire sealant expiration date (where applicable)	<input type="checkbox"/>	AP40.10-P-4054R

<input type="checkbox"/> Activate Tire Pressure Monitoring System <input type="checkbox"/> refer to vehicle Operator's Manual	
<input type="checkbox"/> Check chassis and load bearing body components for damage and corrosion	<input type="checkbox"/>
<input type="checkbox"/> Check ex-factory driving aids (where applicable)	<input type="checkbox"/> AP86.20-P-8649U
<input type="checkbox"/> Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) <input type="checkbox"/> After consultation with customer	
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years	
<input type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet	
<input checked="" type="checkbox"/> Performed (check if performed)	Not OK ↓
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster	AP00.20-P-0043E
<input type="checkbox"/> Engine – oil and filter change engine 177 engine 274 with CODE M005 (4MATIC) engine 274 except CODE M005 (4MATIC) engine 276	AP18.00-P-0101D AP18.00-P-0101CWE AP18.00-P-0101CWI AP18.00-P-0101CWZ
<input type="checkbox"/> Check thickness of brake pads front and rear	<input type="checkbox"/> AP42.10-P-4252D
<input type="checkbox"/> Check and correct all tire air pressures, including spare where applicable	AP40.15-P-4061A
<input type="checkbox"/> Check charging cable and vehicle socket for mechanical damage model 253.954 (Hybrid)	<input type="checkbox"/> AP54.10-P-5458B
<input type="checkbox"/> Inspect driveshaft flexible discs	<input type="checkbox"/> AP41.10-P-4152EW
<input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation	<input type="checkbox"/>
<input type="checkbox"/> Clean visible area of water deflector	
<input type="checkbox"/> Active Body Control - check fluid level, correct if necessary	<input type="checkbox"/>
<input type="checkbox"/> Check coolant level and correct if necessary <input type="checkbox"/> refer to AH20.00-P-1142-01CW <input type="checkbox"/> observe correct coolant composition	<input type="checkbox"/>
<input type="checkbox"/> Check windshield washer system fluid, correct if necessary	<input type="checkbox"/> AP82.35-P-8210C
<input type="checkbox"/> Check brake fluid level and correct if necessary	<input type="checkbox"/> AP42.10-P-4210B
<input type="checkbox"/> Check first aid kit	<input type="checkbox"/> AP68.00-P-6850EW
<input type="checkbox"/> Check starter. Use MB diagnosis tool. Model 253.954 (Hybrid) only	<input type="checkbox"/> AP15.30-P-1550AA
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster <input type="checkbox"/> reminder - if not yet performed	AP00.20-P-0043E
High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years	
<input type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet	
<input checked="" type="checkbox"/> Performed (check if performed)	Not OK ↓
<input type="checkbox"/> Check horn	<input type="checkbox"/>
<input type="checkbox"/> Check warning/indicator lamps	<input type="checkbox"/> AP54.30-P-5451HA
<input type="checkbox"/> Check illumination and interior lighting	<input type="checkbox"/> AP54.30-P-5453CAA
<input type="checkbox"/> Check all exterior lights	<input type="checkbox"/> AP82.10-P-8252EW
<input type="checkbox"/> Check trunk / cargo area light	<input type="checkbox"/>
<input type="checkbox"/> Check battery condition. Attach printout to sheet	<input type="checkbox"/>
<input type="checkbox"/> Check windshield wiper, washer and headlamp washer system operation	<input type="checkbox"/> AP82.35-P-8252C
<input type="checkbox"/> Replace wiper blades	
<input type="checkbox"/> Tire rotation (where applicable)	
<input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed	

pads	<input type="checkbox"/>	AP42.10-P-4252D
discs	<input type="checkbox"/>	AP42.10-P-4256EW
<input type="checkbox"/> Visually inspect brake system components	<input type="checkbox"/>	
<input type="checkbox"/> Inspect tires for damage and measure remaining tread life	<input type="checkbox"/>	AP40.10-P-4051EW
<input type="checkbox"/> Check TIREFIT tire sealant expiration date (where applicable)	<input type="checkbox"/>	AP40.10-P-4054R
<input type="checkbox"/> Activate Tire Pressure Monitoring System <input type="checkbox"/> refer to vehicle Operator's Manual		
<input type="checkbox"/> Check ex-factory driving aids (where applicable)	<input type="checkbox"/>	AP86.20-P-8649U
<input type="checkbox"/> Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) <input type="checkbox"/> After consultation with customer		
High Mileage Additional Work		
<input checked="" type="checkbox"/> Performed (check if performed)		
<input type="checkbox"/> Rear Axle differential fluid replacement with CODE 467 (electronic locking differential) with CODE 471 (mechanical locking differential) with CODE P30 (AMG performance package)	At 2,000 miles, then if more than 30,000 miles or 3 years since last replacement	
<input type="checkbox"/> Replace air filter engine 177	If more than 30,000 miles or 3 years since last replacement	AP09.10-P-0980K
<input type="checkbox"/> Replace air filter engine 274, 276		
engine 274	If more than 50,000 miles or 5 years since last replacement	AP09.10-P-0980CWG
engine 276	If more than 50,000 miles or 5 years since last replacement	AP09.10-P-0980E
<input type="checkbox"/> Replace spark plugs		
engine 177	If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580C
engine 274	If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580CWF
engine 276	If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580D
<input type="checkbox"/> Automatic transmission - oil and filter change engine 177 (AMG models)	If more than 30,000 miles or 3 years since last replacement	AP27.00-P-2702B
<input type="checkbox"/> Automatic transmission - oil and filter change engine 274, 276		
transmission 725.0	If more than 60,000 miles or 6 years since last replacement	AP27.00-P-2702B
transmission 742.2 (hybrid)	If more than 60,000 miles or 6 years since last replacement	AP27.00-P-2702A
<input type="checkbox"/> Replace fuel filter	If more than 120,000 miles or 12 years since last replacement	AP47.20-P-0780E
<input type="checkbox"/> Replace coolant <input type="checkbox"/> observe correct coolant composition		
main circuit	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2082E
low-temperature circuit - engine 177	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083C
low-temperature circuit - engine 274	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083E
low-temperature circuit - engine 276	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083I

Tire inflation pressure (bar/psi)				
LF	RF	LR	RR	Spare

Tire thread depth (mm)				
	LF	RF	LR	RR
outside				
center				
inside				