

Mercedes-Benz

AP00.20-U-1208EF

SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model Year 201 USA	8	Мо	del 117		
Customer:			Repair order nu	mber:	
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommende likely necessitate tire rotati each 10,000-mile maintena 10,000-mile maintenance s	on at least once in betweer ance service and at every	Tires rotated	YES	NO
Note: For any cathe cause and perfor	ondition found while performi m the repair using a separate	ng the checks or inspectior e repair order.	ns included in this r	naintenance shee	t, determine
Current mileage read	ding:	_ (Dil grade/viscosity:		
Additional notes:					
Service work to be p service advisor:	erformed as advised by	Completion date:	Confirm work has below:	s been performed	by signing

P-2374-117-18B (01/18) Dealer Workshop Services www.MBUSA.com www.startekinfo.com

Mercedes-Benz USA, LLC Reproduction or translation in whole or in part is not permitted without written authorization from the publisher. 1-800-FOR-MERCedes

Required Service Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK	
Reset maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0043EL
□ Repalce combination filter			•		•		•		•		•		•		•			AP83.00-P-8384NK
Perform brake test	1	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.00-P-4290BA
Engine – oil and filter change																		
engine 133		٠	•	•	•	•	•	•	•	•	•	•	٠	•	٠	•		AP18.00-P-0101AHH
engine 270		•	•	٠	٠	٠	•	٠	•	•	٠	•	•	•	•	•		AP18.00-P-0101NL
\Box Check thickness of brake pads, front and rear		•	•	•	•	•	•	•	•	•	٠	•	٠	•	•	•		AP42.10-P-4252AH
□ Check vehicle underside for damage and leakage			•		•		•		•		•		•		•			AP00.20-P-0054B
□ Visually inspect condition of steering mechanical components, rubber boots			•		•		•		•		•		•		•			AP46.00-P-4653AK
□ Visually inspect condition of front axle ball joints, rubber boots			•		•		•		•		•		•		•			AP33.20-P-3353AK
Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.15-P-4061A
Replace air filter engine 133		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP09.10-P-0980AHH
Check condition of poly-V-belt			•		•		•		•		•		•		•			AP13.22-P-1352CW
Check all visible parts in engine compartment for damage and leaks			•		•		•		•		•		•		•			AP00.20-P-0055AK
Check catch, safety catch and hinges on engine hood for proper operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Coolant - check fluid level and correct if necessary refer to AH20.00-P-1142-01CW observe correct coolant composition		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Windshield washer system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210AK
Brake system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4210AK
Replace brake fluid			•		•		•		•		•		•		•			AP42.00-P-4280AK
☐ Oil change in rear axle model 117.352		•		•		•		•		•		•		•		•		AP35.00-P-3501A
□Check first aid kit		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP68.00-P-6850EW
Reset maintenance service indicator in instrument cluster In reminder - if not yet performed		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0043EL
Required Additional Workmiles (thousands)Image: Second systemyears(check if performed)years	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK	
Automatic transmission – oil and filter change engine 133 with transmission 724.0				•			•			•			•			•		AP27.00-P-2702NK
Automatic transmission – oil and filter change engine 270 with transmission 724.0							•						•					AP27.00-P-2702NK
Replace air filter engine 270						•					•					•		AP09.10-P-0980NKC
Replace spark plugs engine 133						-					-							AP15.10-P-1580AHH
engine 270																		AP15.10-P-1580NK
Replace fuel filter	-	-			-	-					-		•			-		AP47.20-P-0780NK

Required Additional Work miles (thousands) Performed years (check if performed) years	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK	
Replace coolant observe correct coolant composition													•					AP20.00-P-2080CW
Recommended Service miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Work years Performed years (check if performed) (check if performed)		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK	
		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Check warning/indicator lamps		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451AK
Check illumination and interior lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5453AK
Check windshield wiper, washer and headlamp washer system operation)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.30-P-8252AK
Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable) CODE 413 (Panoramic glass roof with top sliding roof)	•		•		•		•		•		•		•		•			AP77.20-P-7732CW
Check seat belts and buckles for damage and proper function			•		•		•		•		•		•		•			
Check all exterior lights		•	•	•	•	•	•	٠	•	٠	•	٠	٠	٠	٠	•		AP82.10-P-8252EW
Check trunk/cargo compartment lighting		•	•	٠	•	٠	•	٠	•	٠	٠	•	•	٠	٠	•		
Check TIREFIT sealant expiration date (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4054R
Check battery condition. Attach printout to sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-U-5453A
Check operation of headlamp range adjustment			•		•		•		•		•		•		•			AP82.10-P-8250EW
Chek heaplamp settings, correct if necessary			٠		•		•		•	_	٠		٠		٠			AP82.10-P-8260GI
Replace wiper blades		•	•	•	•	•	•	٠	•	•	٠	•	•	•	٠	•		
Check for body paint damage			•		•		•		•	_	٠		•		٠			AP60.00-P-0050NK
Tire rotation (where applicable)		•	•	•	•	•	•	٠	•	•	٠	•	•	٠	٠	•		
Check thickness of brake pads and discs, from and rear wheels removed	:	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4252AH
□ Trailer hitch: check condition and function with CODE 550 (Trailer hitch)			•		•		•		•		•		•		•			AP31.11-P-3152CW
Usually inspect brake system components, lines, hoses, calipers		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
□ Inspect tires for damage, measure thread depth and enter table at the end of the service shee		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051EW
Check chassis and load-bearing body components for damage and corrosion			•		•		•		•	_	•		•		•			
Activate Tire Pressure Monitoring System		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) After consultation with customer		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
High Mileage Required Service Work at ²	160,	000) mi	les	or	16 y	/ea	rs;	the	n ev	/ery	20,0	000 1	nile	s or	2 ye	ars	
 Plus any applicable additional work li Performed (check if performed) 	iste	d at	t th	e er	nd o	of th	ne s	erv	ice	she	et						Not OK ↓	
Reset maintenance service indicator in in	nstr	ume	ent o	clus	ter													AP00.20-P-0043EL
Repaice combination filter	.50																	AP83.00-P-8384NK

Engine – oil and filter change		
engine 133		AP18.00-P-0101AHH
engine 270		AP18.00-P-0101NL AP42.10-P-4252AH
Check thickness of brake pads, front and rear		
Check vehicle underside for damage and leakage		AP00.20-P-0054B
□ Visually inspect condition of steering mechanical components, rubber boots		AP46.00-P-4653AK
□ Visually inspect condition of front axle ball joints, rubber boots		AP33.20-P-3353AK
Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet		AP40.15-P-4061A
Replace air filter engine 133		AP09.10-P-0980AHH
Check condition of poly-V-belt		AP13.22-P-1352CW
Check all visible parts in engine compartment for damage and leaks		AP00.20-P-0055AK
Check catch, safety catch and hinges on engine hood for proper operation		
Coolant - check fluid level and correct if necessary refer to AH20.00-P-1142-01CW observe correct coolant composition		
□ Windshield washer system - check fluid level and correct if necessary		AP82.35-P-8210AK
Brake system - check fluid level and correct if necessary		AP42.10-P-4210AK
Replace brake fluid		AP42.00-P-4280AK
Check first aid kit		AP68.00-P-6850EW
Reset maintenance service indicator in instrument cluster		AP00.20-P-0043EL
i reminder - if not yet performed		
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles	or 2 yea	ars
I Plus any applicable additional work listed at the end of the service sheet	-	
Plus any applicable additional work listed at the end of the service sheet Performed	Not Of	
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed)	-	
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn	Not Of	(
I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps	Not Of	K AP54.30-P-5451AK
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting	Not Of	AP54.30-P-5451AK AP54.30-P-5453AK
I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check windshield wiper, washer and headlamp washer system operation	Not Or	 AP54.30-P-5451AK AP54.30-P-5453AK AP82.30-P-8252AK
I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check windshield wiper, washer and headlamp washer system operation Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable)	Not Of	AP54.30-P-5451AK AP54.30-P-5453AK
I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check windshield wiper, washer and headlamp washer system operation Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable) CODE 413 (Panoramic glass roof with top sliding roof)	Not Of	 AP54.30-P-5451AK AP54.30-P-5453AK AP82.30-P-8252AK
I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check windshield wiper, washer and headlamp washer system operation Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable) CODE 413 (Panoramic glass roof with top sliding roof) Check seat belts and buckles for damage and proper function	Not OF	 AP54.30-P-5451AK AP54.30-P-5453AK AP82.30-P-8252AK
I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check windshield wiper, washer and headlamp washer system operation Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable) CODE 413 (Panoramic glass roof with top sliding roof) Check all exterior lights	Not Of	AP54.30-P-5451AK AP54.30-P-5453AK AP82.30-P-8252AK AP77.20-P-7732CW
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check windshield wiper, washer and headlamp washer system operation Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable) CODE 413 (Panoramic glass roof with top sliding roof) Check seat belts and buckles for damage and proper function Check all exterior lights Check trunk/cargo compartment lighting	Not OF	AP54.30-P-5451AK AP54.30-P-5453AK AP82.30-P-8252AK AP77.20-P-7732CW
I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check windshield wiper, washer and headlamp washer system operation Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable) CODE 413 (Panoramic glass roof with top sliding roof) Check all exterior lights Check trunk/cargo compartment lighting Check TIREFIT sealant expiration date (where applicable)	Not OP	AP54.30-P-5451AK AP54.30-P-5453AK AP82.30-P-8252AK AP77.20-P-7732CW AP82.10-P-8252EW
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check windshield wiper, washer and headlamp washer system operation Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable) CODE 413 (Panoramic glass roof with top sliding roof) Check all exterior lights Check all exterior lights Check trunk/cargo compartment lighting Check TIREFIT sealant expiration date (where applicable) Check battery condition. Attach printout to sheet	Not OF	AP54.30-P-5451AK AP54.30-P-5451AK AP54.30-P-5453AK AP82.30-P-8252AK AP77.20-P-7732CW AP82.10-P-8252EW AP82.10-P-8252EW AP40.10-P-4054R
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check windshield wiper, washer and headlamp washer system operation Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable) CODE 413 (Panoramic glass roof with top sliding roof) Check seat belts and buckles for damage and proper function Check all exterior lights Check trunk/cargo compartment lighting Check TIREFIT sealant expiration date (where applicable) Check battery condition. Attach printout to sheet	Not OP	AP54.30-P-5451AK AP54.30-P-5451AK AP54.30-P-5453AK AP82.30-P-8252AK AP77.20-P-7732CW AP82.10-P-8252EW AP82.10-P-8252EW AP40.10-P-4054R AP54.10-U-5453A
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check windshield wiper, washer and headlamp washer system operation Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable) CODE 413 (Panoramic glass roof with top sliding roof) Check seat belts and buckles for damage and proper function Check all exterior lights Check TIREFIT sealant expiration date (where applicable) Check battery condition. Attach printout to sheet Check operation of headlamp range adjustment Check heaplamp settings, correct if necessary	Not OF	 AP54.30-P-5451AK AP54.30-P-5453AK AP54.30-P-5453AK AP82.30-P-8252AK AP77.20-P-7732CW AP77.20-P-7732CW AP82.10-P-8252EW AP40.10-P-4054R AP54.10-U-5453A AP82.10-P-8250EW
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check windshield wiper, washer and headlamp washer system operation Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable) CODE 413 (Panoramic glass roof with top sliding roof) Check seat belts and buckles for damage and proper function Check all exterior lights Check trunk/cargo compartment lighting Check TIREFIT sealant expiration date (where applicable) Check battery condition. Attach printout to sheet Check operation of headlamp range adjustment Check heaplamp settings, correct if necessary Replace wiper blades	Not OF	 AP54.30-P-5451AK AP54.30-P-5453AK AP54.30-P-5453AK AP82.30-P-8252AK AP77.20-P-7732CW AP77.20-P-7732CW AP82.10-P-8252EW AP40.10-P-4054R AP54.10-U-5453A AP82.10-P-8250EW
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check windshield wiper, washer and headlamp washer system operation Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable) CODE 413 (Panoramic glass roof with top sliding roof) Check seat belts and buckles for damage and proper function Check all exterior lights Check trunk/cargo compartment lighting Check trunk/cargo compartment lighting Check battery condition. Attach printout to sheet Check operation of headlamp range adjustment Check heaplamp settings, correct if necessary Replace wiper blades Check for body paint damage	Not OF	 AP54.30-P-5451AK AP54.30-P-5453AK AP54.30-P-5453AK AP82.30-P-8252AK AP77.20-P-7732CW AP77.20-P-7732CW AP82.10-P-8252EW AP40.10-P-4054R AP54.10-U-5453A AP82.10-P-8250EW AP82.10-P-8250EW AP82.10-P-8260GI
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check windshield wiper, washer and headlamp washer system operation Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable) CODE 413 (Panoramic glass roof with top sliding roof) Check seat belts and buckles for damage and proper function Check trunk/cargo compartment lighting Check trunk/cargo compartment lighting Check trunk/cargo compartment lighting Check battery condition. Attach printout to sheet Check operation of headlamp range adjustment Check for body paint damage Tire rotation (where applicable)	Not OF	 AP54.30-P-5451AK AP54.30-P-5453AK AP54.30-P-5453AK AP82.30-P-8252AK AP77.20-P-7732CW AP77.20-P-7732CW AP82.10-P-8252EW AP82.10-P-8250EW AP82.10-P-8250EW AP82.10-P-8250EW AP82.10-P-8250EW AP82.10-P-8260GI AP60.00-P-0050NK
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check hom Check hom Check warning/indicator lamps Check illumination and interior lighting Check windshield wiper, washer and headlamp washer system operation Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable) CODE 413 (Panoramic glass roof with top sliding roof) Check all exterior lights Check all exterior lights Check trunk/cargo compartment lighting Check TIREFIT sealant expiration date (where applicable) Check operation of headlamp range adjustment Check operation of headlamp range adjustment Check for body paint damage Tire rotation (where applicable) Check thickness of brake pads and discs, front and rear wheels removed	Not OF	 AP54.30-P-5451AK AP54.30-P-5453AK AP54.30-P-5453AK AP82.30-P-8252AK AP77.20-P-7732CW AP77.20-P-7732CW AP82.10-P-8252EW AP40.10-P-4054R AP54.10-U-5453A AP82.10-P-8250EW AP82.10-P-8250EW AP82.10-P-8260GI
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check windshield wiper, washer and headlamp washer system operation Check, clean and lubricate mechanism of panaroma roof with power tilt/sliding panel (where applicable) CODE 413 (Panoramic glass roof with top sliding roof) Check all exterior lights Check trunk/cargo compartment lighting Check trunk/cargo compartment lighting Check trunk/cargo compartment lighting Check trunk/cargo compartment lighting Check battery condition. Attach printout to sheet Check operation of headlamp range adjustment Check for body paint damage Thre rotation (where applicable) Check for body paint damage	Not OP	AP54.30-P-5451AK AP54.30-P-5453AK AP54.30-P-5453AK AP82.30-P-8252AK AP77.20-P-7732CW AP77.20-P-7732CW AP82.10-P-8252EW AP40.10-P-4054R AP54.10-U-5453A AP82.10-P-8250EW AP82.10-P-8260GI AP82.10-P-8260GI AP60.00-P-0050NK AP42.10-P-4252AH

□ Inspect tires for damage, measure thread depth and enter table at the end of the service shee		AP40.10-P-4051EW
Check chassis and load-bearing body components for damage and corrosion		
Activate Tire Pressure Monitoring System Fer to vehicle Operator's Manual		
Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) After consultation with customer		
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 y	/ears	
I Plus any applicable additional work listed at the end of the service sheet		_
Performed (check if performed)	Not OK	< Comparison of the second sec
	4	AP00.20-P-0043EL
Reset maintenance service indicator in instrument cluster Perform brake test		AP42.00-P-4290BA
Engine – oil and filter change		
engine 133		AP18.00-P-0101AHH
engine 270		AP18.00-P-0101NL
Check thickness of brake pads, front and rear		AP42.10-P-4252AH
Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet		AP40.15-P-4061A
Replace air filter engine 133		AP09.10-P-0980AHH
Check catch, safety catch and hinges on engine hood for proper operation		
Coolant - check fluid level and correct if necessary refer to AH20.00-P-1142-01CW		
observe correct coolant composition		
UWindshield washer system - check fluid level and correct if necessary		AP82.35-P-8210AK
Brake system - check fluid level and correct if necessary		AP42.10-P-4210AK
□ Oil change in rear axle model 117.352		AP35.00-P-3501A
Check first aid kit		AP68.00-P-6850EW
Reset maintenance service indicator in instrument cluster Ireminder - if not yet performed		AP00.20-P-0043EL
High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles	or 2 yea	ars
I Plus any applicable additional work listed at the end of the service sheet		
Performed (check if performed)	Not Ok ↓	C
Check horn		
Check warning/indicator lamps		AP54.30-P-5451AK
Check illumination and interior lighting		AP54.30-P-5453AK
Check windshield wiper, washer and headlamp washer system operation		AP82.30-P-8252AK
Check all exterior lights		AP82.10-P-8252EW
Check trunk/cargo compartment lighting		
Check TIREFIT sealant expiration date (where applicable)		AP40.10-P-4054R
Check battery condition. Attach printout to sheet		AP54.10-U-5453A
Replace wiper blades		
Tire rotation (where applicable)		
Check thickness of brake pads and discs, front and rear wheels removed		AP42.10-P-4252AH
Visually inspect brake system components, lines, hoses, calipers		
□ Inspect tires for damage, measure thread depth and enter table at the end of the service shee		AP40.10-P-4051EW

Activate Tire Pressure Monitoring System I refer to vehicle Operator's Manual										
Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) or with CODE 893 (KEYLESS-GO start function) After consultation with customer										
High Mileage Additional Work Performed (check if performed)										
Automatic transmission – oil and filter change engine 133 with transmission 724.0	If more than 30,000 miles or 3 years since last replacement	AP27.00-P-2702NK								
Automatic transmission – oil and filter change engine 270 with transmission 724.0	If more than 60,000 miles or 6 years since last replacement	AP27.00-P-2702NK								
Replace air filter engine 270	If more than 50,000 miles or 5 years since last replacement	AP09.10-P-0980NKC								
Replace spark plugs										
engine 133	If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580AHH								
engine 270	If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580NK								
Replace fuel filter	If more than 120,000 miles or 12 years since last replacement	AP47.20-P-0780NK								
Replace coolant i observe correct coolant composition	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2080CW								

Tire inflation pressure (bar/psi)											
LF	RF	LR	RR	Spare							

Tire thread depth (mm)											
	LF	RF	LR	RR							
outside											
center											
inside											