

Mercedes-Benz

AP00.20-U-1208IA SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

MODEL 220 AMG models and S600

Passenger cars Model Year 2005



Customer:			Repair order r	number:		
First visit	at 1,000 - 3,000 miles		Performed	YES	NO	
Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals		Tires rotated	YES	NO	
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure		Tires inspecte	ed YES	NO	
Current mileage reading:			Oil grade/visc	osity:		
Service work to be performed as advised by Completion date: Confirm work has been performed by signing below:						
1st A service at 10,000 miles or 1 year, then every 20,000 miles or 2 years						
1st B service at 20,000 miles or 2 years, then every 20,000 miles or 2 years						
Determine "Additional Work" needed, if any. Refer to "Additional work section (check if applicable)						
at approx. every:	40,000 mi or 4 years		every:	2 years		
	50,000 mi or 4 years			3 years		
	60,000 mi or 4 years			5 years		
	60,000 mi or 5 years			Spark Plugs		
	150,000 mi or 15 years					

i See last page for "Additional Work".

Additional flat rates apply for procedures marked with AP

Completed ⊠		A-Service 🗌	O B-Service	Not OK	
<u></u>		↓	↓		
	Interior - Required				
	Reset maintenance counter in instrument cluster	×	\otimes		AP00.20-P-0042M
	Replace dust filter		\otimes		AP83.00-P-8381MA
	Check parking brake (function test only)		\otimes		AP42.00-P-4290BA
	Interior - Recommended				
,	Function check				
	Warning/indicator lamps, illumination and interior lighting	\boxtimes	\otimes		
	Windshield wipers, windshield washer	X	\otimes		AP82.35-P-8252BA
	system, where applicable: rear window wiper/washer system				
	Headlamp cleaning system	\boxtimes	\otimes		
	Check seat belts for damage and proper function		\otimes		AP91.40-P-9150M
	Wheels, brakes - Required				
	Check thickness of brake pads, front and rear	\boxtimes	⊗		AP42.10-P-4253I
	Correct tire inflation pressure and enter in bar or psi.	×	\otimes		
	LF RF LR RR				
	bar/psi:				
	Wheels, brakes - Recommended				
	Inspect tires for damage and condition	\boxtimes	\otimes		AP40.10-P-4051Z
	Measure tread depth, enter in mm:		\otimes		AP40.10-P-4051Z
	LF RF LR RR outside				
	center				
	inside				
	Underside of vehicle - Required				
	Leakage - Major components		\otimes		AP00.20-P-0053BA
	Check for chafe marks, line routing, dama-				
	ged components in the event of leakage, determine cau-				
	se and perform repair via separate work or-				
	der				
	S600		\otimes		AP00.20-P-0053H
	Check condition of front axle ball joints and rubber boots		\otimes		AP33.20-P-3353BA
	Check condition of steering mechanical components and rubber boots		\otimes		AP46.00-P-4653F
y (·				
	Engine compartment - Required				
	Leakage - Major components		\otimes		AP00.20-P-0053BA
	Check for chafe marks, line routing, damaged components				
	in the event of leakage, determine cau-				
	se and perform repair via separate work or-				
	der		_		
	\$600		\otimes		AP00.20-P-0053H

Completed	X		A-Service	○ B-Se	ervice Not OK	
	↓		\		<u></u>	
		Check condition of poly-V-belt				
[Engine 113		\otimes		AP13.22-P-1352Z
[Engine 275		\otimes		AP13.22-P-1352L
[Clean water drain in air/water duct	X	\otimes		AP83.10-P-8339M
]		Check catch and safety catch and hinges on engine hood for proper operation.	\boxtimes	8		AP88.40-P-8851M
		Engine oil and filter change				
[Engine 113	X	\otimes		AP18.00-P-0101R
[Engine 275	X	\otimes		AP18.00-P-0101L
		Check fluid level, correct as required i If there is a loss of fluid, determine cause and perform repair via separate work order				
[Engine cooling system, antifreeze and corrosion protection. (engine 275 - main circuit)	☒	8		AP20.00-P-2010H
		Brake system	X	\otimes		AP42.10-P-4210Z
]		Power steering				
		with Active Body Control Code 487a		\otimes		AP46.00-P-4611N
		without Active Body Control Code 487a		\otimes		
		Active Body Control		\otimes		AP32.50-P-3213I
]		Windshield washer system	X	\otimes		AP82.35-P-8210N
		(incl. summer/winter cleanser)				
		Trunk - Required				
[Correct inflation pressure of spare tire and enter in bar or psi. bar/psi:	\boxtimes	8		
	,	Trunk - Recommended				
1		Battery, check battery condition using "Midtronics MCR 717" tester. Attach Midtronics MCR 717 Test Report print out here.	X	8		AP54.10-U-5453A
		Additional Work				
Completed [Perform:	Yes		Not OK	
	<u> </u>		<u> </u>			
Required		At approx. every 40,000 mi or 4 years:				
		Engine 113:				
l≆AP [Replace air cleaner filter element				
		Engine 275:				
F AP [Replace poly-V-belt tensioning device				AP13.25-P-1382H
		Engine 113:				
⊯AP [Replace compressor poly-V-belt				AP13.22-P-1381R
Required		At approx. every 50,000 mi or 4 years:				
⊯AP [Check condition of driveshaft flex discs				AP41.10-P-4152Z

Compl	leted 🗵	Perfo		Not OK	
	<u></u>			<u></u>	
Required		At approx. every 60,000 mi or 4 years:			
		Engine 275:			
₩ÃΡ		Replace air cleaner filter element			AP09.10-P-0980H
Recommended		At approx. every 60,000 mi or 5 years:			
№ AP		Replace activated charcoal filter (if equipped)			AP83.00-P-8382M
Required		At approx. every 60,000 mi or 5 years:			
		Engine 113:			
₩ÃΡ		Replace fuel filter			AP47.20-P-0780DC
		Engine 275:			
β≆AP		Replace fuel filter			AP47.20-P-0780L
Required		At approx. every 150,000 mi or 15 years	3:		
		Engine 113:			
₩AP		Replace coolant (water/ anticorrosion/ tifreeze mixture)	an-		AP20.00-P-2080DA
		Engine 275:			
i≆ AP		Replace coolant for low temperature ci cuit (water/ anticorrosion/ antifreeze m ture)			AP20.00-P-2080H
Required		Replace spark plugs:			
		Engine 113:			
⊯ AP		At approx every 100,000 mi or 5 years			AP15.10-P-1580AB
		Engine 275:			
⊯ AP		At approx every 60,000 mi or 5 years			AP15.10-P-1580L
Required		Every 2 years:			
⊯ AP		Replace brake fluid			
		with extreme protection code Z07			AP42.00-P-4280MB
		without extreme protection code Z07			AP42.00-P-4280BA
Recommended		Every 2 years:			
₩AP		Check body for paint damage by service advisor			AP98.00-P-9850BA
i≆ AP		Check chassis and supporting body part for damage and corrosion by service advisor	s 🗆		AP00.20-P-0090BA
Required		Every 3 years:			
		Engine 275:			
⊯ AP		Replace coolant for main circuit (water/anticorrosion/antifreeze mixture)			AP20.00-P-2080H
Recommended		Every 5 years:			
₩ÃΡ		Tilt/sliding roof: clean sliding rails and s ders	sli-		AP77.20-P-7731A