



Mercedes Benz

AP00.20-U-1208IG SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model Year 2011
USA

Model 221



Customer: \_\_\_\_\_

Repair order number: \_\_\_\_\_

Tire Rotation
(non-staggered width
wheel setup only)

A 5,000-mile recommended tire rotation
interval will likely necessitate tire rotation
at least once in between each 10,000-mile
maintenance service and at every 10,000-
mile maintenance service.

Tires rotated YES [ ] NO [ ]

Note: For any condition found while performing the checks or inspections included in this maintenance sheet, determine the cause and perform the repair using a separate repair order.

Current mileage reading: \_\_\_\_\_

Oil grade/viscosity: \_\_\_\_\_

Additional notes: \_\_\_\_\_
\_\_\_\_\_
\_\_\_\_\_
\_\_\_\_\_
\_\_\_\_\_
\_\_\_\_\_
\_\_\_\_\_
\_\_\_\_\_

Service work to be performed as advised by
service advisor:

Completion date:

Confirm work has been performed by signing
below:

\_\_\_\_\_

<b>Required Service Work</b> <input checked="" type="checkbox"/> Performed (check if performed)	<b>miles (thousands)</b> <b>years</b>	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	<b>Not OK</b> ↓		
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15				
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP00.20-P-0042SX	
<input type="checkbox"/> Engine - oil and filter change																				
Engine 157, 272, 273			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101SX	
Engine 275			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101SZ	
<input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP88.40-P-8851SX	
<input type="checkbox"/> Clean water drain in air/water duct			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP83.10-P-8339M	
<input type="checkbox"/> Check condition of poly-V-belt																				
Engine 157, 273				•		•		•		•		•		•		•		•	<input type="checkbox"/> AP13.22-P-1352SX	
Engine 275				•		•		•		•		•		•		•		•	<input type="checkbox"/> AP13.22-P-1352SZ	
<input type="checkbox"/> Replace V-belts																				
S 400 Hybrid								•										•	AP13.20-P-1380A	
<input type="checkbox"/> Replace fuel filter																				
Engine 272, 273, 157, 275																		•	AP47.20-P-0780SX	
<input type="checkbox"/> Replace coolant																				
Engine 275 main circuit					•			•			•			•				•	AP20.00-P-2080SZ	
Engine 275 low temperature circuit																		•	AP20.00-P-2080SZ	
Engine 272, 273, 157																		•	AP20.00-P-2080SX	
<input type="checkbox"/> Replace brake fluid			•		•		•		•		•		•		•		•		AP42.00-P-4280SX	
<b>Check the following fluid levels, correct if necessary</b>																				
<input type="checkbox"/> Engine cooling system, antifreeze and corrosion protection																				
Engine 275 main circuit			•	•		•	•		•	•		•	•		•	•		•	<input type="checkbox"/>	
<input type="checkbox"/> Check coolant level			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AH20.00-P-1142-01V
<input type="checkbox"/> Brake system			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4210SX
<input type="checkbox"/> Power steering			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP46.00-P-4611SX
<input checked="" type="checkbox"/> The fluid level must always be on the maximum mark, corresponding to the oil temperature.																				
<input type="checkbox"/> Windshield washer system			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP82.35-P-8210SX
<input type="checkbox"/> Active Body Control (if applicable)			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP32.50-P-3213SX
<b>Function check</b>																				
<input type="checkbox"/> Parking brake (function test only)				•		•		•		•		•		•		•		•	<input type="checkbox"/>	
<input type="checkbox"/> Replace combination filter				•		•		•		•		•		•		•		•	AP83.00-P-8384SX	
<input type="checkbox"/> Check thickness of brake pads, front and rear			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4253A
	<b>miles (thousands)</b> <b>years</b>	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150			
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15				

	miles (thousands)		years															
	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1		
<input type="checkbox"/> Correct tire inflation pressure and enter in bar or psi: LF RF LR RR bar/psi: _____		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>	
<input type="checkbox"/> Check inflation pressure in spare tire (if applicable) and enter in bar or psi: bar/psi: _____		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>	
<input type="checkbox"/> <b>Leakage - Major components</b> Check underbody and engine compartment for chafe marks, line routing, damaged components.			•		•		•		•		•		•		•		<input type="checkbox"/> AP00.20-P-0053SX	
<input type="checkbox"/> Visually inspect condition of front axle ball joints, rubber boots			•		•		•		•		•		•		•		<input type="checkbox"/>	
<input type="checkbox"/> Visually inspect condition of driveshaft flexible discs			•		•		•		•		•		•		•		<input type="checkbox"/> AP41.10-P-4152SX	
<input type="checkbox"/> Visually inspect condition of steering mechanical components, rubber boots			•		•		•		•		•		•		•		<input type="checkbox"/>	
<input type="checkbox"/> Automatic transmission - oil and filter change Transmission 722.9 Transmission 722.6						•			•				•				AP27.00-P-2702W AP27.00-P-2702SX	
<input type="checkbox"/> Replace air filter Engine 272, 273 Engine 275 Engine 157					•				•				•				AP09.10-P-0980SX AP09.10-P-0980SZ AP09.10-P-0980MM	
<input type="checkbox"/> Replace spark plugs Engine 272, 273 Engine 275 Engine 157								•					•				AP15.10-P-1580SX AP15.10-P-1580SZ AP15.10-P-1580SX	
<input type="checkbox"/> <b>Reminder: Reset maintenance service indicator in instrument cluster</b>		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP00.20-P-0042SX	
<b>Recommended Service Work</b> <input checked="" type="checkbox"/> Performed (check if performed)																	<b>Not OK</b> ↓	
<b>Check the following fluid levels, correct if necessary</b>																		
<input type="checkbox"/> Main or starter battery		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP54.10-P-5410SX	
<b>Electrical system checks</b>																		
<input type="checkbox"/> Horn, high beam flasher, hazard warning flasher, turn signals		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>	
<input type="checkbox"/> Warning/indicator lamps, illumination and interior lighting/exterior lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP54.30-P-5452C	
<input type="checkbox"/> Check trunk/cargo area lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>	
<input type="checkbox"/> Check and correct headlamp setting			•		•		•		•		•		•		•		<input type="checkbox"/> AP82.10-P-8260SX	
	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
miles (thousands)	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1		
years	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1		

	miles (thousands)		2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	
	years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15		
<input type="checkbox"/> Battery (Main/starter/auxiliary) check condition using "Midtronics MCR 717" tester. Attach Midtronics MCR 717 Test Report print out here				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP54.10-U-5453A
<b>Visual and functional checks</b>																			
<input type="checkbox"/> Check seat belts and buckles for signs of external damage and proper function					•		•		•		•		•		•		•		<input type="checkbox"/> AP91.40-P-9150SX
<input type="checkbox"/> Check windshield washer and headlamp cleaning system				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP82.30-P-8252SX
<input type="checkbox"/> Check, clean, and lubricate tilt/sliding roof mechanism (where applicable)					•		•		•		•		•		•		•		<input type="checkbox"/> AP77.20-P-7731SX
<input type="checkbox"/> Check, clean, and lubricate panoramic roof mechanism (where applicable)					•		•		•		•		•		•		•		<input type="checkbox"/> AP77.20-P-7732SX
<input type="checkbox"/> Check bodywork for paintwork damage					•		•		•		•		•		•		•		<input type="checkbox"/> AP98.00-P-9850SX
<input type="checkbox"/> Night View Assist camera - clean windshield behind the camera cover (where applicable)				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP54.30-P-5431SX
<b>Tire checks</b>																			
<input type="checkbox"/> Tire rotation (where applicable)				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
<input type="checkbox"/> Inspect tires for damage, measure thread depth and enter in mm: LF RF LR RR outside _____ center _____ inside _____				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP40.10-P-4051SX
<input type="checkbox"/> Check TIREFIT tire sealant expiration date (where applicable)				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP40.10-P-4054R
<input type="checkbox"/> Activate Tire Pressure Monitoring System; Refer to vehicle Operator's Manual				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
<b>Chassis checks</b>																			
<input type="checkbox"/> Visually check brake system components, lines, hoses, calipers				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed Pads Discs					•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4253A <input type="checkbox"/> AP42.10-P-4258SX
<input type="checkbox"/> Check chassis and load-bearing body components for damage and corrosion					•		•		•		•		•		•		•		<input type="checkbox"/> AP00.20-P-0090SX
<input type="checkbox"/> Replace wiper blades				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
	miles (thousands)		2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	
	years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15		
<b>High Mileage Required Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years</b>																			
<input checked="" type="checkbox"/> Plus any applicable additional work listed at the end of this service sheet																			
<input checked="" type="checkbox"/> Performed (check if performed)																			Not OK ↓
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster																			AP00.20-P-0042SX
<input type="checkbox"/> Engine - oil and filter change Engine 157, 272, 273 Engine 275																			AP18.00-P-0101SX AP18.00-P-0101SZ

<input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation	<input type="checkbox"/> AP88.40-P-8851SX
<input type="checkbox"/> Clean water drain in air/water duct	AP83.10-P-8339M
<input type="checkbox"/> Check condition of poly-V-belt Engine 157, 273	<input type="checkbox"/> AP13.22-P-1352SX
Engine 275	<input type="checkbox"/> AP13.22-P-1352SZ
<input type="checkbox"/> Replace brake fluid	AP42.00-P-4280SX
<b>Check the following fluid levels, correct if necessary</b>	
<input type="checkbox"/> Engine cooling system, antifreeze and corrosion protection Engine 275 main circuit <b>i</b> if not to be replaced according to additional work schedule listed at the end of this service sheet	<input type="checkbox"/>
<input type="checkbox"/> Check coolant level	<input type="checkbox"/> AH20.00-P-1142-01V
<input type="checkbox"/> Brake system	<input type="checkbox"/> AP42.10-P-4210SX
<input type="checkbox"/> Power steering <b>i</b> The fluid level must always be on the maximum mark, corresponding to the oil temperature.	<input type="checkbox"/> AP46.00-P-4611SX
<input type="checkbox"/> Windshield washer system	<input type="checkbox"/> AP82.35-P-8210SX
<input type="checkbox"/> Active Body Control (if applicable)	<input type="checkbox"/> AP32.50-P-3213SX
<b>Function check</b>	
<input type="checkbox"/> Parking brake (function test only)	<input type="checkbox"/>
<input type="checkbox"/> Replace combination filter	AP83.00-P-8384SX
<input type="checkbox"/> Check thickness of brake pads, front and rear	<input type="checkbox"/> AP42.10-P-4253A
<input type="checkbox"/> Correct tire inflation pressure and enter in bar or psi: LF RF LR RR bar/psi: _____	<input type="checkbox"/>
<input type="checkbox"/> Check inflation pressure in spare tire (if applicable) and enter in bar or psi: bar/psi: _____	<input type="checkbox"/>
<input type="checkbox"/> <b>Leakage - Major components</b> Check underbody and engine compartment for chafe marks, line routing, damaged components.	<input type="checkbox"/> AP00.20-P-0053SX
<input type="checkbox"/> Visually inspect condition of front axle ball joints, rubber boots	<input type="checkbox"/>
<input type="checkbox"/> Visually inspect condition of driveshaft flexible discs	<input type="checkbox"/> AP41.10-P-4152SX
<input type="checkbox"/> Visually inspect condition of steering mechanical components, rubber boots	<input type="checkbox"/>
<b>i</b> <b>Reminder: Reset maintenance service indicator in instrument cluster</b>	AP00.20-P-0042SX

<b>High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years</b>																					
<input checked="" type="checkbox"/> Performed (check if performed)	<b>Not OK</b> ↓																				
<b>Check the following fluid levels, correct if necessary</b>																					
<input type="checkbox"/> Main or starter battery	<input type="checkbox"/> AP54.10-P-5410SX																				
<b>Electrical system checks</b>																					
<input type="checkbox"/> Horn, high beam flasher, hazard warning flasher, turn signals	<input type="checkbox"/>																				
<input type="checkbox"/> Warning/indicator lamps, illumination and interior lighting/exterior lighting	<input type="checkbox"/> AP54.30-P-5452C																				
<input type="checkbox"/> Check trunk/cargo area lighting	<input type="checkbox"/>																				
<input type="checkbox"/> Check and correct headlamp setting	<input type="checkbox"/> AP82.10-P-8260SX																				
<input type="checkbox"/> Battery (Main/starter/auxiliary) check condition using "Midtronics MCR 717" tester. Attach Midtronics MCR 717 Test Report print out here	<input type="checkbox"/> AP54.10-U-5453A																				
<b>Visual and functional checks</b>																					
<input type="checkbox"/> Check seat belts and buckles for signs of external damage and proper function	<input type="checkbox"/> AP91.40-P-9150SX																				
<input type="checkbox"/> Check windshield washer and headlamp cleaning system	<input type="checkbox"/> AP82.30-P-8252SX																				
<input type="checkbox"/> Check, clean, and lubricate tilt/sliding roof mechanism (where applicable)	<input type="checkbox"/> AP77.20-P-7731SX																				
<input type="checkbox"/> Check, clean, and lubricate panoramic roof mechanism (where applicable)	<input type="checkbox"/> AP77.20-P-7732SX																				
<input type="checkbox"/> Check bodywork for paintwork damage	<input type="checkbox"/> AP98.00-P-9850SX																				
<input type="checkbox"/> Night View Assist camera - clean windshield behind the camera cover (where applicable)	AP54.30-P-5431SX																				
<b>Tire checks</b>																					
<input type="checkbox"/> Tire rotation (where applicable)																					
<input type="checkbox"/> Inspect tires for damage, measure thread depth and enter in mm:	<input type="checkbox"/> AP40.10-P-4051SX																				
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;"></td> <td style="width: 15%; text-align: center;">LF</td> <td style="width: 15%; text-align: center;">RF</td> <td style="width: 15%; text-align: center;">LR</td> <td style="width: 15%; text-align: center;">RR</td> </tr> <tr> <td>outside</td> <td style="text-align: center;">_____</td> <td style="text-align: center;">_____</td> <td style="text-align: center;">_____</td> <td style="text-align: center;">_____</td> </tr> <tr> <td>center</td> <td style="text-align: center;">_____</td> <td style="text-align: center;">_____</td> <td style="text-align: center;">_____</td> <td style="text-align: center;">_____</td> </tr> <tr> <td>inside</td> <td style="text-align: center;">_____</td> <td style="text-align: center;">_____</td> <td style="text-align: center;">_____</td> <td style="text-align: center;">_____</td> </tr> </table>		LF	RF	LR	RR	outside	_____	_____	_____	_____	center	_____	_____	_____	_____	inside	_____	_____	_____	_____	
	LF	RF	LR	RR																	
outside	_____	_____	_____	_____																	
center	_____	_____	_____	_____																	
inside	_____	_____	_____	_____																	
<input type="checkbox"/> Check TIREFIT tire sealant expiration date (where applicable)	<input type="checkbox"/> AP40.10-P-4054R																				
<input type="checkbox"/> Activate Tire Pressure Monitoring System; Refer to vehicle Operator's Manual																					
<b>Chassis checks</b>																					
<input type="checkbox"/> Visually check brake system components, lines, hoses, calipers	<input type="checkbox"/>																				
<input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed																					
Pads	<input type="checkbox"/> AP42.10-P-4253A																				
Discs	<input type="checkbox"/> AP42.10-P-4258SX																				

<input type="checkbox"/> Check chassis and load-bearing body components for damage and corrosion	<input type="checkbox"/> AP00.20-P-0090SX
<input type="checkbox"/> Replace wiper blades	
<b>High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years</b>	
<b>i Plus any applicable additional work listed at the end of this service sheet</b>	
<input checked="" type="checkbox"/> Performed (check if performed)	<b>Not OK</b> ↓
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster	AP00.20-P-0042SX
<input type="checkbox"/> Engine - oil and filter change	
Engine 157, 272, 273	AP18.00-P-0101SX
Engine 275	AP18.00-P-0101SZ
<input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation	<input type="checkbox"/> AP88.40-P-8851SX
<input type="checkbox"/> Clean water drain in air/water duct	AP83.10-P-8339M
<b>Check the following fluid levels, correct if necessary</b>	
<input type="checkbox"/> Engine cooling system, antifreeze and corrosion protection Engine 275 main circuit <b>i if not to be replaced according to additional work schedule listed at the end of this service sheet</b>	<input type="checkbox"/>
<input type="checkbox"/> Check coolant level	<input type="checkbox"/> AH20.00-P-1142-01V
<input type="checkbox"/> Brake system	<input type="checkbox"/> AP42.10-P-4210SX
<input type="checkbox"/> Power steering <b>i The fluid level must always be on the maximum mark, corresponding to the oil temperature.</b>	<input type="checkbox"/> AP46.00-P-4611SX
<input type="checkbox"/> Windshield washer system	<input type="checkbox"/> AP82.35-P-8210SX
<input type="checkbox"/> Active Body Control (if applicable)	<input type="checkbox"/> AP32.50-P-3213SX
<input type="checkbox"/> Check thickness of brake pads, front and rear	<input type="checkbox"/> AP42.10-P-4253A
<input type="checkbox"/> Correct tire inflation pressure and enter in bar or psi: LF      RF      LR      RR bar/psi: _____	<input type="checkbox"/>
<input type="checkbox"/> Check inflation pressure in spare tire (if applicable) and enter in bar or psi: bar/psi: _____	<input type="checkbox"/>
<b>i Reminder: Reset maintenance service indicator in instrument cluster</b>	AP00.20-P-0042SX
<b>High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years</b>	
<input checked="" type="checkbox"/> Performed (check if performed)	<b>Not OK</b> ↓
<b>Check the following fluid levels, correct if necessary</b>	
<input type="checkbox"/> Main or starter battery	<input type="checkbox"/> AP54.10-P-5410SX

<b>Electrical system checks</b>																							
<input type="checkbox"/>	Horn, high beam flasher, hazard warning flasher, turn signals		<input type="checkbox"/>																				
<input type="checkbox"/>	Warning/indicator lamps, illumination and interior lighting/exterior lighting		<input type="checkbox"/> AP54.30-P-5452C																				
<input type="checkbox"/>	Check trunk/cargo area lighting		<input type="checkbox"/>																				
<input type="checkbox"/>	Battery (Main/starter/auxiliary) check condition using "Midtronics MCR 717" tester. Attach Midtronics MCR 717 Test Report print out here		<input type="checkbox"/> AP54.10-U-5453A																				
<b>Visual and functional checks</b>																							
<input type="checkbox"/>	Check windshield washer and headlamp cleaning system		<input type="checkbox"/> AP82.30-P-8252SX																				
<input type="checkbox"/>	Night View Assist camera - clean windshield behind the camera cover (where applicable)		AP54.30-P-5431SX																				
<b>Tire checks</b>																							
<input type="checkbox"/>	Tire rotation (where applicable)																						
<input type="checkbox"/>	Inspect tires for damage, measure thread depth and enter in mm:		<input type="checkbox"/> AP40.10-P-4051SX																				
	<table border="0"> <tr> <td></td> <td>LF</td> <td>RF</td> <td>LR</td> <td>RR</td> </tr> <tr> <td>outside</td> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> <tr> <td>center</td> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> <tr> <td>inside</td> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> </table>		LF	RF	LR	RR	outside	_____	_____	_____	_____	center	_____	_____	_____	_____	inside	_____	_____	_____	_____		
	LF	RF	LR	RR																			
outside	_____	_____	_____	_____																			
center	_____	_____	_____	_____																			
inside	_____	_____	_____	_____																			
<input type="checkbox"/>	Check TIREFIT tire sealant expiration date (where applicable)		<input type="checkbox"/> AP40.10-P-4054R																				
<input type="checkbox"/>	Activate Tire Pressure Monitoring System; Refer to vehicle Operator's Manual																						
<b>Chassis checks</b>																							
<input type="checkbox"/>	Visually check brake system components, lines, hoses, calipers		<input type="checkbox"/>																				
<input type="checkbox"/>	Check thickness of brake pads and discs, front and rear wheels removed																						
	Pads		<input type="checkbox"/> AP42.10-P-4253A																				
	Discs		<input type="checkbox"/> AP42.10-P-4258SX																				
<input type="checkbox"/>	Replace wiper blades																						
<b>High Mileage Additional Work</b>																							
<input checked="" type="checkbox"/>	Performed (check if performed)																						
<input type="checkbox"/>	Replace V-belts S 400 Hybrid	If more than 60,000 mi or 6 years since last replacement	AP13.20-P-1380A																				
<input type="checkbox"/>	Replace fuel filter Engine 272, 273, 157, 275	If more than 150,000 mi or 15 years since last replacement	AP47.20-P-0780SX																				
<input type="checkbox"/>	Replace coolant																						
	Engine 275 main circuit	If more than 30,000 mi or 3 years since last replacement	AP20.00-P-2080SZ																				
	Engine 275 low temperature circuit	If more than 150,000 mi or 15 years since last replacement	AP20.00-P-2080SZ																				
	Engine 272, 273, 157	If more than 150,000 mi or 15 years since last replacement	AP20.00-P-2080SX																				



<input type="checkbox"/> Automatic transmission - oil and filter change		
Transmission 722.9	If more than 40,000 mi or 4 years since last replacement	AP27.00-P-2702W
Transmission 722.6	If more than 40,000 mi or 4 years since last replacement	AP27.00-P-2702SX
<input type="checkbox"/> Replace air filter		
Engine 272, 273	If more than 40,000 mi or 4 years since last replacement	AP09.10-P-0980SX
Engine 275	If more than 60,000 mi or 6 years since last replacement	AP09.10-P-0980SZ
Engine 157	If more than 40,000 mi or 4 years since last replacement	AP09.10-P-0980MM
<input type="checkbox"/> Replace spark plugs		
Engine 272, 273	If more than 60,000 mi or 6 years since last replacement	AP15.10-P-1580SX
Engine 275	If more than 60,000 mi or 6 years since last replacement	AP15.10-P-1580SZ
Engine 157	If more than 60,000 mi or 6 years since last replacement	AP15.10-P-1580SX