

Mercedes-Benz

AP00.20-U-1208IC SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

MODEL 221

except AMG models and \$600

Passenger cars Model Year 2007



Customer:		Repair order number:		
First visit	at 1,000 - 3,000 miles	Performed	YES NO	
Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES NO	
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES NO	
Current mileage reading: Additional notes:			r:	
Service work to be performed as advised by service advisor:		Confirm work below:	k has been performed by signing	

i

 $\label{thm:conditional} {\it US Service 4 through US Service 20 apply to "Additional work" items only.}$

Vehicle determines need for US Service 3 (Engine oil and filter change) as well as US Service 1 or US Service 2.

Perform each service as described.

US Service		first at 13,000 mi or 1 year;	after first every 26,000 mi or 2 years	
1	US Service 2	first at 26,000 mi or 2 years;	after first every 26,000 mi or 2 years Not OK	
\downarrow	_ ↓		↓	
64		Interior - Required		
	0	Reset service indicator in instrument cluster		AP00.20-P-0042SX
	0	Check parking brake (function test only)		AP42.00-P-4292SX
64		Interior - Recommended		
	0	Night View Assist camera - clean windshield behind the camera cover		AP54.30-P-5431SX
		Function test		
	0	Horn, warning/indicator lamps, illumination and interior lighting		
	0	Windshield wipers, windshield washer system		AP82.30-P-8252SX
	0	Headlamp cleaning system		
	0	Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150SX
	>	Wheels, brakes - Required		
1			_	
	0	Check thickness of brake pads, front and rear		AP42.10-P-4253A
	0	Correct tire inflation pressure and enter in bar or psi.		
		LF RF LR RR bar/psi:		
		Wheels, brakes - Recommended		
1	† O	Remove and install wheels		AP40.10-P-4050SX
	0	Inspect tires for damage and splits, measu-		AP40.10-P-4051SX
		re tread depth, enter in mm: LF RF LR RR		
		outside		
		center inside		
60		Underside of vehicle - Required		
Ť †	0	Leakage - Major components Check for chafe marks, line routing, damaged components iln the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053SX
	0	Check front axle ball joints for play, check rubber boots		AP33.20-P-3353SX
	0	Inspect condition of driveshaft flexible discs		AP41.10-P-4152SX
	0	Inspect play of tie rod and drag link joints, inspect rubber boots		AP46.00-P-4653SX

US Service	US Service		Not OK	
1 J.	2 ↓		↓	
ind		Vehicle front/rear - Recommended	•	
, 0	Ö	Check and correct headlamp setting		AP82.10-P-8260SX
	0	Check wiper blade condition		AP82.30-P-8253SX
6		Trunk - Required		
	0	Correct inflation pressure in spare tire and enter in bar or psi. bar/psi:		
6		Trunk - Recommended		
	0	Check auxiliary battery condition using "Midtronics MCR 717" Tester. Attach "Midtronics MCR 717" Test Report print out here.		AP54.10-U-5453A
	0	Check trunk lighting		
		Engine compartment - Required		
	0	Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053SX
	0	Check catch, safety catch and hinges on engine hood for proper operation.		AP88.40-P-8851SX
	0	Check condition of poly-V-belt		AP13.22-P-1352SX
		Check fluid level, correct as required i If there is a loss of fluid, determine cause and perform repair via separate work order		
	0	Brake system		AP42.10-P-4210SX
	0	Power steering		AP46.00-P-4611SX
	0	Active Body Control (Code 487)		AP32.50-P-3213SX
	0	Windshield washer system (incl. summer/winter cleanser)		AP82.35-P-8210SX
		Engine compartment - Recommended		
	0	Starter battery, check and correct fluid level		AP54.10-P-5410SX
	0	Check starter battery condition using "Mid- tronics MCR 717" Tester. Attach "Midtronics MCR 717" Test Report print out here.		AP54.10-U-5453A
		Additional Work		
Co	mpleted 🗵		Not OK	
IIC Co.	↓ rvice 3	every 13,000 mi or 1 year:	<u> </u>	
	rvice 3 uired	Engine compartment		
		Engine - oil and filter change		AP18.00-P-0101SX

Completed ⊠	I	Ŋ	Not OK	
US Service 4 Required	every 2 years: Engine compartment		•	
	Replace brake fluid			AP42.00-P-4280SX
US Service 4 Recommended	every 2 years:			
	Check bodywork for paint work damage by service advisor			AP98.00-P-9850SX
	Underside of vehicle			
	Chassis and load-bearing body components: Check for damage and corrosion by service advisor			AP00.20-P-0090SX
US Service 5 Required	every 26,000 mi or 2 years: Passenger compartment			
	Replace combination filter			AP83.00-P-8384SX
US Service 6 & 7	not applicable			
US Service 8 Required	every 52,000 mi or 4 years: Engine compartment			
	Replace engine air-cleaner insert			AP09.10-P-0980SX
US Service 9 Recommended	every 5 years: Passenger compartment			
	Tilting/sliding roof: Clean slide rail and slide block			AP77.20-P-7731SX
US Service 10 Recommended	every 3 years: Passenger compartment			
	Panoramic sliding roof - clean and lubricate quide mechanism			AP77.20-P-7732SX
US Service 11 Required	every 143,000 mi or 15 years: Passenger compartment			
	Replace fuel filter			AP47.20-P-0780SX
US Service 12 Required	every 91,000 mi or 5 years: Engine compartment			
	Replace spark plugs	Engine 273		AP15.10-P-1580SX
US Service 13 Required	every 143,000 mi or 15 years: Engine compartment			
	Replace coolant			AP20.00-P-2080SX
US Service 14 - 19	not applicable			
US Service 20 Required	once at 39,000 mi: Underside of vehicle			
	Automatic transmission - oil and filter change			AP27.00-P-2702W