

Required Service Work <input checked="" type="checkbox"/> Performed (check if performed)	miles (thousands) years	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK ↓
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15		
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP00.20-P-0042SX
<input type="checkbox"/> Engine - oil and filter change		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101EWG
engine 157		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101PIT
engine 272		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101SX
engine 273		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101SZA
engine 275.953		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP18.00-P-0101SZB
engine 275.982		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
<input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP88.40-P-8851SX
<input type="checkbox"/> Check water drain in air/water duct for obstructions; clean if soiled		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP83.10-P-8339M
<input type="checkbox"/> Check condition of poly-V-belt except S400 HYBRID																		<input type="checkbox"/> AP13.22-P-1352SX
engine 157, 273			•		•		•		•		•		•		•		•	<input type="checkbox"/> AP13.22-P-1352SZ
engine 275			•		•		•		•		•		•		•		•	
<input type="checkbox"/> Replace brake fluid			•		•		•		•		•		•		•		•	AP42.00-P-4280SX
<input type="checkbox"/> Replace combination filter			•		•		•		•		•		•		•		•	AP83.00-P-8384SX
<input type="checkbox"/> Check thickness of brake pads, front and rear		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4253A
<input type="checkbox"/> Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP40.15-P-4061A
<input type="checkbox"/> Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components			•		•		•		•		•		•		•		•	<input type="checkbox"/> AP00.20-P-0053SX
<input type="checkbox"/> Visually inspect condition of front axle ball joints, rubber boots			•		•		•		•		•		•		•		•	<input type="checkbox"/> AP33.20-P-3353SX
<input type="checkbox"/> Visually inspect condition of driveshaft flexible discs			•		•		•		•		•		•		•		•	<input type="checkbox"/> AP41.10-P-4152SX
<input type="checkbox"/> Visually inspect condition of steering mechanical components, rubber boots			•		•		•		•		•		•		•		•	<input type="checkbox"/> AP46.00-P-4653SX
<input type="checkbox"/> Coolant - check fluid level and correct if necessary engine 157, 272, 273; engine 275 main and low temperature circuit (main circuit if not to be replaced (every 30k miles/3 yrs)) <input checked="" type="checkbox"/> refer to AH20.00-P-1142-01V <input checked="" type="checkbox"/> observe correct coolant composition		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Brake system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4210SX
<input type="checkbox"/> Power steering - check fluid level and correct if necessary <input checked="" type="checkbox"/> the fluid level must always be on the maximum mark, corresponding to the oil temperature		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP46.00-P-4611SX
<input type="checkbox"/> Windshield washer system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP82.35-P-8210SX
<input type="checkbox"/> Active Body Control - check fluid level and correct if necessary with Code 487 (Active Body Control (ABC))		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP32.50-P-3213SX
<input type="checkbox"/> Parking brake (function test only)			•		•		•		•		•		•		•		•	<input type="checkbox"/> AP42.00-P-4290BA

Required Service Work	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK ↓	
<input checked="" type="checkbox"/> Performed (check if performed)	years	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15			
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster <input checked="" type="checkbox"/> reminder - if not yet performed		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP00.20-P-0042SX	
Required Additional Work	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK ↓	
<input checked="" type="checkbox"/> Performed (check if performed)	years	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15			
<input type="checkbox"/> Replace air filter except engine 275 engine 157 engine 272, 273					•	•				•				•				AP09.10-P-0980AB AP09.10-P-0980SX	
<input type="checkbox"/> Replace air filter engine 275							•							•				AP09.10-P-0980SZ	
<input type="checkbox"/> Automatic transmission - oil and filter change transmission 722.9 transmission 722.6					•	•				•				•				AP27.00-P-2702W AP27.00-P-2702SX	
<input type="checkbox"/> Replace V-belts S400 HYBRID							•							•				AP13.20-P-1380A	
<input type="checkbox"/> Replace spark plugs engine 157, 272, 273 engine 275							•							•				AP15.10-P-1580SX AP15.10-P-1580SZ	
<input type="checkbox"/> Replace fuel filter																	•	AP47.20-P-0780SX	
<input type="checkbox"/> Replace coolant engine 275 main circuit <input checked="" type="checkbox"/> observe correct coolant composition				•			•				•			•				AP20.00-P-2080SZ	
<input type="checkbox"/> Replace coolant except engine 275 main circuit engine 157, 272, 273 engine 275 low temperature circuit																	• •	AP20.00-P-2080SX AP20.00-P-2080SZ	
Recommended Service Work	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	Not OK ↓	
<input checked="" type="checkbox"/> Performed (check if performed)	years	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15			
<input type="checkbox"/> Main/starter battery - Check fluid level and correct if necessary with lead acid battery		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP54.10-P-5410SX
<input type="checkbox"/> Horn - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Warning/indicator lamps - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP54.30-P-5451SX
<input type="checkbox"/> Illumination and interior lighting - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP54.30-P-5453SX
<input type="checkbox"/> Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP82.10-P-8252EW
<input type="checkbox"/> Check trunk/cargo area lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Check and correct headlamp setting			•		•		•		•		•		•		•		•	AP82.10-P-8260SX	
<input type="checkbox"/> Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP54.10-U-5453A
<input type="checkbox"/> Check seat belts and buckles for signs of external damage and proper function			•		•		•		•		•		•		•		•	<input type="checkbox"/> AP91.40-P-9150SX	
<input type="checkbox"/> Check windshield washer and headlamp cleaning system		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP82.30-P-8252SX

Recommended Service Work	miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	years	Not OK ↓	
																				1
<input checked="" type="checkbox"/> Performed (check if performed)																				
<input type="checkbox"/> Check, clean, and lubricate tilt/sliding roof mechanism except CODE 413 (panoramic glass roof with top sliding roof)				•		•		•		•		•		•		•				AP77.20-P-7731SX
<input type="checkbox"/> Check, clean, and lubricate panoramic roof mechanism with CODE 413 (panoramic glass roof with top sliding roof)				•		•		•		•		•		•		•				AP77.20-P-7732SX
<input type="checkbox"/> Check bodywork for paintwork damage				•		•		•		•		•		•		•				<input type="checkbox"/> AP98.00-P-9850SX
<input type="checkbox"/> Night View Assist camera - clean windshield behind the camera cover with CODE 610 (Night View Assist)			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP54.30-P-5431SX
<input type="checkbox"/> Tire rotation where applicable			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
<input type="checkbox"/> Inspect tires for damage, measure thread depth and enter table at the end of the service sheet			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP40.10-P-4051Z
<input type="checkbox"/> Check TIREFIT tire sealant expiration date where applicable			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP40.10-P-4054R
<input type="checkbox"/> Activate Tire Pressure Monitoring System <input checked="" type="checkbox"/> refer to vehicle Operator's Manual			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	AP40.10-P-4054R
<input type="checkbox"/> Visually check brake system components, lines, hoses, calipers			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/>
<input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed																				
pads			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4253A
discs			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	<input type="checkbox"/> AP42.10-P-4258SX
<input type="checkbox"/> Check chassis and load-bearing body components for damage and corrosion				•		•		•		•		•		•		•				<input type="checkbox"/> AP00.20-P-0090SX
<input type="checkbox"/> Replace wiper blades			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
High Mileage Required Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years																				
<input checked="" type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet																				
<input checked="" type="checkbox"/> Performed (check if performed)																				Not OK ↓
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster																				AP00.20-P-0042SX
<input type="checkbox"/> Engine - oil and filter change																				
engine 157																				AP18.00-P-0101EWG
engine 272																				AP18.00-P-0101PIT
engine 273																				AP18.00-P-0101SX
engine 275.953																				AP18.00-P-0101SZA
engine 275.982																				AP18.00-P-0101SZB
<input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation																				<input type="checkbox"/> AP88.40-P-8851SX
<input type="checkbox"/> Check water drain in air/water duct for obstructions; clean if soiled																				AP83.10-P-8339M
<input type="checkbox"/> Check condition of poly-V-belt except S400 HYBRID																				
engine 157, 273																				<input type="checkbox"/> AP13.22-P-1352SX
engine 275																				<input type="checkbox"/> AP13.22-P-1352SZ
<input type="checkbox"/> Replace brake fluid																				AP42.00-P-4280SX
<input type="checkbox"/> Replace combination filter																				AP83.00-P-8384SX
<input type="checkbox"/> Check thickness of brake pads, front and rear																				<input type="checkbox"/> AP42.10-P-4253A
<input type="checkbox"/> Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet																				<input type="checkbox"/> AP40.15-P-4061A

<input type="checkbox"/> Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components	<input type="checkbox"/> AP00.20-P-0053SX
<input type="checkbox"/> Visually inspect condition of front axle ball joints, rubber boots	<input type="checkbox"/> AP33.20-P-3353SX
<input type="checkbox"/> Visually inspect condition of driveshaft flexible discs	<input type="checkbox"/> AP41.10-P-4152SX
<input type="checkbox"/> Visually inspect condition of steering mechanical components, rubber boots	<input type="checkbox"/> AP46.00-P-4653SX
<input type="checkbox"/> Coolant - check fluid level and correct if necessary engine 157, 272, 273; engine 275 main and low temperature circuit (main circuit if not to be replaced (every 30k miles/3 yrs)) <input type="checkbox"/> refer to AH20.00-P-1142-01V <input type="checkbox"/> observe correct coolant composition	<input type="checkbox"/>
<input type="checkbox"/> Brake system - check fluid level and correct if necessary	<input type="checkbox"/> AP42.10-P-4210SX
<input type="checkbox"/> Power steering - check fluid level and correct if necessary <input type="checkbox"/> the fluid level must always be on the maximum mark, corresponding to the oil temperature	<input type="checkbox"/> AP46.00-P-4611SX
<input type="checkbox"/> Windshield washer system - check fluid level and correct if necessary	<input type="checkbox"/> AP82.35-P-8210SX
<input type="checkbox"/> Active Body Control - check fluid level and correct if necessary with Code 487 (Active Body Control (ABC))	<input type="checkbox"/> AP32.50-P-3213SX
<input type="checkbox"/> Parking brake (function test only)	<input type="checkbox"/> AP42.00-P-4290BA
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster <input type="checkbox"/> reminder - if not yet performed	AP00.20-P-0042SX
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 2 years	
<input type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet	
<input checked="" type="checkbox"/> Performed (check if performed)	Not OK ↓
<input type="checkbox"/> Main/starter battery - Check fluid level and correct if necessary with lead acid battery	<input type="checkbox"/> AP54.10-P-5410SX
<input type="checkbox"/> Horn - Electrical system check	<input type="checkbox"/>
<input type="checkbox"/> Warning/indicator lamps - Electrical system check	<input type="checkbox"/> AP54.30-P-5451SX
<input type="checkbox"/> Illumination and interior lighting - Electrical system check	<input type="checkbox"/> AP54.30-P-5453SX
<input type="checkbox"/> Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check	<input type="checkbox"/> AP82.10-P-8252EW
<input type="checkbox"/> Check trunk/cargo area lighting	<input type="checkbox"/>
<input type="checkbox"/> Check and correct headlamp setting	AP82.10-P-8260SX
<input type="checkbox"/> Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here	<input type="checkbox"/> AP54.10-U-5453A
<input type="checkbox"/> Check seat belts and buckles for signs of external damage and proper function	<input type="checkbox"/> AP91.40-P-9150SX
<input type="checkbox"/> Check windshield washer and headlamp cleaning system	<input type="checkbox"/> AP82.30-P-8252SX
<input type="checkbox"/> Check, clean, and lubricate tilt/sliding roof mechanism except CODE 413 (panoramic glass roof with top sliding roof)	AP77.20-P-7731SX
<input type="checkbox"/> Check, clean, and lubricate panoramic roof mechanism with CODE 413 (panoramic glass roof with top sliding roof)	AP77.20-P-7732SX
<input type="checkbox"/> Check bodywork for paintwork damage	<input type="checkbox"/> AP98.00-P-9850SX
<input type="checkbox"/> Night View Assist camera - clean windshield behind the camera cover with CODE 610 (Night View Assist)	AP54.30-P-5431SX
<input type="checkbox"/> Tire rotation where applicable	
<input type="checkbox"/> Inspect tires for damage, measure thread depth and enter table at the end of the service sheet	AP40.10-P-4051Z
<input type="checkbox"/> Check TIREFIT tire sealant expiration date where applicable	<input type="checkbox"/> AP40.10-P-4054R
<input type="checkbox"/> Activate Tire Pressure Monitoring System <input type="checkbox"/> refer to vehicle Operator's Manual	AP40.10-P-4054R
<input type="checkbox"/> Visually check brake system components, lines, hoses, calipers	<input type="checkbox"/>

<input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed pads discs	<input type="checkbox"/> AP42.10-P-4253A <input type="checkbox"/> AP42.10-P-4258SX
<input type="checkbox"/> Check chassis and load-bearing body components for damage and corrosion	<input type="checkbox"/> AP00.20-P-0090SX
<input type="checkbox"/> Replace wiper blades	
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years	
<input type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet	
<input checked="" type="checkbox"/> Performed (check if performed)	Not OK ↓
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster	AP00.20-P-0042SX
<input type="checkbox"/> Engine - oil and filter change engine 157 engine 272 engine 273 engine 275.953 engine 275.982	AP18.00-P-0101EWG AP18.00-P-0101PIT AP18.00-P-0101SX AP18.00-P-0101SZA AP18.00-P-0101SZB
<input type="checkbox"/> Check catch, safety catch and hinges on engine hood for proper operation	<input type="checkbox"/> AP88.40-P-8851SX
<input type="checkbox"/> Check water drain in air/water duct for obstructions; clean if soiled	AP83.10-P-8339M
<input type="checkbox"/> Check thickness of brake pads, front and rear	<input type="checkbox"/> AP42.10-P-4253A
<input type="checkbox"/> Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet	<input type="checkbox"/> AP40.15-P-4061A
<input type="checkbox"/> Coolant - check fluid level and correct if necessary engine 157, 272, 273; engine 275 main and low temperature circuit (main circuit if not to be replaced (every 30k miles/3 yrs)) <input type="checkbox"/> refer to AH20.00-P-1142-01V <input type="checkbox"/> observe correct coolant composition	<input type="checkbox"/>
<input type="checkbox"/> Brake system - check fluid level and correct if necessary	<input type="checkbox"/> AP42.10-P-4210SX
<input type="checkbox"/> Power steering - check fluid level and correct if necessary <input type="checkbox"/> the fluid level must always be on the maximum mark, corresponding to the oil temperature	<input type="checkbox"/> AP46.00-P-4611SX
<input type="checkbox"/> Windshield washer system - check fluid level and correct if necessary	<input type="checkbox"/> AP82.35-P-8210SX
<input type="checkbox"/> Active Body Control - check fluid level and correct if necessary with Code 487 (Active Body Control (ABC))	<input type="checkbox"/> AP32.50-P-3213SX
<input type="checkbox"/> Reset maintenance service indicator in instrument cluster <input type="checkbox"/> reminder - if not yet performed	AP00.20-P-0042SX
High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 years	
<input type="checkbox"/> Plus any applicable additional work listed at the end of the service sheet	
<input checked="" type="checkbox"/> Performed (check if performed)	Not OK ↓
<input type="checkbox"/> Main/starter battery - Check fluid level and correct if necessary with lead acid battery	<input type="checkbox"/> AP54.10-P-5410SX
<input type="checkbox"/> Horn - Electrical system check	<input type="checkbox"/>
<input type="checkbox"/> Warning/indicator lamps - Electrical system check	<input type="checkbox"/> AP54.30-P-5451SX
<input type="checkbox"/> Illumination and interior lighting - Electrical system check	<input type="checkbox"/> AP54.30-P-5453SX
<input type="checkbox"/> Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check	<input type="checkbox"/> AP82.10-P-8252EW
<input type="checkbox"/> Check trunk/cargo area lighting	<input type="checkbox"/>
<input type="checkbox"/> Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here	<input type="checkbox"/> AP54.10-U-5453A
<input type="checkbox"/> Check windshield washer and headlamp cleaning system	<input type="checkbox"/> AP82.30-P-8252SX
<input type="checkbox"/> Night View Assist camera - clean windshield behind the camera cover with CODE 610 (Night View Assist)	AP54.30-P-5431SX

<input type="checkbox"/> Tire rotation where applicable		
<input type="checkbox"/> Inspect tires for damage, measure thread depth and enter table at the end of the service sheet		AP40.10-P-4051Z
<input type="checkbox"/> Check TIREFIT tire sealant expiration date where applicable	<input type="checkbox"/>	AP40.10-P-4054R
<input type="checkbox"/> Activate Tire Pressure Monitoring System <input type="checkbox"/> refer to vehicle Operator's Manual		AP40.10-P-4054R
<input type="checkbox"/> Visually check brake system components, lines, hoses, calipers	<input type="checkbox"/>	
<input type="checkbox"/> Check thickness of brake pads and discs, front and rear wheels removed		
pads	<input type="checkbox"/>	AP42.10-P-4253A
discs	<input type="checkbox"/>	AP42.10-P-4258SX
<input type="checkbox"/> Replace wiper blades		
High Mileage Additional Work		
<input checked="" type="checkbox"/> Performed (check if performed)		
<input type="checkbox"/> Replace air filter except engine 275		
engine 157	If more than 40,000 mi or 4 years since last replacement	AP09.10-P-0980AB
engine 272, 273	If more than 40,000 mi or 4 years since last replacement	AP09.10-P-0980SX
<input type="checkbox"/> Replace air filter engine 275	If more than 60,000 mi or 6 years since last replacement	AP09.10-P-0980SZ
<input type="checkbox"/> Automatic transmission - oil and filter change		
transmission 722.9	If more than 40,000 mi or 4 years since last replacement	AP27.00-P-2702W
transmission 722.6	If more than 40,000 mi or 4 years since last replacement	AP27.00-P-2702SX
<input type="checkbox"/> Replace V-belts S400 HYBRID	If more than 60,000 mi or 6 years since last replacement	AP13.20-P-1380A
<input type="checkbox"/> Replace spark plugs		
engine 157, 272, 273	If more than 60,000 mi or 6 years since last replacement	AP15.10-P-1580SX
engine 275	If more than 60,000 mi or 6 years since last replacement	AP15.10-P-1580SZ
<input type="checkbox"/> Replace fuel filter	If more than 150,000 mi or 15 years since last replacement	AP47.20-P-0780SX
<input type="checkbox"/> Replace coolant engine 275 main circuit	If more than 30,000 mi or 3 years since last replacement	AP20.00-P-2080SZ
<input type="checkbox"/> observe correct coolant composition		
<input type="checkbox"/> Replace coolant except engine 275 main circuit		
<input type="checkbox"/> observe correct coolant composition		
engine 157, 272, 273	If more than 150,000 mi or 15 years since last replacement	AP20.00-P-2080SX
engine 275 low temperature circuit	If more than 150,000 mi or 15 years since last replacement	AP20.00-P-2080SZ

Tire inflation pressure (bar/psi)				
LF	RF	LR	RR	Spare

Tire thread depth (mm)				
	LF	RF	LR	RR
outside				
center				
inside				