

P88.10-2156-09

Shown on left fender liner

- 1 Fender liner front section
- 2 fender liner rear section
- 3 Screw


- 4 Nut
- 5 Bolts
- 6 Screw

- 7 Nut
- 8 Expanding clip
- 9 Screw

Modification notes

4.8.04	Repair method modified	"Remove engine paneling" eliminated
--------	------------------------	-------------------------------------

	Remove/Install		
1	Raise vehicle with lifting platform		AR00.60-P-1000V
2.1	Turn front wheels all the way to the left	When removing left fender liner front section (1)	
2.2	Completely turn front wheels to right	When removing right fender liner front section (1)	
3	Unscrew bolt (6)		
4.1	Unscrew screws (3, 5)	When removing fender liner front section (1)	
5.1	Unscrew nuts (4)	When removing fender liner front section (1)	
6.1	Remove fender liner front section (1) from front fender with mounting wedge	When removing fender liner front section (1)	*110589035900
7.1	Unscrew bolt (9)	When removing fender liner rear section (2)	
8.1	Unscrew nuts (7)	When removing fender liner rear section (2)	
9.1	Remove expanding clips (8)	When removing fender liner rear section (2)	
10.1	Remove inner rear fender section (2) from front fender with mounting wedge	When removing fender liner rear section (2)	*110589035900
11	Install in the reverse order		



110 589 03 59 00

Mounting wedge