



P82.10-4318-09

Illustrated on model 221

- | | | | |
|---|--------------------------|----|---------------------------|
| 1 | Trunk lid | 7 | Trunk lid paneling |
| 2 | Hinge bracket trim piece | 8 | Handle strip cover |
| 3 | Umbrella holder | 9 | Holder |
| 4 | Bracket | 10 | Bolt |
| 5 | Hazard warning triangle | 11 | Adhesive tape (model 221) |
| 6 | Cover | 12 | Clip |

- | | |
|-------|--------------------------|
| E19/1 | Left license plate lamp |
| E19/2 | Right license plate lamp |

 	Remove/install		
1	Detach trunk lid trim (7)		
2	Remove socket (9) of left license plate lamp (E19/1) or right license plate lamp (E19/2)		
3.1	Remove bulb from left or right socket (9)	When replacing the bulbs.	
4	Remove bolts (10)		
5	Unclip handle strip cover (8) from the inside	<p>i Start on the right hand side of the vehicle. On model 216, a clip is installed instead of the adhesive tape (11).</p> <p>i Installation: For model 221, check adhesive tape (11) and replace if necessary.</p>	
6	Unclip left license plate lamp (E19/1) or right license plate lamp (E19/2) from the inside		
7	Install in the reverse order		